



Tutorial: Geocomputation with R



The basics

Jannes Muenchow, Robin Lovelace

ERUM Budapest, 2018-05-14



Find the slides and code

https://github.com/jannes-m/erum18_geocompr

Please install following packages:

```
install.packages(c("sf", "raster", "spData", "dplyr", "RQGIS"))
```

Or from **docker**:

```
docker run -d -p 8787:8787 -v ${pwd}:/data robinlovelace/geocompr
```

Contents of the tutorial

1. Basics



Contents of the tutorial

1. Basics
2. Spatial vector data



Contents of the tutorial

1. Basics
2. Spatial vector data
3. Spatial raster data



Contents of the tutorial

1. Basics
2. Spatial vector data
3. Spatial raster data
4. Mapping



Contents of the tutorial

1. Basics
2. Spatial vector data
3. Spatial raster data
4. Mapping
5. Bridges to GIS



Contents of the tutorial

1. Basics
2. Spatial vector data
3. Spatial raster data
4. Mapping
5. Bridges to GIS
6. (Spatial statistical learning)



Who are we

- **Jannes Muenchow** -
GIScientist from Jena with a
special focus on ecology,
landsliding and
geomarketing; creator of the
RQGIS package



Who are we

- **Jannes Muenchow** - GIScientist from Jena with a special focus on ecology, landsliding and geomarketing; creator of the **RQGIS** package
- **Robin Lovelace** - Geographer and Environmental Scientist focussing on sustainable transport planning; creator of **stplanr**



Who are we


- **Jannes Muenchow** - GIScientist from Jena with a special focus on ecology, landsliding and geomarketing; creator of the **RQGIS** package
- **Robin Lovelace** - Geographer and Environmental Scientist focussing on sustainable transport planning; creator of **stplanr**
- together with **Jakub Nowosad** we are writing:

Geocomputation

with R



Where are we from





Some definitions

What is a GIS?

- A **G**eographic **I**nformation **S**ystem is a system for the analysis, manipulation and visualization of geographical data (Longley, Goodchild, Maguire, and Rhind, 2015).



What is a GIS?

- A **G**eographic **I**nformation **S**ystem is a system for the analysis, manipulation and visualization of geographical data (Longley, Goodchild, Maguire, and Rhind, 2015).
- Six components of a GIS: software, data, procedures, hardware, people, network



What is a GIS?



- A **G**eographic **I**nformation **S**ystem is a system for the analysis, manipulation and visualization of geographical data (Longley, Goodchild, Maguire, and Rhind, 2015).
- Six components of a GIS: software, data, procedures, hardware, people, network
- Typical GIS software packages: QGIS, SAGA-GIS, GRASS-GIS, ArcMap (commercial)





What is geocomputation?

- Geocomputation
- GIScience
- Geographic data science



What is geocomputation?

- Geocomputation
- GIScience
- Geographic data science

Graphical User Interface (GUI) GIS vs Geocomputation with R

Attribute	Desktop GIS (GUI)	R
Home disciplines	Geography	Computing, Statistics
Software focus	Graphical User Interface	Command line
Reproducibility	Minimal	Maximal



What is geocomputation?

- Geocomputation
- GIScience
- Geographic data science

Graphical User Interface (GUI) GIS vs Geocomputation with R

Attribute	Desktop GIS (GUI)	R
Home disciplines	Geography	Computing, Statistics
Software focus	Graphical User Interface	Command line
Reproducibility	Minimal	Maximal

Further reading: <https://geocompr.robinlovelace.net/intro.html#what-is-geocomputation>



Geographic data models



Geographic data

- Geographic data consists of **xy-coordinates** and corresponding **attributes** (this might include a time stamp, otherwise the data is static).



Geographic data

- Geographic data consists of **xy-coordinates** and corresponding **attributes** (this might include a time stamp, otherwise the data is static).
- Usually we neglect the curvature of the Earth when visualizing geographic data.



Geographic data

- Geographic data consists of **xy-coordinates** and corresponding **attributes** (this might include a time stamp, otherwise the data is static).
- Usually we neglect the curvature of the Earth when visualizing geographic data.
- Geographic data only represents a simplified representation of the world. So we decide what we display for which purpose.



Geographic data

- Geographic data consists of **xy-coordinates** and corresponding **attributes** (this might include a time stamp, otherwise the data is static).
- Usually we neglect the curvature of the Earth when visualizing geographic data.
- Geographic data only represents a simplified representation of the world. So we decide what we display for which purpose.
- Geographic data can quickly become big.




Geographic data

- Geographic data consists of **xy-coordinates** and corresponding **attributes** (this might include a time stamp, otherwise the data is static).
- Usually we neglect the curvature of the Earth when visualizing geographic data.
- Geographic data only represents a simplified representation of the world. So we decide what we display for which purpose.
- Geographic data can quickly become big.
- Two data models for representing digitally geographic data: **the vector** and **the raster** data model



Vector data model


- Discrete objects represented by points





Vector data model


- Discrete objects represented by points
- Three main subtypes: points, lines and polygons





Vector data model


- Discrete objects represented by points
- Three main subtypes: points, lines and polygons
- Especially suitable for objects with well-defined borders (lakes, houses, streets, etc.)





Vector data model

- Discrete objects represented by points
- Three main subtypes: points, lines and polygons
- Especially suitable for objects with well-defined borders (lakes, houses, streets, etc.)
- Attribute table



Further reading:


<https://geocompr.robinlovelace.net/spatial-class.html#vector-data>



Raster data model

- Continuous fields represented by pixels (cells)

19	38	72	18
17	31	NA	96
NA	26	16	9
14	45	50	10






Raster data model

- Continuous fields represented by pixels (cells)
- One attribute value for one cell

19	38	72	18
17	31	NA	96
NA	26	16	9
14	45	50	10






Raster data model

- Continuous fields represented by pixels (cells)
- One attribute value for one cell
- Especially suitable for continuous data without sharp borders (elevation, precipitation)

19	38	72	18
17	31	NA	96
NA	26	16	9
14	45	50	10






Raster data model

- Continuous fields represented by pixels (cells)
- One attribute value for one cell
- Especially suitable for continuous data without sharp borders (elevation, precipitation)
- Structure: raster header (origin, resolution, ncol, nrow, crs, NAvalue) and matrix containing the data

19	38	72	18
17	31	NA	96
NA	26	16	9
14	45	50	10






Raster data model

- Continuous fields represented by pixels (cells)
- One attribute value for one cell
- Especially suitable for continuous data without sharp borders (elevation, precipitation)
- Structure: raster header (origin, resolution, ncol, nrow, crs, NAvalue) and matrix containing the data
- Map algebra

19	38	72	18
17	31	NA	96
NA	26	16	9
14	45	50	10






Raster data model

- Continuous fields represented by pixels (cells)
- One attribute value for one cell
- Especially suitable for continuous data without sharp borders (elevation, precipitation)
- Structure: raster header (origin, resolution, ncol, nrow, crs, NAvalue) and matrix containing the data
- Map algebra


19	38	72	18
17	31	NA	96
NA	26	16	9
14	45	50	10



Further reading: <https://geocompr.robinlovelace.net/spatial-class.html#raster-data>



Raster header



header

NCOLS 22
NROWS 16
XLLCORNER 11.05
YLLCORNER 49.435
CELLSIZE 0.0025
NODATA_value NA

NA NA NA NA NA NA NA NA NA NA 1 NA NA NA 1 1 NA 1 NA NA NA NA NA 4
NA NA NA NA NA NA 1 NA NA 3 NA NA NA 2 1 1 2 1 1 NA 2 1 1
NA 1 NA 1 1 NA NA 3 6 NA NA NA 5 NA 2 NA 1 NA NA 4 12 NA
NA NA NA 3 NA NA NA 9 2 1 1 1 4 1 1 1 2 NA 2 3 NA NA
1 2 1 NA 1 NA NA 3 10 3 1 2 2 NA 7 2 NA NA NA NA 2 3
NA 4 2 5 2 4 4 1 4 NA 3 3 5 4 7 1 6 4 5 2 3 3
2 5 6 6 2 9 3 1 1 2 NA NA 1 NA 1 1 6 1 7 8 10 1
NA NA NA 1 1 1 NA 5 2 8 12 7 11 3 3 1 1 NA 4 2 2 NA
2 NA NA 2 3 3 NA 3 2 13 33 20 4 2 NA 1 NA 1 1 NA NA NA
3 6 7 3 3 1 2 6 26 **58** 30 25 5 4 1 NA NA NA NA NA NA NA NA
NA 5 3 7 5 7 5 8 20 12 22 28 10 2 2 2 1 NA 1 NA NA NA
NA NA 2 6 2 7 3 5 2 1 NA NA 3 NA 1 1 2 NA NA 2 1 4
NA NA NA 1 2 NA NA 1 NA NA 2 3 NA 2 7 3 1 5 4 3 1 1
NA 2 1 1 NA NA 1 1 3 1 13 10 19 11 5 7 7 5 NA 2 1 2
2 1 NA NA NA NA 9 6 2 NA 1 10 9 6 2 3 9 NA 4 2 2 NA
3 NA NA NA NA 1 2 3 NA NA NA 2 2 NA 4 1 2 1 3 NA NA NA



A brief word on CRS



A brief word on CRS

We use Coordinate Reference Systems (CRS) to locate our geographic data on Earth.


We distinguish between:

- Geographical CRS span the entire world
- Projected CRS are (usually) localized to minimize visual distortion in a particular region (use a specific ellipsoid which is especially suitable for a this particular part of the Earth)

Geographic CRS



- Usually in decimal degrees
- Used by many people/institutions (GPS)
- Great for locating a place on Earth
- Best for global analysis
- Less suitable if you want to measure distance




Source: [Geocomputation with R](#).

Geographic CRS




- Usually in decimal degrees
- Used by many people/institutions (GPS)
- Great for locating a place on Earth
- Best for global analysis
- Less suitable if you want to measure distance
- Heavily distorted towards the poles





Projected CRS

- Spatial projections flatten the 3D shape of the Earth onto a 2D plane
- Especially suitable for "local" analysis




Source: progonos.com/furuti/



Projected CRS

- Spatial projections flatten the 3D shape of the Earth onto a 2D plane
- Especially suitable for "local" analysis



Source: progonos.com/furuti/

Further reading:

- [Geocomputation with R - Projections](#)
- [QGIS CRS documentation](#)
- [Earth Data Science CRS](#)



Brief history of R-spatial



Brief history of R-spatial

- Spatial packages already available in the S language since the 1990s (Bivand and Gebhardt, 2000)



Brief history of R-spatial

- Spatial packages already available in the S language since the 1990s (Bivand and Gebhardt, 2000)
- By 2000, modifications of these became R packages for point pattern analysis, geostatistics, exploratory spatial data analysis and spatial econometrics



Brief history of R-spatial

- Spatial packages already available in the S language since the 1990s (Bivand and Gebhardt, 2000)
- By 2000, modifications of these became R packages for point pattern analysis, geostatistics, exploratory spatial data analysis and spatial econometrics
- R-GIS bridges (Bivand, 2000)



Brief history of R-spatial

- Spatial packages already available in the S language since the 1990s (Bivand and Gebhardt, 2000)
- By 2000, modifications of these became R packages for point pattern analysis, geostatistics, exploratory spatial data analysis and spatial econometrics
- R-GIS bridges (Bivand, 2000)
- Bivand (2003) proposed a spatial data class system for R which eventually led to the packages **rgdal** (first released in 2003; Bivand, Keitt, and Rowlingson, 2018) and **sp** (first released in 2005; Bivand, Pebesma, and Gomez-Rubio, 2013)



Brief history of R-spatial

- Spatial packages already available in the S language since the 1990s (Bivand and Gebhardt, 2000)
- By 2000, modifications of these became R packages for point pattern analysis, geostatistics, exploratory spatial data analysis and spatial econometrics
- R-GIS bridges (Bivand, 2000)
- Bivand (2003) proposed a spatial data class system for R which eventually led to the packages **rgdal** (first released in 2003; Bivand, Keitt, and Rowlingson, 2018) and **sp** (first released in 2005; Bivand, Pebesma, and Gomez-Rubio, 2013)
- 2008: Applied Spatial Data Analysis with R (Bivand, Pebesma, and Gomez-Rubio, 2013)



Brief history of R-spatial

- Spatial packages already available in the S language since the 1990s (Bivand and Gebhardt, 2000)
- By 2000, modifications of these became R packages for point pattern analysis, geostatistics, exploratory spatial data analysis and spatial econometrics
- R-GIS bridges (Bivand, 2000)
- Bivand (2003) proposed a spatial data class system for R which eventually led to the packages **rgdal** (first released in 2003; Bivand, Keitt, and Rowlingson, 2018) and **sp** (first released in 2005; Bivand, Pebesma, and Gomez-Rubio, 2013)
- 2008: Applied Spatial Data Analysis with R (Bivand, Pebesma, and Gomez-Rubio, 2013)
- 2010: **raster** package (Hijmans, 2017)



Brief history of R-spatial

- Spatial packages already available in the S language since the 1990s (Bivand and Gebhardt, 2000)
- By 2000, modifications of these became R packages for point pattern analysis, geostatistics, exploratory spatial data analysis and spatial econometrics
- R-GIS bridges (Bivand, 2000)
- Bivand (2003) proposed a spatial data class system for R which eventually led to the packages **rgdal** (first released in 2003; Bivand, Keitt, and Rowlingson, 2018) and **sp** (first released in 2005; Bivand, Pebesma, and Gomez-Rubio, 2013)
- 2008: Applied Spatial Data Analysis with R (Bivand, Pebesma, and Gomez-Rubio, 2013)
- 2010: **raster** package (Hijmans, 2017)
- 2011: **rgeos** package (Bivand and Rundel, 2017)



Brief history of R-spatial

- Spatial packages already available in the S language since the 1990s (Bivand and Gebhardt, 2000)
- By 2000, modifications of these became R packages for point pattern analysis, geostatistics, exploratory spatial data analysis and spatial econometrics
- R-GIS bridges (Bivand, 2000)
- Bivand (2003) proposed a spatial data class system for R which eventually led to the packages **rgdal** (first released in 2003; Bivand, Keitt, and Rowlingson, 2018) and **sp** (first released in 2005; Bivand, Pebesma, and Gomez-Rubio, 2013)
- 2008: Applied Spatial Data Analysis with R (Bivand, Pebesma, and Gomez-Rubio, 2013)
- 2010: **raster** package (Hijmans, 2017)
- 2011: **rgeos** package (Bivand and Rundel, 2017)
- 2016-17: **sf** - simple features for R (Pebesma, 2018a)



Brief history of R-spatial

- Spatial packages already available in the S language since the 1990s (Bivand and Gebhardt, 2000)
- By 2000, modifications of these became R packages for point pattern analysis, geostatistics, exploratory spatial data analysis and spatial econometrics
- R-GIS bridges (Bivand, 2000)
- Bivand (2003) proposed a spatial data class system for R which eventually led to the packages **rgdal** (first released in 2003; Bivand, Keitt, and Rowlingson, 2018) and **sp** (first released in 2005; Bivand, Pebesma, and Gomez-Rubio, 2013)
- 2008: Applied Spatial Data Analysis with R (Bivand, Pebesma, and Gomez-Rubio, 2013)
- 2010: **raster** package (Hijmans, 2017)
- 2011: **rgeos** package (Bivand and Rundel, 2017)
- 2016-17: **sf** - simple features for R (Pebesma, 2018a)
- 2017-18: **stars** - spatiotemporal tidy arrays for R (Pebesma, 2018b)



Brief history of R-spatial

- Spatial packages already available in the S language since the 1990s (Bivand and Gebhardt, 2000)
- By 2000, modifications of these became R packages for point pattern analysis, geostatistics, exploratory spatial data analysis and spatial econometrics
- R-GIS bridges (Bivand, 2000)
- Bivand (2003) proposed a spatial data class system for R which eventually led to the packages **rgdal** (first released in 2003; Bivand, Keitt, and Rowlingson, 2018) and **sp** (first released in 2005; Bivand, Pebesma, and Gomez-Rubio, 2013)
- 2008: Applied Spatial Data Analysis with R (Bivand, Pebesma, and Gomez-Rubio, 2013)
- 2010: **raster** package (Hijmans, 2017)
- 2011: **rgeos** package (Bivand and Rundel, 2017)
- 2016-17: **sf** - simple features for R (Pebesma, 2018a)
- 2017-18: **stars** - spatiotemporal tidy arrays for R (Pebesma, 2018b)

Further reading: <https://geocompr.robinlovelace.net/intro.html#the-history-of-r-spatial>

Recap

- What is a GIS?



Recap

- What is a GIS?
- What is Geocomputation?



Recap

- What is a GIS?
- What is Geocomputation?
- Why is geographic data special?



Recap

- What is a GIS?
- What is Geocomputation?
- Why is geographic data special?
- Difference between the spatial vector and raster data model



Recap

- What is a GIS?
- What is Geocomputation?
- Why is geographic data special?
- Difference between the spatial vector and raster data model
- CRS



Recap

- What is a GIS?
- What is Geocomputation?
- Why is geographic data special?
- Difference between the spatial vector and raster data model
- CRS
- Brief history of R-spatial



References

- Bivand, Roger (2003). "Approaches to Classes for Spatial Data in R". In: *Proceedings of DSC*. Ed. by Kurt Hornik, Friedrich Leisch and Achim Zeileis. URL: <https://www.r-project.org/nosvn/conferences/DSC-2003/Proceedings/Bivand.pdf> (visited on Jun. 27, 2017).
- Bivand, Roger S. (2000). "Using the R Statistical Data Analysis Language on GRASS 5.0 GIS Database Files". In: *Computers & Geosciences* 26.9, pp. 1043-1052. URL: <http://www.sciencedirect.com/science/article/pii/S0098300400000571> (visited on Jul. 11, 2017).
- Bivand, Roger S, Edzer Pebesma and Virgilio Gomez-Rubio (2013). *Applied Spatial Data Analysis with R*. 2nd ed.. New York: Springer. 405 pp. ISBN: 978-1-4614-7617-7.
- Bivand, Roger and Albrecht Gebhardt (2000). "Implementing Functions for Spatial Statistical Analysis Using the Language". In: *Journal of Geographical Systems* 2.3, pp. 307-317. URL: <http://www.springerlink.com/index/CJRPUMB78JUYH54W.pdf> (visited on Jul. 12, 2017).
- Bivand, Roger, Tim Keitt and Barry Rowlingson (2018). *Rgdal: Bindings for the 'Geospatial' Data Abstraction Library*. R package version 1.2-18. URL: <https://CRAN.R-project.org/package=rgdal>.
- Bivand, Roger and Colin Rundel (2017). *Rgeos: Interface to Geometry Engine - Open Source ('GEOS')*. R package version 0.3-26. URL: <https://CRAN.R-project.org/package=rgeos>.
- Hijmans, Robert J. (2017). *Raster: Geographic Data Analysis and Modeling*. R package version 2.6-7. URL: <https://CRAN.R-project.org/package=raster>.
- Longley, Paul, Michael Goodchild, David Maguire, et al. (2015). *Geographic Information Science & Systems*. Fourth edition. Hoboken, NJ: Wiley. 477 pp. ISBN: 978-1-118-67695-0.
- Pebesma, Edzer (2018a). *Sf: Simple Features for R*. R package version 0.6-2. URL: <https://CRAN.R-project.org/package=sf>.
- Pebesma, Edzer (2018b). *Stars: Scalable, Spatiotemporal Tidy Arrays for R*. R package version 0.1-1. URL: <https://github.com/r-spatial/stars/>.