## **CONTENTS**

- 1 Stability
- 2 Routh Hurwitz Criterion
- **3** Compensators
- 4 Nyquist Plot
- 5 State Space Analysis

Abstract—This manual is an introduction to control systems based on GATE problems.Links to sample Python codes are available in the text.

Download python codes using

## 1 STABILITY

## 2 ROUTH HURWITZ CRITERION

- 3 Compensators
- 4 NYOUIST PLOT
- 5 STATE SPACE ANALYSIS
- 5.0.1. A second-order LTI system is described by the following state equations

$$\frac{\partial x_1(t)}{\partial t} - x_2(t) = 0 \tag{5.0.1.1}$$

$$\frac{\partial x_2(t)}{\partial t} + 2x_1(t) + 3x_2(t) = r(t)$$
 (5.0.1.2)

$$c(t) = x_1(t)$$
. (5.0.1.3)

where  $x_1(t)$  and  $x_2(t)$  are the two state variables and r(t) denotes the input. The output is c(t). Express this in terms of the state space model. **Solution:** From (??), (5.0.1.1)-(5.0.1.3) can be expressed as

$$\dot{\mathbf{x}}(t) = \mathbf{A}\mathbf{x}(t) + \mathbf{B}\mathbf{u}(t) \tag{5.0.1.4}$$

$$\mathbf{y}(t) = \mathbf{C}\mathbf{x}(t) + \mathbf{D}\mathbf{u}(t) \tag{5.0.1.5}$$

where

$$\mathbf{A} = \begin{pmatrix} 0 & 1 \\ -2 & -3 \end{pmatrix} \tag{5.0.1.6}$$

$$\mathbf{B} = \begin{pmatrix} 0 \\ 1 \end{pmatrix} \tag{5.0.1.7}$$

$$\mathbf{C} = \begin{pmatrix} 1 & 0 \end{pmatrix} \tag{5.0.1.8}$$

$$\mathbf{D} = 0 \tag{5.0.1.9}$$

5.0.2. Find the system transfer function H(s).

**Solution:** From (??),

1

1

1

1

$$H(s) = \mathbf{C}(s\mathbf{I} - \mathbf{A})^{-1}\mathbf{B} + D\mathbf{I}$$
 (5.0.2.1)

$$=\frac{1}{s^2+3s+2}\tag{5.0.2.2}$$

using the code in codes/ee18btech11031.py

5.0.3. Identify the damping type.

Solution: From (??) and

$$\omega = \sqrt{2}, \zeta = \frac{3}{2\sqrt{2}} > 1$$
 (5.0.3.1)

From Table ??, the sytem is overdamped.

5.0.4. Find and plot the unit step response for the system.

## **Solution:**

$$Y(s) = U(s) * H(s)$$
 (5.0.4.1)

$$=\frac{1}{s(s+1)(s+2)}$$
 (5.0.4.2)

$$y(t) = (\frac{1}{2} - e^{-t} + \frac{e^{-2t}}{2})u(t)$$
 (5.0.4.3)

using the code in codes/ee18btech11031(2).py The corresponding step response plot:




Fig. 5.0.4: (a)