Control Systems

G V V Sharma*

Contents

***Abstract*—This manual is an introduction to control systems based on GATE problems.Links to sample Python codes are available in the text.**

Download python codes using

```
svn co https://github.com/gadepall/school/trunk/
    control/codes
```

*The author is with the Department of Electrical Engineering, Indian Institute of Technology, Hyderabad 502285 India e-mail: gadepall@iith.ac.in. All content in this manual is released under GNU GPL. Free and open source.

1 Mason's Gain Formula

2 Bode Plot

2.1 Introduction

2.2 Example

3 Second order System

3.1 Damping

3.2 Example

4 Routh Hurwitz Criterion

4.1 Routh Array

4.2 Marginal Stability

4.3 Stability

5 State-Space Model

5.1. The state equation and the output equation of a control system are given below :

$$\dot{X} = \begin{bmatrix} -4 & -1.5 \\ 4 & 0 \end{bmatrix} X + \begin{bmatrix} 4 \\ 0 \end{bmatrix} U \quad (5.1.1)$$

$$Y = \begin{bmatrix} 1.5 & 0.625 \end{bmatrix} X \quad (5.1.2)$$

Then transfer function representation of the system is

5.2. **Solution:** when

$$\dot{X} = AX + BU \quad (5.2.1)$$

$$Y = CX + DU \quad (5.2.2)$$

where A, B, C, D are matrices
Then the transfer function can be find using

$$T(s) = C[(sI - A)^{-1}].B + D \quad (5.2.3)$$

From the given state space representation of the system, we can find matrices as

$$A = \begin{bmatrix} -4 & -1.5 \\ 4 & 0 \end{bmatrix} \quad (5.2.4)$$

$$B = \begin{bmatrix} 4 \\ 0 \end{bmatrix} \tag{5.2.5}$$

$$C = \begin{bmatrix} 1.5 & 0.625 \end{bmatrix} \tag{5.2.6}$$

We can find the transfer function using

$$T(s) = C[(sI - A)^{-1}].B \tag{5.2.7}$$

$$(sI - A) = \begin{bmatrix} s & 0 \\ 0 & s \end{bmatrix} - \begin{bmatrix} -4 & -1.5 \\ 4 & 0 \end{bmatrix} \tag{5.2.8}$$

$$(sI - A) = \begin{bmatrix} s+4 & -1.5 \\ -4 & s \end{bmatrix} \tag{5.2.9}$$

$$|sI - A| \quad = s(s+4) - (-4) \times (-1.5) \tag{5.2.10}$$

$$|sI - A| = s^2 + 4s + 6 \tag{5.2.11}$$

and from (1.2.9)

$$Adj[sI - A] = \begin{bmatrix} s & -1.5 \\ 4 & s+4 \end{bmatrix} \tag{5.2.12}$$

Hence

$$[sI - A]^{-1} = \frac{Adj[sI - A]}{|sI - A|} \tag{5.2.13}$$

$$= \begin{bmatrix} \frac{s}{(s^2+4s+6)} & \frac{-1.5}{(s^2+4s+6)} \\ \frac{4}{(s^2+4s+6)} & \frac{(s+4)}{(s^2+4s+6)} \end{bmatrix} \tag{5.2.14}$$

$$[sI - A]^{-1}.B = \begin{bmatrix} \frac{s}{(s^2+4s+6)} & \frac{-1.5}{(s^2+4s+6)} \\ \frac{4}{(s^2+4s+6)} & \frac{(s+4)}{(s^2+4s+6)} \end{bmatrix} \begin{bmatrix} 4 \\ 0 \end{bmatrix} \tag{5.2.15}$$

$$\therefore \qquad [sI - A]^{-1}.B = \begin{bmatrix} \frac{4s}{(s^2+4s+6)} \\ \frac{16}{(s^2+4s+6)} \end{bmatrix} \tag{5.2.16}$$

$$Substituting\, the\, values\, of\, [sI - A]^{-1}.B$$
$$and\, C\, in\, equation\, (1.2.7)$$

$$T(s) = \begin{bmatrix} 1.5 & 0.625 \end{bmatrix} \begin{bmatrix} \frac{4s}{(s^2+4s+6)} \\ \frac{16}{(s^2+4s+6)} \end{bmatrix} \tag{5.2.17}$$

$$T(s) = \begin{bmatrix} \frac{6s}{(s^2+4s+6)} + \frac{10}{(s^2+4s+6)} \end{bmatrix} \tag{5.2.18}$$

the transfer function representation of the system is

$$\therefore \qquad \mathbf{T(s)} = \begin{bmatrix} \frac{6s+10}{(s^2+4s+6)} \end{bmatrix} \tag{5.2.19}$$

5.1 Controllability and Observabiity

5.2 Second Order System

6 Nyquist Plot

7 Compensators

8 Phase Margin