

Frame Synchronization : Global Summation of SOF/PLSC Detectors

Theresh Babu Benguluri, Raktim Goswami, Abhishek Bairagi, Siddharth Maurya, Pappu Manasa, Sandeep Khyalia , Raja Pradyumna , B Swaroop reddy and G V V Sharma*

Abstract—This manual provides a brief description about the design and implementation of digital synchronization techniques for reliable communication.

1. FRAME SYNCHRONIZATION : GLOBAL SUMMATION OF SOF/PLSC DETECTORS

Let the frequency offset be Δf and phase offset be $\Delta\phi$. Then,

$$Y_k = X_k e^{j(2\pi\Delta f k M + \phi_k)} + V_k, \quad k = 1, \dots, N \quad (1.1)$$

assuming that no pilot symbols are trasmitted. Let the phase information be θ_k , and defined as

$$e^{\theta(k)} = \frac{Y_k}{|Y_k|} \quad (1.2)$$

At the receiver, the header information is available in the form of

$$g_i(l) = x_s(l)x_s(l-i), l = 0, \dots, SOF - 1 \quad (1.3)$$

$$h_i(l) = x_p(l)x_p(l-i), l = 0, \dots, PLSC - 1 \quad (1.4)$$

where x_s are the mapped SOF symbols, x_p are the scrambled PLSC symbols, both modulated using 8-PSK for $i = 1, 2, 4, 8, 16, 32$. The SOM is choosen as a 64-bit length such that SOF and PLS each are of 32-bit length.

A special kind of correlation is performed to obtain

$$m_i(k) = \sum_{l=0}^{PLSC-1} e^{j(\theta(k-l)-\theta(k-l-i))} h_i(l), \quad (1.5)$$

$$n_i(k) = \sum_{l=0}^{SOF-1} e^{j(\theta(k-l)-\theta(k-l-i))} g_i(l), \quad (1.6)$$

$$k = 1, \dots, N \quad (1.7)$$

Compute

$$p_i(k) = \begin{cases} \max(|n_i(k - PLSC) + m_i(k)|, \\ |n_i(k - PLSC) - m_i(k)|) & k > PLSC \end{cases} \quad (1.8)$$

GLOBAL variable $G_{R,T}(k)$ [1] defined as,

$$G_{R,T}(k) = \sum_{i \geq 1} p_i(k), \quad i = 1, 2, 4, 8, 16, 32 \quad (1.9)$$

At the receiver, let us consider we have sent two types of transmission. One is PLHEADER+DATA (Y_{k1}) and another is only DATA (Y_{k2}) and the GLOBAL variables for (Y_{k1}) and (Y_{k2}) from (1.9) are $G_{1R,T}(k)$, $G_{2R,T}(k)$ respectively.

A. Global Threshold Calculation

The Global Threshold variable is defined as

$$T = \max(\max(G_{1R,T}(k)), \max(G_{2R,T}(k))) \quad (1.10)$$

The probability of false detection of plheader when only DATA frame (Y_{k2}) has been sent is defined as

$$P_{FA} = \frac{\sum \frac{\text{sign}(|Y_{k2}-T|)+1}{2}}{N} \quad (1.11)$$

The probability of missed detection of plheader when PLHEADER+DATA (Y_{k1}) has been sent is defined as

$$P_{MD} = \frac{\sum \frac{\text{sign}(T-|Y_{k1}|)+1}{2}}{N + PLSC + SOF} \quad (1.12)$$

B. Plots

Fig.1 shows the ROC curve (P_{FA} vs P_{MD}) at the receiver for frame synchronization at $\frac{E_b}{N_0} = -2$ dB and with a frequency offset of 250 KHz.

REFERENCES

*The authors are with the Department of Electrical Engineering, Indian Institute of Technology, Hyderabad 502285 India e-mail: gadepall@iith.ac.in.

[1] H. Miyashiro, E. Boutillon, C. Roland, J. Vilca, and D. D  az, "Improved Multiplierless Architecture for Header Detection in




Fig. 1: Frame Synchronization Receiver Operating Characteristics (ROC)

DVB-S2 Standard,” in *2016 IEEE International Workshop on Signal Processing Systems (SiPS)*, Oct 2016, pp. 248–253. [Online]. Available: <https://doi.org/10.1109/SiPS.2016.51>