Digital Synchronization Techniques for Reliable Communication

Theresh Babu Benguluri, Raktim Goswami, Abhishek Bairagi, Siddharth Maurya, Pappu Manasa and G V V Sharma*

Contents

***Abstract*—This manual provides a brief description about the design and implementation of digital synchronization techniques for reliable communication.**

1. Time Offset: Gardner TED

Let the mth sample in the rth received symbol time slot be

$$Y_k(m) = X_k + V_k(m), \quad k = 1, \dots, N, m = 1, \dots, M. \tag{1.1}$$

*The authors are with the Department of Electrical Engineering, Indian Institute of Technology, Hyderabad 502285 India e-mail: gadepall@iith.ac.in.



Fig. 1: SNR vs BER for varying τ.

where X_k is the transmitted symbol in the kth time slot and $V_k(m) \sim \mathcal{N}\left(0, \sigma^2\right)$. The decision variable for the kth symbol is [1]

$$U_k = \frac{1}{N} \sum_{i=1}^{N} Y_{k-i}\left(\frac{M}{2}\right) \left[Y_{k-i+1}(M) - Y_{k-i}(M)\right] \tag{1.2}$$

A. Plots

Fig. 1 is generated by the following code

```
https://github.com/gadepall/EE5837/raw/master/
    synctech/codes/time_sync_offsets.py
```

and shows the variation of the BER with respect to the SNR with different timing offsets τ for $N = 6$.

2. Frequency Offset: LR Technique

Let the frequency offset be Δf [2] . Then

$$Y_k = X_k e^{j2\pi\Delta f k M} + V_k, \quad k = 1, \dots, N \tag{2.1}$$

From (2.1),

$$Y_k X_k^* = |X_k|^2 e^{j2\pi\Delta f k M} + X_k^* V_k \tag{2.2}$$

$$\implies r_k = e^{j2\pi\Delta f k M} + \bar{V}_k \tag{2.3}$$



Fig. 2: Error variation with respect to frequency offset.



Fig. 3: Error variation with respect to the SNR. Δf = 5 MHz, Center frequency f_c = 25 GHz

where

$$r_k = Y_k X_k^*, \bar{V}_k = X_k^* V_k, |X_k|^2 = 1 \tag{2.4}$$

The autocorrelation can be calculated as

$$R(k) \triangleq \frac{1}{N-k} \sum_{i=k+1}^{N} r_i r_{i-k}^*, 1 \le k \le N-1 \tag{2.5}$$

Where N is the length of the received signal. For large centre frequency, the following yields a good approximation for frequency offset upto 40 MHz.

$$\Delta \hat{f} \approx \frac{1}{2\pi M} \frac{\sum_{k=1}^{P} \mathrm{Im}(R(k))}{\sum_{k=1}^{P} k\mathrm{Re}(R(k))}, \quad P\Delta f M << 1 \tag{2.6}$$

where P is the number of pilot symbols.

A. *Plots*

The number of pilot symbols is $P = 18$. The codes for generating the plots are available at

Fig. 2 shows the variation of the error in the offset estimate with respect to the offset Δf when the SNR = 10 dB. Similarly Fig. 3 shows the variation of the error with respect to the SNR for Δf = 5MHz.

3. Phase Offset: Feed Forward Maximum Likelihood (FF-ML)technique

Let the phase offset be $\Delta\phi$ [3] . Then for the kth pilot,

$$Y_k = X_k e^{j\Delta\phi_k} + V_k, \quad k = 1, \ldots, P \tag{3.1}$$

From (3.1),

$$Y_k X_k^* = |X_k|^2 e^{j\Delta\phi_k} + X_k^* V_k \tag{3.2}$$

$$\implies r_k = e^{j\Delta\phi_k} + \bar{V}_k \tag{3.3}$$

where

$$r_k = Y_k X_k^*, \bar{V}_k = X_k^* V_k, |X_k|^2 = 1 \tag{3.4}$$

From (3.3), the estimate for the kth pilot is obtained as

$$\Delta\hat{\phi}_k = \arg(r_k) \tag{3.5}$$

The phase estimate is then obtained using $\Delta\hat{\phi}_k$ in the following update equation as

$$\Delta\theta_k = \Delta\theta_{k-1} + \alpha SAW\left[\Delta\hat{\phi}_k - \Delta\theta_{k-1}\right] \tag{3.6}$$

Where SAW is sawtooth non-linearity

$$SAW[\phi] = [\phi]_{-\pi}^{\pi} \tag{3.7}$$

and $\alpha \le 1$. The estimate is then obtained as $\Delta\theta_P$.

A. *Plots*

Fig. 4 is generated using

```
https://github.com/gadepall/EE5837/raw/master/
    synctech/codes/Error_vs_lp.py
```

and shows the variation of the phase error in the offset estimate with respect to the pilot symbols when the SNR = 10 dB and $\alpha = 0.5$.

Similarly Fig. 5 generated by

```
https://github.com/gadepall/EE5837/blob/master/
    synctech/codes/Error_vs_snr.py
```



Fig. 4: Phase error variation with respect to pilot symbols

shows the variation of the error with respect to the SNR for pilot symbols $P = 18$ and $\alpha = 1$.



Fig. 5: $\Delta f = 5$ MHz

4. Automatic Gain Controller (AGC): Data-Aided Vector-Tracker (DA-VT)

Let the random AGC offset α, then the received symbol equation with amplitude offset as,

$$Y_k = \alpha X_k + V_k \quad k = 1, \ldots, P \tag{4.1}$$

where $\alpha = \alpha_I + j\alpha_Q$ is the gain parameter. According to [4], the $\hat{\alpha}_k$ estimate for the kth pilot is

$$\alpha_{k+1} = \alpha_k - \gamma \left[\alpha_k Y_k^p - X_k^p\right] \left[X_k^p\right]^*, \tag{4.2}$$

where γ is the AGC step size.

A. Plots

The following code plots the real and imaginary parts of the gain parameter α with respect to the number of pilot symbols P. in Fig. 6. $\gamma = 10^{-3}, SNR = 10dB$.



Fig. 6: Convergence of Digital AGC with resepct to P.

```
https://github.com/gadepall/EE5837/raw/master/
    synctech/codes/
    Digital_AGC_with_fixed_SNR.
    pytime_sync_offsets.py
```

5. Frame Synchronization : Differential detection and non-threshold peak search Algorithm

[5]

$$\Lambda = max\left(\left| \sum_{j=1}^{\frac{L_{PLSC}}{2}} R_{2j-1} R_{2j}^* T_j + \sum_{i=1}^{L_{SOF}-1} r_i r_{i+1}^* t_i \right| \right. \tag{5.1}$$

$$\left. , \left| \sum_{j=1}^{\frac{L_{PLSC}}{2}} R_{2j-1} R_{2j}^* T_j - \sum_{i=1}^{L_{SOF}-1} r_i r_{i+1}^* t_i \right| \right) \tag{5.2}$$

Where R denotes the received symbol of PLSC, r is the received symbol of SOF, T and t are the taps corresponding to the differential correlation, $L_{SOF} = 26$, $L_{PLSC} = 64$.

A. Plots

References

[1] F. Gardner, "A BPSK/QPSK Timing-Error Detector for Sampled Receivers," *IEEE Transactions on Communications*, vol. 34, no. 5, pp. 423–429, May 1986. [Online]. Available: https://doi.org/10.1109/TCOM.1986.1096561

[2] M. Luise and R. Reggiannini, "Carrier frequency recovery in all-digital modems for burst-mode transmissions," *IEEE Transactions on Communications*, vol. 43, no. 2/3/4, pp. 1169–1178, Feb 1995. [Online]. Available: https://doi.org/10.1109/26.380149

[3] E. Casini, R. D. Gaudenzi, and A. Ginesi, "DVB-S2 modem algorithms design and performance over typical satellite channels," *International Journal of Satellite Communications and Networking*, vol. 22, no. 3, pp. 281–318, 2004. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10.1002/sat.791

[4] R. De Gaudenzi and M. Luise, "Analysis and design of an all-digital demodulator for trellis coded 16-QAM transmission over a nonlinear satellite channel," *IEEE Transactions on Communications*, vol. 43, no. 2/3/4, pp. 659–668, Feb 1995. [Online]. Available: https://doi.org/10.1109/26.380085

[5] J. Han, "Optimal frame synchronization for DVB-S2," in *2008 IEEE International Symposium on Circuits and Systems*, May 2008, pp. 956–959.