

P. N. V. S. S. K. HAVISH, S. S. Ashish and G V V Sharma

CONTENTS

1	BPSK	1
2	Coherent BFSK	2
3	QPSK	3
4	M-PSK	3

Abstract—The manual frames the problems of receiver design and performance analysis in digital communication as applications of probability theory.

Download all codes in this manual from

svn co <https://github.com/gadepall/comm/trunk/modulation/manual/codes>

1 BPSK

Problem 1. The *signal constellation diagram* for BPSK is given by Fig. 1. The symbols s_0 and s_1 are equiprobable. $\sqrt{E_b}$ is the energy transmitted per bit. Assuming a zero mean additive white gaussian noise (AWGN) with variance $\frac{N_0}{2}$, obtain the symbols that are received.

Solution: The possible received symbols are

$$y|s_0 = \sqrt{E_b} + n \quad (1)$$

$$y|s_1 = -\sqrt{E_b} + n \quad (2)$$

where the AWGN $n \sim \mathcal{N}(0, \frac{N_0}{2})$.

Problem 2. From Fig. 1 obtain a decision rule for BPSK

The authors are with the Department of Electrical Engineering, IIT, Hyderabad 502285 India e-mail: {ee16btech11023, ee16btech11043, jbala, gadepall}@iith.ac.in. All material in the manuscript is released under GNU GPL. Free to use for all.




Fig. 1

Solution: The decision rule is

$$y \underset{s_1}{\overset{s_0}{\geq}} 0 \quad (3)$$

Problem 3. Repeat the previous exercise using the MAP criterion.

Problem 4. Using the decision rule in Problem 2, obtain an expression for the probability of error for BPSK.

Solution: Since the symbols are equiprobable, it is sufficient if the error is calculated assuming that a 0 was sent. This results in

$$P_e = \Pr(y < 0 | s_0) = \Pr(\sqrt{E_b} + n < 0) \quad (4)$$

$$= \Pr(-n > \sqrt{E_b}) = \Pr(n > \sqrt{E_b}) \quad (5)$$

since n has a symmetric pdf. Let $w \sim \mathcal{N}(0, 1)$. Then $n = \sqrt{\frac{N_0}{2}}w$. Substituting this in (5),

$$P_e = \Pr\left(\sqrt{\frac{N_0}{2}}w > \sqrt{E_b}\right) = \Pr\left(w > \sqrt{\frac{2E_b}{N_0}}\right) \quad (6)$$

$$= Q\left(\sqrt{\frac{2E_b}{N_0}}\right) \quad (7)$$

where $Q(x) \triangleq \Pr(w > x)$, $x \geq 0$.

Problem 5. The PDF of $w \sim \mathcal{N}(0, 1)$ is given by

$$p_w(x) = \frac{1}{\sqrt{2\pi}} \exp\left(-\frac{x^2}{2}\right), -\infty < x < \infty \quad (8)$$

and the complementary error function is defined as

$$\text{erfc}(x) = \frac{2}{\sqrt{\pi}} \int_x^\infty e^{-t^2} dt. \quad (9)$$

Show that

$$Q(x) = \frac{1}{2} \text{erfc}\left(\frac{x}{\sqrt{2}}\right) \quad (10)$$

Problem 6. Verify the bit error rate (BER) plots for BPSK through simulation and analysis for 0 to 10 dB.

Solution: The following code

```
codes/bpsk_ber.py
```

yields Fig. 2




Fig. 2

Problem 7. Show that

$$Q(x) = \frac{1}{\pi} \int_0^{\frac{\pi}{2}} e^{-\frac{x^2}{2\sin^2\theta}} d\theta \quad (11)$$

2 COHERENT BFSK

Problem 8. The signal constellation for binary frequency shift keying (BFSK) is given in Fig. 3. Obtain the equations for the received symbols.

Solution: The received symbols are given by

$$\mathbf{y}|s_0 = \begin{pmatrix} \sqrt{E_b} \\ 0 \end{pmatrix} + \begin{pmatrix} n_1 \\ n_2 \end{pmatrix}, \quad (12)$$




Fig. 3

and

$$\mathbf{y}|s_1 = \begin{pmatrix} 0 \\ \sqrt{E_b} \end{pmatrix} + \begin{pmatrix} n_1 \\ n_2 \end{pmatrix}, \quad (13)$$

where $n_1, n_2 \sim \mathcal{N}(0, \frac{N_0}{2})$. and $\mathbf{y} = \begin{pmatrix} y_1 \\ y_2 \end{pmatrix}$.

Problem 9. Obtain a decision rule for BFSK from Fig. 3.

Solution: The decision rule is

$$y_1 \underset{s_1}{\overset{s_0}{\geq}} y_2 \quad (14)$$

Definition 2.1. The joint PDF of X, Y is given by

$$p(x, y) = \frac{1}{2\pi\sigma_x\sigma_y\sqrt{1-\rho^2}} \exp\left[-\frac{1}{2(1-\rho^2)}\right] \times \left\{ \frac{(x-\mu_x)^2}{\sigma_x^2} + \frac{(y-\mu_y)^2}{\sigma_y^2} - \frac{2\rho(x-\mu_x)(y-\mu_y)}{\sigma_x\sigma_y} \right\} \quad (15)$$

where

$$\mu_x = E[X], \sigma_x^2 = \text{var}(X), \rho = \frac{E[(X-\mu_x)(Y-\mu_y)]}{\sigma_x\sigma_y}. \quad (16)$$

Problem 10. For equiprobably symbols, the MAP criterion is defined as

$$p(\mathbf{y}|s_0) \underset{s_1}{\overset{s_0}{\geq}} p(\mathbf{y}|s_1) \quad (17)$$

Use (15) in (17) to obtain (14).

Solution: According to the MAP criterion, assum-

ing equiprobably symbols,

$$p(\mathbf{y}|s_0) \stackrel{s_0}{\geq} p(\mathbf{y}|s_1) \quad (18)$$

Problem 11. Derive and plot the probability of error. Verify through simulation.

Solution: Given that s_0 was transmitted, the received symbols are

$$\mathbf{y}|s_0 = \begin{pmatrix} \sqrt{E_b} \\ 0 \end{pmatrix} + \begin{pmatrix} n_1 \\ n_2 \end{pmatrix}, \quad (19)$$

From (14), the probability of error is given by

$$P_e = \Pr(y_1 < y_2|s_0) = \Pr(\sqrt{E_b} + n_1 < n_2) \quad (20)$$

$$= \Pr(n_2 - n_1 > \sqrt{E_b}) \quad (21)$$

Note that $n_2 - n_1 \sim \mathcal{N}(0, N_0)$. Thus,

$$P_e = \Pr(\sqrt{N_0}w > \sqrt{E_b}) = \Pr\left(w > \sqrt{\frac{E_b}{N_0}}\right) \quad (22)$$

$$\Rightarrow P_e = Q\left(\sqrt{\frac{E_b}{N_0}}\right) \quad (23)$$

where $w \sim \mathcal{N}(0, 1)$. The following code plots the BER curves in Fig. 4

```
codes/fsk_ber.py
```




Fig. 4

3 QPSK

Let

$$\mathbf{y} = \mathbf{s} + \mathbf{n} \quad (24)$$

where $\mathbf{s} \in \{\mathbf{s}_0, \mathbf{s}_1, \mathbf{s}_2, \mathbf{s}_3\}$ and

$$\mathbf{s}_0 = \begin{pmatrix} \sqrt{E_s} \\ 0 \end{pmatrix}, \mathbf{s}_1 = \begin{pmatrix} 0 \\ \sqrt{E_s} \end{pmatrix}, \quad (25)$$

$$\mathbf{s}_2 = \begin{pmatrix} -\sqrt{E_s} \\ 0 \end{pmatrix}, \mathbf{s}_3 = \begin{pmatrix} 0 \\ -\sqrt{E_s} \end{pmatrix}, \quad (26)$$

$$E[\mathbf{n}] = \mathbf{0}, E[\mathbf{n}\mathbf{n}^T] = \sigma^2 \mathbf{I} \quad (27)$$

Problem 12. Show that the MAP decision for detecting \mathbf{s}_0 results in

$$|y_2| < y_1 \quad (28)$$

Problem 13. Express $\Pr(\hat{\mathbf{s}} = \mathbf{s}_0|\mathbf{s} = \mathbf{s}_0)$ in terms of r_1, r_2 . Let $X = n_2 - n_1, Y = -n_2 - n_1$, where $\mathbf{n} = (n_1, n_2)$. Their correlation coefficient is defined as

$$\rho = \frac{E[(X - \mu_x)(Y - \mu_y)]}{\sigma_x \sigma_y} \quad (29)$$

X and Y are said to be uncorrelated if $\rho = 0$

Problem 14. Show that if X and Y are uncorrelated. Verify this numerically.

Problem 15. Show that X and Y are independent, i.e. $p_{XY}(x, y) = p_X(x)p_Y(y)$.

Problem 16. Show that $X, Y \sim \mathcal{N}(0, N_0)$.

Problem 17. Show that

$$\Pr(\hat{\mathbf{s}} = \mathbf{s}_0|\mathbf{s} = \mathbf{s}_0) = \Pr(X < \sqrt{E_s}, Y < \sqrt{E_s}). \quad (30)$$

Problem 18. Show that

$$\Pr(X < \sqrt{E_s}, Y < \sqrt{E_s}) = \left(1 - Q\left(\sqrt{\frac{E_s}{N_0}}\right)\right)^2 \quad (31)$$

Problem 19. Verify the above through simulation.

Solution: This is shown in Fig. 5 through the following code.

```
codes/qpsk.py
```

Problem 20. Modify the above script to obtain the probability of symbol error.

4 M-PSK

Consider a system where $\mathbf{s}_i = \begin{pmatrix} \cos\left(\frac{2\pi i}{M}\right) \\ \sin\left(\frac{2\pi i}{M}\right) \end{pmatrix}, i = 0, 1, \dots, M-1$. Let

$$\mathbf{y}|s_0 = \begin{pmatrix} y_1 \\ y_2 \end{pmatrix} = \begin{pmatrix} \sqrt{E_s} + n_1 \\ n_2 \end{pmatrix} \quad (32)$$

Problem 26. Verify the SER through simulation.




Fig. 5

where $n_1, n_2 \sim \mathcal{N}\left(0, \frac{N_0}{2}\right)$.

Problem 21. Substituting

$$y_1 = R \cos \theta \quad (33)$$

$$y_2 = R \sin \theta \quad (34)$$

show that the joint pdf of R, θ is

$$p(R, \theta) = \frac{R}{\pi N_0} \exp\left(-\frac{R^2 - 2R\sqrt{E_s}\cos\theta + E_s}{N_0}\right) \quad (35)$$

Problem 22. Show that

$$\lim_{\alpha \rightarrow \infty} \int_0^\infty (V - \alpha) e^{-(V-\alpha)^2} dV = 0 \quad (36)$$

$$\lim_{\alpha \rightarrow \infty} \int_0^\infty e^{-(V-\alpha)^2} dV = \sqrt{\pi} \quad (37)$$

Problem 23. Using the above, show that

$$\begin{aligned} \int_0^\infty V \exp\left\{-\left(V^2 - 2V\sqrt{\gamma}\cos\theta + \gamma\right)\right\} dV \\ = e^{-\gamma\sin^2\theta} \sqrt{\gamma\pi} \cos\theta \end{aligned} \quad (38)$$

for large values of γ .

Problem 24. Find a compact expression for

$$I = 1 - \sqrt{\frac{\gamma}{\pi}} \int_{-\frac{\pi}{M}}^{\frac{\pi}{M}} e^{-\gamma\sin^2\theta} \cos\theta d\theta \quad (39)$$

Problem 25. Show that

$$P_{e|s_0} = 2Q\left(\sqrt{2\left(\frac{E_s}{N_o}\right)} \sin\frac{\pi}{M}\right) \quad (40)$$