

# Scientific Computing on Hardware

Subhodeep Chakraborty, Krishna Patil, Nara Prajwal and G.V.V. Sharma

Department of Electrical Engineering

IIT Hyderabad

Email: gadepall@ee.iith.ac.in

**Abstract**—In this paper, various algebraic and transcendental functions are implemented on microcontroller hardware. This is done by first modeling most functions using high school level differential equations, converting them to difference equations using elementary numerical techniques and then porting these algorithms to an ATMEGA328P microcontroller using AVR-GCC. In the process, we compare different numerical methods and finalize the Runge-Kutta (RK4) method for hardware implementation, based on numerical accuracy. We demonstrate the practical utility of this approach by building a scientific calculator based on the RK4 algorithm.

**Index Terms**—Scientific Calculator, Microcontroller, Runge-Kutta Method, Quake III Algorithm, Shunting Yard Algorithm, Embedded C.

## I. INTRODUCTION

Physical systems are typically modeled as a system of ordinary differential equations (ODE) where the rate of change of a state variable  $y$  is a function of time  $t$  and the state itself:  $\frac{dy}{dt} = f(t, y)$ , given an initial condition  $y(t_0) = y_0$ . Most physical systems are now being implemented on digital platforms. This requires the design and implementation of algorithms capable of approximating complex functions under tight resource constraints. With respect to the ubiquity of differential equations as descriptors of real-world systems, the algorithms under the lens are those that perform or approximate numerical integration [1].

Numerical methods for function approximation on hardware often prioritize either simplicity or specialized efficiency. Euler's method [2] is the simplest to program, yet its first-order accuracy ( $O(h)$ ) leads to significant numerical drift and instability unless excessively small step sizes are used. Second-order Runge-Kutta (RK2) methods improve precision but still feature much greater absolute error magnitudes than RK4 [3].

Alternative approximation strategies such as Taylor series or Maclaurin expansions are geometrically intuitive but often impractical for embedded systems [4]. This is because these methods require either the tedious recursive calculation of high-order derivatives, which are computationally expensive to evaluate, or for the coefficients for each function to be pre-stored, which results in memory usage piling up quickly for acceptable accuracy [5]. Also, the number of terms, and thus calculations needed for convergence, are much higher for Taylor series as compared to RK4 for the same accuracy [6]. In contrast, the RK4 framework achieves high-order accuracy without needing derivatives, instead evaluating the function at four strategically chosen intermediate points. This allows

for a more robust and maintainable implementation when derivatives are complex or unavailable [7].

For specific transcendental functions, the CORDIC algorithm is highly efficient as it uses simple shift-and-add operations instead of multiplications [8]. However, CORDIC is limited by specific convergence ranges and requires different recursive sequences for different classes of functions [9]. Linear multistep methods like Adams-Bashforth can reduce function evaluations but are not self-starting and necessitate a queue of past history to be stored that increases memory usage [10].

More advanced structural equations and orthogonal collocation methods offer low levels of error but frequently involve complex and heavy computations or iterative non-linear solvers [11]. Similarly, adaptive methods like ode45 (used in MATLAB) provide excellent accuracy but introduce variable execution times that can cause unacceptable jitter in real-time environments, such as the those mentioned above [12].

A fixed-step RK4 approach is superior for predictable performance under the constraints discussed in this work, ensuring that calculations complete reliably within strict sampling windows, such as those in robotics or flight controllers [7]. Further, the single-step nature of RK4 is more suitable for limited microcontrollers as it avoids the RAM overhead of managing past solution data.

Despite extensive research into specialized hardware like FPGAs or complex applications such as GPS orbit computation and motor control, there is a lack of a mathematically unified framework for general scientific computing on 8-bit platforms [13], [14], [12]. Most related works treat different transcendental functions as separate implementation problems rather than a single unified mathematical structure [15].

This work bridges that gap by reformulating diverse scientific functions into high school-level ODEs, providing a robust, high-precision, and conceptually accessible framework for relatively limited microcontrollers like the ATMEGA328P.

## II. SOFTWARE IMPLEMENTATION

This paper presents the implementation of scientific calculator functions such as trigonometric, logarithmic, exponential, power, factorial, and expression parsing using the C programming language on a microcontroller platform. Various numerical algorithms such as Runge-Kutta (RK4), series expansions, iterative methods, and parsing algorithms have been employed. Each function is discussed with its algorithmic basis followed

by its C implementation. Instead of using “general expansion methods” (like Taylor/Maclaurin series with many terms), each function was reformulated as a differential equation. The algorithms used to calculate the values are RK4 (for ODEs), Newton–Raphson (for refinements like inverse sqrt).

#### A. Supported Functions

TABLE I  
SUPPORTED FUNCTIONS AND OPERATIONS

| Category                  | Functions / Operations                      |
|---------------------------|---------------------------------------------|
| Trigonometric             | $\sin(x), \cos(x), \tan(x)$                 |
| Inverse Trigonometric     | $\arcsin(x), \arccos(x), \arctan(x)$        |
| Exponential / Logarithmic | $e^x, \ln(x)$                               |
| Power / Root              | $x^y, \frac{1}{\sqrt{x}}$                   |
| Factorial                 | $n!$                                        |
| Basic Arithmetic          | $+, -, \times, \div$                        |
| Constants                 | $\pi, e$                                    |
| Input Symbols             | Digits 0–9, decimal point, parentheses (, ) |

#### B. Runge–Kutta Method (RK4)

The fourth-order Runge–Kutta (RK4) method is employed to solve ordinary differential equations for trigonometric and exponential functions.[2], [16] This was chosen over alternative ODE solvers due to maintainability and accuracy. A detailed analysis of the choice of algorithm is given in Appendix B. The full derivation and step-by-step procedure for RK4 are provided in Appendix A.

#### C. Trigonometric Functions

1) *Sine Function*: The sine function is computed by solving the second-order differential equation: [17]

$$\frac{d^2y}{dx^2} + y = 0, \quad y(0) = 0, \quad y'(0) = 1 \quad (1)$$

using the fourth-order Runge–Kutta method.

System:

$$\frac{dy}{dx} = z, \quad \frac{dz}{dx} = -y, \quad y(0) = 0, \quad z(0) = 1 \quad (2)$$

The  $k_1, k_2, k_3, k_4$  correspond to the RK-4 terms of the equation  $\frac{dy}{dx} = z$  and the  $l_1, l_2, l_3, l_4$  corresponds to the RK-4 terms of the equation  $\frac{dz}{dx} = -y$

RK4 step values:

$$k_1 = h z_n, \quad (3)$$

$$l_1 = -h y_n, \quad (4)$$

$$k_2 = h \left( z_n + \frac{l_1}{2} \right), \quad (5)$$

$$l_2 = -h \left( y_n + \frac{k_1}{2} \right), \quad (6)$$

$$k_3 = h \left( z_n + \frac{l_2}{2} \right), \quad (7)$$

$$l_3 = -h \left( y_n + \frac{k_2}{2} \right), \quad (8)$$

$$k_4 = h(z_n + l_3), \quad (9)$$

$$l_4 = -h(y_n + k_3), \quad (10)$$

$$y_{n+1} = y_n + \frac{1}{6}(k_1 + 2k_2 + 2k_3 + k_4), \quad (11)$$

$$z_{n+1} = z_n + \frac{1}{6}(l_1 + 2l_2 + 2l_3 + l_4). \quad (12)$$

2) *Cosine Function*: The cosine function is computed by  $\sin(\frac{\pi}{2} - x)$ . [17]

3) *Tangent Function*: Tangent is implemented as the ratio of sine and cosine. [17]

#### D. Inverse Square Root

1) *Inverse Square Root*: The fast inverse square root algorithm (Quake III method) is used to efficiently compute  $x^{-1/2}$ . Detailed derivation and Newton–Raphson refinement are included in Appendix A.

#### E. Inverse Trigonometric Functions

1) *Arcsine*: The ODE for the arcsine function is ODE: [17]

$$\frac{dy}{dx} = \frac{1}{\sqrt{1-x^2}}, \quad y(0) = 0 \quad (13)$$

2) *Arccosine*: The identity used is: [17]

$$\arccos(x) = \frac{\pi}{2} - \arcsin(x) \quad (14)$$

3) *Arctangent*: The ODE for the arctan function is ODE: [17]

$$\frac{dy}{dx} = \frac{1}{1+x^2}, \quad y(0) = 0 \quad (15)$$

#### F. Logarithmic Functions

The natural logarithm can be obtained by solving the differential equation: [17]

$$\frac{dy}{dx} = \frac{1}{x}, \quad y(1) = 0 \quad (16)$$

which has the exact solution  $y(x) = \ln(x)$ . Using the RK4 method,  $\ln(x)$  can be approximated by integrating this ODE from  $x = 1$  to the target value.

#### G. Exponential Functions

1) *Power Function*: The power function  $y = x^w$  satisfies: [17]

$$\frac{dy}{dx} = \frac{w}{x} y, \quad y(1) = 1 \quad (17)$$

#### H. Factorial Function

The algorithm is a simple recursive function in C:

$$y_n = n \cdot y_{n-1} \quad (18)$$

[18]

#### Algorithm 1 Recursive Factorial Function

```

1: function FACTORIALRECURSIVE(x)
2:   if  $x \leq 1$  then
3:     return 1
4:   else
5:     return  $x \times \text{FactorialRecursive}(x - 1)$ 
6:   end if
7: end function

```

TABLE II  
RK4 UPDATE EQUATIONS FOR SINGLE-VARIABLE FUNCTIONS

| Function                | $k_1$                       | $k_2$                                                                | $k_3$                                                                | $k_4$                                 | $y_{n+1}$                                    |
|-------------------------|-----------------------------|----------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------|----------------------------------------------|
| Arcsine $\arcsin(x)$    | $\frac{h}{\sqrt{1-x_n^2}}$  | $\frac{h}{\sqrt{1-(x_n+\frac{h}{2})^2}}$                             | $\frac{h}{\sqrt{1-(x_n+\frac{h}{2})^2}}$                             | $\frac{h}{\sqrt{1-(x_n+h)^2}}$        | $y_n + \frac{1}{6}(k_1 + 2k_2 + 2k_3 + k_4)$ |
| Arctangent $\arctan(x)$ | $\frac{h}{1+x_n^2}$         | $\frac{h}{1+(x_n+\frac{h}{2})^2}$                                    | $\frac{h}{1+(x_n+\frac{h}{2})^2}$                                    | $\frac{h}{1+(x_n+h)^2}$               | $y_n + \frac{1}{6}(k_1 + 2k_2 + 2k_3 + k_4)$ |
| Natural Log $\ln(x)$    | $\frac{h}{x_n}$             | $\frac{h}{x_n+\frac{h}{2}}$                                          | $\frac{h}{x_n+\frac{h}{2}}$                                          | $\frac{h}{x_n+h}$                     | $y_n + \frac{1}{6}(k_1 + 2k_2 + 2k_3 + k_4)$ |
| Power $y = x^w$         | $h \cdot \frac{w}{x_n} y_n$ | $h \cdot \frac{w}{x_n+\frac{h}{2}} \left(y_n + \frac{k_1}{2}\right)$ | $h \cdot \frac{w}{x_n+\frac{h}{2}} \left(y_n + \frac{k_2}{2}\right)$ | $h \cdot \frac{w}{x_n+h} (y_n + k_3)$ | $y_n + \frac{1}{6}(k_1 + 2k_2 + 2k_3 + k_4)$ |

### I. Expression Parsing

The Shunting Yard algorithm is employed for converting infix expressions into postfix form for evaluation.

### J. Overview

The **Shunting Yard Algorithm**, proposed by Edsger Dijkstra, is a method for converting mathematical expressions in infix notation into postfix notation (Reverse Polish Notation, RPN). It relies on two structures:

- A **stack** for operators/functions
- An **output queue** for the final postfix expression

### K. Algorithm Steps

- 1) Initialize an empty stack and output queue.
- 2) For each token:
  - a) Numbers  $\rightarrow$  add to output.
  - b) Functions  $\rightarrow$  push to stack.
  - c) Operators  $\rightarrow$  pop higher/equal precedence operators from stack to output (respecting associativity), then push current operator.
  - d) "("  $\rightarrow$  push to stack.
  - e) ")"  $\rightarrow$  pop to output until matching "(" is found, discard brackets.
- 3) After processing, pop remaining operators to output.

### L. Operator Precedence

TABLE III  
OPERATOR PRECEDENCE AND ASSOCIATIVITY

| Operator       | Precedence | Associativity |
|----------------|------------|---------------|
| $\vee$ (power) | 4          | Right         |
| $*, /$         | 3          | Left          |
| $+, -$         | 2          | Left          |

### M. Example

For the expression  $3 + 4 * 2 / (1 - 5)$ , the Shunting Yard Algorithm yields the postfix form:

$$3 \ 4 \ 2 \ * \ 1 \ 5 \ - \ / \ + \quad (19)$$

Algorithmic Steps :

### Algorithm 2 Shunting Yard Algorithm (Infix to Postfix)

```

1: function SHUNTINGYARD(expr)
2:   Initialize empty stack operators
3:   Initialize empty string output
4:   for each character c in expr do
5:     if c is a number or '.' then
6:       Append c to output until number ends
7:       Append space to output
8:     else if c is a function then
9:       Push c onto operators
10:    else if c = ( then
11:      Push c onto operators
12:      Increment unmatched_brackets
13:    else if c = ) then
14:      while Top of operators  $\neq$  ( do
15:        Pop from operators and append to output
16:      end while
17:      Pop ')' from operators
18:      Decrement unmatched_brackets
19:      if Top of operators is a function then
20:        Pop function and append to output
21:      end if
22:    else if c is an operator in {+, -, *, /, !} then
23:      while operators not empty and precedence(Top of operators)  $\geq$  precedence(c) do
24:        Pop from operators and append to output
25:      end while
26:      Push c onto operators
27:    end if
28:  end for
29:  while operators not empty do
30:    Pop from operators and append to output
31:  end while
32:  return output
33: end function

```

TABLE IV  
SHUNTING YARD EXAMPLE FOR  $3 + 4 * 2 / (1 - 5)$

| Token | Action        | Stack   | Output            |
|-------|---------------|---------|-------------------|
| 3     | Add to output |         | 3                 |
| +     | Push to stack | +       | 3                 |
| 4     | Add to output | +       | 3 4               |
| *     | Push to stack | + *     | 3 4               |
| 2     | Add to output | + *     | 3 4 2             |
| /     | Pop *, push / | + /     | 3 4 2 *           |
| (     | Push to stack | + / (   | 3 4 2 *           |
| 1     | Add to output | + / (   | 3 4 2 * 1         |
| -     | Push to stack | + / ( - | 3 4 2 * 1         |
| 5     | Add to output | + / ( - | 3 4 2 * 1 5       |
| )     | Pop until (   | + /     | 3 4 2 * 1 5 -     |
| End   | Pop stack     |         | 3 4 2 * 1 5 - / + |

#### N. Reverse Polish Notation (RPN)

Reverse Polish Notation, also known as postfix notation, is a way of writing mathematical expressions in which operators follow their operands. Unlike infix notation (e.g.,  $3 + 4$ ), RPN eliminates the need for parentheses by unambiguously encoding operator precedence.

- Example (infix):  $3 + 4$
- Equivalent RPN:  $3 4 +$

This simplicity makes RPN especially suitable for evaluation using a stack-based algorithm.

#### O. Evaluating RPN

Evaluation of RPN uses a stack:

- 1) Scan tokens left to right.
- 2) Push numbers on the stack.
- 3) For operators, pop required operands, apply operation, push result.

For the above example, evaluating the postfix expression gives the result 1 as expected .

#### P. Complexity and Applications

The algorithm runs in  $O(n)$  time, where  $n$  is the number of tokens. Combined with RPN evaluation, it provides an efficient method for handling expressions in calculators, compilers, and symbolic computation systems.

#### Q. Function Handling

The Shunting Yard Algorithm can also be used to implement functions such as  $\sin(x)$ ,  $\cos(x)$ , and others. Function handling follows these rules:

- 1) When a function token is encountered, it is pushed onto the operator stack.
- 2) Arguments are processed as sub-expressions normally.
- 3) When the closing parenthesis “)” is reached:
  - Operators are popped from the stack to the output queue until the matching “(” is found.
  - The function token itself is then moved from the stack to the output queue.

As a result, function calls are correctly represented in postfix form. For example:

$$\sin(x) \rightarrow x \sin, \quad (20)$$

#### R. Conclusion

The Shunting Yard Algorithm, together with RPN evaluation, ensures efficient parsing and evaluation of mathematical expressions. It respects operator precedence, associativity, and bracket handling, making it a cornerstone in expression processing across computing applications.

#### S. Code Repository

The complete C implementations of the algorithms discussed in this paper are available at: <https://github.com/gadepall/calculator/tree/main/codes>. Instructions for installation of a software based prototype for testing the algorithms are given in Appendix C.

```

1 codes/
2 |-- ShuntingYard.c
3 |-- inv_sq_root.c
4 |-- inv_trig_func.c
5 |-- log.c
6 |-- power_func.c
7 |-- trig_func.c

```

Listing 1. Repository Structure in codes/

### III. HARDWARE IMPLEMENTATION

#### A. Hardware Required

TABLE V  
MATERIALS REQUIRED FOR THE SCIENTIFIC CALCULATOR

| Quantity | Component     |
|----------|---------------|
| 25       | Pushbuttons   |
| 1        | LCD 16×2      |
| 1        | Arduino Uno   |
| –        | Jumper wires  |
| 1        | Potentiometer |

- A button matrix for user input.
- An Arduino Uno microcontroller to process inputs and execute calculations.
- A 16×2 LCD connected to Arduino for showing results.
- Connections as shown in Fig. 2.

## B. Circuit Connections

TABLE VI  
ARDUINO TO LCD PIN CONNECTIONS

| Arduino Pin | LCD Pin | LCD Label | Description                 |
|-------------|---------|-----------|-----------------------------|
| GND         | 1       | GND       | Ground                      |
| 5V          | 2       | Vcc       | Power Supply                |
| GND         | 3       | Vee       | Contrast Control            |
| D2          | 4       | RS        | Register Select             |
| GND         | 5       | R/W       | Read/Write (fixed to Write) |
| D3          | 6       | EN        | Enable                      |
| D4          | 11      | DB4       | Data Bus (4-bit mode)       |
| D5          | 12      | DB5       | Data Bus (4-bit mode)       |
| D6          | 13      | DB6       | Data Bus (4-bit mode)       |
| D7          | 14      | DB7       | Data Bus (4-bit mode)       |
| 5V          | 15      | LED+      | Backlight Anode             |
| GND         | 16      | LED-      | Backlight Cathode           |

## C. Button Matrix

The button matrix is a grid of push-buttons arranged in rows and columns. It allows multiple buttons to be connected to the microcontroller using fewer pins.

### Working Principle:

- The Arduino scans the matrix by activating each row (setting it LOW) one at a time while reading the columns.
- When a button is pressed, it completes the circuit.
- By identifying the active row and column, the Arduino determines which button was pressed.
- Example: If second row is pressed when first column is active, the first column's second button is pressed.

This reduces the number of pins required to implement a calculator with 25 buttons.

TABLE VII  
KEY ASSIGNMENTS IN MODE 1 WITH ARDUINO PIN MAPPING

|       | Col 1     | Col 2 | Col 3 | Col 4      | Col 5 |
|-------|-----------|-------|-------|------------|-------|
| Row 1 | 0         | 1     | 2     | 3          | 4     |
| Row 2 | 5         | 6     | 7     | 8          | 9     |
| Row 3 | +         | -     | ×     | ÷          | sin(  |
| Row 4 | cos(      | tan(  | e(    | ln(        | Clear |
| Row 5 | Backspace | .     | =     | Mode shift | $\pi$ |


TABLE VIII  
KEY ASSIGNMENTS IN MODE 2 WITH ARDUINO PIN MAPPING

|       | Col 1     | Col 2   | Col 3 | Col 4        | Col 5   |
|-------|-----------|---------|-------|--------------|---------|
| Row 1 | 0         | 1       | 2     | 3            | 4       |
| Row 2 | 5         | 6       | 7     | 8            | 9       |
| Row 3 | (         | )       | $x^y$ | fact(        | arcsin( |
| Row 4 | arccos(   | arctan( | mod   | $\log_{10}($ | Clear   |
| Row 5 | Backspace | .       | =     | Mode shift   | $\pi$   |

TABLE IX  
KEYPAD ROW/COLUMN CONNECTIONS TO ARDUINO PINS

| Keypad Line | Arduino Pin |
|-------------|-------------|
| Row 1       | D8          |
| Row 2       | D9          |
| Row 3       | D10         |
| Row 4       | D11         |
| Row 5       | D12         |
| Col 1       | A0          |
| Col 2       | A1          |
| Col 3       | A2          |
| Col 4       | A3          |
| Col 5       | A4          |

Fig. 1. Button Matrix



## D. Circuit Schematic

The schematic for circuit connections is shown below,




Fig. 2. Schematic of Circuit.

## APPENDIX A

### RUNGE-KUTTA METHOD (RK4)

The RK4 method is a numerical technique to solve

$$\frac{dy}{dx} = f(x, y), \quad y(x_0) = y_0 \quad (21)$$

with step size  $h$ . The next value is calculated as:

$$y_{n+1} = y_n + \frac{1}{6}(k_1 + 2k_2 + 2k_3 + k_4) \quad (22)$$

where

$$k_1 = h \cdot f(x_n, y_n), \quad (23)$$

$$k_2 = h \cdot f(x_n + h/2, y_n + k_1/2), \quad (24)$$

$$k_3 = h \cdot f(x_n + h/2, y_n + k_2/2), \quad (25)$$

$$k_4 = h \cdot f(x_n + h, y_n + k_3). \quad (26)$$

*Quake III Algorithm:* The method obtains an initial approximation by manipulating the IEEE 754 floating-point representation of  $x$ , then refines it using Newton-Raphson iterations.

- 1) Bit manipulation with a “magic constant” (0x5f3759df) produces an initial guess  $y_0$ .
- 2) A single Newton-Raphson iteration dramatically improves accuracy.
- 3) An optional second iteration yields nearly full precision.

*Newton-Raphson Refinement:* We want to approximate

$$y = x^{-\frac{1}{2}}. \quad (27)$$

Define

$$f(y) = \frac{1}{y^2} - x, \quad f'(y) = -\frac{2}{y^3}. \quad (28)$$

Applying Newton-Raphson,

$$y_{k+1} = y_k - \frac{f(y_k)}{f'(y_k)} \quad (29)$$

$$= y_k - \frac{\frac{1}{y_k^2} - x}{-\frac{2}{y_k^3}} \quad (30)$$

$$= y_k + \frac{y_k}{2} (1 - xy_k^2) \quad (31)$$

$$= y_k \left( \frac{3}{2} - \frac{1}{2}xy_k^2 \right). \quad (32)$$

Thus one Newton-Raphson iteration is simply

$$y \leftarrow y (1.5 - 0.5xy^2). \quad (33)$$

## APPENDIX B

### COMPARATIVE ANALYSIS OF NUMERICAL METHODS

Three criteria were considered in the choosing of RK4 as the algorithm for a microcontroller base:

- Computing complexity
- Accuracy for the chosen precision level
- Memory usage

### A. Rejected Alternative Algorithms

1) *Euler's Method:* The Euler method is the simplest numerical solver. The basic idea is to approximate the curve by its tangent line, meaning it is a first order solver.

- **Forward Euler (Explicit)** The slope at the current point is used as the approximation for the value at the end of the step.

$$y_{n+1} = y_n + h \cdot f(x_n, y_n) \quad (34)$$

- **Backward Euler (Implicit)** The slope at the end of the step is used as the approximation.  $y_{n+1}$  is present on both sides of the equation, so another algorithm is needed to separate it at each step.

$$y_{n+1} = y_n + h \cdot f(x_{n+1}, y_{n+1}) \quad (35)$$

- **Drawback:** For a step size of  $h$ , the error is  $O(h)$ . Thus to reduce error, the step size would have to be increased drastically, which is computationally prohibitive.

2) *Trapezoidal Rule:* This is a second-order method approximates the integral by dividing the area under the curve into trapezoids instead of rectangles.

$$y_{n+1} = y_n + \frac{h}{2} \cdot (f(x_n, y_n) + f(x_{n+1}, y_{n+1})) \quad (36)$$

- **Drawbacks:** The error is  $O(h^2)$ . It is also implicit, meaning each step would require another iterative solving mechanism such as Newton-Raphson to separate the target variable.

*Aside: Signal Processing Perspective:* Another way to approach the previous formula is transforming it through the  $s$ -domain and  $z$ -domain in succession, this reduces the work in solving of ODEs to simple algebraic manipulations. As an example, presented here is the solution to the *sin* function, whose ODE is:

$$y'' + y = 0 \quad (37)$$

1. **Laplace Transform:** Take the Laplace transform of the ODE (assuming zero initial conditions for the transfer function derivation):

$$s^2 Y(s) + Y(s) = 1 \implies Y(s) = H(s) = \frac{1}{s^2 + 1}$$

2. **Bilinear Substitution:** Apply the Bilinear transform substitution  $s \approx \frac{2}{h} \frac{1-z^{-1}}{1+z^{-1}}$ , where  $h$  is the step:

$$H(z) = \frac{1}{\left[ \left( \frac{2}{h} \frac{1-z^{-1}}{1+z^{-1}} \right)^2 + 1 \right]}$$

3. **Algebraic Simplification:** Let  $c = 2/h$ ,  $A = c^2 + 1$ . Simplify and group by powers of  $z$

$$H(z) = \frac{(1 + z^{-1})^2}{c^2(1 - z^{-1})^2 + (1 + z^{-1})^2} \quad (38)$$

$$H(z) = \frac{1 + 2z^{-1} + z^{-2}}{c^2(1 - 2z^{-1} + z^{-2}) + (1 + 2z^{-1} + z^{-2})} \quad (39)$$

$$\frac{Y(z)}{X(z)} = \frac{1 + 2z^{-1} + z^{-2}}{(c^2 + 1) + (2 - 2c^2)z^{-1} + (c^2 + 1)z^{-2}} \quad (40)$$

$$Y(z) \cdot \left[ 1 + \frac{2 - 2c^2}{A} z^{-1} + z^{-2} \right] \quad (41)$$

$$= X(z) \cdot \frac{1}{A} [1 + 2z^{-1} + z^{-2}] \quad (42)$$

5. **Difference Equation:** Converting from  $z$ -domain to discrete time  $n$  (where  $z^{-k}Y(z) \rightarrow y_{n-k}$ ):

$$y[n] = \frac{1}{A} \underbrace{(x[n] + 2x[n-1] + x[n-2])}_{\text{Input Terms (Source of Energy)}} \quad (43)$$

$$- \underbrace{\frac{2 - 2c^2}{A} y[n-1] - y[n-2]}_{\text{Feedback Terms (Oscillation)}} \quad (44)$$

Solving for the current term  $y_n$  after the impulse has passed:

$$y_n = \frac{8 - 2h^2}{4 + h^2} y_{n-1} - y_{n-2}$$

3) *Series Expansion Methods:* Taylor/Maclaurin series can also be used for this purpose.

- **Drawbacks:** Precision cannot be achieved consistently as the number of terms needed vary with function and also with input value. As the input increases, convergence is slow, and number of terms needed to be stored in memory increases.

4) *Second-Order Runge-Kutta Methods (RK2):* A step up in accuracy from Euler's method are the second-order Runge-Kutta (RK2) methods. These methods use a preliminary slope calculation to make a more accurate step.

- **Heun's Method:** This method averages the slope at the beginning and end of the interval (using an Euler step as a predictor):

$$\tilde{y}_{n+1} = y_n + h \cdot f(x_n, y_n)$$

$$y_{n+1} = y_n + \frac{h}{2} (f(x_n, y_n) + f(x_{n+1}, \tilde{y}_{n+1}))$$

- **Drawback:** The global error is  $O(h^2)$ . While this is a significant improvement over Euler's method, it is still much less accurate than the fourth-order RK4 method ( $O(h^4)$ ). Given that RK4 only requires twice the number of function evaluations per step as these RK2 methods (four vs. two), the substantial gain in accuracy was judged as a highly favourable trade-off, as shown in Fig.3.

## B. Justification for RK4 Selection

The fixed-step RK4 method was determined to be the optimal choice for this specific hardware implementation based on the following analysis (summarized in Table X). The code for this analysis can be found at: <https://github.com/gadepall/calculator/tree/main/analysis>:




Fig. 3. Comparison of the accuracy of the algorithms

Here, each algorithm was compared against the gold-standard MPFR library up to 50 decimal places. Accuracy is represented using **Units in Last Place (ULP)** measure.

$$\text{Error}_{\text{ULP}} = \frac{|y_{\text{calc}} - y_{\text{true}}|}{\epsilon(y_{\text{true}})} \quad (45)$$

As per the results in Fig.3, RK4 demonstrates a clear dominance, with both maximum and average errors being many orders of magnitude less than the other algorithms. The Euler methods demonstrate an increasing drift from the true value with increase in input value, while the trapezoidal method, while stable in its error variation, featured much more absolute error than RK4. As expected, RK2 showed similar error variation as RK4 but much greater in magnitude.

TABLE X  
ACCURACY COMPARISON FOR  $\sin(x)$  GENERATION ( $h \approx 0.06$ )

| Algorithm      | Max Error (ULP)       | RMS Error             | Stability |
|----------------|-----------------------|-----------------------|-----------|
| RK4            | $2.38 \times 10^{11}$ | $3.44 \times 10^{-7}$ | High      |
| Trapezoidal    | $6.00 \times 10^{14}$ | $8.77 \times 10^{-4}$ | High      |
| Heun           | $1.20 \times 10^{15}$ | $1.74 \times 10^{-3}$ | Moderate  |
| Forward Euler  | $1.86 \times 10^{15}$ | $8.56 \times 10^{-2}$ | Unstable  |
| Backward Euler | $2.84 \times 10^{15}$ | $7.27 \times 10^{-2}$ | Unstable  |

## APPENDIX C SOFTWARE SETUP

### A. Termux

- 1) On your android device, follow the instructions in <https://github.com/gadepall/fwc-1> to setup and install Debian on Termux.

## B. Platformio

### 1) Install Packages

```
1 apt install avra avrdude gcc-avr  
avr-libc
```

### 2) Follow the instructions in <https://docs.platformio.org/en/stable/core/installation/methods/installer-script.html#super-quick-macos-linux> to install platformio.

### 3) Execute the following on debian

```
1 cd ide/piosetup/codes  
2 pio run
```

See Fig. 4 for the Arduino pin diagram.




Fig. 4. Arduino Pinout

## C. Arduino Droid

- 1) Install ArduinoDroid from apkpure
- 2) Open ArduinoDroid and grant all permissions
- 3) Connect the Arduino to your phone via USB-OTG
- 4) For flashing the bin files, in ArduinoDroid,

```
1 Actions->Upload->Upload Precompiled
```

then go to your working directory and select

```
1 .pio/build/uno/firmware.hex
```

for uploading hex file to the Arduino Uno

### 5) The LED beside pin 13 will start blinking

## D. App Upload

- 1) Download the files present in <https://github.com/gadepall/calculator/tree/main/software>.
- 2) Compile the C files:

```
1 gcc -shared -o libcalc.so -fPIC func.c  
pars.c
```

- 3) Copy the app APK file calci.apk to the phone Internal Storage and install it from the File Manager.
- 4) Run the server in proot-distro:

```
1 python3 server.py
```

### 5) The app now functions as a scientific calculator.

## REFERENCES

- [1] N. A. Udoh and U. P. Egbuhuzor, "Balancing precision and efficiency: Comparative analysis of numerical methods for initial value problems," *International Journal of Pure and Applied Mathematics Research*, vol. 5, no. 1, p. 61–69, Apr. 2025. [Online]. Available: <http://dx.doi.org/10.51483/IJPAMR.5.1.2025.61-69>
- [2] B. S. Grewal, *Higher Engineering Mathematics*, 43rd ed. New Delhi, India: Khanna Publishers, 2014.
- [3] N. Ahmad, S. Charan, and V. P. Singh, "Study of numerical accuracy of Runge-Kutta second, third and fourth order method," *International Journal of Computer and Mathematical Sciences (IJCMS)*, vol. 4, no. 6, pp. 111–117, June 2015. [Online]. Available: [https://www.researchgate.net/publication/279849033\\_Study\\_of\\_Numerical\\_Accuracy\\_of\\_Runge-Kutta\\_Second\\_Third\\_and\\_Fourth\\_Order\\_Method](https://www.researchgate.net/publication/279849033_Study_of_Numerical_Accuracy_of_Runge-Kutta_Second_Third_and_Fourth_Order_Method)
- [4] G. Gadisa and M. A. Islam, "Comparison of higher order Taylor's method and Runge-Kutta methods for solving first order ordinary differential equations," *Computing and Mathematical Sciences (Comp. & Math. Sci.)*, vol. 8, no. 1, pp. 12–13, January 2017. [Online]. Available: [https://www.researchgate.net/publication/314100718\\_Comparison\\_of\\_Higher\\_Order\\_Taylor's\\_Method\\_and\\_Runge-Kutta\\_Methods\\_for\\_Solving\\_First\\_Order\\_Ordinary\\_Differential\\_Equations](https://www.researchgate.net/publication/314100718_Comparison_of_Higher_Order_Taylor's_Method_and_Runge-Kutta_Methods_for_Solving_First_Order_Ordinary_Differential_Equations)
- [5] A. E. Parker, "Runge-kutta 4 (and other numerical methods for ODEs)," *Differential Equations*, 7, 2021, accessed: 2025-02-09. [Online]. Available: [https://digitalcommons.ursinus.edu/triumphs\\_differ/7](https://digitalcommons.ursinus.edu/triumphs_differ/7)
- [6] N. A. Z. M. Noar, N. I. A. Apandi, and N. Rosli, "A comparative study of Taylor method, fourth order Runge-Kutta method and Runge-Kutta Fehlberg method to solve ordinary differential equations," in *THE 7TH BIOMEDICAL ENGINEERING'S RECENT PROGRESS IN BIOMATERIALS, DRUGS DEVELOPMENT, AND MEDICAL DEVICES: The 15th Asian Congress on Biotechnology in conjunction with the 7th International Symposium on Biomedical Engineering (ACB-ISBE 2022)*, vol. 3080. AIP Publishing, 2024, p. 020003. [Online]. Available: <http://dx.doi.org/10.1063/5.0192085>
- [7] K. Murugesan, D. P. Dhayabaran, E. C. H. Amirtharaj, and D. J. Evans, "A fourth order embedded Runge-Kutta rk4em(4, 4) method based on arithmetic and centroidal means with error control," *International Journal of Computer Mathematics*, vol. 79, no. 2, p. 247–269, Jan. 2002. [Online]. Available: <http://dx.doi.org/10.1080/00207160211925>
- [8] N. Eklund, "CORDIC: Elementary function computation using recursive sequences," *The College Mathematics Journal*, vol. 32, no. 5, p. 330–333, Nov. 2001. [Online]. Available: <http://dx.doi.org/10.1080/07468342.2001.11921899>
- [9] AN5325: *How to use the CORDIC to perform mathematical functions on STM32 MCUs*, STMicroelectronics, Mar. 2024, rev 6. [Online]. Available: [https://www.st.com/resource/en/application\\_note/an5325-how-to-use-the-cordic-to-perform-mathematical-functions-on-stm32-mcus-stm.pdf](https://www.st.com/resource/en/application_note/an5325-how-to-use-the-cordic-to-perform-mathematical-functions-on-stm32-mcus-stm.pdf)
- [10] G. K. Gupta, R. Sacks-Davis, and P. E. Tescher, "A review of recent developments in solving ODEs," *ACM Computing Surveys*, vol. 17, no. 1, p. 5–47, Mar. 1985. [Online]. Available: <http://dx.doi.org/10.1145/4078.4079>
- [11] J. P. Allamaa, P. Patrinos, H. Van der Auweraer, and T. D. Son, "Safety envelope for orthogonal collocation methods in embedded optimal control," in *2023 European Control Conference (ECC)*, 2023, pp. 1–7.
- [12] A. Akpunar Bozkurt, "Real-time sensorless speed control of PMSMs using a Runge-Kutta extended Kalman filter," *Mathematics*, vol. 14, no. 2, p. 274, Jan. 2026. [Online]. Available: <http://dx.doi.org/10.3390/math14020274>
- [13] L. De Micco and H. A. Larrondo, "FPGA implementation of a chaotic oscillator using RK4 method," in *2011 VII Southern Conference on Programmable Logic (SPL)*. IEEE, Apr. 2011, p. 185–190. [Online]. Available: <http://dx.doi.org/10.1109/SPL.2011.5782646>
- [14] S. A. Medjahed, "Introduction of the Runge-Kutta method in GPS orbit computation," *International Journal of Engineering and Geosciences*, vol. 9, no. 2, p. 256–263, Jul. 2024. [Online]. Available: <http://dx.doi.org/10.26833/ijeg.1403435>
- [15] L. Moroz, V. Samoty, P. Gepner, M. Wegrzyn, and G. Nowakowski, "Power function algorithms implemented in microcontrollers and FPGAs," *Electronics*, vol. 12, no. 16, p. 3399, Aug. 2023. [Online]. Available: <http://dx.doi.org/10.3390/electronics12163399>
- [16] E. Kreyszig, *Advanced Engineering Mathematics*, 10th ed. Hoboken, NJ, USA: John Wiley & Sons, 2011.



- [17] National Council of Educational Research and Training, *Mathematics: Textbook for Class XII, Part 1 and 2*. New Delhi, India: NCERT, 2006.
- [18] G. V. V. Sharma, *C Programming in Middle School*.