AE : AEROSPACE ENGINEERING

EE25BTECH11018-Darisy Sreetej

Q.1 – Q.25 carry one mark each.

1) The constraint $A^2 = A$ on any square matrix A is satisfied for

a) the identity matrix only
b) the null matrix only
c) both the identity matrix and the null matrix
d) no square matrix A

(GATE AE 2012)

2) The general solution of the differential equation $\frac{d^2y}{dt^2} + \frac{dy}{dt} - 2y = 0$ is

a) $Ae^{-t} + Be^{2t}$
b) $Ae^{-2t} + Be^{-t}$
c) $Ae^{-2t} + Be^{t}$
d) $Ae^{t} + Be^{2t}$

(GATE AE 2012)

3) An aircraft in trimmed condition has zero pitching moment at

a) its aerodynamic centre
b) its centre of gravity
c) 25% of its mean aerodynamic chord
d) 50% of its wing root chord

(GATE AE 2012)

4) In an aircraft, constant roll rate can be produced using ailerons by applying

a) a step input
b) a ramp input
c) a sinusoidal input
d) an impulse input

(GATE AE 2012)

5) For a symmetric airfoil, the lift coefficient for zero degree angle of attack is

a) -1.0 b) 0.0 c) 0.5 d) 1.0

(GATE AE 2012)

6) The critical Mach number of an airfoil is attained when

a) the freestream Mach number is sonic
b) the freestream Mach number is supersonic
c) the Mach number somewhere on the airfoil is unity
d) the Mach number everywhere on the airfoil is supersonic

(GATE AE 2012)

7) The shadowgraph flow visualization technique depends on

a) the variation of the value of density in the flow
b) the first derivative of density with respect to spatial coordinate
c) the second derivative of density with respect to spatial coordinate
d) the third derivative of density with respect to spatial coordinate

(GATE AE 2012)

8) The Hohmann ellipse used as earth-Mars transfer orbit has

a) apogee at earth and perigee at Mars
b) both apogee and perigee at earth
c) apogee at Mars and perigee at earth
d) both apogee and perigee at Mars

(GATE AE 2012)

9) The governing equation for the static transverse deflection of a beam under an uniformly distributed load, according to Euler-Bernoulli (engineering) beam theory, is a
a) 2^{nd} order linear homogenous partial differential equation
b) 4^{th} order linear non-homogenous ordinary differential equation
c) 2^{nd} order linear non-homogenous ordinary differential equation
d) 4^{th} order nonlinear homogenous ordinary differential equation

(GATE AE 2012)

10) The Poisson's ratio, ν of most aircraft grade metallic alloys has values in the range

a) $-1 \leq \nu \leq 0$ b) $0 \leq \nu \leq 0.2$ c) $0.2 \leq \nu \leq 0.4$ d) $0.4 \leq \nu \leq 0.5$

(GATE AE 2012)

11) The value of k for which the system of equations $x + 2y + kz = 1$; $2x + ky + 8z = 3$ has no solution is

a) 0 b) 2 c) 4 d) 8

(GATE AE 2012)

12) If $u(t)$ is a unit step function, the solution of the differential equation $m\frac{d^2x}{dt^2} + kx = u(t)$ in Laplace domain is

a) $\frac{1}{s(ms^2 + k)}$
b) $\frac{1}{ms^2 + k}$
c) $\frac{s}{ms^2 + k}$
d) $\frac{1}{s^2(ms^2 + k)}$

(GATE AE 2012)

13) The general solution of the differential equation $\frac{dy}{dx} - 2\sqrt{y} = 0$ is

a) $y - \sqrt{x} + C = 0$
b) $y - x + C = 0$
c) $\sqrt{y} - \sqrt{x} + C = 0$
d) $\sqrt{y} - x + C = 0$

(GATE AE 2012)

14) During the ground roll manoeuvre of an aircraft, the force(s) acting on it parallel to the direction of motion

a) is thrust alone.
b) is drag alone.
c) are both thrust and drag.
d) are thrust, drag and a part of both weight and lift.

(GATE AE 2012)

15) An aircraft in a steady climb suddenly experiences a 10% drop in thrust. After a new equilibrium is reached at the same speed, the new rate of climb is

a) lower by exactly 10%.
b) lower by more than 10%.
c) lower by less than 10%.
d) an unpredictable quantity.

(GATE AE 2012)

16) In an aircraft, the dive manoeuvre can be initiated by

a) reducing the engine thrust alone.
b) reducing the angle of attack alone.
c) generating a nose down pitch rate.
d) increasing the engine thrust alone.

(GATE AE 2012)

17) In an aircraft, elevator control effectiveness determines

a) turn radius.
b) rate of climb.
c) forward-most location of the centre of gravity.
d) aft-most location of the centre of gravity.

(GATE AE 2012)

18) The Mach angle for a flow at Mach 2.0 is

a) 30° b) 45° c) 60° d) 90°

(GATE AE 2012)

19) For a wing of aspect ratio AR, having an elliptical lift distribution, the induced drag coefficient is (where C_L is the lift coefficient)

a) $\frac{C_L}{\pi AR}$ b) $\frac{C_L^2}{\pi AR}$ c) $\frac{C_L}{2\pi AR}$ d) $\frac{C_L^2}{\pi AR^2}$

(GATE AE 2012)

20) Bernoulli's equation is valid under steady state

a) only along a streamline in inviscid flow, and between any two points in potential flow.
b) between any two points in both inviscid flow and potential flow.
c) between any two points in inviscid flow, and only along a streamline in potential flow.
d) only along a streamline in both inviscid flow and potential flow.

(GATE AE 2012)

21) The ratio of flight speed to the exhaust velocity for maximum propulsion efficiency is

a) 0.0 b) 0.5 c) 1.0 d) 2.0

(GATE AE 2012)

22) The ideal static pressure coefficient of a diffuser with an area ratio of 2.0 is

a) 0.25 b) 0.50 c) 0.75 d) 1.0

(GATE AE 2012)

23) A rocket is to be launched from the bottom of a very deep crater on Mars for earth return. The specific impulse of the rocket, measured in seconds, is to be normalized by the acceleration due to gravity at

a) the bottom of the crater on Mars.
b) Mars standard "sea level".
c) earth's standard sea level.
d) the same depth of the crater on earth.

(GATE AE 2012)

24) In a semi-monocoque construction of an aircraft wing, the skin and spar webs are the primary carriers of

a) shear stresses due to an aerodynamic moment component alone.
b) normal (bending) stresses due to aerodynamic forces.
c) shear stresses due to aerodynamic forces alone.
d) shear stresses due to aerodynamic forces and a moment component.

(GATE AE 2012)

25) The logarithmic decrement measured for a viscously damped single degree of freedom system is 0.125. The value of the damping factor in % is closest to

a) 0.5 b) 1.0 c) 1.5 d) 2.0

(GATE AE 2012)

26) The integration $\int_0^1 x^3 dx$ computed using trapezoidal rule with $n = 4$ intervals is .... (GATE AE 2012)

27) An aircraft has a steady rate of climb of $300\,m/s$ at sea level and $150\,m/s$ at $2500\,m$ altitude. The time taken (in sec) for this aircraft to climb from $500\,m$ altitude to $3000\,m$ altitude is .... (GATE AE 2012)

28) An airfoil generates a lift of $80\,N$ when operating in a freestream flow of $60\,m/s$. If the ambient pressure and temperature are $100\,kPa$ and $290\,K$ respectively (specific gas constant is $287\,J/kg \cdot K$), the circulation on the airfoil in m^2/s is .... (GATE AE 2012)

29) A rocket motor has combustion chamber temperature of $2600\,K$ and the products have molecular weight of $25\,g/mol$ and ratio of specific heats 1.2. The universal gas constant is $8314\,J/kg \cdot mol \cdot K$. The value of theoretical c^* (in m/s) is .... (GATE AE 2012)

30) The mode shapes of an un-damped two degrees of freedom system are $\{1 \;\; 0.5\}^T$ and $\{1 \;\; -0.675\}^T$. The corresponding natural frequencies are $0.45\,Hz$ and $1.247\,Hz$. The maximum amplitude (in mm) of vibration of the first degree of freedom due to an initial displacement of $\{2 \;\; 1\}^T$ (in mm) and zero initial velocities is ... (GATE AE 2012)

Questions Q.31 to Q.55 are multiple choice type

31) The n^{th} derivative of the function $y = \frac{1}{x+3}$ is

a) $\frac{(-1)^n n!}{(x+3)^{n+1}}$ b) $\frac{(-1)^{n+1} n!}{(x+3)^{n+1}}$ c) $\frac{(-1)^n (n+1)!}{(x+3)^n}$ d) $\frac{(-1)^n n!}{(x+3)^n}$

(GATE AE 2012)

32) The volume of a solid generated by rotating the region between semi-circle $y = 1 - \sqrt{1 - x^2}$ and straight line $y = 1$, about x-axis, is

a) $\pi^2 - \frac{4}{3}\pi$ b) $4\pi^2 - \frac{1}{3}\pi$ c) $\pi^2 - \frac{3}{4}\pi$ d) $\frac{\pi}{4}\pi^2 - \pi$

(GATE AE 2012)

33) One eigenvalue of the matrix $A = \begin{pmatrix} 2 & 7 & 105 \\ 2 & 251 & 6 \\ 5 \end{pmatrix}$ is -9.33. One of the other eigenvalues is

a) 18.33 b) -18.33 c) $18.33 - 9.33i$ d) $18.33 + 9.33i$

(GATE AE 2012)

34) If an aircraft takes off with 10% less fuel in comparison to its standard configuration, its range is

a) lower by exactly 10%
b) lower by more than 10%
c) lower by less than 10%
d) an unpredictable quantity

(GATE AE 2012)

35) An aircraft has an approach speed of 144 kmph with a descent angle of 6.6°. If the aircraft load factor is 1.2 and constant deceleration at touch down is $0.25g$ ($g = 9.81\,\text{m/s}^2$), its total landing distance approximately over a 15 m high obstacle is

a) 1830 m b) 1380 m c) 830 m d) 380 m

(GATE AE 2012)

36) An aircraft is trimmed straight and level at true air speed (TAS) of 100 m/s at standard sea level (SSL). Further, pull of 5 N holds the speed at 90 m/s without re-trimming at SSL (air density = 1.22 kg/m^3). To fly at 3000 m altitude (air density = 0.91 kg/m^3) and 120 m/s TAS without re-trimming, the aircraft needs

a) 1.95 N upward force
b) 1.95 N downward force
c) 1.85 N upward force
d) 1.75 N downward force

(GATE AE 2012)

37) An oblique shock wave with a wave angle β is generated from a wedge angle of θ. The ratio of the Mach number downstream of the shock to its normal component is

a) $\sin(\beta - \theta)$ b) $\cos(\beta - \theta)$ c) $\sin(\theta - \beta)$ d) $\cos(\theta - \beta)$

(GATE AE 2012)

38) In a closed-circuit supersonic wind tunnel, the convergent-divergent (C-D) nozzle and test section are followed by a C-D diffuser to swallow the starting shock. Here, we should have the

a) diffuser throat larger than the nozzle throat and the shock located just at the diffuser throat.
b) diffuser throat larger than the nozzle throat and the shock located downstream of the diffuser throat.
c) diffuser throat of the same size as the nozzle throat and the shock located just at the diffuser throat.
d) diffuser throat of the same size as the nozzle throat and the shock located downstream of the diffuser throat.

(GATE AE 2012)

39) A vortex flowmeter works on the principle that the Strouhal number of 0.2 is a constant over a wide range of flow rates. If the bluff-body diameter in the flowmeter is 20 mm and the piezo-electric transducer registers the vortex shedding frequency to be 10 Hz, then the velocity of the flow would be measured as

a) 0.1 m/s b) 1 m/s c) 10 m/s d) 100 m/s

(GATE AE 2012)

40) The stagnation temperatures at the inlet and exit of a combustion chamber are 600 K and 1200 K, respectively. If the heating value of the fuel is 44 MJ/kg and specific heat at constant pressure for air and hot gases are 1.005 kJ/kg.K and 1.147 kJ/kg.K respectively, the fuel-to-air ratio is

a) 0.0018 b) 0.018 c) 0.18 d) 1.18

(GATE AE 2012)

41) A solid propellant of density 1800 kg/m^3 has a burning rate law $r = 6.65 \times 10^{-3} p^{0.45}$ mm/s, where p is pressure in Pascals. It is used in a rocket motor with a tubular grain with an initial burning area of 0.314 m^2. The characteristic velocity is 1450 m/s. What should be the nozzle throat diameter to achieve an equilibrium chamber pressure of 50 bar at the end of the ignition transient?

a) 35 mm b) 38 mm c) 41 mm d) 45 mm

(GATE AE 2012)

42) A bipropellant liquid rocket motor operates at a chamber pressure of 40 bar with a nozzle throat diameter of 50 mm. The characteristic velocity is 1540 m/s. If the fuel-oxidizer ratio of the propellant is 1.8, and the fuel density is 900 kg/m^3, what should be the minimum fuel tank volume for a burn time of 8 minutes

a) 1.65 m^3 b) 1.75 m^3 c) 1.85 m^3 d) 1.95 m^3

(GATE AE 2012)

43) The propellant in a single stage sounding rocket occupies 60% of its initial mass. If all of it is expended instantaneously at an equivalent exhaust velocity of 3000 m/s, what would be the altitude attained by the payload when launched vertically? (Neglect drag and assume acceleration due to gravity to be constant at 9.81 m/s^2)

a) 315 km b) 335 km c) 365 km d) 385 km

(GATE AE 2012)

44) The Airy stress function, $\phi = \alpha x^2 + \beta xy + \gamma y^2$ for a thin square panel of size $l \times l$ automatically satisfies compatibility. If the panel is subjected to uniform tensile stress, σ_o, on all four edges, the traction boundary conditions are satisfied by

a) $\alpha = \sigma_o/2;\ \beta = 0;\ \gamma = \sigma_o/2$
b) $\alpha = \sigma_o;\ \beta = 0;\ \gamma = \sigma_o$
c) $\alpha = 0;\ \beta = \sigma_o/4;\ \gamma = 0$
d) $\alpha = 0;\ \beta = \sigma_o/2;\ \gamma = 0$

(GATE AE 2012)

45) The boundary condition of a rod under longitudinal vibration is changed from fixed-fixed to fixed-free. The fundamental natural frequency of the rod is now k times the original frequency, where k is

a) $\frac{1}{2}$ b) 2 c) $\frac{1}{\sqrt{2}}$ d) $\sqrt{2}$

(GATE AE 2012)

46) A spring-mass system is viscously damped with a viscous damping constant c. The energy dissipated per cycle when the system is undergoing a harmonic vibration $X\cos\omega_d t$ is given by

a) $\pi c\omega_d X^2$ b) $\pi\omega_d X^2$ c) $\pi c\omega_d^2 X$ d) $\pi c\omega_d^2 X^2$

(GATE AE 2012)

47) Buckling of the fuselage skin can be delayed by

a) increasing internal pressure
b) placing stiffeners farther apart
c) reducing skin thickness
d) placing stiffeners farther and decreasing internal pressure

(GATE AE 2012)

Common Data Questions

Common Data for Questions 48 and 49: A wing and tail are geometrically similar, while tail area is one-third of the wing area and distance between two aerodynamic centres is equal to wing semi-span ($b/2$). In addition, following data is applicable: $\epsilon_a = 0.3,\ C_L = 1.0,\ C_{L_\epsilon} = 0.08$ / deg., $\overline{c} = 2.5$ m, $b = 30$ m, $C_{M_{ac}} = 0,\ \eta_t = 1$. The symbols have their usual aerodynamic interpretation.

48) The maximum distance that the centre of gravity can be behind aerodynamic centre without destabilizing the wing-tail combination is

a) 0.4 m b) 1.4 m c) 2.4 m d) 3.4 m

(GATE AE 2012)

49) The angle of incidence of tail to trim the wing-tail combination for a 5% static margin is

a) -1.4° b) -0.4° c) 0.4° d) 1.4°

(GATE AE 2012)

Common Data for Questions 50 and 51: A thin long circular pipe of 10 mm diameter has porous walls and spins at 60 rpm about its own axis. Fluid is pumped out of the pipe such that it emerges radially relative to the pipe surface at a velocity of 1 m/s. [Neglect the effect of gravity.]

50) What is the radial component of the fluid's velocity at a radial location 0.5 m from the pipe axis?

a) 0.01 m/s b) 0.1 m/s c) 1 m/s d) 10 m/s

(GATE AE 2012)

51) What is the tangential component of the fluid's velocity at the same radial location as above?

a) 0.01 m/s b) 0.03 m/s c) 0.10 m/s d) 0.31 m/s

(GATE AE 2012)

Linked Answer Questions Statement for Linked Answer Questions 52 and 53: Air at a stagnation temperature of 15°C and stagnation pressure 100 kPa enters an axial compressor with an absolute velocity of 120 m/s. Inlet guide vanes direct this absolute velocity to the rotor inlet at an angle of 18° to the axial direction. The rotor turning angle is 27° and the mean blade speed is 200 m/s. The axial velocity is assumed constant through the stage.

52) The blade angle at the inlet of the rotor is

a) 25.5° b) 38.5° c) 48.5° d) 59.5°

(GATE AE 2012)

53) If the mass flow rate is 1 kg/s, the power required to drive the compressor is

a) 50.5 kW b) 40.5 kW c) 30.5 kW d) 20.5 kW

(GATE AE 2012)

Statement for Linked Answer Questions 54 and 55: A thin-walled spherical vessel (1 m inner diameter and 10 mm wall thickness) is made of a material with $|\sigma_y|$ = 500 MPa in both tension and compression.

54) The internal pressure p_t at yield, based on the von Mises yield criterion, if the vessel is floating in space, is approximately

a) 500 MPa b) 250 MPa c) 100 MPa d) 20 MPa

(GATE AE 2012)

55) If the vessel is evacuated (internal pressure = 0) and subjected to external pressure, yielding according to the von Mises yield criterion (assuming elastic stability until yield)

a) occurs at about half the pressure Y p
b) occurs at about double the pressure Y p
c) occurs at about the same pressure Y p
d) never occurs.

(GATE AE 2012)

General Aptitude (GA) Questions

Q.56 – Q.60 carry one mark each.

56) Choose the most appropriate alternative from the options given below to complete the following sentence: I . . . to have bought a diamond ring.

a) have a liking b) should have liked c) would like d) may like

(GATE AE 2012)

57) Choose the most appropriate alternative from the options given below to complete the following sentence: Food prices . . . again this month.

a) have raised b) have been raising c) have been rising d) have arose

(GATE AE 2012)

58) Choose the most appropriate alternative from the options given below to complete the following sentence: *The administrators went on to implement yet another unreasonable measure, arguing that the measures were already . . . and one more would hardly make a difference.*

a) reflective b) utopian c) luxuriant d) unpopular

(GATE AE 2012)

59) Choose the most appropriate alternative from the options given below to complete the following sentence: *To those of us who had always thought him timid, his . . . came as a surprise.*

a) intrepidity b) inevitability c) inability d) inertness

(GATE AE 2012)

60) The arithmetic mean of five different natural numbers is 12. The largest possible value among the numbers is

a) 12 b) 40 c) 50 d) 60

(GATE AE 2012)

Q.61 – Q.65 carry two marks each.

61) Two policemen, A and B, fire once each at the same time at an escaping convict. The probability that A hits the convict is three times the probability that B hits the convict. If the probability of the convict not getting injured is 0.5, the probability that B hits the convict is

a) 0.14 b) 0.22 c) 0.33 d) 0.40

(GATE AE 2012)

62) The total runs scored by four cricketers P, Q, R, and S in years 2009 and 2010 are given in the following table:

Player	2009	2010
P	802	1008
Q	765	912
R	429	619
S	501	701

The player with the lowest percentage increase in total runs is

a) P b) Q c) R d) S

(GATE AE 2012)

63) If a prime number on division by 4 gives a remainder of 1, then that number can be expressed as

a) sum of squares of two natural numbers
b) sum of cubes of two natural numbers
c) sum of square roots of two natural numbers
d) sum of cube roots of two natural numbers

(GATE AE 2012)

64) Two points (4, p) and (0, q) lie on a straight line having a slope of 3/4. The value of $(p - q)$ is

a) -3 b) 0 c) 3 d) 4

(GATE AE 2012)

65) **In the early nineteenth century, theories of social evolution were inspired less by Biology than by the conviction of social scientists that there was a growing improvement in social institutions. Progress was taken for granted and social scientists attempted to discover its laws and phases.** Which one of the following inferences may be drawn with the greatest accuracy from the above passage?
Social scientists

a) did not question that progress was a fact.
b) did not approve of Biology.
c) framed the laws of progress.
d) emphasized Biology over Social Sciences.

(GATE AE 2012)

GATE 2012 - Answer Key - Paper : AE

Paper	Question no.	Key	Paper	Question no.	Key
AE	1	C	AE	36	B
AE	2	C	AE	37	A
AE	3	B	AE	38	B
AE	4	D	AE	39	B
AE	5	B	AE	40	B
AE	6	C	AE	41	B
AE	7	C	AE	42	B
AE	8	C	AE	43	D
AE	9	B	AE	44	A
AE	10	C	AE	45	A
AE	11	C	AE	46	A
AE	12	A	AE	47	A
AE	13	D	AE	48	B
AE	14	D	AE	49	A
AE	15	B	AE	50	A
AE	16	C	AE	51	Marks to All
AE	17	C	AE	52	Marks to All
AE	18	A	AE	53	Marks to All
AE	19	B	AE	54	D
AE	20	A	AE	55	C
AE	21	C	AE	56	C
AE	22	Marks to All	AE	57	C
AE	23	C	AE	58	D
AE	24	D	AE	59	A
AE	25	D	AE	60	C
AE	26	0.26 to 0.27	AE	61	A
AE	27	13 to 14	AE	62	B
AE	28	1.1 to 1.2	AE	63	A
AE	29	1430 to 1440	AE	64	C
AE	30	2	AE	65	A
AE	31	A			
AE	32	A			
AE	33	A			
AE	34	B			
AE	35	Marks to All			