

Problem 2.10.52

ee25btech11023-Venkata Sai

September 2, 2025

1 Problem

2 Solution

- Coplanarity
- Finding projection
- Conclusion
- Plot

3 C Code

4 Python Code

Problem

Let $\mathbf{a} = \hat{\mathbf{i}} + 2\hat{\mathbf{j}} + \hat{\mathbf{k}}$, $\mathbf{b} = \hat{\mathbf{i}} - \hat{\mathbf{j}} + \hat{\mathbf{k}}$ and $\mathbf{c} = \hat{\mathbf{i}} + \hat{\mathbf{j}} - \hat{\mathbf{k}}$. A vector in the plane of $\mathbf{a}$ and $\mathbf{b}$ whose projection on $\mathbf{c}$ is $\frac{1}{\sqrt{3}}$, is

- ① $4\hat{\mathbf{i}} - \hat{\mathbf{j}} + 4\hat{\mathbf{k}}$
- ② $3\hat{\mathbf{i}} + \hat{\mathbf{j}} - 3\hat{\mathbf{k}}$
- ③ $2\hat{\mathbf{i}} + \hat{\mathbf{j}} - 2\hat{\mathbf{k}}$
- ④ $4\hat{\mathbf{i}} + \hat{\mathbf{j}} - 4\hat{\mathbf{k}}$

Coplanarity

Let $\mathbf{r}$ be coplanar to $\mathbf{a}$ and $\mathbf{b}$

$$\mathbf{r} = \mathbf{a} + t\mathbf{b} \quad (1.1)$$

$$= \begin{pmatrix} 1 \\ 2 \\ 1 \end{pmatrix} + t \begin{pmatrix} 1 \\ -1 \\ 1 \end{pmatrix} = \begin{pmatrix} 1+t \\ 2-t \\ 1+t \end{pmatrix} \quad (1.2)$$

Finding projection

Given the projection of $\mathbf{r}$ on $\mathbf{c}$ is $\frac{1}{\sqrt{3}}$

$$\frac{\mathbf{r} \cdot \mathbf{c}}{\|\mathbf{c}\|} = \frac{1}{\sqrt{3}} \quad (1.3)$$

$$\mathbf{r} \cdot \mathbf{c} = \mathbf{r}^T \mathbf{c} = \begin{pmatrix} 1+t & 2-t & 1+t \end{pmatrix} \begin{pmatrix} 1 \\ 1 \\ -1 \end{pmatrix} \quad (1.4)$$

$$= 1+t+2-t-1-t = 2-t \quad (1.5)$$

$$\|\mathbf{c}\|^2 = \mathbf{c}^T \mathbf{c} = \begin{pmatrix} 1 & 1 & -1 \end{pmatrix} \begin{pmatrix} 1 \\ 1 \\ -1 \end{pmatrix} \quad (1.6)$$

$$= 1+1+1 = 3 \quad (1.7)$$

$$\frac{|2-t|}{\sqrt{3}} = \frac{1}{\sqrt{3}} \quad (1.8)$$

Conclusion

yielding

$$(2 - t) = \pm 1 \quad (1.9)$$

$$\implies t = 1 \text{ or } 3 \quad (1.10)$$

When $t=1$, we have

$$\mathbf{r} = \begin{pmatrix} 2 \\ 1 \\ 2 \end{pmatrix} \quad (1.11)$$

When $t=3$, we have

$$\mathbf{r} = \begin{pmatrix} 4 \\ -1 \\ 4 \end{pmatrix} \quad (1.12)$$

Hence Option(1) is the correct answer

Plot




Figure:

C Code

```
void get_vectors(double* vector_data) {  
    vector_data[0] = 1.0; vector_data[1] = 2.0; vector_data[2] =  
        1.0;  
    vector_data[3] = 1.0; vector_data[4] = -1.0; vector_data[5] =  
        1.0;  
    vector_data[6] = 1.0; vector_data[7] = 1.0; vector_data[8] =  
        -1.0;  
    vector_data[9] = 4.0; vector_data[10] = -1.0; vector_data[11]  
        = 4.0;  
}
```


Calling C Function

```
import ctypes
import numpy as np
def load_vectors_from_c():
    lib = ctypes.CDLL('./plane.so')
    # Define the C function signature
    get_vectors_c = lib.get_vectors
    get_vectors_c.argtypes = [ctypes.POINTER(ctypes.c_double)]
    get_vectors_c.restype = None

    vector_data = np.zeros(12, dtype=np.float64)
    get_vectors_c(vector_data.ctypes.data_as(ctypes.POINTER(
        ctypes.c_double)))
    # Reshape the data and return the individual vectors
    vectors_from_c = vector_data.reshape(4, 3)
    a, b, c, v = vectors_from_c[0], vectors_from_c[1],
        vectors_from_c[2], vectors_from_c[3]
    return a, b, c, v
```

Python Code for Plotting

```
#Code by GVV Sharma  
#September 12, 2023  
#Revised July 21, 2024  
#released under GNU GPL  
  
import sys  
import matplotlib.pyplot as plt  
import numpy as np  
sys.path.insert(0, '/workspaces/urban-potato/matgeo/codes/  
    CoordGeo/')  
from call import load_vectors_from_c  
hat_symbol = '\u0302'  
from line.funcs import *  
from triangle.funcs import *  
from conics.funcs import circ_gen  
  
a, b, c, v = load_vectors_from_c()
```

Python Code for Plotting

```
vx, vy, vz = v[0], v[1], v[2]
j_part_str = f"+ {vy}j{hat_symbol}" if vy >= 0 else f"- {abs(vy)}j{hat_symbol}"
k_part_str = f"+ {vz}k{hat_symbol}" if vz >= 0 else f"- {abs(vz)}k{hat_symbol}"
print(f"The vector in the plane of a and b is: {vx}i{hat_symbol} {j_part_str} {k_part_str}")

# Create a 3D plot
fig = plt.figure(figsize=(10, 8))
ax = fig.add_subplot(111, projection='3d')
origin = [0, 0, 0]

# Plot vectors
vectors = {'a': (a, 'r'), 'b': (b, 'g'), 'c': (c, 'b'), 'v': (v, 'orange')}
for name, (vec, color) in vectors.items():
    x, y, z = int(vec[0]), int(vec[1]), int(vec[2])
    j_part = f"+ {y}j{hat_symbol}" if y >= 0 else f"- {abs(y)}j{hat_symbol}"
```

Python Code for Plotting

```
k_part = f"+ {z}k{hat_symbol}" if z >= 0 else f"- {abs(z)}k{hat_symbol}"
label_text = f'${name}$ = {x}i{hat_symbol} {j_part} {k_part}'
ax.quiver(origin[0], origin[1], origin[2], vec[0], vec[1], vec[2],
          color=color, label=label_text,
          arrow_length_ratio=0.1, linewidth=2)
ax.text(vec[0]*1.1, vec[1]*1.1, vec[2]*1.1, f'${name}$',
        color=color, fontsize=15)
# Plot the plane
x_plane = np.linspace(-5, 5, 10); y_plane = np.linspace(-5, 5, 10)
X, Y = np.meshgrid(x_plane, y_plane)
Z = X
ax.plot_surface(X, Y, Z, alpha=0.2, color='gray')
```

Python Code for Plotting

```
ax.view_init(elev=25, azim=45)
ax.set_xlabel('X'); ax.set_ylabel('Y'); ax.set_zlabel('Z')
ax.set_title('Finding a vector that is in the plane of vectors a
             and b')
ax.legend()
ax.grid(True)
ax.set_xlim([-5, 5]); ax.set_ylim([-5, 5]); ax.set_zlim([-5, 5])
```