

137 . You are a professional robber planning to rob houses along a street. Each house has a certain amount of money stashed. All houses at this place are arranged in a circle. That means the first house is the neighbor of the last one. Meanwhile, adjacent houses have security systems connected, and it will automatically contact the police if two adjacent houses were broken into on the same night.

Examples:

(i) Input : nums = [2, 3, 2]

Output : The maximum money you can rob without alerting the police is 3(robbing house 1).

AIM: To find the maximum money you can rob without alerting the police

PROGRAM:

```
def rob(nums):  
    if not nums:  
        return 0  
    if len(nums) == 1:  
        return nums[0]  
    def rob_linear(nums):  
        if not nums:  
            return 0  
        if len(nums) == 1:  
            return nums[0]  
  
        prev2 = 0  
        prev1 = nums[0]  
  
        for i in range(1, len(nums)):  
            current = max(prev1, prev2 + nums[i])  
            prev2 = prev1  
            prev1 = current  
  
        return prev1  
    return max(rob_linear(nums[:-1]), rob_linear(nums[1:]))  
nums1 = [2, 3, 2]
```

```
nums2 = [1, 2, 3, 1]
```

```
nums3 = [2, 7, 9, 3, 1]
```

```
print("Maximum money you can rob without alerting the police:")
```

```
print("Case 1:", rob(nums1))
```

```
print("Case 2:", rob(nums2))
```

```
print("Case 3:", rob(nums3))
```

```
Maximum money you can rob without alerting the police:  
Case 1: 3  
Case 2: 4  
Case 3: 11
```

OUTPUT:

TIME COMPLEXITY:  $O(n)$