



RISC-V External Debug Security Specification

Version v0.5.0, 2024-08-05: Draft

Table of Contents

Preamble.....	1
Copyright and license information.....	2
Contributors.....	3
1. Introduction.....	4
1.1. Terminology.....	4
2. External Debug Security Threat model.....	6
3. Sdsec (ISA extension).....	7
3.1. External Debug.....	7
3.1.1. M-mode Debug Control.....	7
3.1.2. Supervisor Domain Debug Control.....	8
3.1.3. Debug Access Privilege.....	8
Configuring dcsr for External Debugger Access Privileges.....	8
3.1.4. Privilege Level Changing Instructions.....	9
3.1.5. Interrupt during Single Stepping.....	9
3.2. Trace.....	9
M-Mode Trace Control.....	9
Supervisor Domain Trace Control.....	10
3.3. Trigger (Sdtrig).....	10
3.3.1. M-mode accessibility to <code>dmode</code>	10
3.3.2. External triggers.....	11
3.3.3. Trigger chain.....	11
3.3.4. Sdtrig CSR.....	11
3.4. Other CSR updates.....	12
3.4.1. Debug Control and Status (dcsr).....	12
3.4.2. Debug PC (dpc) and Debug Scratch Register (dscratch0 and dscratch1).....	13
3.4.3. Sdsec CSR.....	13
4. Debug Module Security Extension (non-ISA extension).....	14
4.1. External Debug Security Extensions Discovery.....	14
4.2. Halt.....	14
4.3. Reset.....	15
4.4. Keepalive.....	15
4.5. Abstract Commands.....	15
4.5.1. Relaxed Permission Check <code>relaxedpriv</code>	15
4.5.2. Address Translation <code>aamvirtual</code>	15
4.6. System Bus Access.....	15
4.7. Security Fault Error Reporting.....	16
4.8. Update of Debug Module Registers.....	16
Appendix A: Theory of Operation.....	17

A.1. Debug Module security control	17
A.2. Trace Encoder security control	18
Bibliography	19

Preamble



This document is in the [Development state](#)

Expect potential changes. This draft specification is likely to evolve before it is accepted as a standard. Implementations based on this draft may not conform to the future standard.

Copyright and license information

This specification is licensed under the Creative Commons Attribution 4.0 International License (CC-BY 4.0). The full license text is available at creativecommons.org/licenses/by/4.0/.

Copyright 2023-2024 by RISC-V International.

Contributors

This RISC-V specification has been contributed to directly or indirectly by (in alphabetical order): Aote Jin (editor), Beeman Strong, Gokhan Kaplayan, Greg Favor, Iain Robertson, Joe Xie (editor), Ravi Sahita, Robert Chyla, Ved Shanbhogue, Vicky Goode

Chapter 1. Introduction

Debugging and tracing are essential tools utilized by developers to identify and rectify software and hardware issues, optimize performance, and ensure robust system functionality. The debugging and tracing extensions in RISC-V ecosystem play a pivotal role in enabling these capabilities, allowing developers to monitor and control the execution of programs during the development, testing and production phases. However, the current RISC-V Debug and trace specification grants the external debugger highest privilege in the system, regardless of the privilege level at which the target system is running. It leads to privilege escalation issues when multiple actors are present.

This specification defines non-ISA extension [Debug Module Security Extension \(non-ISA extension\)](#) and ISA extension [Sdsec \(ISA extension\)](#) to address the above security issues in the current *The RISC-V Debug Specification* [1] and trace specifications [2] [3].

A summary of the changes introduced by *The RISC-V External Debug Security Specification* follows.:

- **Per-Hart Debug Control:** Introduce per-hart control knobs to control whether external debug is allowed in M-mode and/or supervisor domains [4]
- **Debug Mode:** External debugger can only halt the hart and enter debug mode when debug is allowed in current privilege mode; all operations are executed with [debug access privilege](#) instead of M-mode privilege
- **Memory Access:** Memory access from a hart's point of view using a Program Buffer or the Abstract Command must be checked by the hart's memory protection mechanisms as if the hart is running at [debug access privilege](#); memory access from Debug Module using System Bus Access block without involving a hart must be checked by system memory protection mechanism, such as IOPMP or WorldGuard
- **Register Access:** Register access using Program Buffer or the Abstract Command works as if the hart is running in [debug access privilege](#) instead of M-mode privilege
- **Triggers:** Triggers (with action=1) can only fire or match when external debug is allowed in current privilege
- **Per-Hart Trace Control:** Introduce per-hart knobs to control whether tracing is allowed in M-mode and supervisor domains

1.1. Terminology

Abstract command	A high-level command in Debug Module used to interact with and control harts
Debug Access Privilege	The privilege with which abstract commands or instructions in program buffers access hardware resources
Debug Mode	An additional privilege mode to support off-chip debugging
Hart	A RISC-V hardware thread
IOPMP	Input-Output Physical Memory Protection unit
M-mode	The highest privileged mode in the RISC-V privilege model

PMA	Physical Memory Attributes
PMP	Physical Memory Protection unit
Program buffer	A buffer in Debug Module to execute arbitrary instructions on a hart
Supervisor domain	A isolated supervisor execution context defined in RISC-V Supervisor Domains Access Protection [4]
Trace encoder	A piece of hardware that takes in instruction execution information from a RISC-V hart and transforms it into trace packets

Chapter 2. External Debug Security Threat model

Modern SoC development consists of several different actors who may not trust each other, resulting in the need to isolate actors' assets during the development and debugging phases. The current RISC-V Debug specification [1] grants external debuggers the highest privilege in the system regardless of the privilege level at which the target system is running. This leads to privilege escalation issues when multiple actors are present.

For example, the owner of a SoC, who needs to debug their M-mode firmware, may be able to use the external debugger to bypass PMP lock (pmpcfg.L=1) and attack Boot ROM (the SoC creator's asset).

Additionally, RISC-V privilege architecture supports multiple software entities or "supervisor domains" that do not trust each other. The supervisor domains are managed by secure monitor running in M-mode, they are isolated from each other by PMP/IOPMP and they may need different debug policies. The entity that owns secure monitor wants to disable external debug when shipping the secure monitor, however, the entity that owns the supervisor domain needs to enable external debug to develop the supervisor domain. Since the external debugger will be the granted highest privilege in the system, a malicious supervisor domain will be able to compromise M-mode secure monitor with the external debugger.

Chapter 3. Sdsec (ISA extension)

This chapter introduces the Sdsec ISA extension, which enhances the Sdext extension defined in *The RISC-V Debug Specification* [1]. The Sdsec extension provides privilege based protection for debug operations and triggers in Sdtrig [1]. Furthermore, it constrains trace functionality [2] according to RISC-V privilege levels.

3.1. External Debug

Chapter 3 of *The RISC-V Debug Specification* [1] outlines all mandatory and optional debug operations. The operations listed below are affected by the Sdsec extension, other operations remain unaffected. In the context of this chapter, **debug operations** refer to those listed below.

Debug operations affected by Sdsec

- Halting the hart to enter Debug Mode
- Executing Program buffer
- Serving abstract commands (Access Register, Quick Access, Access Memory)

When external debug is disallowed in running privilege level, the hart behaves as the following:

- The hart will not enter Debug Mode. Halt requests, except those generated by Quick Access will remain pending until debug is allowed.
- Triggers with `action=1` will not match or fire.
- Abstract commands without halting and Quick Access will be dropped and set `cmderr` to 6.

The subsequent subsections describe how external debug is authorized by [M-mode debug control](#) and [supervisor domain debug control](#).



A pending request to enter Debug Mode can dynamically change from a disallowed state to an allowed state due to updates in debug controls. For example, once the software completes executing confidential code, it can grant debuggability for an external debugger. Afterwards, the software can enter a `while(1)` loop, waiting for the debugger to take control and break out of the loop.

3.1.1. M-mode Debug Control

An input port, named `mdbgcn[i]`, is introduced to control the debuggability of M-mode for each hart `i` as depicted in [Figure 1](#). When `mdbgcn[i]` is set to 1, the following rules apply:

- The [debug access privilege](#) for the hart `i` can be configured to any legal privilege level
- The [debug operations](#) are permitted when hart `i` executes in all modes
- Abstract commands without halting the hart `i` carries M-mode privilege if supported

When `mdbgcn[i]` is set to 0, the [debug operations](#) are disallowed and the [behaviors](#) applies when the hart `i` runs in M-mode.



Since each hart has an input port for `mdbgen`, the implementation can choose to group several harts together and use one signal to drive their ports or assign each hart a dedicated signal. For example, a homogeneous computing system can consolidate all `mdbgen[i]` into a single port to enforce a unified debug policy across all harts.

3.1.2. Supervisor Domain Debug Control

The `Smsdedbg` extension [4] introduces `sdedbgalw` field (bit 7) in CSR `msdcfg` to control the debuggability of supervisor domains. The `sdedbgalw` along with `mdbgen[i]` determines the debug allowed privilege levels, as illustrated in Table 1. The `debug access privilege` can only be configured to debug allowed levels.

Table 1. External debug allowed privilege levels per debug controls

<code>mdbgen[i]</code>	<code>sdedbgalw</code>	Debug allowed privilege levels
1	Don't care	All
0	1	All except M
0	0	None

When debug is allowed in supervisor domain, `debug operations` are allowed when hart executes in supervisor domain. The abstract commands without halting the hart carries supervisor mode privilege if supported.

3.1.3. Debug Access Privilege

The **debug access privilege** is defined as the privilege level granted to the external debugger to access hardware resources with abstract commands or program buffers. Memory and register accesses from Debug Mode also carry **debug access privilege** instead of always with M-mode. The **debug access privilege** is represented by the `prv` and `v` fields in `dcsr`. The legal privilege levels programmable to `dcsr` in Debug Mode are elaborated in Section 3.1.3.1. Debugger accesses to registers and memory will be checked by permission check mechanisms against **debug access privilege**, and trigger traps if they violate corresponding rules.

Configuring `dcsr` for External Debugger Access Privileges

The `dcsr` (at 0x7b0) is always accessible in Debug Mode and the `prv` and `v` fields in the `dcsr` have been modified to authorize privilege for external debug accesses. Upon transitioning into Debug Mode, the `prv` and `v` fields are updated to the privilege level the hart was previously operating in. The maximum debug privilege level that can be configured in `prv` and `v` is determined in Table 2. The fields retain legal values when the `prv` and `v` are configured with an illegal privilege level. Illegal privilege levels include unsupported levels and any level higher than the maximum allowed debug privilege. When the hart resumes from Debug Mode, the current privilege mode and virtualization mode are changed to that specified by `prv` and `v`.

Table 2. Determining maximum debug access privilege with `mdbgen[i]` and `sdedbgalw`

mdbgen[i]	sdedbgalw	Maximum debug privilege allowed
1	Don't care	M
0	1	S(HS)
0	0	None



As the **prv** and **v** fields in **dcsr** are Write Any Read Legal (WARL) fields, the external debugger is able to read back the written value to determine the maximum debug privilege level.

3.1.4. Privilege Level Changing Instructions

The RISC-V Debug Specification [1] defines that the instructions that change the privilege mode have UNSPECIFIED behavior when executed within the Program Buffer, with exception of the **ebreak** instruction. In **Sdsec**, those instructions including **mret**, **sret**, **uret**, **ecall**, must either act as NOP or trigger an exception (stopping execution and setting **cmderr** to 3) in Program Buffer. Notably, these instructions retain their normal functionality during single stepping.

3.1.5. Interrupt during Single Stepping

The interrupt can be disabled by **stepie** in the **dcsr** during single stepping. When **mdbgen[i]** is 1, **stepie** disables interrupts in all privilege modes for hart *i*. When **mdbgen[i]** is 0 and **sdedbgalw** is 1, only interrupts delegated to the supervisor domain are disabled, while interrupts that trap to M-mode are not affected.



When debugging is only allowed for the supervisor domain, M-mode interrupts must not be disabled. Otherwise, debugging might impact the behavior of other parts of the system. For example, if a context switch for the supervisor domain triggered by a timer interrupt is suppressed, some real-time workloads might not be completed on time, resulting in unexpected errors.

3.2. Trace

When **Sdsec** is supported, the optional sideband signal to trace encoder, **sec_check[i]** [2], must be implemented for each hart *i*. The **sec_check[i]** signal is only cleared when trace is allowed by **M-mode trace control** and/or **supervisor domain trace control**.

M-Mode Trace Control

For each hart *i*, an input port, **mtrcen[i]**, controls M-mode trace availability. Setting **mtrcen[i]** to 1 enables M-mode and supervisor domain trace by clearing the **sec_check[i]** signal to 0 across all privilege levels. Conversely, if **mtrcen[i]** is set to 0, the **sec_check[i]** signal cannot be cleared when the hart *i* runs in M-mode.



For a homogeneous computing system, similar to M-mode debug control, the implementation can consolidate all **mtrcen[i]** into a single port to constrain trace

capability across all harts.

Supervisor Domain Trace Control

The Smsdetr extension introduces `sdetr calw` field (bit 8) in CSR `msdcfg` within hart *i*. The `sec_check[i]` signal for hart *i* in supervisor domain is determined by the `sdetr calw` field and `mtrcen[i]`. When the logical-OR of `sdetr calw` and `mtrcen[i]` is 1, the `sec_check[i]` signal is cleared while the hart *i* runs in supervisor domain.

When both `sdetr calw` and `mtrcen[i]` are set to 0, the `sec_check[i]` signal cannot be cleared at all.

Table 3. Status of the `sec_check[i]` sideband signal across privilege levels

<code>mtrcen</code>	<code>sdetr calw</code>	M-mode	Supervisor domain
1	x	<code>sec_check[i] = 0</code>	<code>sec_check[i] = 0</code>
0	1	<code>sec_check[i] = 1</code>	<code>sec_check[i] = 0</code>
0	0	<code>sec_check[i] = 1</code>	<code>sec_check[i] = 1</code>



The `sec_check` signal serves as an additional signal for the trace module, indicating that trace output is prohibited due to security controls. Functionally, `sec_check` behaves identically to the halted signal. Both `sec_check` and halted signals cannot be active simultaneously. Reserved for future applications, the combined state of [`sec_check`, halted] as 0b11 remains unutilized. In cases where a trace module lacks support for the `sec_check` signal, the hart may alternatively toggle the halted signal to restrict trace output.

3.3. Trigger (Sdtrig)

Triggers configured to enter Debug Mode can only fire or match when external debug is allowed, as outlined in Table 1. A trigger enabled for a privilege level higher than debug allowed privilege is not accessible by an external debugger. When this trigger is selected using `tselect`, it always reads as 0, and any writes to it are ignored.



Implementations must ensure that pending triggers intending to enter Debug Mode match or fire only when the hart is in a state where debug is allowed. For example, if an interrupt traps the hart to a debug-disallowed privilege mode, the trigger can only take effect either before the privilege is updated and control flow is transferred to the trap handler, or after the interrupt is completely handled and returns from the trap handler. The implementation must prevent Debug Mode from being entered in an intermediate state where privilege is changed or the PC is updated. This also applies to scenarios where a trigger is configured to enter Debug Mode before instruction execution and an interrupt occurs simultaneously.

3.3.1. M-mode accessibility to `dmode`

When Sdsec extension is implemented, `dmode` is read/write for both M-mode and Debug Mode when

mdbgen[i] is 0 and remains only accessible to Debug Mode when mdbgen[i] is 1.



The **dmode** being read/write allows M-mode to switch trigger context. The trigger can form a side-channel to debug disallowed supervisor domains from a debug allowed supervisor domain if the trigger context is not switched. Although the trigger cannot fire or match in disallowed supervisor domain to enter Debug Mode, the malicious debugger can exploit it by setting a trigger to raise breakpoint exception (**action** = 0) when it is in debug allowed supervisor domain. If the trigger hits in debug disallowed supervisor domain, the external debugger can indirectly observe the executed PC, accessed memory address or read/write data in debug disallowed supervisor domain by the checking value in **hit0/hit1**. As the **dmode** is accessible when mdbgen[i] is 0, such attack can be mitigated by having M-mode firmware switch the trigger context at supervisor domain boundary.

3.3.2. External triggers

The external trigger outputs (with **action** = 8/9) will not fire or match when the privilege level of the hart exceeds debug allowed privilege as specified in [Table 1](#).

The external trigger input can be driven by any input signals, e.g. the external trigger output from another hart or interrupt signals etc. The input signals cause the trigger (with **action** = 1) to fire only when the hart is allowed to debug. The initiators of these signals are responsible for determining whether the signal is allowed to assert. For example, if the external trigger input of hart i is connected to external trigger output of hart j. The assertion of output signal from hart j is determined by its own allowed privilege level for debug. The output signal of hart j must not assert when debug is disallowed. Similarly, signals from other module in the system are managed by the individual module. When the module is not allowed to debug, the signal connected to external trigger input must not be asserted.

3.3.3. Trigger chain

The privilege level of the trigger chain is determined by the trigger enabled for the highest privilege level inside the chain. The entire trigger chain cannot be modified if the chain privilege level exceeds debug allowed privilege level.



This represents a balance between usability and hardware complexity. There may be instances where the triggers are linked across different privilege levels (e.g., from S-mode to M-mode), while the external debugger may only have access with S-mode privilege. The external debugger should not modify the chain, because it could be suppressed or incorrectly match or fire in M-mode.

3.3.4. Sdtrig CSR

The CSRs tcontrol, scontext, hcontext, mcontext, and mscontext must follow access rules defined in [debug access privilege](#). Meanwhile, tselect, tdata1, tdata2, and tdata3 are read/write accessible when debug is allowed. If debug is disallowed, writes to these registers are ignored, and reads return zero. The table below illustrates the access conditions for tselect, tdata1, tdata2, and tdata3.

Table 4. Tselect, tdata1, tdata2, tdata3 CSR access condition in Debug Mode

Register	Access condition
tselect(0x7a0)	mdbgen[i] == 1 sdedbgalw == 1
tdata1(0x7a1)	mdbgen[i] == 1 sdedbgalw == 1
tdata2(0x7a2)	mdbgen[i] == 1 sdedbgalw == 1
tdata3(0x7a3)	mdbgen[i] == 1 sdedbgalw == 1
tinfo(0x7a4)	mdbgen[i] == 1 sdedbgalw == 1

The fields in mcontrol, mcontrol6, icount, itrigger, etrigger, and tmexttrigger are read/write accessible only when the access conditions are met. When access is disallowed, writes to these fields are ignored, and reads return zero.

Table 5. Tdata1 fields access condition against privilege granted to external debugger

Field	Access condition
m	mdbgen[i] == 1
s	mdbgen[i] == 1 sdedbgalw == 1
u	mdbgen[i] == 1 sdedbgalw == 1
vs	mdbgen[i] == 1 sdedbgalw == 1
vu	mdbgen[i] == 1 sdedbgalw == 1

3.4. Other CSR updates

3.4.1. Debug Control and Status (dcsr)

The dcsr is always accessible in Debug Mode. The access rules for field **prv** and **v** are addressed in subsection [Section 3.1.3.1](#). Beside **prv** and **v**, the access condition of remaining fields are listed in the following table. When the access conditions are met, they are read/write accessible. When access is disallowed, writes to these fields are ignored, and reads return zero.

Table 6. Dcsr fields access condition against privilege granted to external debugger

Field	Access condition
debugver	mdbgen[i] == 1 sdedbgalw == 1
extcause	mdbgen[i] == 1 sdedbgalw == 1
cetrig	mdbgen[i] == 1
ebreakvs	mdbgen[i] == 1 sdedbgalw == 1
ebreakvu	mdbgen[i] == 1 sdedbgalw == 1
ebreakm	mdbgen[i] == 1
ebreaks	mdbgen[i] == 1 sdedbgalw == 1
ebreaku	mdbgen[i] == 1 sdedbgalw == 1

Field	Access condition
stepie	mdbgen[i] == 1 sdedbgalw == 1
stoptime	mdbgen[i] == 1
mprven	mdbgen[i] == 1
nmip	mdbgen[i] == 1

3.4.2. Debug PC (dpc) and Debug Scratch Register (dscratch0 and dscratch1)

Debug PC (at 0x7b1) and Debug Scratch Register (at 0x7b2 and 0x7b3) are not restricted by [debug access privilege](#), they are always accessible in Debug Mode.

3.4.3. Sdsec CSR

The Sdsec extension does not introduce any new CSR. The CSR control knobs in [msdcfg](#) for supervisor domain debug and trace are specified in Smsdedbg and Smsdetr extension respectively in *RISC-V Supervisor Domains Access Protection* [4]. The Smsdedbg and/or Smsdetr extension must be implemented to support security control for debugging and/or tracing in supervisor domain.

Chapter 4. Debug Module Security Extension (non-ISA extension)

This chapter outlines the security enhancements defined for the Debug Module as non-ISA extension. The debug operations listed below are modified by the non-ISA extension. All features in this chapter must be implemented in Debug Module to achieve external debug security. If any hart in the system implements the Sdsec extension, the Debug Module must also implement the non-ISA extension. The debug operations affected by the non-ISA extension include:

- Halt
- Reset
- Keepalive
- Abstract commands (Access Register, Quick Access, Access Memory)
- System bus access

4.1. External Debug Security Extensions Discovery

The ISA and non-ISA external debug security extensions impose security constraints and introduce non-backward-compatible changes. The presence of the extensions can be determined by polling the `allsecured` or/and `anysecured` bits in `dmstatus` [Table 7](#). If the field `allsecured` or `anysecured` is set to 1, it represents that all or any selected harts adopt the Sdsec extension. When any hart adopts the Sdsec extension, it indicates the Debug Module implements Debug Module Security Extension as described in this chapter.

4.2. Halt

The halt behavior for a hart is detailed in [Section 3.1](#). According to *The RISC-V Debug Specification* [1], a halt request must be responded within one second. However, this constraint must be removed as the request might be pending due to the situations where debugging is disallowed. In the case of halt-on-reset request, the request is only acknowledged by the hart when it is permitted to debug after the deassertion of reset. Besides, when a Quick Access abstract command is issued to a hart while the hart is not yet allowed to debug, the Quick Access cannot halt the hart, and the Debug Module will receive a security error fault (`cmderr=6`).



The halt action in Quick Access is handled differently because other types of halts can be canceled by external debugger when debugging is disallowed, while the Quick Access command can only complete successfully or respond with an error. Otherwise, the debug interface to the selected hart will appear to be hung. Additionally, reset is not always applicable to the hart to recover from a hang situation. To avoid such situations, the halt action in Quick Access must be handled separately by the hart.

4.3. Reset

The hartreset operation resets selected harts. When M-mode is not allowed to be debugged, the hart will raise a security fault error to Debug Module. The debugger could monitor the error by polling `allsecfault` or/and `anysecfault` in `dmstatus`.

The ndmreset operation is a system-level reset not tied to hart privilege levels and reset the entire system (excluding the Debug Module). It can only be secured by the system. Thus, it must be de-featured. The debugger can determine support for the ndmreset operation by setting the field to 1 and subsequently verifying the returned value upon reading.

4.4. Keepalive

The keepalive bit serves as an optional request for the hart to remain available for debugging. This bit only takes effect when M-mode is allowed to be debugged; otherwise, the hart behaves as if the bit is not set.

4.5. Abstract Commands

The hart's response to abstract commands is detailed in [Section 3.1](#). The following subsection delineates the constraints when the Debug Module issues the abstract commands.

4.5.1. Relaxed Permission Check `relaxedpriv`

The `relaxedpriv` field is hardwired to 0.

4.5.2. Address Translation `aamvirtual`

The field `aamvirtual` in the command (at 0x17 in the Debug Module) determines whether the Access Memory command uses a physical or virtual address. When an Access Memory command is issued with `aamvirtual`=0, the hart must check whether the physical access is allowed to access memory. The hart responds with an exception to the Debug Module when M-mode is not permitted to debug, `tvm` (in `mstatus`) is set to 1, and `mode` (in `satp`) enables any kind of virtual translation. In the event of an exception, the Debug Module set `cmderr` to 3 and clear the data registers to 0.

4.6. System Bus Access

The System Bus Access must be checked by bus initiator protection mechanisms such as IOPMP [5], WorldGuard [6]. The bus protection unit can return error to Debug Module on illegal access, in that case, Debug Module will set `sberror` to 6 (security fault error).




Trusted entities like RoT should configure IOPMP or equivalent protection before granting debug access to M-mode. Similarly, M-mode should apply the protection before enabling supervisor domain debug.

4.7. Security Fault Error Reporting

A dedicated error code, security fault error (cmderr 6), is included in **cmderr** of abstractcs (at 0x16 in Debug Module). Misconfigurations of the dcsr and issuance of abstract commands under disallowed circumstance can signify such an error. Additionally, the bus security fault error (serror 6) is introduced in **serror** of sbcs (at 0x38 in Debug Module) to denote errors related to system bus access.

The error raised by resethaltreq, reset can be identified through the fields **allsecfault** and **anysecfault** in dmstatus. Error status bits are internally maintained for each hart, with the **allsecfault** and **anysecfault** fields indicating the error status of the currently selected harts. These error statuses are sticky and can only be cleared by writing 1 to **acksecfault** in dmcs2.


4.8. Update of Debug Module Registers



Register 1: Newly introduced fields in dmstatus

Table 7. Details of newly introduced fields in dmstatus

Field	Description	Access	Reset
allsecured	The field is 1 when all currently selected harts implement Sdsec extension	R	-
anysecured	The field is 1 when any currently selected hart implements Sdsec extension	R	-
allsecfault	The field is 1 when all currently selected harts have raised security fault due to reset or keepalive operation.	R	-
anysecfault	The field is 1 when any currently selected hart has raised security fault due to reset or keepalive operation.	R	-



Register 2: Newly introduced acksecfault in dmcs2

Table 8. Detail of acksecfault in dmcs2

Field	Description	Access	Reset
acksecfault	0 (nop): No effect. 1 (ack): Clears error status bits for any selected harts.	W1	-

Appendix A: Theory of Operation

This chapter explains the theory of operation for the External Debug Security Extension. The subsequent diagram illustrates the reference implementation of security control for the Debug Module and trace encoder, respectively.

A.1. Debug Module security control

As outlined in the specification, the security control on the Debug Module can vary for each hart. The dedicated security policy for hart *i* is enforced by the input port `mdbggen[i]` and the `sdedbgalw` field inside CSR `msdcfg`. The security control logic examines all debug operations and triggers (with `action=1`) firing/matching based on `mdbggen[i]`, `sdedbgalw`, and the privilege level of the hart. The failed action will either be dropped or pending. Additionally, the platform-specific external trigger inputs must obey to platform constraints, which must be carefully handled by platform owner. The `mdbggen[i]` can be bundled in an MMIO (Memory-Mapped I/O) outside the hart, such as in the Debug Module, or implemented as fuses.

The privilege level of the hart is determined by code execution, while the debug requests are validated against the privilege level generated by the hart. This process involves two actors, which may lead to a potential Time-of-Check Time-of-Use (TOCTOU) issue. To mitigate this, the implementation must ensure that the inspection and execution of debug requests occur within the same privilege level of the hart. Failure to do so could result in debug requests bypassing access controls intended for higher privilege levels. If the accesses fail the security check, it must prompt an immediate termination of access to prevent any information leakage.

When the external debugger is stepping through an instruction that triggers a transition to a higher privilege level, the security control logic must verify against debug capability according to [Table 1](#) before entering Debug Mode. If debugging is permitted, the hart re-enters Debug Mode after executing the instruction. Otherwise, the hart continues executing with the pending single step request until it becomes debuggable and can re-enter Debug Mode. In scenarios where multiple supervisor domains are debuggable, the secure monitor in M-mode may switch the context during single stepping. In such cases, the debugger might stop in a different application than the original one. Users of the debugger should be mindful of this possibility.

Application-level debugging is primarily accomplished through self-hosted debugging, allowing the management of debug policies at the supervisor/hypervisor level. As a result, user-level debugging management is not addressed within this extension.



Figure 1. The security control on Debug Module

A.2. Trace Encoder security control

Similar to the Debug Module, the trace encoder is controlled by the `mtrcen[i]` and `sdetrca1w` in CSR `msdcfg` for each hart `i`. The halted sideband signal to the trace encoder is determined by [Table 3](#).




Figure 2. The security control on trace module

Bibliography

- [1] “RISC-V Debug Specification.” [Online]. Available: github.com/riscv/riscv-debug-spec.
- [2] “RISC-V Efficient Trace for RISC-V.” [Online]. Available: github.com/riscv-non-isa/riscv-trace-spec.
- [3] “RISC-V N-Trace (Nexus-based Trace) Specification.” [Online]. Available: github.com/riscv-non-isa/tg-nexus-trace.
- [4] “RISC-V Supervisor Domains Access Protection.” [Online]. Available: github.com/riscv/riscv-smmmtt.
- [5] “RISC-V IOPMP Architecture Specification.” [Online]. Available: github.com/riscv-non-isa/iopmp-spec/releases.
- [6] “WorldGuard Specification.” [Online]. Available: github.com/riscv-admin/security/blob/main/papers/worldguard%20proposal.pdf.