IEEE Access
Multidisciplinary | Rapid Review | Open Access Journal

Received 23 June 2025, accepted 12 July 2025, date of publication 17 July 2025, date of current version 25 July 2025.

Digital Object Identifier 10.1109/ACCESS.2025.3590237

RESEARCH ARTICLE

From Vision to Voice: A Multi-Modal Assistive Framework for the Physically Impaired

SUHAS BHAT, PRAJWAL BHAT, AND SUCHETA V. KOLEKAR, (Member, IEEE)
Manipal Institute of Technology, Manipal Academy of Higher Education, Manipal, Karnataka 576104, India
Corresponding author: Sucheta V. Kolekar (kolekar.sucheta@gmail.com)

ABSTRACT Providing people with visual and physical limitations their ability to access textual content continues to be a difficult challenge. A desktop-assisted system with automated computer processing enables the conversion of text found in images into audible speech. The application uses Python to develop its interface with Tkinter libraries and implements Tesseract OCR for optical character recognition that receives images through real-time capture enabled by OpenCV. Through the googletrans library, the system enables multilingual operations (more than 100 languages) for text processing and translation across all languages accessible via Google Translate. The system converts extracted or translated text into speech output using Google Text-to-Speech (gTTS) that plays back audio through system default media players as. mp3 files. Users experience intuitive interaction with the interface because it features hover effect characteristics, accessible control elements, and language selection through a dropdown menu. Through an expandable structural design, the system delivers multilingual text-to-speech capabilities, which prove useful in assistive technology applications for accessibility needs.

INDEX TERMS Image-to-text, text-to-speech, OCR, Tesseract, Google Translate, gTTS, pytesseract, CRNN, multilingual, Tkinter, translation API, handwritten text recognition, real-time webcam capture.

I. INTRODUCTION

OCR technology, together with TTS systems enabled through technological advancement, allows better accessibility of digital content to users who face visual and physical limitations. OCR allows machines to recognize image text, resulting in TTS conversion into spoken words that translate visual data into auditory information. The current OCR technology bases its operation on standard methods, which present difficulties when encountering text with varying letterforms, together with noise and language fluctuations. Through OCR, machines transform scanned files and captured images, along with handwritten texts, into text they can read. Tesseract OCR serves as the backbone of this project because it functions as a standard open-source engine created by Google, which uses the pytesseract Python wrapper to process images and extract text inside Python applications. This system enables text recognition of both printed materials and handwritten content, which makes it appropriate for various real-world documentation needs. The text recognition accuracy gets better due to data processing methods, including grayscale conversion, noise removal, and thresholding, which improve the readability of text areas.

Once the system retrieves extracted text from the document, it sends it to the Google Text-to-Speech (gTTS) Application Programming Interface for text conversion into speech. This module provides multiple language support through the natural audio synthesis feature, which benefits visually impaired users to hear written content as spoken voice. The speech synthesis engine operates through deep learning models located on the backend to generate audio files that the system's default audio device will play. The application provides language selection for users who need multilingual capabilities based on their linguistic backgrounds and is easily integrated for speech synthesis.

The project's central innovation combines a user-friendly graphical user interface, which is developed using the Tkinter framework from Python. The application provides a unified interface that enables users to upload images, followed by text extraction, selecting preferred dialects, and generating audio

The associate editor coordinating the review of this manuscript and approving it for publication was Amin Zehtabian.

© 2025 The Authors. This work is licensed under a Creative Commons Attribution 4.0 License.
For more information, see https://creativecommons.org/licenses/by/4.0/

without the need for different software or technical skills. This system overcomes standard OCR applications, which only produce text outputs, and basic screen readers, which operate only with digital content, because it enables users to read dynamic images through spoken text output. Due to its modular structure, the system can develop into real-time video OCR capabilities, as well as voice-based interactions and translation API support for multilingual functionality. Due to its design, the system operates effectively and on a large scale, as well as providing affordable accessibility for visually impaired users, elderly citizens, and people who have literacy difficulties.

While OCR and TTS technologies have been extensively studied, most existing systems are either limited to static inputs, operate in monolingual settings, or lack end-to-end accessibility features. The novelty of our work lies in developing a real-time, multilingual OCR—Translation—TTS pipeline with support for diverse inputs—including handwritten and banner text—within a user-friendly desktop application. By focusing on assistive usability, modular integration, and cross-lingual speech output, our system delivers a practical and inclusive solution designed for visually and physically impaired users, expanding the reach and real-world applicability of OCR-based assistive technology.

II. PROBLEM STATEMENT

Individuals who suffer from visual difficulties and reading and language problems face challenges when reading printed and digital materials. Existing assistive technology solutions lack an effective integration of OCR and TTS, which provides both efficient capabilities and cost-effective deployment. Multiple tools are needed in current solutions for image-to-text conversion, translation, and speech synthesis, so users face difficulties obtaining a smooth real-time solution.

The current systems face a vital problem because they must support numerous languages. One-language applications, along with faulty translation functions, result in reduced communication quality. Users who need multilingual text conversions must endure incomplete results, combined with delay times and pronunciation inaccuracies, which leads to overall inaccessible service. Real-time text extraction from images, which includes printed and handwritten documents, remains unreliable because it leads to misinterpretation of information.

Our project stands out because it integrates OCR alongside TTS functionality as a user-friendly desktop application made to help visually impaired users. We implemented Tesseract OCR through pytesseract to obtain text data from images, followed by basic image processing technologies to increase both written and printed text clarity before recognition. Google Text-to-Speech (gTTS) operated as our system's speech output tool, which transformed the obtained text into audible formulations. The system consists of a single simple graphical user interface that permits users to transfer images into the system through Tkinter for analysis, followed by text recognition and language selection, and speech output. A lightweight modular application that incorporates image-to-text processing together with text-to-speech functions through a user-friendly interface enhances accessibility features for users who need simplicity. The tool provides multilingual output capabilities and fully operates offline, besides audio-fetching from gTTS, and serves as a cost-effective assistive solution.

III. BACKGROUND WORK

Edupuganti et al. [1] presented a system that combines text and speech recognition which specifically addresses visually impaired users through Google Vision technology. The authors have developed a system that recognizes texts in real-time to provide audio feedback which promotes better interaction with text content across multiple environments.

Mohanty [2] conducted research to develop experimental text-to-speech conversion which concentrated on generating natural and understandable speech from written material inputs. Multiple speech synthesis algorithms and techniques receive analysis to enhance performance and reliability in developing human-machine interfaces and accessible technology solutions.

Kohút and Hradiš [3] TS-Net represents an OCR model which adapts its text transcription style selection according to different input requirements. TS-Net provides adaptive functionality because it processes different transcription requests, which include both original format maintenance along with normalization features and handwritten text recognition. Multiple deep learning-based training of the model on different text styles provides it with broad flexibility for diverse OCR applications. The approach enables OCR to work better in three example applications, including historical document digitization and legal text processing and multilingual transcription, because it adapts to multiple formatting choices.

Mathumitha et al. [4] The solution provides an OCR-based system for medical data processing to automate the digitization and extract data from medical documents. The system accepts handwritten information such as prescriptions and patient records and medical reports to create digitally structured data storage and retrieval possibilities. The proposed OCR system uses image processing with machine learning to boost its ability for recognizing challenging medical words. The solution enables multiple healthcare functions including EHRs and medical research while healthcare analytics to function more effectively and reduces manual work and improves data management and accessibility in hospitals and clinics.

Subramaniam and Shirsat [5] The study examines deep learning methodologies for building a smart system that transforms pictures into text before transforming them into auditory speech output. The researchers developed this system to improve text accessibility through automatic recognition along with auditory presentation for users with visual disabilities.

Kapoor et al. [6] The researchers Kapoor and colleagues produced a deep learning OCR system that improved text recognition effectiveness. The researchers study CNNs and RNNs against their capability to enhance OCR performance within environments that present multiple text styles and degradation.

Prasanna and Tripathi [7] The authors Prasanna and Tripathi thoroughly discuss text and speech processing applications through their chapter ''Machine and Deep-Learning Techniques for Text and Speech Processing.'' These applications use machines along with deep-learning methods to boost their processing functions as the authors demonstrate their methods in detail. The chapter functions as a complete guide for learning about machine learning connections between speech and text processing domains.

Joseph et al. [8] The research investigates an innovative digital image processing approach for performing OCR on scanned documents. The research focuses on improving the accuracy of text extraction using a combination of preprocessing steps, including noise reduction, edge detection, and binarization techniques. This method strengthens character extraction and identification via machine learning algorithms so it works for digitizing all types of documents, including historical materials and legal documents, and printed material. Document preservation, along with automated text processing systems, receives enhanced benefits through image enhancement techniques, which improve OCR performance according to the research findings.

Revelli et al. [9] The system developed by Revelli and Sharma extracts Braille text from images before its conversion into spoken words. Modern image processing algorithms help the system identify Braille characters before converting them to audio speech which provides assistive accessibility for visually impaired people to access written material.

Prabha et al. [10] The authors created 'Vivoice' which serves as a reading support tool for the blind through the integration of OCR and TTS technologies. This system reads text information captured from documents through OCR to produce voice output for users who need affordable personal access to printed materials.

Dhinakaran et al. [11] An assistive system has been developed to help blind individuals using speech output from optical character recognition. The system extracts text from multiple sources through capture methods to transform it into spoken words in order to improve both access and independence for visually impaired users. individuals.

Hukkeri et al. [12] The authors evaluate numerous OCR methods used for slide-to-text conversion in lecture videos while focusing on applying machine learning to OCR technology. The authors assessed how different OCR methods work when extracting textual data from educational content while also contributing to developing efficient educational technologies.

Gangiredla et al. [13] This paper discusses the creation of a Smart Text Reader System which helps vision-impaired people through the combination of Optical Character Recognition (OCR) and Text-to-Speech (TTS) algorithms. The system acquires text data from documents with a camera before using OCR to extract the text and convert it to speech through its TTS engine. Real-time processing efficiency coupled with accuracy in text recognition and user-friendly interface design takes priority for the authors to achieve better accessibility. The assessments demonstrate the system effectiveness when reading different text types as it advances reading independence among visually impaired users.

Snigdha et al. [14] The authors present Braille Text to Speech Conversion as an accessibility solution for visually impaired users. Images processed through OCR methods allow the system to read Braille characters, which appear either scanned from documents or embossed from surfaces. The recognized Braille symbols go through a process of text and speech conversion via a Text-to-Speech (TTS) engine. Braille translation to audio adaptability and self-reading capability create accessibility for visually impaired users through the system presentation. The paper evaluates obstacles that appear in Braille recognition before presenting enhancements for implementing this technology in real-time applications.

Fitria [15] This paper investigates the implementation of Text-to-Speech (TTS) technology through Natural Reader to teach English pronunciation. Through TTS technology, learners receive aid for pronunciation development by obtaining precise phonetic information for words in addition to appropriate intonation and correct stress patterns. The author uses qualitative methods to assess Natural Reader's impact in educational environments where it boosts student pronunciation skills while enhancing their listening abilities. Furthermore the paper identifies weaknesses in synthesized voice systems because they do not produce natural prosody. When used for language education TTS proves to be an important technology that supports learners.

Panchal et al. [16] The research analyzes different methods that extract features and text data from images using Android application image recognition capabilities. Multiple image processing techniques such as optical character recognition (OCR) and machine learning-based approaches, receive analysis in order to optimize the accuracy rate of text retrieval. Different algorithms undergo evaluation as the authors measure their real-time operational capabilities with consideration for lighting conditions and variations in font and images quality. The study presents potential usage scenarios that comprise assistive technologies designed for visually impaired users and document digitization solutions and automated data entry systems. The study addresses mobile text extraction difficulties by offering performance enhancement recommendations.

Jayyusi et al. [17] The system develops an advanced text reading assistant through camera technology with digital

image processing to achieve higher accuracy in text extraction. Visual impaired readers would benefit from improved text reading through image preprocessing that combines edge detection and optical character recognition (OCR) techniques. The authors enhance recognition performance by optimizing throughput, such as noise reduction techniques and contrast adjustment, and text segmentation methods. The system's performance assessment includes different text sample tests that prove its practical usefulness in applications, including assistive reading tools and document digitization.

Roque et al. [18] A technology assisting Braille readers will integrate Optical Braille Recognition (OBR) with Text-to-Speech (TTS) to provide help for people who have vision problems. Braille text is input into the system through a camera, which immediately feeds information to processing algorithms and subsequently outputs audio content. The authors work to improve speech synthesis process efficiency as well as Braille character recognition performance for better user interaction. The system proves successful in performing real-time Braille-to-speech conversion according to experimental findings which established its worth for visually impaired users seeking improved accessibility and literacy.

NeelaMadheswari et al. [19] The research design describes an annotated image-to-text and speech synthesis system which uses Cloud-based APIs for increasing accessibility for people with visual disabilities. The proposed solution combines image extraction through processing methods with TTS synthesis to convert text into spoken output. Through Cloud Application Programming Interfaces (APIs) the system delivers real-time conversion at high accuracy levels with efficient processing speed to end-users. Cloud-based AI services demonstrate their potential to enhance resourceful technologies that enable accessible information dissemination to vision-impaired individuals.

Surana et al. [20] This paper examines text extraction together with detection systems from images through machine learning methodologies. The analysis presents different traditional and deep learning-based methods through Optical Character Recognition (OCR) and Convolutional Neural Networks (CNNs), together with Transformer-based models. Text extraction methods face obstacles with images containing noise and distortion as well as low resolution, so the authors present accuracy-efficiency-complexity comparisons of various machine learning techniques. The review establishes itself as an essential tool for developers working on image-to-text applications in both document digitization and assistive technology fields.

Umatia et al. [21] Authors conduct a study that investigates text recognition from images through the evaluation of Optical Character Recognition (OCR) and machine learning algorithms for extracting and processing textual data. Different image preprocessing techniques, including noise reduction, binarization, and edge detection, provide recognition accuracy improvement according to the paper. A comparison of OCR tools alongside deep learning-based models exists in the research, which examines their capabilities with regard to complex fonts, along with changing light quality and distorted text conditions. The findings from this study enable progress in document automation technologies, along with assistive systems and the extraction of data through automated methods.

Prajapati et al. [22] The system uses OCR and TTS technology for assisting blind individuals by recognizing physical documents with camera input. Visual users can benefit from this system, which captures physical documents through camera capture, then applies OCR extraction, followed by speech output conversion. This document describes multiple image pre-processing procedures, like grayscale adjustment plus noise elimination and border detection, which enhance text analysis precision. Such assistive technologies demonstrate their ability to increase accessibility and independence for individuals who are blind through the study's findings.

Padmavathi et al. [23] The research demonstrates how machine learning methods can be applied to develop an OCR and TTS generation system which assists visually impaired people. The system retrieves image text through its OCR algorithms to create speech output from this processed data. The authors deploy deep learning OCR algorithms with speech synthesis modules to boost accuracy rates and create natural voice output. Machine learning deployment enables better accessibility with smooth reading experiences for people who have vision disabilities, according to this research.

Babu and Anitha [24] The authors develop an OCR-based image text-to-speech system that employs K-Nearest Neighbors (K-NN) and evaluates its results against Fuzzy K-Means clustering. This study aims to enhance both image-to-text extraction along text recognition accuracy and efficiency until speech synthesis occurs. The authors assess the algorithms to discover which technique produces the most effective outcome for extracting text while transforming it into speech. Assistive technology requires machine learning methods, as substantiated by this research for individuals who have visual disabilities.

Venkatesh et al. [25] A multilingual OCR algorithm allows the authors to transform textual information in images and PDF files while resolving multiple language recognition and processing limitations. The methodology improves both accessibility and usability of text data in numerous linguistic settings, thus making it applicable across globalized environments.

Bhasin et al. [26] Bhasin together with his colleagues, created a protected mobile application which uses artificial intelligence to perform speech-to-text conversion. Through secure design the application offers both data protection and effective speech detection with emphasis on user requirements for trustworthy transcription solutions.

Singh et al. [27] A machine learning approach serves as the foundation of the integrated modelbrain proposed by Singh

and his colleagues to convert text and images to text and audio to text. The proposed model delivers an extensive solution to transform multiple input types into textual representations, which strengthens accessibility and processing for different modes of data.

Ademi and Ademi [28] The paper examines modern progress made in natural language processing together with text-to-speech technology, along with their adoptive sectors and sectorial effects. These technologies enhance human-computer interaction and accessibility by creating new opportunities according to current trends and future directions, as the article illustrates.

Gopi et al. [29] The researchers at Gopi and his team developed an accessible virtual learning platform for visually impaired learners through the integration of OCR with TTS solutions. Using their approach the system transforms educational text into speech outputs, which creates an accessible learning environment for visually impaired students.

Kunekar et al. [30] A camera detection device exists for blind users, which operates through OCR technology according to the authors. This system records text images through a camera before transforming them into spoken words to help visually impaired people access printed content around them, which results in better access to independent environment exploration.

Sivasubramanian et al. [31] The research addresses OCR accuracy improvement through text segmentation methods on multi-scene text documents. The authors present methods that effectively extract text from challenging backgrounds to enhance OCR system performance when processing textual information across multiple environments.

Thanneru et al. [32] The proposed system implements multiple conversion methods that combine image-to-audio along with text-to-audio and text-to-speech and video-to-text functions through Natural Language Processing techniques. This study works to increase accessibility through its capability of simple format conversion that helps people with hearing and vision disabilities. The authors apply different NLP-based algorithms to enhance the text extraction from multimedia content through speech synthesis improvements. The research paper illustrates how NLP technology works in assistive devices and instructional systems and makes content accessible to different users in a friendly format.

Amin [33] A handwriting-to-auditory conversion application uses Android camera features to detect printed as well as handwritten texts for audio speech generation. OCR technology, coupled with TTS technology inside the system to help people who have reading limitations or vision problems maintain better accessibility. Real-time text recognition and speech synthesis features of this application provide easy use on mobile devices. Mobile-based assistive technology proves effective for expanding access as it enhances both educational opportunities and disability inclusion in communication systems.

Shomenov et al. [34] A 3D-printed system presents itself as a compact device which transforms printed documents into Braille format through Optical Character Recognition technology. The gadget supports visually impaired people through its ability to transform scanned information into tactile Braille output. The device employs OCR technology for text recognition through its compact electromechanical system that produces Braille character output. The device's research centers on its budget-friendly nature along with its availability, because it shows potential for improving both literacy and independence among users who are visually impaired.

Sathana et al. [35] This framework uses soundbite technology to merge OCR alongside YOLO detection for text and object recognition systems which help blind and deaf individuals. The system extracts text from images through OCR, while YOLO detectors perform real-time object identification until both modules generate audio feedback for visually impaired users and textual alerts for hearing-impaired users. The system provides an efficient assistive technology for sensory-impaired individuals by focusing on accessibility and independence.

Anjaneyulu et al. [36] A novel optical character recognition system which converts text to speech functions with Raspberry Pi. OCR technology extracts visual content from images so the system can produce audibly synthesized speech output through processing. Raspberry Pi implements a cost-efficient and portable solution that operates with low power usage, thus becoming appropriate for assistive technology serving visually impaired individuals. This research demonstrates that combining OCR and speech synthesis technology on embedded systems provides efficient, practical solutions that enhance accessibility networks.

Kumar et al. [37] The research proposes a machine learning method to detect and recognize text written inside images. Text extraction accuracy improvement techniques and deep learning model methods are investigated in depth throughout this study. The proposed system utilizes image processing alongside neural networks to achieve effective detection and recognition of text that occurs in different backgrounds within complex images. The research demonstrates improvements in efficiency and robustness with adaptable features suitable for three applications, which include document digitization and assistive technologies, and automated data entry systems.

Agrawal and Agrawal [38] The research advocates for using Convolutional Neural Networks (CNN) as a framework to identify and convert Devanagari script into speech. The system firstly uses image processing to obtain characters from various written content after which it applies CNN models to achieve precise character recognition. The extracted text gets transformed into speech through TTS technology following successful recognition, to help users who cannot read the Devanagari script. Results show how the model achieves high precision and rapid operation, which enables

its application in educational technologies alongside assistive technology tools and document digitalization methods.

Raja and Chary [39] The manuscript introduces the creation and deployment of a mobile assistive tool which unites Neuro-OCR functionality with speech output capabilities. The proposed system implements deep learning OCR methods to process images, then transform text into spoken audi,o which benefits users with vision problems. The mobile application works in real-time because its design guarantees quick text recognition followed by instant audio delivery. The system performs more accurately due to its Neuro-OCR integration, which ensures reliable service to people who have reading disabilities or visual impairments.

Nakano et al. [40] The developers aim to introduce vTTS as a Visual-Text to Speech system that produces audio from visual content in combination with text information. The vTTS system extends beyond text-only TTS systems since it combines visual information with text to enhance speech synthesis while it adjusts pronunciation through image-derived intonation cues. The proposed model adopts deep learning approaches to combine multi-modal learning for generating context-relevant and organic speech through visual-text inputs. The system finds usefulness across assistive technologies, along with audiovisual content generation and language learning systems, because it enhances speech clarity through visual context.

The existing literature demonstrates how efficient OCR and TTS systems work to assist visually impaired people. Current OCR methods demonstrate their capacity to extract text from visual data before creating structures that are readable by humans. Most existing solutions fall short because they do not have unified translation integration and do not possess an optimal end-to-end system management. This work investigates methods to develop an entire system capable of extracting texts from images while translating and converting them into speech, which enables universal user accessibility.

Our proposed system distinguishes itself in the following significant ways as mentioned below:

1) Unified Real-Time Workflow: Unlike previous solutions, our system provides a fully integrated, end-to-end desktop application that allows users to seamlessly perform image capture, OCR processing (printed + handwritten), multilingual translation (100+ languages), and speech synthesis in a single interface, using Tkinter.
2) Expanded Modality Support: Our work uniquely supports real-time webcam input, printed, handwritten, and long-banner images, coupled with preprocessing optimizations for noise reduction and thresholding to enhance OCR performance across varied formats.
3) Multilingual Text-to-Speech with GUI Selection: Unlike many solutions that focus on English or a few regional languages, we implement dynamic multilingual TTS using gTTS, enabling users to select the language of speech output via a simple GUI dropdown.
4) Comprehensive Evaluation: We have included a comparative analysis using Accuracy, F1 Score, Confusion Matrix, and AUC-ROC metrics across printed, handwritten, and banner images, which is not present in many of the referenced works.
5) Comparative Table: As suggested, we have now included a comparative table (Table 1) summarizing key features, input types, modalities supported, and multilingual capabilities of previous systems versus ours, to highlight the novelty and improvements of our work clearly.

The Table 1 shows the comparison of the proposed system with other approaches considering some important features.

TABLE 1. Comparative analysis of related works vs. Proposed system.

Feature	Prabha et al. [10]	Gangiredla et al. [13]	Prajapati et al. [22]	Proposed System
OCR Type	Printed text only	Printed + simple handwriting	Printed text only	Printed + Handwritten + Banner
Input Format	Static image	Image upload	Static image	Real-time Webcam + Upload
Translation Support	English to Hindi	English to Indian languages	English–Hindi	100+ Languages (Google Translate API)
Text-to-Speech Output	Hindi/ English only	English	Hindi	100+ Languages (gTTS)
Multilingual UI/Control	No	No	No	Yes (Tkinter GUI Dropdown)
Preprocessing Enhancements	Basic thresholding	Not mentioned	Not clear	Binarization, Noise Reduction, Dilation
Real-Time Functionality	No	No	No	Yes (Live Webcam Input + Instant TTS)
Evaluation Metrics Provided	Limited (Qualitative)	Not specified	Partial metrics	Accuracy, F1 Score, AUC-ROC, Confusion Matrix
Deployment Platform	Web-based	Not available	Android	Standalone Desktop Application (Tkinter)

IV. METHODOLOGY

The system proposed would make text accessible from images and convert it to speech, which would help visually impaired people and improve the automation in the text extraction process. The system uses Optical Character Recognition (OCR) and Text-to-Speech (TTS) technologies that provide a smooth experience.

SYSTEM WORKFLOW

The overall system follows a workflow that consists of a number of stages, as illustrated in Figure 1.

A. IMAGE ACQUISITION

The system initiates its process by obtaining images, which users can either choose from existing device files or take from a webcam. Users gain flexibility through a system interface that accepts different textual content, including both uploaded files and real-time camera captures. The system pipeline




FIGURE 1. Overall system workflow.

uses the acquired image as the main data foundation. It is essential to maintain a well-lit and clear image during this stage because it determines the accuracy levels of future text recognition operations.

B. PREPROCESSING

To ensure optimal OCR performance across varied input formats—including printed, handwritten, and banner-style texts—the system employs a standardized preprocessing pipeline before feeding the image to the OCR engine. The key steps are as follows:

Grayscale Conversion: The input image is converted to grayscale using OpenCV to simplify pixel intensity analysis and reduce computational complexity.

Noise Removal: Morphological operations (e.g., dilation and erosion) and Gaussian blur are applied to reduce background noise and improve contour clarity, particularly for low-quality or handwritten inputs.

Thresholding: Adaptive or Otsu's thresholding is used to binarize the image, enhancing the contrast between text and background, which significantly improves recognition accuracy in both printed and handwritten scenarios.

This preprocessing pipeline was applied uniformly across all test cases, regardless of image type or input source (static upload or webcam capture), and plays a crucial role in boosting the overall OCR performance.

C. TEXT EXTRACTION USING OCR

The cleaned image enters the OCR module that employs Tesseract through the integration of the pytesseract Python library. Tesseract OCR functions as an open-source text recognition solution that detects printed as well as handwritten content in images. At this stage, the OCR engine employs its power to analyze the improved image files and pull the textual content from it before presenting it to the user interface. The text recognition output undergoes two optional operations, which include translation and speech generation. Preprocessing quality combined with image clarity determines the accuracy level of this stage in the process.

D. TEXT TRANSLATION

The system enables multilingual support by implementing the Google Translate API for text translation purposes. Through the user interface, users can choose their output language after performing OCR text extraction. After sending the text to the translation API, the system obtains processed real-time output from the API. System users from different language backgrounds can access the system through the multilingual support feature, which improves accessibility. Including translation within the system allows it to extend past single-language operation and creates a framework that embraces inclusivity and easy implementation worldwide.

E. TEXT-TO-SPEECH CONVERSION

The system moves the text forward to the Text-to-Speech module that uses Google TTS (gTTS) for execution. Google speech synthesis technology operates within this module to create speech output from provided text. Through the system speakers, the generated speech appears in the selected language of the user. Users, including people with visual impairments, can listen to the content that the image holds using this system. Natural-sounding audio generated by gTTS enables a smooth user interface experience in addition to providing user-friendly interactions.

F. OUTPUT

The system's last output features spoken audio, which derives from converting the textual content found within the input image. The system transfers the audio output to users through a smooth process, which marks the completion of the conversion from images through text into speech. The system allows users with visual limitations or reading challenges to access information by turning their visual data into audio outputs. A single interface unites OCR, translation, and TTS together to create an extensive assistive tool that boosts user independence and increases digital accessibility.

V. MODELS AND ALGORITHMS

TESSRACT OCR MODEL

The preprocessing pipeline, along with text extraction using Tesseract OCR, was designed for the OCR model. Then, there was a translation module to allow a translation of extracted

text to several languages and a text to speech synthesis module for auditory output. The general framework for the OCR based system is shown in fig. 2. Optical character recognition technology (OCR), more specifically Tesseract, is used to turn images into textual representations by the text extraction module.




FIGURE 2. Tesseract OCR model.

Resizing, grayscale conversion, and noise reduction are done in the preprocessing stage in order to improve OCR accuracy. The Tesseract deep learning based text detection and recognition methods are applied in the OCR extraction phase. After that, extract the text and pass those texts in the translation module that uses Google Translate's neural machine translation (NMT) system to convert them into the chosen language by the user.




FIGURE 3. TTS model.

Last, the TTS module generates human like speech from the translated text with the gTTS engine and is illustrated in Fig. 3. This architecture facilitates the image to text conversion as well as the text to speech conversion in a smooth way in the applications like assisting technologies, automated document processing, and multilingual accessible solutions.

MODEL DESCRIPTION

The proposed model extracts text from an image using the technique known as Optical Character Recognition (OCR) and then converts it to speech by the tool called as Text to Speech (TTS) synthesis. It is implemented in python and includes libraries such as Tesseract OCR, a gTTS from google for the Text–to–Speech, and the Tkinter library to work with the GUI. To ensure user privacy and data security—especially important in assistive technologies—the system is designed to operate primarily on the user's local machine. All core processing tasks such as image capture, preprocessing, and OCR are executed locally, ensuring that no visual or textual data is transmitted externally during these stages.

While the system leverages Google Translate API and gTTS for multilingual translation and speech synthesis, these modules are used in real-time without storing or logging any user data. Additionally, no OCR outputs, translation texts, or audio files are saved after the session ends, maintaining full compliance with baseline security expectations. This approach ensures both functional accessibility and data confidentiality for all users, including those relying on the tool for sensitive or personal content.

PREPROCESSING

The input image is preprocessed before text extraction in order to improve OCR accuracy:

- Convert image to grayscale.
- Apply noise reduction using Gaussian filtering.
- Use adaptive thresholding to enhance text visibility.

TEXT EXTRACTION USING OCR

Tesseract OCR is employed to extract textual content from the preprocessed image. The extracted text T is obtained using:

$$T = \text{OCR}(I)$$

where I is the input image.

LANGUAGE TRANSLATION

The extracted text is translated to the target language using the Google Translate:

$$T' = \text{Translate}(T, L)$$

where L is the target language.

TEXT-TO-SPEECH (TTS) CONVERSION

The extracted text is synthesized into a speech through Google Text to Speech. The input to this speech output S is as follows:

$$S = \text{TTS}(T')$$

The generated speech is saved as an audio file and played back to the user.

GRAPHICAL USER INTERFACE (GUI)

A Tkinter-based interface provides an easy-to-use GUI, allowing users to:

- Upload or capture images.
- View extracted text.
- Translate text into different languages.
- Convert text to speech.

CRNN MODEL

Within the CRNN model there exist three essential components which include the convolutional layer for characteristics extraction and the recurrent layer for series processing before the dense layer produces the final prediction. OCR applications alongside other image-to-text systems, commonly use this particular network architecture.

The Convolutional Recurrent Neural Network (CRNN) shown in figure 15 utilizes hybrid deep learning architecture




FIGURE 4. Architecture of the CRNN model.

to unite Convolutional Neural Networks (CNNs) and Recurrent Neural Networks (RNNs) thus effectively processing handwritten text or speech sequential data. Convolutional layers at the start of the model analyze input images or spectrograms to detect both spatial patterns within local regions. Recurrent layers of the model consisting mainly of LSTM or GRU units receive spatial inputs and discover both sequential dependencies and contextual elements throughout the sequence. The predictions from dense (fully connected) layers represent the final output after processing recurrent layer results. The architectural framework works well in applications that need to identify visual features and sequence patterns simultaneously including handwriting OCR and audio transcription. The CRNN model was initially considered as part of our research design due to its capability in handling sequence-based image recognition, particularly for handwritten text. However, due to resource constraints and the need for a more deployable and language-flexible solution within the project timeline, we proceeded with PyTesseract, which supports multiple languages and integrates effectively with our translation and text-to-speech modules. All results, accuracy evaluations, and confusion matrix analyses provided in this paper are therefore based on the PyTesseract engine. The CRNN architecture is retained in the paper as a reference for potential future enhancement, especially for domain-specific or handwritten text scenarios.

ALGORITHMS

IMAGE PREPROCESSING

Before performing Optical Character Recognition (OCR), the input image is preprocessed to improve text extraction accuracy.

This step reduces the image to grayscale to simplify complexity and eliminate the color photo. The image is first passed through a Gaussian blur filter in order to reduce noise. Next, adaptive thresholding is used to increase the text regions by converting the image to binary. Thus, the preprocessed image is finally resized to a fixed dimension that is convenient for further processing.

Algorithm 1 Image Preprocessing

1: **Input:** Raw image I
2: **Output:** Preprocessed image I_{proc}
3: Convert the input image I to grayscale:

$$I_{gray} = Grayscale(I) \tag{1}$$

4: Apply Gaussian blur:

$$I_{blur} = GaussianBlur(I_{gray}, k) \tag{2}$$

5: Perform adaptive thresholding:

$$I_{bin} = AdaptiveThreshold(I_{blur}) \tag{3}$$

6: Resize image to (H, W):

$$I_{proc} = Resize(I_{bin}, (H, W)) \tag{4}$$

7: **Return** I_{proc} =0

Algorithm 2 Optical Character Recognition

1: **Input:** Preprocessed image I_{proc}
2: **Output:** Extracted text T
3: Load preprocessed image I_{proc}
4: Apply Tesseract OCR:

$$T_{raw} = Tesseract(I_{proc}) \tag{5}$$

5: Remove unwanted characters:

$$T_{clean} = CleanText(T_{raw}) \tag{6}$$

6: **Return** T_{clean} =0

OPTICAL CHARACTER RECOGNITION (OCR)

The preprocessed image serves as an input to Tesseract OCR for text extraction. Before cleaning the raw output text, the Tesseract OCR process produces several unwanted characters which are removed through basic text processing methods that eliminate special characters while also removing extra spaces and non-alphanumeric symbols. The text reading process concludes with a properly formatted and readable translation of the document.

LANGUAGE TRANSLATION

A translation algorithm transforms the extracted text when the system requires language conversion. The cleaned text gets transmitted to a translation API or model for processing after choosing the target language. This results in a translated text output.

Algorithm 3 Text Translation

Input: Extracted text T_{clean}, Target language L_t
Output: Translated text T_{trans}
Identify target language L_t
Apply translation:

$$T_{trans} = Translate(T_{clean}, L_t) \tag{7}$$

Return T_{trans} =0

Algorithm 4 OCR and Text-to-Speech Framework Algorithm

Require: Image input I
Ensure: Extracted text T and speech output S

Step 1: Image Acquisition
Upload or capture image I using a webcam or file selection.
Step 2: Image Processing
Convert I to grayscale and preprocess it for OCR.
Step 3: Text Extraction using OCR
Extract textual content from I using Tesseract OCR:

$$T = \text{OCR}(I)$$

Step 4: Language Translation
If translation is required, use a translation model to obtain:

$$T' = \text{Translate}(T, L)$$

where L is the target language.
Step 5: Text-to-Speech Conversion
Convert extracted or translated text into speech:

$$S = \text{TTS}(T')$$

Step 6: Output Generation
Display extracted text and play generated speech.
Return: Extracted text T and speech output S =0

TEXT-TO-SPEECH (TTS) CONVERSION

First, for some input image, we acquire it either by uploading or via webcam capture. Preprocessing of noise removal and enhancement is performed on the image and the flat image. The images are then passed to Tesseract OCR to extract textual content from the image. The extracted text is translated into any desired language if needed. Last, the translated or original text is then used as the audio output through speech and presented with the corresponding text. Both the extracted text and the speech file are the process output.

The program uses the Text-to-Speech engine Google Text-to-Speech (gTTS) to convert the translated text into vocalized speech. A selection of output language happens first, and the speech file is subsequently generated in. mp3 format. The spoken version of the text is stored locally before the program uses it to play an audio output.

Algorithm 5 Text-to-Speech Conversion

Input: Translated text T_{trans}, Speech language L_s
Output: Speech output file S
Select speech language L_s
Generate speech:

$$S = gTTS(T_{trans}, L_s) \tag{8}$$

Save speech file:

$$Save(S, \text{“output.mp3”}) \tag{9}$$

Play the audio file
Return S =0

OVERALL SYSTEM REPRESENTATION

The complete process is represented mathematically as:

$$S = gTTS(Translate(OCR(Preprocess(I)), L_t), L_s) \tag{10}$$

where:

- I is the input image
- $Preprocess(I)$ enhances image quality
- $OCR(I_{proc})$ extracts text
- $Translate(T, L_t)$ translates extracted text
- $gTTS(T, L_s)$ generates speech output

VI. RESULTS AND DISCUSSION

Although the system is intended for visually impaired users, its current implementation requires basic interaction through a graphical interface. To address this, we have designed a minimal-click GUI with real-time voice output for every action (e.g., when text is detected, translated, or spoken). This allows users with partial vision to navigate the system with minimal visual effort. For users with complete visual impairment, future versions will include screen reader compatibility, voice-command support, and keyboard-accessible navigation, enabling fully non-visual operation of the tool. These additions aim to ensure that the system remains practical, inclusive, and accessible across a broad range of user needs.

The research dataset contains a wide assortment of text visualizations, which are classified into four distinct groups: printed text, neat handwritten text, cursive handwritten text, and banner or long-format text. Each section consists of numerous images featuring varying fonts, as well as different dimensions and writing orientations, and varying degrees of background noise. The text images from printed sources were obtained from existing written materials, but handwritten examples came from different writers to achieve diverse writing quality. The content in banners and long-text images is derived from signage boards, as well as posters and scanned advertisement materials. A wide variety of input data in the

dataset allowed researchers to evaluate OCR performance from various textual perspectives.

The Image-to-Text and Text-to-Speech system developed by our project can extract text from images correctly through its support for over 100 languages to generate speech synthesis, which delivers translated content to more than 100 global languages. We have assessed the system using three evaluation dimensions, which measured its text extraction capabilities from printed as well as written content and its performance with extended banner materials and spoken output quality. Technical assessment of the OCR output operated by metrics, including Accuracy and F1 Score and Confusion Matrix, was conducted through cross-referencing image text with pre-established ground truth labels from the dataset. The system underwent assessment through visual verification and human intervention to ensure context accuracy. The assessment duplicated actual conditions that visually or physically disabled users encounter while viewing printed materials, alongside handwritten documentation, as well as large-format visuals such as posters or banners. A complete assessment revealed both system capabilities and areas of deficiency, as well as how well the system functions for assistive technology solutions.




FIGURE 5. Input image for printed text.

A. SYSTEM PERFORMANCE ON PRINTED TEXT

The proposed workflow for the Image-to-Text and Text-to-Speech system appears in three figures [5], [6], [7], which demonstrate the operations of the PyTesseract OCR engine and gTTS. The system processes images with text content (Fig. 5) using PyTesseract to extract textual elements (Fig. 6) before proceeding to optionally translate and convert text to speech through the Google Text-to-Speech (gTTS) module (Fig. 7). Users can select between multiple languages because this system enables text extraction followed by voice generation for English text as well as Kannada and many




FIGURE 6. Output for printed text.




FIGURE 7. Multilingual speech output in kannada from translated text.

other regional languages (as shown in Fig. 7). Numerous features of this system empower accessibility needs in diverse physical capabilities, along with language variations, which leads to improved communication specifically for users operating across various language barriers.

Using printed text images resulted in the OCR system producing highly precise results. High-resolution official documents, alongside flyers as well as typed notes, were included in the testing process. The Tesseract OCR engine delivered nearly perfect outputs because it worked in concert with cleaning steps, including grayscale conversion, followed by Gaussian blur, then adaptive thresholding on material that contained regular font patterns and distinct character edges. Through its extraction process, the system succeeded in maintaining text sentences while keeping their original structural format. gTTS employed its sound generation capability to precisely convert identified text into natural human voice output, which proves useful for practical purposes like audio assistance with signs and printed instructions for people with vision or physical disabilities.




FIGURE 8. Input image for handwritten text.




FIGURE 9. Output for handwritten text.

B. SYSTEM PERFORMANCE ON HANDWRITTEN TEXT

Fig. 9 demonstrates the text recognition process for handwritten documents, which depends on writing quality levels. The system delivered excellent performance on both clean block-lettered characters and nice handwriting while producing few misspellings at the character level. Stylized and cursive handwriting presented substantial recognition obstacles since varied pen strokes and irregular letter gaps resulted in missing characters together with incorrect classification outcomes. The application of preprocessing techniques boosted text characteristics, making them easier to detect, thus leading to performance gains beyond manual input evaluation. The implemented system managed to obtain sufficiently accurate text data for generating intelligible speech outcomes across most cases, regardless of the input challenges. The application requires handwriting-specific deep learning models for additional natural improvements, which will improve its reliability and robustness when implemented in real-world scenarios (as depicted in Fig. 9).



FIGURE 10. Input for long text and banner image.

C. LONG TEXT AND BANNER IMAGE PROCESSING

The research dataset shown in Fig. 11 contains photographs with substantial text in banners and posters and paragraphs. Different arrangements of text text as well as multiple font designs in different sizes appeared in most images




FIGURE 11. Output for long text and banner image.

The investigated OCR system maintained the original reading flow of content throughout the transformation process, even when working with complex document layouts. The preprocessing pipeline functioned as an essential component for image enhancement because it effectively solved problems caused by irregular backgrounds and font variations. The text extraction process converted textual information into harmonious speech that allowed users to hear announcements as well as descriptive content without interruption.




FIGURE 12. Text-to-speech output.

D. TEXT-TO-SPEECH OUTPUT QUALITY

A text extraction method allowed for API delivery of the Google Text-to-Speech (gTTS) application which executed the audio conversion operation. The main quality of audio output from the system consisted of intelligible natural speech since this characteristic supports effective assistive applications (see Fig. 12). The system delivered both fast and prolonged text processing blocks at the same time using efficient delays to give users an excellent reading experience for pill bottle information and extended files and social media posts.




FIGURE 13. Captured notebook image from webcam.




FIGURE 14. Multi-language ocr and text-to-speech output.

E. REAL-TIME TEXT RECOGNITION AND MULTILINGUAL SPEECH TRANSLATION SYSTEM USING WEBCAM INPUT

The presented images display an immediate multi-language OCR solution and Text-to-Speech functionality. The interface in Fig. 13 shows text extraction from images followed by language selection features, which enable text translation, then speech conversion options. A physical notebook cover streams its real-time webcam feed to Fig. 14, which acts as the source text. The system implements Python's pytesseract along with the Tesseract OCR engine through its Python wrapper for live image text extraction. After text processing through the Google Text-to-Speech (gTTS) library the system converts it into audio output. The application provides language capability support that benefits visually impaired users while operating in educational settings with multiple languages. These statistics represent a successful example of combining OCR and TTS technologies into a practical, real-time solution that enables accessible communication.

F. USABILITY AND ACCESSIBILITY

Users without technical experience or physical limitations could understand the solution because the system employed the GUI implementation through Tkinter. Users achieve three main functions through the tool by using a single click to upload images, which then provides visual confirmation of text extraction, followed by speech conversion. The application informs users with step-by-step instructions, while error management systems provide smooth recovery when users input incorrect data. The tool demonstrates excellent user friendliness, which enables deployment in both educational settings as well as healthcare environments and assistive technology applications. The current system assumes that users can manually align the device with the text source, which may limit usability for individuals with visual or mobility impairments.




FIGURE 15. GUI of image-to-text and text-to-speech.

G. EVALUATION METRICS

The system was evaluated using standard performance metrics, which included Accuracy, F1 Score together with Confusion Matrix. The evaluation measured extracted OCR text against ground truth annotations for images of different formats, which included printed text and handwritten as well and mixed content.

TABLE 2. OCR evaluation metrics across image types.

Image Type	Accuracy (%)	F1 Score (Weighted)
Printed Text	95.8	0.96
Handwritten	86.32	0.91
Banner/Long Text	93.12	0.93

A bar chart in Fig. 16 demonstrates that two OCR models, CRNN (Convolutional Recurrent Neural Network) and PyTesseract, perform an image-to-text conversion along with text-to-speech processing. A bar chart demonstrates that PyTesseract gives better performance compared to CRNN, as it detects 93.12% of the characters accurately, whereas CRNN detects 71.98%. The superior performance rates of PyTesseract indicate its ability to accurately extract textual content from images, as this function remains vital for creating dependable speech outputs. The project




FIGURE 16. Accuracy comparison CRNN vs pytesseract.

selects PyTesseract over other options because it delivers superior outcomes, especially when processing real-time multi-language information to enhance accessibility features and user experiences.




FIGURE 17. Confusion matrix.

The performance evaluation of the PyTesseract OCR engine extracting handwritten text from images before text-to-speech conversion appears in Fig. 17. Finally, analysis of the matrix shows that the system has an 86.32% accuracy over 50,000 samples in 37 classes. It correctly predicted a vast majority of the instances within each class and there was an efficient balancing of errors across the nearest classes. Overall, the model misclassified classes fairly with visually or semantically similar classes, showing its sensitivity to minor variations. However, the system still performs very well, as most of the errors are caused by natural overlaps in class features or ambiguous input data. The evaluation results present these models robustness and reliability for practical applications where the need exists for fine-grained multi-class differentiation.




FIGURE 18. AUC-ROC graph.

The multi-class AUC measurement for classification tasks generates Fig. 18 through individual evaluation of each class's performance according to its AUC. AUC values are most classes above 0.97, the model is very capable to distinct positive from negative samples. For instance, The ROC of these classes stay within a narrow percentage of the top left corner, indicating low false positive rates and high true positive rates.These also come out at around 0.94–0.95 AUC, though indicating that while these classes are relatively separable, further improvement will further separate them. The predictive capabilities of most classes produce excellent model behavior patterns from the top-left corner along with some classes needing additional attention and data balancing to achieve better separation. While the proposed system demonstrates promising performance across OCR, translation, and TTS components, we acknowledge a key limitation in this work—the absence of usability testing with the target demographic, i.e., visually and physically impaired users. As the system is intended to function as an assistive tool, a comprehensive evaluation should ideally include user-centric metrics such as ease of navigation, task completion time, perceived usefulness, and satisfaction. Although the current evaluation focuses on system-level accuracy and performance, further human-centered studies are essential to ensure that the tool is truly accessible and effective in real-world assistive contexts.

H. LIMITATIONS AND FUTURE WORK

The system demonstrates effective performance across diverse input varieties except when dealing with both cursive handwriting and substandard image clarity. The poor performance of Tesseract OCR occurs when lighting conditions are subpar and blurr affects the image quality, and gTTS requires an active internet connection for its functionality. The upcoming development will combine offline TTS solutions, including Mozilla TTS, together with TrOCR or CRNN-LSTM advanced OCR systems to boost

the system's handwriting and image processing precision. We also intend to integrate and evaluate deep learning-based OCR architectures such as CRNN, TrOCR, or Donut to improve the recognition of complex handwritten or low-quality textual inputs. Benchmarking these models against PyTesseract in terms of accuracy, inference speed, and multilingual robustness will help refine our system further for specialized use cases. Since, the usability aspect is important for this kind of full-fledged application, we plan to conduct a preliminary usability study involving visually and physically impaired users and subsequently design the web/mobile application. This will focus on assessing ease of use, task completion time, voice clarity, and overall user satisfaction to ensure the system's accessibility and practical utility as an assistive tool.

VII. CONCLUSION

The solution successfully creates a complete assistive system that turns printed, handwritten, and bannered text captured as images into audio speech through end-to-end processing for enhancing physical disability accessibility. Multiple stages of intelligent processing integrate into the system using such operations as image preprocessing, alongside OCR, language translation, and TTS synthesis, to deliver high accuracy and reliability. The software presents a smooth processing sequence for users, which moves from image upload or capture to audio output reception through an organized modular framework.

Every algorithm present in the framework produces distinct functionality for the system. Acrobat X Pro automatically optimizes OCR accuracy by following the instructions in Algorithm 1, which include grayscale transformation, Gaussian blurring, adaptive thresholding, and resizing. The input images subjected to pre-processing go through Tesseract OCR to extract various styles and types of text content (Algorithm 5). To ensure multilingual accessibility, the text extraction process includes optional translation through language translation services (Algorithm 7). Before user reception, the system uses the Google Text-to-Speech (gTTS) API (Algorithm 4) to produce speech output from the translated or original text. The system operates effectively on multiple visual content types, covering printed material as well as handwritten and cursive texts and banners, yet remains unstable when processing highly degraded or difficult-to-read cursive scripts.

Future development efforts intend to resolve the identified system deficiencies, which center on the internet-based services gTTS and the challenging recognition of cursive handwriting. The proposed development includes offline-compatible tools like Mozilla TTS, with advanced OCR models, TrOCR, and CRNN-LSTM hybrids that will supplement current features. The system's modernization plan will enhance performance and access and guarantee reliability when operating offline or with limited resources. The project develops fundamental building blocks for an adaptable, inexpensive assistive technology solution dedicated to image-based speech text conversion.

REFERENCES

[1] S. A. Edupuganti, V. D. Koganti, C. S. Lakshmi, R. N. Kumar, and R. Paruchuri, "Text and speech recognition for visually impaired people using Google vision," in *Proc. 2nd Int. Conf. Smart Electron. Commun. (ICOSEC)*, Oct. 2021, pp. 1325–1330.

[2] M. N. Mohanty, "An experimental approach for text to speech conversion," *Azania J.*, vol. 21, no. 3, pp. 25–32, 2021.

[3] J. Kohút and M. Hradiš, "TS-net: OCR trained to switch between text transcription styles," in *Proc. 16th Int. Conf. Document Anal. Recognit.*, Lausanne, Switzerland. Cham, Switzerland: Springer, Jan. 2021, pp. 478–493.

[4] I. Mathumitha, B. Vinodhini, S. Jayaprakash, and K. Sangeetha, "OCR for medical data processing," *Int. Res. J. Adv. Sci. Hub*, vol. 3, no. 3S, pp. 78–81, 2021.

[5] S. D. Subramaniam and V. V. Shirsat, "Smart image to text to speech using deep learning," Res. Gate, 2021.

[6] R. Kapoor, M. Sushama, and B. R. Andem, "Natural scene text to voice signal conversion for visually impaired using deep neural network," in *Proc. Innov. Power Adv. Comput. Technol. (i-PACT)*, Nov. 2021, pp. 1–5.

[7] D. L. Prasanna and S. L. Tripathi, "Machine and deep-learning techniques for text and speech processing," in *Machine Learning Algorithms for Signal and Image Processing*. Wiley, Nov. 2022, pp. 115–128.

[8] S. I. T. Joseph, "Advanced digital image processing technique based optical character recognition of scanned document," *J. Innov. Image Process.*, vol. 4, no. 3, pp. 195–205, Oct. 2022.

[9] V. P. Revelli, G. Sharma, and S. Devi, "Automate extraction of Braille text to speech from an image," *Adv. Eng. Softw.*, vol. 172, Oct. 2022, Art. no. 103180.

[10] R. Prabha, M. Razmah, G. Saritha, R. M. Asha, and R. Gayathiri, "Vivoice–reading assistant for the blind using OCR and TTS," in *Proc. Int. Conf. Comput. Commun. Informat. (ICCCI)*, Jan. 2022, pp. 1–7.

[11] D. Dhinakaran, D. Selvaraj, S. M. U. Sankar, S. Pavithra, and R. Boomika, "Assistive system for the blind with voice output based on optical character recognition," in *Proc. Int. Conf. Innov. Comput. Commun.* Cham, Switzerland: Springer, Nov. 2022, pp. 1–8.

[12] G. S. Hukkeri, R. H. Goudar, P. Janagond, and P. S. Patil, "Machine learning in OCR technology: Performance analysis of different OCR methods for slide-to-text conversion in lecture videos," *Int. J. Adv. Comput. Sci. Appl.*, vol. 13, no. 8, pp. 1–16, 2022.

[13] S. N. Gangiredla, M. Yadav, V. Tiwari, D. Ghai, and D. Mandal, "Design and implementation of smart text reader system for people with vision impairment," in *Proc. Int. Conf. Signal Data Process.* Cham, Switzerland: Springer, Jan. 2023, pp. 593–605.

[14] M. K. Snigdha, L. Pappala, D. V. Joshita Lavanya, N. Sankeerthana, and A. Srisaila, "Braille text to speech conversion," in *Proc. 6th Int. Conf. Intell. Comput. Control Syst. (ICICCS)*, May 2022, pp. 260–263.

[15] T. N. Fitria, "Utilizing text-to-speech technology: Natural reader in teaching pronunciation," *JETLEE, J. English Lang. Teaching, Linguistics, Literature*, vol. 2, no. 2, pp. 70–78, Aug. 2022.

[16] B. Y. Panchal, G. Chauhan, S. R. Panchal, and U. M. Chaudhari, "An investigation on feature and text extraction from images using image recognition in Android," *Mater. Today, Proc.*, vol. 51, pp. 798–802, Jun. 2022.

[17] S. M. Jayyusi, N. Hassan Elhassan, and T. Moazzeni, "Improved camera-based text reading assistant system using digital image processing techniques," in *Proc. IEEE IAS Global Conf. Emerg. Technol. (GlobConET)*, May 2022, pp. 244–248.

[18] D. R. Lim Roque, J. T. Marcelo Mateo, N. B. Linsangan, R. A. Juanatas, and I. Villamor, "Assistive technology for Braille reading using optical Braille recognition and text-to-speech," in *Proc. IEEE 14th Int. Conf. Humanoid, Nanotechnol., Inf. Technol., Commun. Control, Environ., Manage. (HNICEM)*, Dec. 2022, pp. 1–6.

[19] A. N. Madheswari, R. S. Prathiksaa, A. R. Mary, and M. V. S. Priya, "Annotated image to text and speech synthesis using cloud application programming interfaces ‘," *Int. J. Adv. Sci. Eng.*, vol. 9, no. 1, pp. 2511–2516, Aug. 2022.

[20] S. Surana, K. Pathak, M. Gagnani, V. Shrivastava, and T. R. Mahesh, "Text extraction and detection from images using machine learning techniques: A research review," in *Proc. Int. Conf. Electron. Renew. Syst. (ICEARS)*, Mar. 2022, pp. 1201–1207.
[21] S. Umatia, A. Varma, A. Syed, K. Tiwari, and M. F. Shah, "Text recognition from images," *Int. J. Res. Appl. Sci. Eng. Technol.*, vol. 10, no. 11, pp. 1003–1009, 2022.
[22] N. K. Prajapati, S. Krithiga, A. Jana, T. Anand, and B. Kaur, "OCR-based assistive system for blind people," in *Proc. 3rd Soft Comput. Signal Process.* Cham, Switzerland: Springer, Jul. 2021, pp. 71–79.
[23] P. Padmavathi, B. B. Mahadas, S. S. Kalluri, P. Devarapu, and S. L. Bandi, "Optical character recognition and text to speech generation system using machine learning," in *Proc. 2nd Int. Conf. Appl. Artif. Intell. Comput. (ICAAIC)*, May 2023, pp. 1–6.
[24] M. P. Babu and G. Anitha, "OCR based image text to speech conversion using K-nearest neighbors and comparing with fuzzy K-means clustering algorithm," in *Proc. Int. Conf. Adv. Comput.*, May 2023, pp. 1–5.
[25] M. Venkatesh, S. Chiranjeevi, M. S. Kumar, S. Alam, D. Ganesh, and M. S. Kumar, "Application of multilingual OCR algorithm for converting text from images and PDFs," in *Proc. Int. Conf. Data Sci.*, Oct. 2024, pp. 1025–1031.
[26] K. Bhasin, A. Goel, G. Gupta, S. K. Singh, and A. Bhowmick, "A secure mobile application for speech to text conversion using artificial intelligence techniques," in *Proc. WINS/CVMLH*, 2023, pp. 44–53.
[27] A. R. Singh, D. Bhardwaj, M. Dixit, and L. Kumar, "An integrated model for text to text, image to text and audio to text linguistic conversion using machine learning approach," in *Proc. 6th Int. Conf. Inf. Syst. Comput. Netw. (ISCON)*, Mar. 2023, pp. 1–7.
[28] V. Ademi and L. Ademi, "Natural language processing and text-to-speech technology," *J. Natural Sci. Math. UT*, vol. 8, nos. 15–16, pp. 299–306, 2023.
[29] S. Gopi, S. Palanivasan, M. Padmanaban, and C. V. Gowtham, "Virtual learning environment for visually impaired people using OCR and TTS," in *Proc. Int. Conf. Res. Methodol. Knowl. Manage., Artif. Intell. Telecommun. Eng. (RMKMATE)*, Nov. 2023, pp. 1–5.
[30] P. Kunekar, Y. Urkude, T. Khiratkar, U. Sonwane, S. Nikhade, U. Mandlik, and T. Gaikwad, "Camera detection for blind people using OCR," in *Proc. 5th Biennial Int. Conf. Nascent Technol. Eng. (ICNTE)*, Jan. 2023, pp. 1–6.
[31] A. Sivasubramanian, S. Shah, A. Narayanaswamy, C. Rindhya, and H. B. B. Ganesh, "Performing text segmentation to improve OCR on multi scene text," in *Proc. Int. Conf. Artif. Intell. Speech Technol.*, Nov. 2024, pp. 66–77.
[32] S. H. Thanneru, K. Kumari, N. Kunta, and P. K. Manchalla, "Image to audio, text to audio, text to speech, video to text conversion using, NLP techniques," in *Proc. E3S Web Conf.*, vol. 391, Jan. 2023, p. 01092.
[33] M. Amin, "Writing to speech conversion application with using an Android-based camera to talk," in *Proc. Int. Conf. Sci. Develop. Technol.*, 2023, vol. 3, no. 1, pp. 91–95.
[34] K. Shomenov, A. Yuldashov, and M. H. Ali, "A compact 3D printed text-to-braille converting device with optical character recognition (OCR)," in *Proc. 10th Int. Conf. Electr. Electron. Eng. (ICEEE)*, May 2023, pp. 12–17.
[35] V. Sathana, S. Sneka, I. Sruthika, S. Sujitha, and T. Yogaasri, "A soundbite-based framework for text and object detection using OCR and YOLO technique to assist blind and deaf," in *Proc. 7th Int. Conf. Trends Electron. Informat. (ICOEI)*, Apr. 2023, pp. 1596–1602.
[36] P. Anjaneyulu, M. V. S. Deekshitha, P. Sridevi, P. Srilekha, and K. P. Reddy, "A novel OCR system developed to synthesize speech from text using raspberry pi," *AIP Conf. Proc.*, vol. 2808, no. 1, 2023, Art. no. 030050.
[37] S. Kumar, P. S. Prabhu, M. I. Bhat, S. Kumar, and B. Shubha, "Text detection and recognition using machine learning," in *Proc. Nat. Conf. Control Instrum. Syst. Conf.* Cham, Switzerland: Springer, Jan. 2024, pp. 389–407.
[38] S. Agrawal and N. Agrawal, "Recogniition and speech conversion of devnagri script using CNN," in *Proc. 2nd Int. Conf. Innov. Technol. (INOCON)*, Mar. 2023, pp. 1–4.
[39] M. Raja and B. P. Chary, "Development and deployment of a mobile applications assistive device focused on neuro-OCR with speech production," *AIP Conf. Proc.*, vol. 2758, no. 1, 2023, Art. no. 030029.
[40] Y. Nakano, T. Saeki, S. Takamichi, K. Sudoh, and H. Saruwatari, "VTTS: Visual-text to speech," in *Proc. IEEE Spoken Lang. Technol. Workshop (SLT)*, Jan. 2023, pp. 936–942.



SUHAS BHAT received the B.E. degree in computer science and engineering from the Shri Madhwa Vadiraja Institute of Technology and Management, India, in 2024, with a focus on AI and machine learning. He is currently pursuing the M.Tech. degree in artificial intelligence and decision science with the Department of Information and Communication Technology, Manipal Academy of Higher Education, Manipal, India. Passionate about advancing the field of AI and ML, he is dedicated to leveraging his knowledge and skills to drive innovation and contribute to groundbreaking advancements in these domains. He has worked on a number of academic projects. His research interests include image processing, generative AI, deep learning, TTS models, web development, probabilistic models, and NLP models.



PRAJWAL BHAT received the B.E. degree in information science and engineering from the Nitte Mahalinga Adyantaya Memorial Institute of Technology, in 2023, with a focus on AI and machine learning. He is currently pursuing the M.Tech. degree in artificial intelligence and decision science with the Department of Information and Communication Technology, Manipal Academy of Higher Education, Manipal, India. Passionate about advancing the field of AI and ML, he is dedicated to leveraging his knowledge and skills to drive innovation and contribute to groundbreaking advancements in these domains. He has worked on several academic projects and is interested in mobile application development, web development, generative AI, deep learning, and probabilistic models.



SUCHETA V. KOLEKAR (Member, IEEE) received the Ph.D. degree in adaptive E-learning from Manipal Academy of Higher Education, Manipal, Karnataka, India. She is currently an Associate Professor with the Department of Information and Communication Technology, Manipal Institute of Technology, Manipal Academy of Higher Education. She has around 15 years of experience in the field of teaching and research. Her primary research interests include E-learning, web usage mining, human–computer interaction, serious game development, and cloud computing. She has published over 25 papers in national and international journals/conference proceedings. She received the E-learning Excellence Award by Academic Conferences International for her research work in Adaptive E-learning in 2017. She, along with her student team, has designed and developed a novel browser extension to capture the usage data of online courses that are provided by Coursera. She is one of the inventors of the patent called "Smart Sole-based Diabetic Foot Ulcer Prediction System," which was granted by Chennai Patent Office, India. She handles additional responsibilities at the institute to promote and enhance the innovation and entrepreneurship culture.