


WEEK 12

To understand the operation of TELNET by accessing the router in server room from a PC in IT office.

OBSERVATION:



Step 10: password p0
Step 11: Exit : Exit
Step 12: W9

Routing
IT of PC

- Ping message to router
password for user. Access verification is p0
password for enable is P1
Accessing Router CLI from PC
show IP route.

PCNG output -

Packet trace PC command line 1.0

PC > ping 10.0.0.1

pinging 10.0.0.1 with 32 bytes of data

Reply from 10.0.0.1: bytes=32 time=0ms TTL=255

Reply from 10.0.0.1: bytes=32 time=0ms TTL=255

Reply from 10.0.0.1: bytes=32 time=0ms TTL=255

Reply from 10.0.0.1: bytes=32 time=0ms TTL=255

Ping statistics for 10.0.0.1:

Packet sent=4, Received, lost=0 (0% loss)

Approximate round trip times in milliseconds

Minimum = 0ms * Maximum = 0ms Average = 0ms

PC > telnet 10.0.0.1

typing 10.0.0.1 ... open

User Access verification


password: p0

! > enable


password: P1

81 # show ip route

C 10.0.0.0/8 is directly connected, FastEthernet



TOPOLOGY:



OUTPUT:

```
PC0
Physical Config Desktop Custom Interface

Command Prompt

Packet Tracer PC Command Line 1.0
PC>ping 10.0.0.1

Pinging 10.0.0.1 with 32 bytes of data:

Reply from 10.0.0.1: bytes=32 time=1ms TTL=255
Reply from 10.0.0.1: bytes=32 time=0ms TTL=255
Reply from 10.0.0.1: bytes=32 time=0ms TTL=255
Reply from 10.0.0.1: bytes=32 time=0ms TTL=255

Ping statistics for 10.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms

PC>telnet 10.0.0.1
Trying 10.0.0.1 ...Open

User Access Verification

Password:
! Password: timeout expired!

[Connection to 10.0.0.1 closed by foreign host]
PC>telnet 10.0.0.1
Trying 10.0.0.1 ...Open

User Access Verification

Password:
Password:
Password:

[Connection to 10.0.0.1 closed by foreign host]
PC>telnet 10.0.0.1
Trying 10.0.0.1 ...Open

User Access Verification

Password:
rl>enable
Password:
rl#show ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
        i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
        * - candidate default, U - per-user static route, o - ODR
        P - periodic downloaded static route

Gateway of last resort is not set

C    10.0.0.0/8 is directly connected, FastEthernet0/0
rl#
```