

Faking out XHR and Timer Calls



Nathan Taylor

SOFTWARE ENGINEER


@taylonr taylonr.com

Problem: Making External API Calls



GLOBOMANTICS

Core Competency



Extraneous






GLOBOMANTICS



exchangeratesapi.io



```
var settings = {  
    url: 'https://exchangeratesapi.io/api/latest?base=USD',  
    method: 'GET'  
};  
  
$.ajax(settings).done(...)
```

Currency Conversion

Running Tests in the Browser

Making a Fake Request

```
var settings = {  
    url: 'https://exchangeratesapi.io/api/latest?base=USD',  
    method: 'GET'  
};  
  
$.ajax(settings).done(...)
```

XMLHttpRequest

Creating a Fake Request

```
sinon.useFakeXMLHttpRequest();
```

Capturing Requests

```
xhr.onCreate = (req) => {  
    requests.push(req);  
};
```

FakeXMLHttpRequest Properties

URL

Method

Headers

Body

Username

Password

Request Actions



Error

Respond

Responding to a Request

```
request.respond(200, {'Content-Type': 'application/json'},  
'{title: "Don\'t Waste Your Life"}');
```

```
request.setStatus(200);
```

```
request.setResponseHeaders({'Content-Type':  
'application/json'});
```

```
request.setResponseBody('{title: "Don\'t Waste Your  
Life"}');
```

```
request.respond();
```

Demo



Faking out XHR

Demo: Fake XHR

Faking a Server

Multiple Requests

```
$.ajax('/user/1', () => {});
```

```
$.ajax('/roles', () => {});
```

```
$.ajax('/locations', () => {});
```

```
$.ajax({url: '/user/1', method: 'PUT', data: {}},  
      () => {});
```

Required Actions for Requests



Capture

Find

Respond

Creating a Server

```
sinon.createFakeServer();
```

Setting up Responses

```
server.respondWith('https://exchangeratesapi.io/api/latest?
base=USD',
[200,
  { 'Content-Type': 'application/json' },
  '{ "rates": {"AUD": 1}}'
]);
```

respondWith Options

(method, url, response)

(urlRegEx, response)

(method, urlRegEx, response)

(response)

Responding to Requests

```
server.with('https://exchangeratesapi.io/api/latest?  
base=USD', response);
```

```
getPrices(10, 'AUD', callback);
```

```
server.respond();
```

Configuring the Server

```
const server = sinon.createFakeServer({  
  autoRespond: true  
});
```

Configuring the Server

```
const server = sinon.createFakeServer({  
  autoRespond: true  
});
```

```
const server = sinon.createFakeServer({  
  autoRespondAfter: 500  
});
```


Don't forget to `.restore()`



Faking out XHR is simpler

Faking a Date

Checking a Date

```
return controller.create(req, res).then(() => {  
    expect(userCreate.calledWith(sinon.match({  
        customerSince: sinon.match.date  
    }))))).to.eq(true);  
});
```

Checking a Date

```
return controller.create(req, res).then(() => {  
    expect(userCreate.calledWith(sinon.match({  
        customerSince: sinon.match.date  
    }))))).to.eq(true);  
});
```



Time to execute code can vary

Creating a Fake Timer

```
const timer = sinon.useFakeTimers();
```

Creating a Fake Timer

```
const timer = sinon.useFakeTimers();  
console.log(new Date()); //1970-01-01T00:00:00.000Z
```


Creating a Specific Fake Timer

```
const timer = sinon.useFakeTimers(new Date(2015, 10, 1));  
console.log(new Date()); //2015-11-01T05:00:00.000Z
```

Advancing the Timer

```
timer.tick('01:20');  
console.log(new Date()); //2015-11-01T05:01:20.000Z
```

Don't forget `.restore()`

Demo: Cleaning up Date Verification

Coming Up

You've learned all the
doubles and fakes!



Sinon sandboxes