20-06-2024 Writing Executable Statements

Commenting Code

1.DECLARE

v_sal NUMBER (9,2);

BEGIN

/* Compute the annual salary based on the

monthly salary input from the user */

v_sal := :g_monthly_sal * 12;

END; -- This is the end of the block

SQL Functions in PL/SQL

2. v_mailing_address := v_name||CHR(10)|| v_address||CHR(10)||v_state||

CHR(10)||v_zip;

3. v_ename := LOWER(v_ename);

Data type Conversion

4.v_date := TO_DATE ('January 13, 2001', 'Month DD, YYYY');

Operator	Operation
**	Exponentiation
+, -	Identity, negation
*, /	Multiplication, division
+, -, ||	Addition, subtraction, concatenation
=, <, >, <=, >=, <>, !=, ~=, ^=, IS NULL, LIKE, BETWEEN, IN	Comparison
NOT	Logical negation
AND	Conjunction
OR	Inclusion

SELECT Statements in PL/SQL

5.DECLARE

v_deptno NUMBER(4);

v_location_id NUMBER(4);

BEGIN

SELECT department_id, location_id

INTO v_deptno, v_location_id

FROM departments

WHERE department_name = 'Sales';

END;

Retrieving Data in PL/SQL

6.SET SERVEROUTPUT ON

DECLARE

v_sum_sal NUMBER(10,2);

v_deptno NUMBER NOT NULL := 60;

BEGIN

SELECT SUM(salary) -- group function

INTO v_sum_sal

FROM employees

WHERE department_id = v_deptno;

DBMS_OUTPUT.PUT_LINE ('The sum salary is ' ||

TO_CHAR(v_sum_sal));

END;

Naming Convention

7.DECLARE

hire_date employees.hire_date%TYPE;

sysdate hire_date%TYPE;

employee_id employees.employee_id%TYPE := 176;

BEGIN

SELECT hire_date, sysdate

INTO hire_date, sysdate

FROM employees

WHERE employee_id = employee_id; **END;**