


26-06-2024

Creating Procedures

Procedural Parameter Modes



IN Parameters

1.CREATE OR REPLACE PROCEDURE raise_salary

(p_id IN employees.employee_id%TYPE)

IS

BEGIN

UPDATE employees

SET salary = salary * 1.10

WHERE employee_id = p_id;

END raise_salary;

OUT Parameters

2.CREATE OR REPLACE PROCEDURE query_emp

(p_id IN employees.employee_id%TYPE,

p_name OUT employees.last_name%TYPE,

p_salary OUT employees.salary%TYPE,

p_comm OUT employees.commission_pct%TYPE)

IS

BEGIN

SELECT last_name, salary, commission_pct

```

INTO p_name, p_salary, p_comm
FROM employees
WHERE employee_id = p_id;
END query_emp;

```

Viewing OUT Parameters

```

3.VARIABLE g_name VARCHAR2(25)
VARIABLE g_sal NUMBER
VARIABLE g_comm NUMBER
EXECUTE query_emp(171, :g_name, :g_sal, :g_comm)
PRINT g_name

```

IN OUT Parameters

```

4.CREATE OR REPLACE PROCEDURE format_phone
(p_phone_no IN OUT VARCHAR2)
IS
BEGIN
p_phone_no := '(' || SUBSTR(p_phone_no,1,3) ||
')' || SUBSTR(p_phone_no,4,3) ||
'-' || SUBSTR(p_phone_no,7);
END format_phone;

```

```

5.VARIABLE g_phone_no VARCHAR2(15)
BEGIN
:g_phone_no := '8006330575';
END;
PRINT g_phone_no
EXECUTE format_phone (:g_phone_no)
PRINT g_phone_no

```

DEFAULT Option for Parameters

```

6.CREATE OR REPLACE PROCEDURE add_dept
(p_name IN departments.department_name%TYPE
DEFAULT 'unknown',

```

```

p_loc IN departments.location_id%TYPE
DEFAULT 1700)

IS

BEGIN

INSERT INTO departments(department_id,
department_name, location_id)
VALUES (departments_seq.NEXTVAL, p_name, p_loc);

END add_dept;

PASSING VALUE

BEGIN

add_dept;

add_dept ('TRAINING', 2500);

add_dept ( p_loc => 2400, p_name => 'EDUCATION');

add_dept ( p_loc => 1200) ;

END;

```

Handled Exceptions

```

7.CREATE PROCEDURE p2_ins_dept(p_locid NUMBER) IS

v_did NUMBER(4);

BEGIN

DBMS_OUTPUT.PUT_LINE('Procedure p2_ins_dept started');

INSERT INTO departments VALUES (5, 'Dept 5', 145, p_locid);

SELECT department_id INTO v_did FROM employees

WHERE employee_id = 999;

END;


CREATE PROCEDURE p1_ins_loc(p_lid NUMBER, p_city VARCHAR2)

IS

v_city VARCHAR2(30); v_dname VARCHAR2(30);

BEGIN

DBMS_OUTPUT.PUT_LINE('Main Procedure p1_ins_loc');

```

```
INSERT INTO locations (location_id, city) VALUES (p_lid, p_city);  
SELECT city INTO v_city FROM locations WHERE location_id = p_lid;  
DBMS_OUTPUT.PUT_LINE('Inserted city '||v_city);  
DBMS_OUTPUT.PUT_LINE('Invoking the procedure p2_ins_dept ...');  
p2_ins_dept(p_lid);
```

EXCEPTION

WHEN NO_DATA_FOUND THEN

```
DBMS_OUTPUT.PUT_LINE('No such dept/loc for any employee');
```

END;