WS-C2960-24PC-L Datasheet

Get a Quote



Overview

WS- C2960-24PC-L is one of the Cisco Catalyst 2960 Series switches. This series support voice, video, data, and highly secure access. They also deliver scalable management as your business needs change. The Common Features are included: Enhanced security including Cisco TrustSec for providing authentication, access control, and security policy administration, Multiple Fast or Gigabit Ethernet performance options, Cisco EnergyWise for power management, Scalable network management.

Quick Specs

Figure 1 shows the appearance of the WS-C2960-24PC-L.



Table 1 shows the Quick Spec of the WS-C2960-24PC-L.

Product Code	WS-C2960-24PC-L
Enclosure Type	Rack-mountable - 1U
Feature Set	LAN Base
Uplink Interfaces	2 dual-purpose (10/100/1000 or SFP) ports
Ports	24 x Ethernet 10/100 PoE ports
Throughput	6.5 Mpps
Backplane Capacity	16 Gbps
DRAM	64 MB
Dimensions	1.73 x 17.5 x 9.3 in.
Package Weight	9.5 Kg

Product Details

Figure 2 shows the front panel of the Cisco 2960-24PC-L switch.



Note:

(1)	LED Area
(2)	24 x Ethernet 10/100 PoE ports
(3)	2 dual-purpose uplinks

Figure 3 shows the back panel of the WS-C2960-24PC-L.



Note:

(1)	RJ45 Console Port	(3)	RPS Connector
(2)	Fan Exhaust	(4)	AC power connector

The Accessories

Table 2 shows some accessories of the WS-C2960-24PC-L.

Models	Description
GLC-LH-SM	GE SFP, LC connector LX/LH transceiver
GLC-SX-MMD	1000BASE-SX SFP transceiver module, MMF, 850nm, DOM
CAB-CONSOLE-RJ45	Console Cable 6ft with RJ45 and DB9F

Compare to Similar Items

Table 3 shows the comparison of similar items.

Models	WS-C2960-24PC-L	WS-C2960-24TC-L
PoE Available	Yes	N/A
Ports	24 x Ethernet 10/100 PoE ports	24 x Ethernet 10/100 ports
Uplinks	2 dual-purpose uplinks	2 dual-purpose uplinks
Feature Set	LAN Base	LAN Base

Get more information

Do you have any question about the Cisco Catalyst C2960-24PC-L switch?

Contact us now via ${\bf Live\ Chat}$ or ${\bf sales@router-switch.com}.$

Specification

	WS-C2960-24PC-L Specification		
Туре	Fixed		
Topology	Ethernet (10/100BaseTX) Ethernet (10/100/1000BaseT) Gigabit Ethernet (SFP)		
Maximum Port density	24 10/100 PoE ports		
Uplinks	2 dual-purpose (10/100/1000 or SFP) ports		
Modular/Expansion Slots	n/a		
Architecture	Layer 2 Switching (basic connectivity), Layer 2 Switching (intelligent services), Voice Enabled		
Form Factor	Fixed, Rack Mountable, Standalone/Clustering		
Dimensions	1.73 x 17.5 x 13 in.		
DRAM	64 MB		
Features			
Specialized Service Modules	n/a		
	Security		
DHCP Snooping			
Dynamic ARP Inspection			
IP Source Guard			
RP Rate Limiters			
TCP Intercept			
802.1x			
Port Security			
Dynamic VLANs			
Private VLANs			
Private VLAN Edge			

Secure Shell	
SNMPv3	
Unicast RPF	
ACLs (L2-L4)	
Kerberos	
TACACS+	
RADIUS	
	High Availability/Resilliency
Hardware Redundancy	External Redundant Power Supply
High Availability/Resilliency	PVST, Broadcast Suppression, Unicast Suppression, Mulitcast Suppression, Spanning Tree, Portfast, Uplink Fast, Backbone Fast, 802.1s, 802.1w
	Management
Management features	SPAN, RSPAN, CiscoView, Cisco Discover Protocol (CDP), Virtual Trunking Protocol (VTP), Telnet Client, BOOTP, TFTP, CiscoWorks, CWSI, RMON, SNMP, Clustering, Web-Based Management
Scalability	
WAN Interface Support	n/a
Throughput	6.5 Mpps
Backplane Capacity	16 Gbps
Number of VLANs	255

Download Resource

Transition Guide

Cisco Catalyst 2960/2960-SF/2960-S Series Transition Guide

Guide to Upgrade Cisco Access and Backbone Switch

🔁 Selecting Cisco Switches-Campus, Branch, Digital Building

Want to Buy

Order Now

Get a Quote

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of Cisco, Huawei, HPE, Dell, Hikvision, Juniper, Fortinet, etc.











Countries we Sold Customers Trusted Inventory Available Off Global List Price Safe Online Shopping

Contact Us

● Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166

Fax: +852-3050-1066 (Hong Kong)Email: sales@router-switch.com