

Assignment 4

Thread synchronisation using counting semaphores

```
#include <stdio.h>
#include <unistd.h>
#include <stdlib.h>
#include <string.h>
#include <pthread.h>
#include <semaphore.h>

#define BufferSize 5

void *producer(void *arg);
void *consumer(void *arg);

sem_t *empty;
sem_t *full;
pthread_mutex_t mutex;
int in=0;
int out=0;
int buffer[BufferSize];

int main() {

    int res,i,sizeP,sizeC;
    pthread_t *threadP,*threadC;

    //Accepting Number of Prodecers and Consumers
    printf("\nNumber of Producers: ");
    scanf("%d",&sizeP);

    printf("Number of Consumers: ");
    scanf("%d",&sizeC);
    printf("\n");

    //Creating one thread per precessor and per consumer. For
    example if 3 producer then 3 threads for each producer.
    threadP=(pthread_t*)malloc(sizeof(pthread_t)*sizeP);
    threadC=(pthread_t*)malloc(sizeof(pthread_t)*sizeC);
    int pno[sizeP],cno[sizeC];

    //Creating semaphores
    full=sem_open("/fullSem", O_CREAT, 0644, 0);
    empty=sem_open("/emptySem", O_CREAT, 0644, BufferSize);
    pthread_mutex_init(&mutex, NULL);
```

```

//Function Calls
for(i=0;i<sizeP;i++) {
    pno[i]=i+1;
    res=pthread_create(&threadP[i], NULL, producer, &pno[i]);
}
for(i=0;i<sizeC;i++) {
    cno[i]=i+1;
    res=pthread_create(&threadC[i], NULL, consumer, &cno[i]);
}
for(i=0;i<sizeP;i++)
    res=pthread_join(threadP[i], NULL);
for(i=0;i<sizeC;i++)
    res=pthread_join(threadC[i], NULL);

//destroying the semaphores
pthread_mutex_destroy(&mutex);
sem_unlink("/fullSem");
sem_unlink("/emptySem");

exit(EXIT_SUCCESS);
}

void *producer(void *arg) {

    while(1) {
        int item=rand();

        sem_wait(empty);
        pthread_mutex_lock(&mutex); //Entering Critical Region

        buffer[in]=item%100;
        int pos=in;
        in=(in+1)%BufferSize;

        printf("Thread ID: %d. Producer: %d", (int)pthread_self()
%100, *(int*)arg); //Printing Thread ID and Producer Number
        printf("\nProduced item %d at %d position\nBuffer:
[ ", item%100, pos);

        //Displaying Buffer after Production
        for(int i=0;i<BufferSize;i++) {
            printf("%d ", buffer[i]);
        }
        printf("]\n\n");

        pthread_mutex_unlock(&mutex); //Exiting Critical Region
        sem_post(full);
        sleep(3);
    }
}

```

```

    }
    pthread_exit(NULL);
}

void *consumer(void *arg) {

    while(1) {

        sem_wait(full);
        pthread_mutex_lock(&mutex); //Entering Critical Region

        int item=buffer[out];
        int pos=out;
        out=(out+1)%BufferSize;

        printf("Thread ID: %d. Consumer: %d", (int)pthread_self(),
%100, *(int*)arg); //Printing Thread ID and Consumer Number
        printf("\nConsuming item %d from %d position\nBuffer:
[ ", item, pos);

        //Displaying Buffer before Consumption
        for(int i=0; i<BufferSize; i++) {
            printf("%d ", buffer[i]);
        }
        printf("]->[ ");

        //Displaying Buffer after Consumption
        buffer[pos]=0;
        for(int i=0; i<BufferSize; i++) {
            printf("%d ", buffer[i]);
        }
        printf("\n\n");

        pthread_mutex_unlock(&mutex); //Exiting Critical Region
        sem_post(empty);
        sleep(3);
    }
    pthread_exit(NULL);
}

#include <stdio.h>
#include <unistd.h>
#include <stdlib.h>
#include <string.h>
#include <pthread.h>
#include <semaphore.h>

#define BufferSize 5

```

```

void *producer(void *arg);
void *consumer(void *arg);

sem_t *empty;
sem_t *full;
pthread_mutex_t mutex;
int in=0;
int out=0;
int buffer[BufferSize];

int main() {

    int res,i,sizeP,sizeC;
    pthread_t *threadP,*threadC;

    //Accepting Number of Prodecers and Consumers
    printf("\nNumber of Producers: ");
    scanf("%d",&sizeP);

    printf("Number of Consumers: ");
    scanf("%d",&sizeC);
    printf("\n");

    //Creating one thread per precessor and per consumer. For
    example if 3 producer then 3 threads for each producer.
    threadP=(pthread_t*)malloc(sizeof(pthread_t)*sizeP);
    threadC=(pthread_t*)malloc(sizeof(pthread_t)*sizeC);
    int pno[sizeP],cno[sizeC];

    //Creating semaphores
    full=sem_open("/fullSem", O_CREAT, 0644, 0);
    empty=sem_open("/emptySem", O_CREAT, 0644, BufferSize);
    pthread_mutex_init(&mutex, NULL);

    //Function Calls
    for(i=0;i<sizeP;i++) {
        pno[i]=i+1;
        res=pthread_create(&threadP[i], NULL, producer, &pno[i]);
    }
    for(i=0;i<sizeC;i++) {
        cno[i]=i+1;
        res=pthread_create(&threadC[i], NULL, consumer, &cno[i]);
    }
    for(i=0;i<sizeP;i++)
        res=pthread_join(threadP[i], NULL);
    for(i=0;i<sizeC;i++)
        res=pthread_join(threadC[i], NULL);
}

```

```

//destroying the semaphores
pthread_mutex_destroy(&mutex);
sem_unlink("/fullSem");
sem_unlink("/emptySem");

exit(EXIT_SUCCESS);
}

void *producer(void *arg) {

    while(1) {
        int item=rand();

        sem_wait(empty);
        pthread_mutex_lock(&mutex); //Entering Critical Region

        buffer[in]=item%100;
        int pos=in;
        in=(in+1)%BufferSize;

        printf("Thread ID: %d. Producer: %d", (int)pthread_self()
%100, *(int*)arg); //Printing Thread ID and Producer Number
        printf("\nProduced item %d at %d position\nBuffer:
[ ", item%100, pos);

        //Displaying Buffer after Production
        for(int i=0; i<BufferSize; i++) {
            printf("%d ", buffer[i]);
        }
        printf("]\n\n");

        pthread_mutex_unlock(&mutex); //Exiting Critical Region
        sem_post(full);
        sleep(3);
    }
    pthread_exit(NULL);
}

void *consumer(void *arg) {

    while(1) {

        sem_wait(full);
        pthread_mutex_lock(&mutex); //Entering Critical Region

        int item=buffer[out];
        int pos=out;
        out=(out+1)%BufferSize;
    }
}

```

```

        printf("Thread ID: %d. Consumer: %d", (int)pthread_self()
%100, *(int*)arg); //Printing Thread ID and Consumer Number
        printf("\nConsuming item %d from %d position\nBuffer:
[ ", item, pos);

        //Displaying Buffer before Consumption
        for(int i=0; i<BufferSize; i++) {
            printf("%d ", buffer[i]);
        }
        printf("]->[ ");

        //Displaying Buffer after Consumption
        buffer[pos]=0;
        for(int i=0; i<BufferSize; i++) {
            printf("%d ", buffer[i]);
        }
        printf("]\n\n");

        pthread_mutex_unlock(&mutex); //Exiting Critical Region
        sem_post(empty);
        sleep(3);
    }
    pthread_exit(NULL);
}

```

Output:

Someshwars-MacBook-Pro:Assignments someshwargaikwad\$./Assignment

Number of Producers: 3
Number of Consumers: 2

Thread ID: 40. Consumer: 2
Consuming item 0 from 0 position
Buffer:[0 0 0 0 0]->[0 0 0 0 0]

Thread ID: 64. Consumer: 1
Consuming item 0 from 1 position
Buffer:[0 0 0 0 0]->[0 0 0 0 0]

Thread ID: 12. Producer: 2
Produced item 49 at 0 position
Buffer:[49 0 0 0 0]

Thread ID: 36. Producer: 1
Produced item 7 at 1 position

Buffer:[49 7 0 0 0]

Thread ID: 40. Consumer: 2
Consuming item 0 from 2 position
Buffer:[49 7 0 0 0]->[49 7 0 0 0]

Thread ID: 64. Consumer: 1
Consuming item 0 from 3 position
Buffer:[49 7 0 0 0]->[49 7 0 0 0]

Thread ID: 88. Producer: 3
Produced item 73 at 2 position
Buffer:[49 7 73 0 0]

Thread ID: 36. Producer: 1
Produced item 58 at 3 position
Buffer:[49 7 73 58 0]

Thread ID: 64. Consumer: 1
Consuming item 0 from 4 position
Buffer:[49 7 73 58 0]->[49 7 73 58 0]

Thread ID: 40. Consumer: 2
Consuming item 49 from 0 position
Buffer:[49 7 73 58 0]->[0 7 73 58 0]

Thread ID: 12. Producer: 2
Produced item 30 at 4 position
Buffer:[0 7 73 58 30]

Thread ID: 36. Producer: 1
Produced item 72 at 0 position
Buffer:[72 7 73 58 30]

Thread ID: 40. Consumer: 2
Consuming item 7 from 1 position
Buffer:[72 7 73 58 30]->[72 0 73 58 30]

Thread ID: 88. Producer: 3
Produced item 72 at 1 position
Buffer:[72 72 73 58 30]

Thread ID: 64. Consumer: 1
Consuming item 73 from 2 position
Buffer:[72 72 73 58 30]->[72 72 0 58 30]

Thread ID: 12. Producer: 2
Produced item 44 at 2 position

Buffer:[72 72 44 58 30]

Thread ID: 40. Consumer: 2

Consuming item 58 from 3 position

Buffer:[72 72 44 58 30]->[72 72 44 0 30]

Thread ID: 64. Consumer: 1

Consuming item 30 from 4 position

Buffer:[72 72 44 0 30]->[72 72 44 0 0]

Thread ID: 36. Producer: 1

Produced item 78 at 3 position

Buffer:[72 72 44 78 0]

Thread ID: 88. Producer: 3

Produced item 23 at 4 position

Buffer:[72 72 44 78 23]

Thread ID: 40. Consumer: 2

Consuming item 72 from 0 position

Buffer:[72 72 44 78 23]->[0 72 44 78 23]

Thread ID: 64. Consumer: 1

Consuming item 72 from 1 position

Buffer:[0 72 44 78 23]->[0 0 44 78 23]

Thread ID: 12. Producer: 2

Produced item 9 at 0 position

Buffer:[9 0 44 78 23]

Thread ID: 36. Producer: 1

Produced item 40 at 1 position

Buffer:[9 40 44 78 23]

^C

Someshwars-MacBook-Pro:Assignments someshwargaikwad\$