

# PyGame Sprites

- these notes show how sprites can be created
  - without object orientation
  - and also with object orientation
- they re-implement the bouncing ball demo which we covered in earlier weeks
  - using sprites rather than images

# PyGame Sprites

- sprites are quite complicated
  - in my experience this is due to their close association with object orientation
  - you can use sprites without object orientation
  - for a small number of sprites this is easy enough and the code is smaller than its object orientated counterpart (and much simpler)
  - for any reasonable number of sprites  $\geq 3$  then should use OO as the reduction in code probably offsets the OO complication
- use object orientated sprites when implementing

## When to use sprites in PyGame

- when you have:
  - many instances of an object on the screen at a time
  - some objects that you need to track closely (e.g. collision detection)
    - sprites have a `self.rect` attribute, which can be passed to the function `colliderect` so Pygame will handle all collisions
  - a sprite's `update()` method, with a time argument, makes it easy to deal with a dynamic environment
- you can easily kill sprites if collisions occur (or create sounds)
  - sprites can be thought of as semi autonomous

## When not to use sprites

- when your:
  - objects don't share much (if any) code
    - and if you rarely have more than one copy of each object instantiated at a time
  - game entities (images) never move *by themselves* (eg. card decks)
- simple user interfaces are often easier to do with surfaces than with sprites

## Creating a simple sprite

```
#!/usr/bin/python3

import pygame
from pygame.locals import KEYDOWN

width  = 320
height = 240
size   = [width, height]
pygame.init()
screen = pygame.display.set_mode(size)
background = pygame.Surface(screen.get_size())

b = pygame.sprite.Sprite() # create sprite
b.image = pygame.image.load("ball.png").convert() # load ball image
b.rect = b.image.get_rect() # use image extent values
b.rect.topleft = [0, 0] # put the ball in the top left corner
screen.blit(b.image, b.rect)

pygame.display.update()
while pygame.event.poll().type != KEYDOWN:
    pygame.time.delay(100)
```

## The sprite in PyGame

- is an object that contains both:
  - an image (a surface)
  - and a location at which to draw that image (a Rect)
  
- term *sprite* is actually a holdover from older display systems that did such manipulations directly in hardware
  - Commodore 64, Commodore Amiga used this technique in early 1980s to early 1990s
  - other manufactures did exactly the same, Atari etc

## The sprite in PyGame

- sprites work well in object-oriented languages like Python
  - you have a standard sprite interface `pygame.sprite.Sprite`, and extend those classes as specific sprites
- see the `BallSprite` class in the example later on

## The sprite in PyGame

- sprites have two important instance variables
  - `self.image` and `self.rect`
  - `self.image` is a surface, which is the current image that will be displayed. `self.rect` is the location at which this image will be displayed when the sprite is drawn to the screen
- sprites also have one important instance method, `self.update`.



## Creating a simple sprite using an extra Class

```
#!/usr/bin/env python3

import pygame
from pygame.locals import KEYDOWN

class BallSprite(pygame.sprite.Sprite):
    image = None

    def __init__(self, location):
        pygame.sprite.Sprite.__init__(self)

        if BallSprite.image is None:
            # This is the first time this class has been
            # instantiated. So, load the image for this and
            # all subsequence instances.
            BallSprite.image = pygame.image.load("ball.png")
        self.image = BallSprite.image

        # Make our top-left corner the passed-in location.
        self.rect = self.image.get_rect()
        self.rect.topleft = location
```

## Creating a simple sprite using an extra Class



```
pygame.init()
screen = pygame.display.set_mode([320, 320])
b = BallSprite([0, 0]) # put the ball in the top left corner
screen.blit(b.image, b.rect)
pygame.display.update()
while pygame.event.poll().type != KEYDOWN:
    pygame.time.delay(10)
```

## Bouncing ball using sprites and no user defined classes

```
#!/usr/bin/env python3

import pygame
from pygame.locals import KEYDOWN

width  = 320
height = 240
size   = [width, height]
ydir = 1
xdir = 1
xpos = 0
ypos = 0
pygame.init()
screen = pygame.display.set_mode(size)
background = pygame.Surface(screen.get_size())

b = pygame.sprite.Sprite() # create sprite
b.image = pygame.image.load("ball.png").convert() # load image
b.rect = b.image.get_rect() # use image extent values
b.rect.topleft = [xpos, ypos] # put the ball in the top left corner
screen.blit(b.image, b.rect)
slow = 0
```

## Bouncing ball using sprites and no user defined classes

```
def gravity(y):  
    global height  
    return int (((height+height/20) * 3) / y)  
  
pygame.display.update()  
while pygame.event.poll().type != KEYDOWN:  
    pygame.time.delay(gravity(ypos))  
    # If we're at the top or bottom of the screen,  
    # switch directions.  
  
    if b.rect.bottom>=height:  
        ydir = -1  
    elif ypos == 0:  
        ydir = 1  
    if xpos == 0:  
        xdir = 1  
    elif b.rect.right>=width:  
        xdir = -1
```

## Bouncing ball using sprites and no user defined classes

```
if slow:
    screen.fill([0, 0, 0]) # blank the screen
else:
    rectlist = [screen.blit(background, b.rect)]

# Move our position up or down by one pixel
xpos += xdir
ypos += ydir
b.rect.topleft = [xpos, ypos]

if slow:
    screen.blit(b.image, b.rect)
    pygame.display.update()
else:
    rectlist += [screen.blit(b.image, b.rect)]
    pygame.display.update(rectlist)
```

## Bouncing ball using sprites and no user defined classes

```
#!/usr/bin/env python3

import pygame
from pygame.locals import KEYDOWN

class BallSprite(pygame.sprite.Sprite):
    image = None

    def __init__(self, initial_position):
        pygame.sprite.Sprite.__init__(self)
        if BallSprite.image is None:
            BallSprite.image = pygame.image.load("ball.png")
        self.image = BallSprite.image

        self.rect = self.image.get_rect()
        self.rect.topleft = initial_position
        self.going_down = True # Start going downwards
        self.next_update_time = 0 # update() hasn't been called yet.
```

## Bouncing ball using sprites and no user defined classes

```
def update(self, current_time, bottom):
    # Update every 10 milliseconds = 1/100th of a second.
    if self.next_update_time < current_time:

        # If we're at the top or bottom of the screen, switch directions.
        if self.rect.bottom == bottom - 1: self.going_down = False
        elif self.rect.top == 0: self.going_down = True

        # Move our position up or down by one pixel
        if self.going_down: self.rect.top += 1
        else: self.rect.top -= 1

    self.next_update_time = current_time + 10
```

## Bouncing ball using sprites and no user defined classes

```
pygame.init()
boxes = []
for location in [[0, 0],
                 [60, 60],
                 [120, 120]]:
    boxes.append(BallSprite(location))

screen = pygame.display.set_mode([150, 150])
while pygame.event.poll().type != KEYDOWN:
    screen.fill([0, 0, 0]) # blank the screen.

    time = pygame.time.get_ticks()
    for b in boxes:
        b.update(time, 150)
        screen.blit(b.image, b.rect)
    pygame.display.update()
```



## Bouncing ball using sprites and no user defined classes

- it is worth noting that the OO solution uses processor resources efficiently

## The event loop

```
while True:
    event = pygame.event.wait()
    if event.type == pygame.QUIT:
        sys.exit(0)
    if event.type == KEYDOWN:
        if event.key == K_ESCAPE:
            sys.exit (0)
```

- consider the above section of code

- it waits for an event to occur and then acts upon the event
- an event will be mouse movement, mouse click, key up/down etc

- what happens if there is no event present?

## The event loop

- various event retrieval mechanisms in Pygame
  - read the documentation for ideas
- how do we handle the problem of no events occurring?

## USEREVENTS

- one mechanism is to poll the event queue
  - this is a lazy programming mechanism and cpu intensive
- a better solution is to introduce USEREVENTS

## USEREVENT example code (snippet)



```
def updateAll ():
    if allExplosions != []:
        for e in allExplosions:
            e.update ()
        pygame.display.flip ()
        pygame.time.set_timer (USEREVENT+1, delay)
```

## USEREVENT example code (snippet)

```
def wait_for_event ():  
    global screen  
    while True:  
        event = pygame.event.wait ()  
        if event.type == pygame.QUIT:  
            sys.exit(0)  
        if event.type == KEYDOWN and event.key == K_ESCAPE:  
            sys.exit (0)  
        if event.type == pygame.MOUSEBUTTONDOWN and event.button == 1:  
            createExplosion (pygame.mouse.get_pos ())  
        if event.type == USEREVENT+1:  
            updateAll ()
```

## Tutorial

- try out the example code given in the lecture
- make sure you completed last weeks tutorial and adapt this code and
  - without using sprites, implement an explosion class
  - which is activated at the cursor position on the screen
- an explosion can be visually generated by drawing expanding circles
  - and then by reversing the size (remembering to blank out the larger ones)