

Programming Proverbs

- 13 Do not recompute constants within a loop
- 14 Avoid implementation-dependent features
- Henry F. Ledgard, “Programming Proverbs: Principles of Good Programming with Numerous Examples to Improve Programming Style and Proficiency”, (Hayden Computer Programming Series), Hayden Book Company, 1st edition, ISBN-13: 978-0810455221, December 1975.

Know your tools

- “a bad workman blames his tools”,

Cambridge Idioms Dictionary

- we will examine:

- emacs, etags, grep, diff, patch, gcc, gm2, cvs, gdb, git

emacs customisation (\$HOME/.emacs) for ioquake

```
;; F5 loads in the .gdbinit file ready for debugging ioquake
(defun my-find-file-debug ()
  "load a file"
  (interactive)
  (find-file (concat (getenv "HOME") "/Sandpit/ioquake-latest/ioquake3/.gdbinit")))
(global-set-key [f5] 'my-find-file-debug)

;; F12 compiles ioquake
(setq compile-command "make")
(defun my-compile ()
  "run the compile command after moving to the correct directory"
  (interactive)
  (find-file (concat (getenv "HOME") "/Sandpit/ioquake-latest/ioquake3/.gdbinit")))
(compile compile-command)

;; compile ioquake by pressing
(global-set-key [f12] 'my-compile)

;; F8 moves to the next error in the source file.
(global-set-key [f8] 'next-error)
```

emacs

- in conclusion you *need* to use an editor which is capable of running gdb, etags and grep.
- there are other candidates codeblocks, kdevelop and elipse.
- however emacs is the most mature and also it can be used for many other activities (other than programming).

etags

- the etags program is used to create a tag table file, in a format understood by emacs
- it understands the syntax for the following languages:
 - C, Objective C, C++, Java, Fortran, Ada, Cobol, Erlang, LaTeX, Emacs Lisp/Common Lisp, makefiles, Pascal, Perl, Postscript, Python, Prolog, Scheme and most assembler

Obtaining the modified ioquake tarball

- you will need this to undertake the following tutorial and also the coursework
- open up a terminal and type:

```
$ cd $HOME
$ mkdir -p Sandpit
$ cd Sandpit
$ wget http://floppsie.comp.glam.ac.uk/download/c/ioquake-latest.tar.gz
$ tar xzf ioquake-latest.tar.gz
```

Running etags

- open up a terminal and change directory to the ioquake-latest directory

- ```
$ cd $HOME/Sandpit/ioquake-latest
$ cd ioquake3
$ etags */*.[ch] */**/*.[ch]
```

- the last command requests etag scan each C .c and .h file in all directories one level below the current
- etags builds an index for every type, function, variable declaration
  - it also builds indices for #define's

## Using etags

- now start emacs and press <F5>
- now load in a new file: `^x^f code/server/sv_game.c`
- cursor down to the declaration of the function `SV_GameSystemCalls`
- now continue further and find the call to function `SV_CheckRPC`
  - place the cursor on top of this function
  - now press <Esc> . <enter>
  - emacs will request you enter the TAGS file, you can delete the last path entry. So the path will match the location where you invoked the etags program
  - ie the path must match `~/Sandpit/ioquake-latest/ioquake3`
  - now emacs will now take you to the declaration of



SV\_CheckRPC

## Using etags

- now split the screen into two and continue to follow the function calls
- `updatePy -> testFor -> execFunction`
- now use etags to find the function `putPacket`



- or how to find where functions are called
- read the manual page for `grep`
  - this can be done from within emacs via `M-x man <enter> grep <enter>`
- return back to the buffer `sv_game.c`
- now type: `M-x grep <enter> putPacket ../*/*. [ch] <enter>`
- now you can use the `<F8>` key to move to the next occurrence of `putBuffer`



- the previous `grep` command was instructed to find all occurrences of `putPacket` in all C `.c` and `.h` files and output these findings in an emacs compatible format

## diff and patch

- read the manual pages for `diff` and `patch`
- see if you can do this from within `emacs`

## diff and patch

- now switch to the `sv_game.c` buffer and split the screen into two
- move to the top of the `sv_game.c` and mark this position  
`<ctrl><space>`
- now move to the end of the buffer and copy the whole file into the yank buffer `<esc>w`
- move to the other window `^xo` and open up a new file `^x^f`  
`sv_game.c-test`

## diff and patch

- now yank the internal buffer into this file ^y
- now make a single line change (maybe just add your name in a comment)
  - anywhere in the file
- save the file ^xs

## diff and patch

- now make emacs run the bash shell via M-x shell <enter>
- and type:
- ```
$ diff sv_game.c sv_game.c-test
```
- note the output

diff and patch

- `diff`'s are a useful method of transferring textual changes and posting changes to co-developers
- nearly all free software/open source projects operate on this principle
 - this has had a major impact on keeping these free software/open source projects highly portable
- give the flexibility of `diff` and `patch` it is often possible to apply textual patches to later releases of the same project
 - not always, and sometimes a few *hunks* require fixing

diff and patch

- in the early days of free software projects were maintained by creating patches and diffs by hand
- fortunately now there are tools which perform most of this automatically
 - and coordinate all the source files in a project
- these are content management systems such as:
 - cvs, git, svn

diff and patch

- [svn or subversion](http://subversion.tigris.org/) `<http://subversion.tigris.org/>`
- [git](http://git-scm.com/) `<http://git-scm.com/>`
- [cvs](http://www.nongnu.org/cvs/) `<http://www.nongnu.org/cvs/>`
- we will be concentrating on git as it is used by the ioquake3 project



- open up a terminal and type in the following:

```
$ mkdir -p $HOME/Sandpit/ioquake3-git  
$ cd $HOME/Sandpit/ioquake3-git  
$ git clone git://github.com/ioquake/ioq3.git
```

- these commands create a new directory
\$HOME/Sandpit/ioquake3-git and change your current working
directory to this location
- finally it checks out the latest copy of the development version of
ioquake3



- now type:

- ```
$ cd ioquake3
$ make
```

- this builds the latest `ioquake3`

- you should be able to run this by typing:

- ```
$ ./build/debug-linux-x86_64/ioquake3.x86_64
```



- run it, load up the level `pom_bots` and play against alien or legoman
- take note at the smoke and blood when using the grenade launcher and the rocket launcher



- now open up another terminal and type:

```
$ cd $HOME/Sandpit/ioquake-latest/ioquake3  
$ ./compilequake  
$ ./build/debug-linux-x86_64/ioquake3.x86_64
```

- run it, load up the level `pom_bots` and play against alien or legoman
- take note at the smoke and blood when using the grenade launcher and the rocket launcher



- open up another terminal and type:

```
$ cd $HOME/Sandpit/ioquake-latest/ioquake3  
$ svn diff
```

- this will yield the code changes which were made in order that the blood, smoke, gibs and Python bot work

Tutorial work

- see if you can create a patch set from the modified ioquake3 which can be applied to the ioquake3-svn tree
- hint you need to capture the `diff`'s and use `patch` to apply them
 - however you also need to make copies of some new files which are not in the svn tree
- the new files can be found by typing:

```
$ cd $HOME/Sandpit/ioquake-latest/ioquake3
$ svn status
```

Tutorial

- read through the code: `$HOME/Sandpit/ioquake-latest/python-bot/bot-legoman/botfiles/bots/legoman.py`
`$HOME/Sandpit/ioquake-latest/python-bot/bot-legoman/botfiles/bots/botlib.py`
`$HOME/Sandpit/ioquake-latest/ioquake3/code/botlib/be_ai_py.[ch]`
`$HOME/Sandpit/ioquake-latest/ioquake3/code/botlib/be_ai_char.c`
also read the directed reading at the end of lecture 0



- GNU debugger
 - online documentation is available [here](http://sourceware.org/gdb/current/onlinedocs/gdb) `<http://sourceware.org/gdb/current/onlinedocs/gdb>`.

- read the
 - summary
 - sample session
 - GDB commands and
 - stopping and continuing

Debugging ioquake3

- you will need two computers, side by side
- on the left computer log in, open a terminal and change directory to ioquake-latest
- ```
$ cd $HOME/Sandpit/ioquake-latest/ioquake3
```
- and start the debugging version of ioquake3 under the debugger

## Debugging ioquake3

- \$ ./debugquake
- at this point the debugger (GDB) is split into two
  - the server is manipulating ioquake3
- the GDB client will be controlled by you

## Debugging ioquake3

- on the right computer login and start emacs
  - maximise it to its rightful size, full screen
  - press F5

## Debugging ioquake3

- the first line requires modifying, change `localhost` for the FQDN of the computer running ioquake3 under the debugger
- you should be given a GDB prompt
  - now type
- (gdb) **cont**
- and debug the ioquake3 as you would debug an ordinary binary
  - there are a few differences
  - never type `run`
  - and always finish the debugging session by typing `quit`