```
#
#   create_cache – Pre-condition:  None.
#                  Post-condition:  directory $HOME/.cache/touchgui created.
#

def _create_cache ():
    d = os.path.join (os.path.join (os.environ["HOME"], ".cache"), "touchgui")
    os.system ("mkdir -p %s" % (d))
```

■ **$HOME/Sandpit/touchgui/touchgui.py**

```
#
#  reset_cache - Pre-condition:  None.
#                Post-condition:  all contents of $HOME/.cache/touchgui are deleted.
#


def reset_cache ():
    d = os.path.join (os.path.join (os.environ["HOME"], ".cache"), "touchgui")
    _safe_system ("rm -r %s" % (d))
    _create_cache ()

reset_cache ()
```

■ you should enable `reset_cache()` which will delete the cache and create an empty cache directory

Adding double tap to construct walls

- it would be good to add the ability for users to double tap and create walls along an axis

- requires a change to `cell_back` and keeping track of the `last_pos` tapped

Adding double tap to construct walls

```python
last_pos = [] # the last saved position

#
#   save_wall_pos - saves the coordinate [x, y] to last_pos
#

def save_wall_pos (x, y):
    global last_pos
    last_pos = [x, y]


#
#   match_line - return True if [x, y] is the same as the last_pos
#

def match_line (x, y):
    return (last_pos != []) and ((last_pos[0] == x) or (last_pos[1] == y))
```

Adding double tap to construct walls

```python
def cellback (param, tap):
    global clicked, cell_array, button_array, last_pos
    clicked = True
    mouse = pygame.mouse.get_pos ()
    x, y = get_cell (mouse)
    old = cell_array.get (x + xoffset, y + yoffset)
    button = button_array.get (x + xoffset, y + yoffset)
    if (old in ["v", " "]) and (tap == 2):
        save_wall_pos (x + xoffset, y + yoffset)
    elif old == " ":
        # blank -> next_tile
        if match_line (x + xoffset, y + yoffset):
            draw_line (x + xoffset, y + yoffset)
        else:
            function_create[next_tile] (button)
        last_pos = []  # forget about last_pos
    ...
```

Adding double tap to construct walls

```
#
#   draw_line - draw a line from the last_pos to, [x, y] providing [x, y]
#               lies on the same axis.
#

def draw_line (x, y):
    global cell_array, button_array
    if last_pos != []:
        if last_pos[0] == x:
            for j in range (min (y, last_pos[1]), max (y, last_pos[1])+1):
                old = cell_array.get (x, j)
                button = button_array.get (x, j)
                if old == " ":
                    button.to_wall ()
                    cell_array.set_contents (x, j, "v")
```

Adding double tap to construct walls

```
        elif last_pos[1] == y:
            for i in range (min (x, last_pos[0]), max (x, last_pos[0])+1):
                old = cell_array.get (i, y)
                button = button_array.get (i, y)
                if old == " ":
                    button.to_wall ()
                    cell_array.set_contents (i, y, "v")
```

Implementing a safe export

- it would be good if the export facility checked to see that the map exported was successfully converted by chisel
  - `chisel` like all GNU/Linux and Unix programs exits with status 0 on success
  - and non zero on failure
  - we can test this and change the doom3 button (freeze it)

- we need to change: `myexport` and add `try_export` which can also be called from the `mydoom3` callback

Implementing a safe export

```
def myexport (name, tap):
    pygame.display.update ()
    save_map (current_map_name)
    try_export (os.getcwd (), current_map_name)

def try_export (directory, map_name):
    os.chdir (os.path.join (os.getenv ("HOME"), "Sandpit/chisel/python"))
    r = os.system ("./developer-txt2map " + os.path.join (directory, map_name))
    os.chdir (directory)
    if r == 0:
        print "all ok"
        doom_button.set_images (private_list ("doom3"))
    else:
        doom_button.set_images (error_list ("doom3"))
```

Implementing a safe export

```
def mydoom3 (param, tap):
    pygame.display.update ()
    pygame.time.delay (toggle_delay * 2)
    try_export (os.getcwd (), "test.txt")
    pygame.quit ()
    dmap ()
    exec_doom_map ()
    quit ()
```