

Interprocess communication

- in Operating systems we find there are a number of mechanisms used for interprocess communication (IPC)
- the IPC mechanisms can be divided into two groups, those which work well using shared memory and those which work with non shared memory
- some common methods of IPC are: sockets, semaphores and mailboxes
- sockets and mailboxes are normally used by non shared memory programs
 - ie client and server on different machines

Interprocess communication in shared memory systems

- semaphores are more appropriate for multiple processes sharing some common memory
- we will be covering a semaphores and message passing after networking with sockets
- message passing
 - can be used in shared memory systems

Interprocess communication in non shared memory systems

- network sockets (Berkeley and System V Transport Layer Interface)
 - work well with programs (clients and servers) which do not share the same memory

- message passing
 - can be used in non shared memory systems

Berkeley Sockets

- the Berkeley interface to sockets ultimately gives the programmer a file descriptor on both client and server which can be both read from and written to
- this is elegant as the user application can map its functionality onto basic file primitives: read, write
- Berkeley sockets are available in many languages and available on most operating systems

Berkeley Sockets



Program	Description	Function
server	create end point	<code>socket ()</code>
	bind address	<code>bind ()</code>
	specify queue	<code>listen ()</code>
	wait for connection	<code>accept ()</code>
client	create end point	<code>socket ()</code>
	bind address	<code>bind ()</code>
	connect to server	<code>connect ()</code>

Berkeley Sockets



Program	Description	Function
	transfer data	<code>read()</code> <code>write()</code> <code>recv()</code> <code>send()</code>
	datagrams	<code>recvfrom()</code> <code>sendto()</code>
	terminate	<code>close()</code> <code>shutdown()</code>

Connection oriented sockets (TCP sockets)



Consider Python Code for a TCP Server

tcpserver.py

```
#!/usr/bin/python

from socket import *
myHost = ""
myPort = 2000

# create a socket
s = socket(AF_INET, SOCK_STREAM)
# bind it to the server port number
s.bind((myHost, myPort))
# allow 5 pending connections
s.listen(5)

while True:
    # wait for next client to connect
    connection, address = s.accept()
    data = connection.recv(1024)
    while data:
        connection.send("echo -> " + data)
        data = connection.recv(1024)
    connection.close()
```


Consider Python Code for a TCP client



`tcpclient.py`

```
#!/usr/bin/python

import sys
from socket import *
serverHost = "localhost"
serverPort = 2000

# create a TCP socket
s = socket(AF_INET, SOCK_STREAM)

s.connect((serverHost, serverPort))
s.send("Hello world")
data = s.recv(1024)
print data
```

Testing the code

- open up an editor and type in the server Python code
- save it as `tcpserver.py`
- now open up a terminal and type
- ```
$ python tcpserver.py
```
- make a note of the FQDN of the server

## Testing the code

- open up another editor and type in the client Python code
- save it as `tcpclient.py`
- open up a terminal

## Testing the code

- `$ python tcpclient.py`
- notice that both client and server are working on the same machine

## Testing the code

- change the variable `serverHost` in `tcpclient.py` to the FDQN of your neighbours machine
  - and run your client again!

## Application protocol using TCP

- TCP is used by many application level protocols
  - a very common one is http
- let us build a tiny web server in Python!

# Tiny web server in Python



mywebserver.py

```
#!/usr/bin/python

from socket import *
myHost = ""
myPort = 2000

create a socket
s = socket(AF_INET, SOCK_STREAM)
bind it to the server port number
s.bind((myHost, myPort))
allow 5 pending connections
s.listen(5)
```

# Tiny web server in Python

mywebserver.py

```
while True:
 # wait for next client to connect
 connection, address = s.accept()
 data = connection.recv(1024)
 while data:
 reply = """HTTP-Version: HTTP/1.0 200 OK
Content-Length: 3012
Content-Type: text/html

<p>Hello world!</p>
<body>
"""
 connection.send(reply)
 data = connection.recv(1024)
 connection.close()
```



## Testing your web server

- open up a terminal and run

- `pythonmywebserver.py`

- now open up a browser and enter the url `<http://localhost:2000>`

- you should now have a start of a tiny web server

## Testing your web server

- we can see that a socket is created to give us access to manage the TCP port 2000
- in turn the program will read from the socket and form a http response
  - which is sent back to the client which renders the html after stripping it from the http packet

## UDP sockets

- we can also produce a UDP client and server
  - these are functionally different to TCP servers, despite the similarity between the Python code implementation

## UDP server

```
#!/usr/bin/python

from socket import *
myHost = ""
myPort = 2000

create a UDP socket
s = socket(AF_INET, SOCK_DGRAM)
bind it to the server port number
s.bind((myHost, myPort))

data, address = s.recvfrom(1024)
while data:
 print "UDP server:", data, "from", address
 s.sendto("echo -> " + data, address)
 data, address = s.recvfrom(1024)
```

# UDP client

udpclient.py

```
#!/usr/bin/python

import sys
from socket import *
serverHost = "localhost"
serverPort = 2000

create a UDP socket
s = socket(AF_INET, SOCK_DGRAM)

s.connect((serverHost, serverPort))
s.send("Hello world")
data = s.recv(1024)
print data
```