Lecture: 2-1

Prerequisites for this lecture are: 1-1 and.

John Romero Programming Proverbs

- 2. "It's incredibly important that your game can always be run by your team. Bulletproof your engine by providing defaults (for input data) upon load failure."
- John Romero, "The Early Days of Id Software John Romero @ WeAreDevelopers Conference 2017"

Python

Python is a scripting language

Python Gotha's

- blocks are defined by indentation!
- turn off tabs in your favourite editor
- in your own programs examples never create a name clash with a Python library module
- Python2 vs Python3
 - we will be using Python3

Python verses similar tools

- Python is a scripting language
 - it can be compiled if necessary to increase speed
- is more powerful than many other scripting languages, Tcl
 - applicable to larger systems development (games, net admin)
- has a much cleaner syntax than Perl
 - easier to maintain
- does not compete head on with Java
 - Java is a systems language like C++

Python and games

examples of games which use Python \(\text{http://} \)
wiki.python.org/moin/PythonGames \(\text{} \)

Python can be simple

#!/usr/bin/python3

print("hello world")

Python Modules allow for problem decomposition

similar to Modula-2

myfile.py

```
#!/usr/bin/python3
title = "hello world"
```

foo.py

```
#!/usr/bin/python3
import myfile
print(myfile.title)
```

when run prints hello world

Alternative import

bar.py

```
#!/usr/bin/python3
from myfile import title
print(title)
```

- note that all python modules need to be saved as *name*.py
 - so in our example the module myfile was saved into a file called myfile.py

Python builtin types

- python contains many builtin types
 - use them..
- builtin objects make simple programs easy to understand
 - lists, dictionaries, exist, don't reinvent the wheel
- built in objects are more efficient than custom data types

Builtin objects

```
numbers 3.14159, 1234
strings 'spam', "fred's"
lists [1, [2, 'three'], 4]
dictionaries {'food':'spam', 'taste':'yum'}
tuples (1, 'spam', 4, 'U')
files text=open('/etc/passwd', 'r').read()
```

Expression operators

or, and, not logical operators (short circuit) <, <=, >, >=, ==, <>, != comparison operators $x \mid y$ bitwise or z & y bitsize and shift left by y bits x << y shift right by y bits x >> y x[i]indexing x[i:y]slicing qualifying (imports) x.y function calls x(y)

Strings

- concatenation via +
 - repeated via *