

Python Modules

- there are many Python modules available
- which cover many topics
 - networking modules
 - graphic modules, OpenGL, GUI, graphing
 - mail, http, telnet, pop3, imap modules
 - operating system modules
- html parsing modules
- examine the Python modules [python online docs](http://floppsie.comp.glam.ac.uk/python/html/index.html) `<http://floppsie.comp.glam.ac.uk/python/html/index.html>`



- used to download files from servers using
 - ftp, http and local file access

urllib example



```
#!/usr/bin/python3

from urllib.request import urlretrieve

urlretrieve("http://floppsie.comp.glam.ac.uk/index.html",
            "temp.html")
```

urllib example



```
#!/usr/bin/python3

import os
import urllib.request, urllib.parse, urllib.error
Version = "3.7.4"
filename = "Python-%s.tgz" % Version
remoteaddr = "https://www.python.org/ftp/python/%s/" % Version

urllib.request.urlretrieve(remoteaddr + filename,
                           filename)
```

smtp module

- Simple Mail Transport Protocol is the most common protocol whereby email is transmitted across the Internet



```
#!/usr/bin/python3

import smtplib, string, sys, time

mailserver = "localhost"

From = input("From: ").strip ()
To = input("To: ").strip ()
Subject = input("Subject: "). strip ()

Date = time.ctime(time.time())
Header = ("From: %s\nTo: %s\nDate: %s\nSubject: %s\n\n"
          % (From, To, Date, Subject))

Text = "my message"
server = smtplib.SMTP(mailserver)
failed = server.sendmail(From, To, Header + Text)
server.quit()
if failed:
    print("failed to send mail")
else:
    print("all done..")
```

Python Gotya's

- be careful to ensure that your code is indented correctly
- be very careful not to name your file to a name used by a library you are importing

Python Gotya's

- for example do **not** call this file `string.py`

```
#!/usr/bin/python3

import string

words=string.split("hello world again")
print words
```


Python Gotya's

- the python interpreter will read your file twice
 - one when you run the file
 - and again when it comes across the `import string` !
- name the file `teststring` and it will work fine
 - if you did call it `string.py` and run then you will need to remove `string.py` and also `string.pyc`

Python and file handling

- file manipulation primitives are by default available
 - no need to import library to, read, write files

Python and file handling

- creating a simple text file

- ```
#!/usr/bin/python3

file = open("newfile.txt", "w")
file.write("hello world in the new file\n")
file.write("and another line\n")
file.close()
```

# Python and file handling



```
#!/usr/bin/python3
```

```
file = open("newfile.txt", "w")
file.writelines(["hello world in the new file\n",
 "and another line\n"])
file.close()
```

# Python and file handling

```
#!/usr/bin/python3

file = open("newfile.txt", "r")
for line in file.readlines():
 print(line)
```

## ■ many ways to read a file

- `file.read()` returns a string containing all characters in the file
- `file.read(N)` returns a string containing next N characters
- `file.readline()` returns a string containing characters up to `\n`
- `file.readlines()` returns the complete file as a list of strings each separated by `\n`

## Further Python Networking

- many python modules which give access to application layer networking services
  - ftp, http, telnet, etc

## Further Python Networking

- sometimes you may have to implement your own application layer protocol
- in which case you use `sockets` (a transport layer service)

## server.py

```
#!/usr/bin/python3

from socket import *
myHost = ""
myPort = 2000

create a TCP socket
s = socket(AF_INET, SOCK_STREAM)
bind it to the server port number
s.bind((myHost, myPort))
allow 5 pending connections
s.listen(5)

while True:
 # wait for next client to connect
 connection, address = s.accept()
 while True:
 data = connection.recv(1024)
 if data:
 connection.send("echo -> " + data)
 else:
 break
 connection.close()
```



## client.py

```
#!/usr/bin/python3

import sys
from socket import *
serverHost = "localhost"
serverHost = "localhost"
serverPort = 2000

create a TCP socket
s = socket(AF_INET, SOCK_STREAM)

s.connect((serverHost, serverPort))
s.send("Hello world")
data = s.recv(1024)
print(data)
```

## To run the server client example

- open up another terminal and type this at the command line

- ```
$ python3 server.py
```

- open up another terminal and type this:

- ```
$ python3 client.py
```

## IMAP library

```
#!/usr/bin/python3

import getpass, imaplib, string

m = imaplib.IMAP4_SSL("unimail.isd.glam.ac.uk")
m = imaplib.IMAP4_SSL("outlook.office365.com")
m.login(getpass.getuser(), getpass.getpass())
m.select ()
typ, data = m.search (None, "ALL")
for num in string.split (data[0]):
 typ, data = m.fetch (num, "(RFC822)")
 print("Message %s\n%s\n" % (num, data[0][1]))
m.logout()
```

## Arguments in Python

- `getopts`, provides a useful method for handling arguments
  - in fact many languages have adopted `getopts`
  - C, C++, bash and python

## Autoftp arguments in python

```
#!/usr/bin/python3

import sys, getopt

def Usage ():
 print("autoftp [-v] [-p] [-h]")
 sys.exit(0)

optlist, list = getopt.getopt(sys.argv[1:], ":vphf:")
print("optlist =", optlist)
print("list =", list)
for opt in optlist:
 print(opt)
 if opt[0] == "-h":
 Usage()
 if opt[0] == "-f":
 print("file found")
 if opt[0] == "-v":
 print("verbose found")
 if opt[0] == "-p":
 print("probeonly found")
```

## Autoftp arguments in python

- notice that the script fails if an unsupported option is issued

- ```
./autoftp2.py -x
...
getopt.GetoptError: option -x not recognised
```

Better argument handling

- so we need a way to trap these errors
 - python uses an exception handler for this



```
#!/usr/bin/python3

import sys, getopt

def Usage ():
    print("autoftp [-v] [-p] [-h]")
    sys.exit(0)

try:
    optlist, list = getopt.getopt(sys.argv[1:],
                                   ":vphf:")
except getopt.GetoptError:
    Usage()
    print("called exception")
    sys.exit(1)

for opt in optlist:
    print(opt)
    if opt[0] == "-h":
        Usage()
    if opt[0] == "-v":
        print("verbose found")
    if opt[0] == "-p":
        print("probeonly found")
    if opt[0] == "-f":
        print("file option found")
```


Better argument handling

- when run it yields the following

- ```
./autoftp3.py -x
autoftp [-v] [-p] [-h]
```