Company Header

Definition:

Includes: Gutter or downspout, fittings, silicone caulk, and installation labor. Labor cost to remove downspout and to discard in a job-site waste receptacle.

Quality: Aluminum gutter up to 5" with or without baked on enamel finish. Aluminum downspout Green: LEED considers aluminum gutters/downspouts to be green for being manufactured with a n 25% recycled product.

Note: May be seamless. Each downspout fitting and mitered corner should be accounted for. For each downspout fitting equals one lineal foot. Longest measurements are typically used; measure to outside of an outside corner and to the inside of an inside corner. It may be helpful to add a note to item in order to detail the quantities of gutter and/or downspout being replaced. Generally, a contra have and use standard ladders, jacks, and plank scaffolding as part of their normal equipment toolse such, the labor yield assumption addresses the average time necessary for normal one or two story applications, including the set up and use of this equipment as needed, where the ladder scaffold planot exceed 20'. If additional labor is required, use item SFG LAB. The main material component fincludes an assumed waste factor of 10%.

Average life expectancy 25 years Average depreciation 4% per year Maximum depreciation 100%

Price list DOL

There are only a few people in our industry that understand the relationship between building codes, the construction process properly integrate that into the estimate. With 20 years of experience we can do that for you. There are only a few people in understand the relationship between building codes, the construction process and how to properly integrate that into the estimate of experience we can do that for you. There are only a few people in our industry that understand the relationship between but construction process and how to properly integrate that into the estimate. With 20 years of experience we can do that for you.