
COMP9319 Web Data Compression and Search

Space Efficient Linear Time
Construction of Suffix Arrays

Suffix Array

- Sorted order of suffixes of a string T .
- Represented by the starting position of the suffix.

Text	M	I	S	S	I	S	S	I	P	P	I	\$
Index	1	2	3	4	5	6	7	8	9	10	11	12
Suffix Array	12	11	8	5	2	1	10	9	7	4	6	3

Brief History

- Introduced by Manber and Myers in 1989.
- Takes $O(n \log n)$ time, and $8n$ bytes.
- Many other non-linear time algorithms.

Authors	Time	Space (bytes)
Manber & Myers	$n \log n$	$8n$
Sadakane	$n \log n$	$9n$
String-sorting	$n^2 \log n$	$5n$
Radix-sorting	n^2	$5n$

Our Result

1. Among the first linear-time direct suffix array construction algorithms. Solves an important open problem.
2. For constant size alphabet, only uses $8n$ bytes.
3. Easily implementable.
4. Can also be used as a space efficient suffix tree construction algorithm.

Notation

- String $T = t_1 \dots t_n$.
- Over the alphabet $\Sigma = \{1 \dots n\}$.
- $t_n = '$', '$' is a unique character.$
- $T_i = t_i \dots t_n$ denotes the i -th suffix of T .
- For strings α and β , $\alpha < \beta$ denotes α is lexicographically smaller than β .

Overview


- Divide all suffixes of T into two types.
 - Type S suffixes = $\{T_i \mid T_i < T_{i+1}\}$
 - Type L suffixes = $\{T_j \mid T_j > T_{j+1}\}$
 - The last suffix is both type S and L .
- Sort all suffixes of one of the types.
- Obtain lexicographical order of all suffixes from the sorted ones.

Identify Suffix Types


Type	L	S	L	L	S	L	L	S	L	L	L	L/S
Text	M	I	S	S	I	S	S	I	P	P	I	\$

The type of each suffix in T can be determined in one scan of the string.


Notation



Notation



Notation



Sorting Type S Suffixes

- Sort all type S substrings.
- Replace each type S substrings by its bucket number.
- New string is the sequence of bucket numbers.
- Sorting all type S suffixes = Sorting all suffixes of the new string.

Sorting Type *S* Substrings

Type

S

S

S

S

Text

M	I	S	S	I	S	S	I	P	P	I	\$
---	---	---	---	---	---	---	---	---	---	---	----

Bucket Sort

\$	I	I	I
	P	S	S
	P	S	S
	I	I	I
\$			

Sort each substring
until the next type
S character

Sorting Type S Substrings

Type

Text

3	3	2	1
---	---	---	---

Bucket Sort

\$	I	I	I
	P	S	S
	P	S	S
	I	I	I
	\$		

Substitute the substrings with the bucket numbers to obtain a new string.

Apply sorting recursively to the new string.

Sorting Type S Substrings

Type

Text

3	3	2	1
---	---	---	---

Bucket Sort

\$	I	I	I
	P	S	S
	P	S	S
	I	I	I
\$			

Bucket Sort
takes potentially
 $O(n^2)$ time

Solution

- Observation: Each character participates in the bucket sort at most twice.
 - Type L characters only participate in the bucket sort once.
- Solution:
 - Sort all the characters once.
 - Construct m lists according the distance to the closest type S character to the left

Illustration

Type		S			S			S				S
Index	1	2	3	4	5	6	7	8	9	10	11	12
Text	M	I	S	S	I	S	S	I	P	P	I	\$
Distance	0	0	1	2	3	1	2	3	1	2	3	4

Sorted
Order of
characters

12	2	5	8	11	1	9	10	3	4	6	7
----	---	---	---	----	---	---	----	---	---	---	---

Illustration

Type		S			S			S				S
Index	1	2	3	4	5	6	7	8	9	10	11	12
Text	M	I	S	S	I	S	S	I	P	P	I	\$
Distance	0	0	1	2	3	1	2	3	1	2	3	4

The Lists

9	3	6
10	4	7
5	8	11
12		

Sort the type *S*
substrings
using the lists

T		M	I	S	S	I	S	S	I	P	P	I	\$
Type			S			S			S				S
Pos		1	2	3	4	5	6	7	8	9	10	11	12
A		12	2	5	8	11	1	9	10	3	4	6	7

Step 1. Record the S-distances

Pos		1	2	3	4	5	6	7	8	9	10	11	12
Dist		0	0	1	2	3	1	2	3	1	2	3	4

Step 2. Construct S-distance Lists

1	9	3	6
2	10	4	7
3	5	8	11
4	12		

Step 3. Sort all type S substrings

Original

12	2	5	8
----	---	---	---

Sort according to list 1

12	8	5	2
----	---	---	---

Sort according to list 2

12	8	5	2
----	---	---	---

Sort according to list 3

12	8	5	2
----	---	---	---


Sort according to list 4

12	8	5	2
----	---	---	---

Fig. 3. Illustration of the sorting of type *S* substrings of the string MISSISSIPPI\$.

Construct Suffix Array for all Suffixes

- The first suffix in the suffix array is a type S suffix.
- For $1 \leq i \leq n$, if $T_{SA[i]-1}$ is type L, move it to the current front of its bucket



Sorted order of
type S suffixes

Run-Time Analysis (Sketch)

- Identify types of suffixes -- $O(n)$ time.
- Bucket sort type S (or L) substrings -- $O(n)$ time.
- Construct suffix array from sorted type S (or L) suffixes -- $O(n)$ time.

Conclusion

- Among the first suffix array construction algorithm takes $O(n)$ time.
- The algorithm can be easily implemented in $8n$ bytes (plus a few Boolean arrays).
- Equal or less space than most non-linear time algorithm.

Exercise

- Consider the popular example string S:
 - **bananaipajamas\$**
1. Construct the suffix array of S using the linear time algorithm
 2. Then compute the BWT(S)
 3. What's the relationship between the suffix array and BWT ?

Step – Identify the type of each suffix

- **LSLSLSSSLSLSLSL_{L/S}**
- **bananainpajamas\$**
- **1**
- **1234567890123456**

Step – Compute the distance from S

- LSLSSLSSLSLSLSLSL_{L/S}
- bananaipajamas\$
- 1111111
- 1234567890123456
- 0012121112121212

Step – Sort order of chars

■ **L S L S L S S S L S L S L S L**_{L/S}

■ **b a n a n a i n p a j a m a s \$**

■ **1 1 1 1 1 1 1**

■ **1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6**

■ **0 0 1 2 1 2 1 1 1 2 1 2 1 2 1 2**

■ **\$ a b i j m n p s**

■ **1 1 1 1 1 1 1**

■ **6 2 4 6 0 2 4 1 7 1 3 3 5 8 9 5**

Step – Construct m-Lists

■ **L S L S L S S S L S L S L S L**_{L/S}

■ **b a n a n a i n p a j a m a s \$**

■ **1 1 1 1 1 1 1**

■ **1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6**

■ **0 0 1 2 1 2 1 1 1 2 1 2 1 2 1 2**

■ **\$ a b i j m n p s**

■ **1 1 1 1 1 1 1**

■ **6 2 4 6 0 2 4 1 7 1 3 3 5 8 9 5**

Scan this
once and
bucket it
according to
dist.

Step – Generate m-Lists

- List 1
- [7], [11], [13], [3, 5, 8], [9], [15]
- List 2
- [16], [4, 6, 10, 12, 14]

■	2	0	2	2	2	2	2	0	1	1	1	1	1	1	1	1	1
■	\$	a							b	i	j	m	n		p	s	
■	i			1	1	1				1	1					1	
■	6	2	4	6	0	2	4	1	7	1	3	3	5	8	9	5	

Step – Sort S substrings

Bucket the S substrings

[16] , [2 , 4 , 6 , 10 , 12 , 14] , [7] , [8]

The diagram shows a 16-bit register with 16 columns and 6 rows of data. The columns are indexed 0 to 15. The data is as follows:

Index	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Bit 15											1	1	1	1	1	1
Bit 14	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6
Bit 13	0	0	1	2	1	2	1	1	1	2	1	2	1	2	1	2
Character	\$	a							b	i	j	m	n			p
Bit 12	1				1	1	1				1	1				1
Bit 11	6	2	4	6	0	2	4	1	7	1	3	3	5	8	9	5

Step – Sort S substrings

Bucket the S substrings

[16], [2, 4, 6, 10, 12, 14], [7], [8]

After using List 1:

[16], [6], [10], [12], [2, 4], [14], [7], [8]

List 2 useless. Then?

- List 1
- [7], [11], [13], [3, 5, 8], [9], [15]
- List 2
- [16], [4, 6, 10, 12, 14]

Step – Sort S substrings

Bucket the S substrings

[16], [2, 4, 6, 10, 12, 14], [7], [8]

After using List 1:

[16], [6], [10], [12], [2, 4], [14], [7], [8]

List 2 useless. Consider 6 before 4:

[16], [6], [10], [12], [4], [2], [14], [7], [8]

- List 1
- [7], [11], [13], [3, 5, 8], [9], [15]
- List 2
- [16], [4, 6, 10, 12, 14]

Step – Generate the Suffix Array

[16] , [6] , [10] , [12] , [4] , [2] , [14] , [7] , [8]

- \$a b i j m n p s
- 1 1 1 1 1 1 1
- 6 2 4 6 0 2 4 1 7 1 3 3 5 8 9 5

- \$a i n s
- 1 1 1 1 1
- 6 6 0 2 4 2 4 7 8 5

Step – Generate the Suffix Array

- \$a bi jmn ps
- 1 111 11 1
- 6246024171335895

- \$a in s
- 1 11 1 1
- 66024247585

Step – Generate the Suffix Array

- \$a b i j m n p s
- 1 1 1 1 1 1 1
- 6 2 4 6 0 2 4 1 7 1 3 3 5 8 9 5

- \$a i n p s
- 1 1 1 1 1
- 6 6 0 2 4 2 4 7 5 8 9 5

Step – Generate the Suffix Array

- \$a b i j m n p s
- 1 1 1 1 1 1 1
- 6 2 4 6 0 2 4 1 7 1 3 3 5 8 9 5

- \$a i j n p s
- 1 1 1 1 1 1
- 6 6 0 2 4 2 4 7 1 5 8 9 5

Step – Generate the Suffix Array

- \$a b i j m n p s
- 1 1 1 1 1 1 1
- 6 2 4 6 0 2 4 1 7 1 3 3 5 8 9 5

- \$a i j n p s
- 1 1 1 1 1 1
- 6 6 0 2 4 2 4 7 1 5 3 8 9 5

type S



Step – Generate the Suffix Array

- \$a b i j m n p s
- 1 1 1 1 1 1 1
- 6 2 4 6 0 2 4 1 7 1 3 3 5 8 9 5

- \$a b i j n p s
- 1 1 1 1 1 1
- 6 6 0 2 4 2 4 1 7 1 5 3 8 9 5

Step – Generate the Suffix Array

- \$a bi jmn ps
- 1 111 11 1
- 6246024171335895

- \$a bi jmn ps
- 1 11 1 11 1
- 6602424171353895

Final answer

- **bananaipajamas\$**
- **1111111**
- **1234567890123456**
- **Suffix Array:**
- **1 11 1 11 1**
- **6602424171353895**

Final answer

- **bananaipajamas\$**
- **1111111**
- **1234567890123456**
- **Suffix Array:**
- **1 11 1 11 1**
- **6602424171353895**

What is the BWT(S) ?

BWT is easy!

- **bananaipajamas\$**

- **1111111**

- **1234567890123456**

- **Suffix Array:**

- **1 11 1 11 1**

- **6602424171353895**

- **BWT:**

- **1 1 11 11 1**

- **5591313660242784**

BWT construction in linear time

- **bananaipajamas\$**
- **1111111**
- **1234567890123456**
- **BWT :**
- **1 1 11 11 1**
- **5591313660242784**
- **snpjnbm\$aaaaaina**