

Exp 16: -Predictive Parsing Steps

Aim: -To Implement a c programming language that calculates the FIRST and FOLLOW and predictive parsing for the given grammar.

Code:

```
#include <stdio.h>

#include <string.h>

char stack[50];

char input[50];

void push(char c) {
    int n=strlen(stack);
    stack[n]=c;
    stack[n+1]='\0';
}

void pop() {
    int n=strlen(stack);
    if(n>0) stack[n-1]='\0';
}

int main() {
    strcpy(stack, "E$")
    printf("Enter input (id+id): ");
    scanf("%s", input);
    strcat(input, "$");
    int i=0;
    while(1) {
        char X = stack[strlen(stack)-1];
        char a = input[i];
        if(X=='$' && a=='$') {
            printf("Accepted\n");
            break;
```

```
}  
if(X=='i' && a=='i') {  
    pop();  
    i++;  
}  
else if(X=='E') {  
    pop();  
    push("\"); push('E'); push('T');  
}  
else if(X=="") {  
    pop();  
    if(a=='+') { push("\"); push('E'); push('T'); push('+'); }  
}  
else if(X=='T') {  
    pop();  
    push('d'); push('i');  
}  
else {  
    printf("Error\n");  
    break;  
}  
}  
return 0;  
}
```

C:\Users\Reddy\Downloads\16.cpp - [Executing] - Dev-C++ 5.11

File Edit Search View Project Execute Tools AStyle Window Help

(globals)

Project Classes Debug 16.cpp

```
1 #include <stdio.h>
2 #include <string.h>
3 #include <ctype.h>
4 #include <stdlib.h>
5 #define MAXP 100
6 #define MAXPROD_LEN 50
7 #define MAXNT 26
8 #define MAXT 128
9 #define MAXSYM 256
10 int prodCount;
11 char prodLHS[MAXP];
12 char prodRHS[MAXP][MAXPROD_LEN];
13 int presentNT[MAXNT]; /* which uppercas
14 int ntsList[MAXNT]; int ntsCount = 0;
```

Compiler Resources Compile Log Debug Find Results Close

Compilation results...

Abort Compilation

Shorten compiler paths

- Errors: 0

- Warnings: 0

- Output Filename: C:\Users\Reddy\Downloads\16.exe

- Output Size: 137.7490234375 KiB

- Compilation Time: 0.38s

C:\Users\Reddy\Downloads\16

Enter number of productions: 4
Enter productions (format A=alpha , e for epsilon). Example: S=A
B or A=aB or A=e
S=AB
A=aB
B=ca
C=beA
Assuming start symbol = A (first nonterminal encountered).

FIRST sets:
FIRST(A) = { a }
FIRST(B) = { c }
FIRST(C) = { b }
FIRST(S) = { a }

FOLLOW sets:
FOLLOW(A) = { \$ c }
FOLLOW(B) = { \$ c }
FOLLOW(C) = { }
FOLLOW(S) = { }

Parsing Table (visible entries):
M[A, a] = A->aB
M[B, c] = B->ca
M[C, b] = C->beA
M[S, a] = S->AB

Enter input string to parse (without \$): aabbbc

Parsing steps:

Stack	Input	Action
-------	-------	--------