

Tensioner Hoses

Order No.	Topside, with Locking Collar DESCRIPTION
HL1M	1 m Hose, 1,500 bar, CE, with locking collar (only stocked in Europe & Asia)
HL13M	1.3 m Hose, 1,500 bar, CE, with locking collar (Optionally available in the Americas)
HL3M	3 m Hose, 1,500 bar, CE, with locking collar
HL5M	5 m Hose, 1,500 bar, CE, with locking collar
HL8M	8 m Hose, 1,500 bar, CE, with locking collar
HL10M	10 m Hose, 1,500 bar, CE, with locking collar

Additional lengths available upon request.

TENSION HOSES

1,500 bar/21,750 psi



9042D61500		1,500 bar; 21,750 psi digital gauge for P59L-1500 pumps
2002278		2,000 bar; 30,000 psi gauge for PE8 pumps. Typically attached with quick coupler (ordered separately).
HHAMA150001		1,500 Bar Elbow Block: Used to change direction of tensioner hoses if standard orientation is not possible. Hoses can swivel around coupling axis.
HHAMA150003		1,500 Bar Tee Block Assembly: Used to interconnect tensioners with single ports.
HHAMA150004		1,500 Bar Banjo Assembly: Used to allow a hose to connect to a tool at 90 degrees. The nipple can be oriented in any direction around the port axis but must be tightened to create a seal. Does not act as a swivel around port axis.

2001772		Male Coupling: Quick-connect, push-in male nipple. Used on 1,500 bar tensioners and pumps. 6 1/4" Female Thread
2008548		Female Coupling: Quick-connect, push-in female coupling with locking collar. Used on 1,500 bar tensioners hoses. 6 1/4" Female Thread.
STDHC000025		1/4" BSP Plug: Used to plug a port when a banjo assembly or coupling will not be used.

Hoses come standard with recessed female coupler type (2008548). Flat Face couplers available upon request.