

Complexity

Decidability

Decision problem

- A problem with a yes / no answer
- E.g. Does graph G have an independent set of size k ?
- E.g. Is the maximum flow of graph G greater than k ?

Decidability

- A decision problem is decidable if there exists a Turing machine that halts on all inputs and accepts exactly the inputs for which the answer to the decision problem is "yes"
 - Either accepts or rejects, but doesn't loop
 - Equivalently, there exists an algorithm to solve the problem
-
- How do we know if there is a "good" algorithm to solve the problem?

Complexity

What should be the cutoff between a “good” algorithm and a “bad” algorithm?

- Proposal:
 - A “good” algorithm is one whose running time is a polynomial function of the size of the input
 - Other algorithms are “bad”
- This definition was adopted:
 - A problem is called tractable if there exists a “good” (polynomial-time) algorithm that solves it.
 - A problem is called intractable otherwise.

Complexity

- Is this a valid cutoff?

Assuming you can process 1 million computations per second

Time complexity function	Size n					
	10	20	30	40	50	60
n	.00001 second	.00002 second	.00003 second	.00004 second	.00005 second	.00006 second
n^2	.0001 second	.0004 second	.0009 second	.0016 second	.0025 second	.0036 second
n^3	.001 second	.008 second	.027 second	.064 second	.125 second	.216 second
n^5	.1 second	3.2 seconds	24.3 seconds	1.7 minutes	5.2 minutes	13.0 minutes
2^n	.001 second	1.0 second	17.9 minutes	12.7 days	35.7 years	366 centuries
3^n	.059 second	58 minutes	6.5 years	3855 centuries	2×10^8 centuries	1.3×10^{13} centuries

The Class P

The Class P contains all decision problems that are decidable by an algorithm that runs (on a deterministic Turing machine) in polynomial time in the size of the input

- Note - many of these problems are described as functional optimization problems
 - We'll discuss later how we can cast them as decision problems
- Greedy
 - Huffman: $O(n \log n)$, Interval scheduling: $O(n \log n)$
- Divide-and-Conquer
 - Mergesort: $O(n \log n)$, Select: $O(n)$
- Dynamic Programming
 - Floyd-Warshall: $O(n^3)$, Matrix Multiplication: $O(n^3)$
- Network Flow
 - Edmonds-Karp: $O(m^2n)$

Polynomial-Time Reductions

We've seen some examples already of polynomial-time reductions of one problem to another

- Using max-flow to solve maximum bipartite matching
- Weighted interval scheduling (with weights of 1) to solve regular interval scheduling

Polynomial-Time Reductions

Basic Idea. Suppose we could solve Y in polynomial time. What else could we solve in polynomial time?

Reduction. Problem X **polynomially reduces to** problem Y if arbitrary instances of problem X can be solved using:

- Polynomial number of standard computational steps, plus
- Polynomial number of calls to black box that solves problem Y .

Notation. $X \leq_p Y$.

Polynomial-Time Reduction

Purpose. Classify problems according to **relative** difficulty.

Design algorithms. If $X \leq_p Y$ and Y can be solved in polynomial time, then X **can** also be solved in polynomial time. Why?

Establish intractability. If $X \leq_p Y$ and X cannot be solved in polynomial time, then Y **cannot** be solved in polynomial time.

Establish equivalence. If $X \leq_p Y$ and $Y \leq_p X$, we use notation $X \equiv_p Y$.



up to cost of reduction

Does Transitivity hold for polynomial-time reduction?

If $X \leq_p Y$ and $Y \leq_p Z$, then $X \leq_p Z$.

YES!

The Class NP

For many problems, no polynomial-time algorithm has been discovered yet to solve the problem.




- Independent Set: given graph G and number k , does there exist an independent set of size $\geq k$?
- Hamiltonian Cycle: given directed graph G , does G contain a Hamiltonian Cycle, that is a cycle that visits all nodes without repeating?

For many such problems, it is possible to check if a given solution is correct in polynomial time

- Independent Set: given a set of k nodes, check graph G to see if it has any edge that has both endpoints among the k nodes.
- Hamiltonian Cycle: given a solution cycle, check graph G to confirm that edges exist for each step along the path.

The Class NP

The class NP contains all decision problems that have polynomial-time verifiers

- The verifier is an algorithm that takes as input the encoding of the problem along with a proposed solution, and verifies the proposed solution in polynomial time
 - The proposed solution is also known as:
 -  Certificate
 -  Witness
 - The verification algorithm is also known as:
 -  Certifier
- Is $P \subseteq NP$? **YES!**

The Class NP

NP stands for non-deterministic polynomial time

- An alternative characterization of NP problems
- A decision problem is in NP if it can be solved in non-deterministic polynomial time
 - Imagine an algorithm that can simultaneously follow all branches of computation
 - E.g. Solve Hamiltonian cycle by following all possible paths out of a node simultaneously at each step.
 - E.g. or solve SAT by simultaneously following all branches of assignment (0 or 1) to each variable

$P = NP?$

Big open question in complexity theory: Does $P = NP$?

- There are many problems that have eluded polynomial-time solutions.
- Yet no one has been able to prove that there is any problem in NP that does not belong to P
- Most people believe that $P \neq NP$
 - Too unlikely that there could be a general transformation from the task of checking a solution to that of finding a solution.
 - A huge amount of unsuccessful effort has gone into finding polynomial-time algorithms for many NP problems

Revisiting Polynomial-Time Reductions

In the absence of a solution to the $P=NP$ question:

- We can identify the most “difficult” of the problems in NP
- An NP problem Y is classified as “difficult” if all other problems in NP can be polynomial reduced to Y
- What would a polynomial-time solution to a “difficult” problem imply?
 - A polynomial time solution to all NP problems!
 - This would show $P = NP$!

NP-Hard and NP-Complete

The class NP-Complete contains all decision problems Y that are in NP and for which every other problem in NP can be polynomial reduced to Y

- Y is an NP-Complete problem if:
 - $Y \in \text{NP}$
 - For all $X \in \text{NP}$, $X \leq_p Y$

The class NP-Hard contains all decision problems Y for which every other problem in NP can be polynomial reduced to Y

- Y is an NP-Complete problem if:
 - For all $X \in \text{NP}$, $X \leq_p Y$
- There are problems that are in NP-Hard but that are not NP-Complete. This implies that they have no polynomial-time verifier.



NP-Hard and NP-Complete

What is the value of NP-Complete?

- If a polynomial-time algorithm is found for any problem Y in NP-Complete:
 - Since for all $X \in \text{NP}$, $X \leq_p Y$, this implies that every problem in NP has a polynomial-time algorithm
 - There's no need to try to solve all NP-Complete problems
 - If a new problem is shown to be NP-Complete, it's probably not worth spending much time trying to find an efficient algorithm for solving it

NP-Hard and NP-Complete

How to demonstrate that a new problem, Z , is NP-Complete?

- First show that Z is in NP
 - Find a “witness” (a solution) of polynomial size
 - Describe how to verify the solution in polynomial time
- Then find another problem in NP-Complete that reduces to Z
 - Find Y in NP-Complete such that $Y \leq_p Z$
 - Why does this show that Z is NP-Complete?
 -  Transitivity: $X \leq_p Y$ for all X in NP, so
 -  $X \leq_p Y \leq_p Z$ and thus any problem in NP can be reduced to Z in polynomial time

NP-Hard and NP-Complete

How to get started - how to find the first NP-Complete problem

- Once we have a problem in NP-Complete, it's straight-forward to extend the class NP-Complete
- But how to find a first NP-Complete problem?
 - It requires showing that every other problem in NP reduces to it

NP-Hard and NP-Complete

How to get started - how to find the first NP-Complete problem

- Cook-Levin Theorem

- CNF-SAT is NP-Complete

- Conjunctive Normal Form Boolean Satisfiability

- ✎ Given a collection of boolean variables x_1, x_2, \dots, x_n

- ✎ Given a boolean expression in x_1, x_2, \dots, x_n

- ✎ CNF means logical "AND" of a collection of terms


- ✎ Each term is a logical "OR" of some variables

- ✎ CNF-SAT Problem: Determine if there is an assignment of values to x_1, x_2, \dots, x_n that satisfies the boolean expression

Examples of NP-Complete Problems

CLIQUE

- Given graph $G = (V, E)$ and a number k , does there exist a clique of size k ? That is a set of vertices $S \subset V$ such that for every $u, v \in S$, the edge $(u, v) \in E$?
- Can we show that $\text{CLIQUE} \in \text{NP}$?
- Can we show $\text{CNF-SAT} \leq_p \text{CLIQUE}$?



Examples of NP-Complete Problems


CLIQUE

- Note that just because a problem is NP-complete doesn't mean that all instances of it take exponential time.
- Given a graph G , and a number k , does there exist a clique of size less than or equal to k ?
 - If you have a clique of size k , you automatically have cliques smaller than that. All you have to do is check for a clique of size 2. That just requires one edge! (or you could argue it's automatically true for $k=1$ as long as you have a node)
- Given a graph G , does there exist a clique of size 5?
 - Given n nodes, there are $O(n^5)$ different cliques possible of size 5. Just check them all. Polynomial-time.
- Given a graph G , does there exist a clique of size $n-5$?
 - Given n nodes, there are $O(n^5)$ different cliques possible of size $n-5$. Just check them all. Polynomial-time.

Examples of NP-Complete Problems

INDEPENDENT SET


- Given graph $G = (V, E)$ and a number k , does there exist an independent set of size k ? That is a set of vertices $S \subset V$ such that for every $u, v \in S$, the edge $(u, v) \notin E$?
- Can we show that INDEPENDENT SET \in NP?
- Can we reduce an existing NP-Complete problem to IND. SET?



Examples of NP-Complete Problems

VERTEX COVER

- Given a graph $G = (V, E)$ and an integer k , is there a subset of vertices $S \subseteq V$ such that $|S| = k$, and for each edge, at least one of its endpoints is in S ?
- Can we show that VERTEX COVER \in NP?
- Can we reduce an existing NP-Complete problem to VERTEX COVER?



Proving that a Problem Belongs to NP-Complete

Finding the right problem to reduce from

- $\text{CNF-SAT} \leq_p \text{CLIQUE} \leq_p \text{INDEPENDENT SET} \leq_p \text{VERTEX COVER}$

Co-NP

For every decision problem X , there is a natural complementary decision problem X' .

- E.g. Given graph $G = (V, E)$ and a number k , does there NOT exist a clique of size k ?
- While problems in NP can be verified easily, the complementary problems aren't verified easily
 - How would you verify that there is NO clique of size k ?

The class Co-NP contains all decision problems whose complement belongs to NP.

- Open question: does $NP = Co-NP$?
 - Prevailing belief is no
- Another open question: is $P = NP \cap Co-NP$?
 - Are the only problems in NP, for which the complementary problem can be checked easily, problems that are polynomial to begin with?

More NP-Complete Examples

HAMILTONIAN CYCLE

- Given an undirected graph $G = (V, E)$, does there exist a simple cycle C that visits every node?
- Can we show that HAMILTONIAN CYCLE \in NP?
 - Certificate: a permutation of the vertices
 - Verifier: checks that edges exist for each pair of vertices along the proposed cycle
- It can be shown that $3\text{-SAT} \leq_p \text{HAMILTONIAN CYCLE}$
 - (3-SAT is a variant of SAT in which each clause has exactly 3 variables. 3-SAT is also NP-Complete.)

More NP-Complete Examples

TRAVELING SALESMAN PROBLEM

- Given a complete weighted graph $G = (V, V \times V)$, with weights w , and a threshold t , does there exist a simple cycle C that visits every node exactly once and has a total weight $< t$?
- Can we show that TRAVELING SALESMAN PROBLEM \in NP?
 - Certificate: a permutation of the vertices
 - Verifier: checks that total weight of corresponding edges is less than threshold t
- HAMILTONIAN CYCLE \leq_p TRAVELING SALESMAN PROBLEM
 - Thus TSP is NP-Complete
 - This is a Question on the final homework!

More NP-Complete Examples

3-COLORING

- Given a graph $G = (V, E)$, is it possible to color the vertices of G with 3 colors so that no edge has endpoints both the same color?
- Can we show that $3\text{-COLORING} \in \text{NP}$?
 - Certificate: a coloring of the vertices
 - Verifier: checks that each edge has endpoints of different color
- $3\text{-SAT} \leq_p 3\text{-COLORING}$ (proof in book)
 - Thus 3-COLORING is NP-Complete

More NP-Complete Examples

k-COLORING

- Given a graph $G = (V, E)$, is it possible to color the vertices of G with k colors so that no edge has endpoints both the same color?
 - 4-COLORING \in NP-Complete
 - 3-COLORING \leq_p 4-COLORING
 - More generally, 3-COLORING \leq_p k-COLORING for $k > 3$

More NP-Complete Examples

k-COLORING

- Given a graph $G = (V, E)$, is it possible to color the vertices of G with k colors so that no edge has endpoints both the same color?
 - 2-COLORING: what kind of graph is required for a 2-coloring to exist?
 - ✎ Bipartite graph
 - ✎ We can decide the 2-coloring problem in $O(V + E)$ time
 - 2-COLORING $\in P$
 - (Do a BFS then confirm that there are no edges between vertices at the same depth.)

More NP-Complete Examples

KNAPSACK PROBLEM

- Given n items each having associated cost and weight, what is the maximum cost of items that can be placed in a knapsack of capacity W ?
 - Can solve using Dynamic Programming in $O(nW)$
 - But KNAPSACK is NP-Complete
 - Why?
 - ✎ $O(nW)$ is not polynomial in the length (number of bits) of the input W

Decision Problem versus Functional Optimization

NP-Completeness is defined for decision problems

- Problems with a Yes / No answer
- E.g. Does graph G have a max flow equal to k

Often, however, we are presented with functional optimization problems

- E.g. Determine the max flow for a graph

Although the optimization problem is at least as hard as the decision problem, in most cases we can show that they are equivalent with respect to polynomial-time solvability

Decision Problem versus Functional Optimization

Example

- Find the longest simple path in undirected graph G (optimization)
- Does undirected graph G have a longest simple path of length k

Often the optimization problem can be solved via a polynomial number of decision problems



- For the longest path problem, at most n decision problems must be solved

It is often easy to solve a decision problem given the solution to the functional optimization problem

- Simply apply the optimization solution to the particular decision problem
- Thus the optimization and decision problem are often equivalent with respect to polynomial-time solvability

Decision Problem versus Functional Optimization

More Examples

- What is the largest size clique in graph G
 - How many decision problems?
- Sorting as a decision problem:
 - Does element a_j end up at position p in the sorted array?
 - How many decision problems needed to know the sorted array?
- Max flow as a decision problem:
 - Does graph G have a maximum flow equal to k ?
 - How many decision problems to find max flow?
 - Is this a polynomial number in the size of the input C ?
 - Instead:
 -  Is the i^{th} bit of (binary representation of) the max flow a 1?
 -  Now the number of decision problems is linear in the size of the input C !

Decision Problem versus Construction

NP-Completeness is defined for decision problems

- Problems with a Yes / No answer
- E.g. Does graph G have a clique of size k ?

Often, however, we would like to construct the solution, not just know that one exists

- E.g. What is a size k clique of G ?

Although the construction problem is at least as hard as the decision problem, in most cases we can show that they are equivalent with respect to polynomial-time solvability

Decision Problem versus Construction

Examples

- What is a clique of size k in graph G ?
 - First, make call to decision problem to confirm a solution exists
 - Next, make calls to decision problem with individual vertices removed one by one if they are not necessary to maintain a clique of size k
 - ✎ $O(|V|)$ total number of calls to the decision problem to determine which vertices are part of a clique of size k
- What is an assignment of variables x_1, x_2, \dots, x_n that satisfies a given SAT expression?
 - First, make call to decision problem to confirm a solution exists
 - Next, make calls to decision problem with individual variables hardcoded to value 0 or 1. At least one of the two must admit a solution. Continue along a path having a solution until all variables have value assigned.
 - ✎ $O(n)$ total number of calls to the decision problem