

Big Oh Analysis

Matthew Galitz

University of Virginia, Charlottesville, VA 22904

Time (ms) of Method Execution

Input Size:	1	10	10^2	10^3	10^4	10^5	10^6	10^7	10^8
Binary Search ($\log n$)	0	0	0	0	0	0	0	1	1
Max (n)	0	0	0	1	2	2	5	8	33
Multi Binary Search ($n \log n$)	1	1	1	1	2	11	67	755	8348
All Pairs (n^2)	0	0	1	10	188	17752	>60000	>60000	>60000
All Triads (n^3)	1	1	8	221	>60000	>60000	>60000	>60000	>60000
All Subsets (2^n)	1	1	>60000	>60000	>60000	>60000	>60000	>60000	>60000

The time complexity of the Binary Search method is $O(\log(n))$. The function $y = \log(x)$ grows logarithmically. Thus it makes sense that the Binary Search maintains quick runtimes as n increases drastically. The method starts to slow drastically for some $n > 10^8$.

The time complexity of the Max method is $O(n)$. The function $y = n$ grows more quickly than the logarithmic function. The runtime of Max is directly proportional to n . The method starts to slow drastically for some $n > 10^8$.

The time complexity of the Multi Binary Search method is $O(n \log(n))$. The function $y = n \log(n)$ grows linearly but is greater than $y = n$ for all $n > 10$. Thus it makes sense that as n increases the runtimes are larger than that of the Max() method. The method slows drastically for some $n > 10^8$.

The time complexity of the All Pairs method is $O(n^2)$. The function $y = n^2$ grows exponentially and is greater than the $y = n \log(n)$ for all n . Thus it makes sense that as n increases the runtimes are larger than that of the Multi Binary Search method. The method slows drastically approximately when $n \geq 10,000$.

The time complexity of the All Triads method is $O(n^3)$. The function $y = n^3$ grows exponentially and is greater than $y = n^2$ for all $n > 1$. Thus it makes sense that as n increases the runtimes are larger than that of the All Pairs method. The method slows drastically when $n \geq 10,000$.

The time complexity for the All Subsets method is $O(2^n)$. The function $y = 2^n$ grows exponentially and is greater than $y = n^3$ for all n . Thus it makes sense that the runtimes are larger than that of the All Triads method. The method slows drastically when $n \geq 100$.