

# *Showtrakt*



## *Documentación*

## Índice

1. Public Controllers .....	4
1.1 CommentController .....	4
1.2 EpisodeController .....	5
1.3 HomeController .....	6
1.4 ItemController .....	7
1.5 PostController .....	10
1.6 UserController .....	11
2. Auth Controllers .....	12
2.1 ForgotPasswordController .....	12
2.2 LoginController .....	13
2.3 RegisterController .....	14
2.4 ResetPasswordController .....	15
2.5 VerificationController .....	16
3. Admin Controllers .....	17
3.1 AdminController .....	17
3.2 CommentController .....	18
3.3 PostController .....	18
3.3 UsersController .....	20
4. MiddleWare .....	22
4.1 IsAdmin .....	22
5. Models .....	22
5.1 Comment .....	22
5.2 Episode .....	23
5.3 Invite .....	24
5.4 Item .....	24
5.5 Post .....	27
5.6 TMDB .....	27
5.7 User .....	31
6. Views .....	33
6.1 Admin Views .....	33
6.1.1 Comments .....	33
6.1.2 Layouts .....	37
6.1.3 Partials .....	40
6.1.4 posts .....	43

6.1.5	Users.....	46
6.1.6	Dashboard.blade .....	53
6.2	Auth Views .....	56
6.2.1	Login.blade .....	56
6.2.2	Register.blade.....	59
6.3	Comments Views.....	63
6.3.1	index.blade .....	63
6.4	Items Views .....	64
6.4.1	index.blade .....	64
6.4.2	Search.blade .....	64
6.4.3	Show.blade .....	67
6.5	Layouts Views.....	75
6.5.1	layout.blade.....	75
6.6	Partials Views .....	77
6.6.1	avatarmodal.blade .....	77
6.6.2	head.blade.....	77
6.6.3	helpmodal.blade .....	79
6.6.4	loginmodal.blade.....	80
6.6.5	messages.blade .....	81
6.6.6	nav.blade .....	81
6.7	Posts Views.....	83
6.7.1	Index.blade .....	83
6.7.2	Show.blade .....	84
6.8	Profiles.....	86
6.8.1	Show.blade .....	86
6.9	CookieConsent Views .....	93
6.9.1	dialogContents.blade .....	93
6.9.2	index.blade .....	94
6.10	home.blade .....	95
7.	Notifications .....	96
7.1	InviteNotification.....	96
7.2	ShowtraktStats .....	98
7.3	TotalStats.....	99
8.	Commands .....	101
8.1	TotalStats.....	101

9.	Kernel .....	102
10.	Requests .....	103
10.1	PostFormRequest .....	103

## 1. Public Controllers

### 1.1 CommentController

```
<?php

namespace App\Http\Controllers;

use App\Comment;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;

class CommentController extends Controller
{
    public function index()
    {
        $comments= Comment::where('user_id', Auth::id())-
>paginate(10);

        return view('comments.index')->with('comments', $comments);
    }
    public function store(Request $request)
    {
        $this->validate($request, ['body' => 'required','tmdb_id'
=> 'required', 'item_title' => 'required', 'media_type' =>
'required' ]);

        //dd($request->all());

        $comment = new Comment();
        $comment->body = $request->body;
        $comment->user_id = auth()->user()->id;
        $comment->item_id = $request->tmdb_id;
        $comment->item_title = $request->item_title;
        $comment->media_type = $request->media_type;

        $comment->save();

        return redirect()->back();
    }

    public function destroy(Comment $comment)
    {
        $comment->delete();

        return redirect()->back();
    }
}
```

## 1.2 EpisodeController

```
<?php

namespace App\Http\Controllers;

use App\Episode;
use App\Item;
use App\TMDB;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\DB;

class EpisodeController extends Controller
{
    public function store(Request $request, TMDB $tmdb)
    {
        $request->validate([
            'tmdb_id' => 'required',
            'episode_tmdb_id' => 'required',
        ]);

        //dd($request->all());

        $request->request->add(['user_id' => Auth::id()]);

        $find=Episode::EpisodeExist($request->user_id, $request->episode_tmdb_id);

        if ($find)
        {
            $this->destroy($find);

            return redirect()->back();
        }else{

            $episode=new Episode();

            $episode->tmdb_id = $request->tmdb_id;
            $episode->episode_tmdb_id = $request->episode_tmdb_id;
            $episode->user_id = $request->user_id;
            $episode->seen = true;

            $episode->save();

            if (! Item::ItemExist($request->user()->id, $request->tmdb_id))
            {
                $item=new Item($tmdb);

                $item->title = $request->item['title'];
                $item->tmdb_id = $request->item['tmdb_id'];
            }
        }
    }
}
```

```

        $item->user_id = $request->user_id;
        $item->poster = $request->item['poster'];
        $item->media_type = $request->item['media_type'];
        $item->watched = true;

        $item->save();

    }

    return redirect()->back();

}

}

public function destroy($data)
{
    DB::table('episodes')->where('episode_tmdb_id', $data->episode_tmdb_id)->where('user_id', Auth::id())->delete();
}
}

```

### 1.3 HomeController

```

<?php

namespace App\Http\Controllers;
use App\TMDB;
use Illuminate\Http\Request;

class HomeController extends Controller
{
    private $tmdb;

    /**
     * Create a new controller instance.
     *
     * @return void
     */
    public function __construct(TMDB $tmdb)
    {
        //$this->middleware('auth');
        $this->tmdb = $tmdb;
    }

    /**
     * Show the application dashboard.
     *
     * @return \Illuminate\Contracts\Support\Renderable
     */
    public function index()
    {
        $popular=$this->tmdb->trending();
        //dd($popular);
    }
}

```

```

        return view('home')->with('movies', $popular);
    }
    public function dashboard()
    {
        $popular=$this->tmdb->trending();
        //dd($popular);
        return view('welcome')->with('movies', $popular);
    }
}

```

## 1.4 ItemController

En el método `item`, llamo a las funciones del modelo *Item*, para crear el objeto según sea una película o una serie.

```

<?php

namespace App\Http\Controllers;

use App\Episode;
use App\Item;
use App\Item\Model;
use GuzzleHttp\Client;
use App\TMDB;
use App\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\App;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\DB;

class ItemController extends Controller
{
    public function item($tmdbId, $mediaType, Item $item)
    {
        if ($mediaType == 'tv')
        {
            $episodes=$item->ItemEpisode($tmdbId, $mediaType);
            $item=$item->item($tmdbId,$mediaType);
            $comments=DB::table('comments')->where('item_id',
$tmdbId)->get();

            $watched=Item::ItemWatched(Auth::id(), $tmdbId, true);
            $watchlist=Item::ItemWatchlist(Auth::id(), $tmdbId, true);

            return view('items.show')->with('item', $item)-
>with('watched', $watched)->with('watchlist', $watchlist)-
>with('episodes', $episodes)->with('comments', $comments);

        }else{

            $item=$item->item($tmdbId,$mediaType);

            $watched=Item::ItemWatched(Auth::id(), $tmdbId, true);
            $watchlist=Item::ItemWatchlist(Auth::id(), $tmdbId, true);
            $comments=DB::table('comments')->where('item_id',
$tmdbId)->get();

```



```
        return view('items.show')->with('item', $item)-
>with('watched', $watched)->with('watchlist', $watchlist)-
>with('comments', $comments);

    }

}

public function search()
{

    return view('items.search');

}

public function searchItem(Request $request, Item $item)
{
    //dd($request->all());
    $items=$item->search($request->search);
    //dd($item);

    return view('items.search')->with('items',$items);
}

public function store(Request $request, TMDB $tmdb)
{
    $nameRoute = $request->route()->getName();

    $request->validate([
        'title' => 'required',
        'tmdb_id' => 'required',
        'poster' => 'required',
        'media_type' => 'required',
    ]);

    $request->request->add(['user_id' => Auth::id()]);

    $item=new Item($tmdb);

    $find=Item::ItemExist($request->user_id, $request->tmdb_id);

    if ($find){

        if ($nameRoute == 'items.store') {

            $this->handleWatch($request, $find, $item);

            return redirect()->back();

        }

        if ($nameRoute == 'item.watchlist') {

            $this->handleWatchlist($request, $find, $item);

            return redirect()->back();

        }

    }

}
```

```
    }else{

        $item->title = $request->title;
        $item->tmdb_id = $request->tmdb_id;
        $item->user_id = $request->user_id;
        $item->poster = $request->poster;
        $item->media_type = $request->media_type;

        if ($nameRoute == 'item.watchlist')
        {
            $item->watchlist = true;
        }
        if ($nameRoute == 'items.store')
        {
            $item->watched = true;
        }

        $item->save();

        return redirect()->back();

    }

}

public function handleWatch($data1, $data2, $data3)
{
    if ($data2->watched) {

        $this->destroy($data2);

    } else {

        $data3->watched = true;

        DB::table('items')->where('tmdb_id', $data1->tmdb_id)-
>where('user_id', $data1->user_id)->update(['watched' => $data3-
>watched]);

    }

}

public function handleWatchlist($data1, $data2, $data3)
{
    if ($data2->watchlist) {

        DB::table('items')->where('tmdb_id', $data1->tmdb_id)-
>where('user_id', $data1->user_id)->update(['watchlist' => false]);

    } else {

        $data3->watchlist = true;

        DB::table('items')->where('tmdb_id', $data1->tmdb_id)-
>where('user_id', $data1->user_id)->update(['watchlist' => $data3-
>watchlist]);

    }

}
```

```
public function destroy($data)
{
    DB::table('items')->where('tmdb_id', $data->tmdb_id)->delete();
    DB::table('episodes')->where('tmdb_id', $data->tmdb_id)->delete();
}
}
```

## 1.5 PostController

```
<?php

namespace App\Http\Controllers;

use App\Post;
use Illuminate\Http\Request;

class PostController extends Controller
{
    public function index()
    {
        $posts = Post::paginate(5);
        //dd($posts);

        return view('posts.index')->withPosts($posts);
    }

    public function show($slug)
    {
        $post = Post::where('slug', $slug)->first();
        if(!$post)
        {
            return redirect('/')->withErrors('requested page not found');
        }

        return view('posts.show')->withPost($post);
    }
}
```

## 1.6 UserController

En el método `registration_view`, creo la vista para registrarse comprobando el *token* único de registro

```
<?php

namespace App\Http\Controllers;

use App\Comment;
use App\Invite;
use App\Item;
use App\TMDB;
use Illuminate\Http\Request;
use App\User;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\DB;

class UserController extends Controller
{
    public function __construct()
    {
        $this->middleware('auth')->except('registration_view');
    }
    public function show()
    {
        $user=User::find(Auth::id());
        $totalusers=User::count();
        $phrase=Item::PhraseRand();
        $comments=Comment::where('user_id', Auth::id())-
>orderByDesc('created_at')->take(10)->get();
        $userItemsWatched = Item::ItemsPerUser(Auth::id());
        $topusers= User::topUsers();
        $topusersMovie= User::topUsersMovies();
        $topusersTv= User::topUsersTv();

        $user->comments = $comments;
        $user->totalusers = $totalusers;
        $user->phrase = $phrase;
        $user->userItemsWatched = $userItemsWatched;
        $user->topusers = $topusers;
        $user->topusersMovie = $topusersMovie;
        $user->topusersTv = $topusersTv;

        //dd($user);

        $items=DB::table('items')->where('user_id', $user->id)->get();

        return view('profiles.show')->with('user', $user)-
>with('items',$items);
    }

    public function registration_view($token)
    {
        $invite = Invite::where('token', $token)->first();
        return view('auth.register',['invite' => $invite]);
    }
}
```

```

    }

    public function update_avatar(Request $request){

        $request->validate([
            'avatar' =>
            'required|image|mimes:jpeg,png,jpg,gif,svg|max:2048',
        ]);

        $user = Auth::user();

        $avatarName = $user->id.'_avatar'.time().'.'.request()-
        >avatar->getClientOriginalExtension();

        $request->avatar->storeAs('avatars',$avatarName);

        $user->avatar = $avatarName;
        $user->save();

        return back()
            ->with('success','You have successfully upload image.');
```

## 2. Auth Controllers

### 2.1 ForgotPasswordController

```

<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Foundation\Auth\SendsPasswordResetEmails;

class ForgotPasswordController extends Controller
{
    /**
     |-----
    | Password Reset Controller
    |-----
    |
    | This controller is responsible for handling password reset
    emails and
    | includes a trait which assists in sending these notifications
    from
    | your application to your users. Feel free to explore this
    trait.
    |
    */

    use SendsPasswordResetEmails;

    /**
     * Create a new controller instance.

```

```

        *
        * @return void
        */
        public function __construct()
        {
            $this->middleware('guest');
        }
    }
}

```

## 2.2 LoginController

```

<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Foundation\Auth\AuthenticatesUsers;

class LoginController extends Controller
{
    /**
     |-----
    | Login Controller
    |-----
    |
    | This controller handles authenticating users for the application
and
    | redirecting them to your home screen. The controller uses a
trait
    | to conveniently provide its functionality to your applications.
    |
    */
    use AuthenticatesUsers;

    /**
     * Where to redirect users after login.
     *
     * @var string
     */
    protected $redirectTo = '/';

    /**
     * Create a new controller instance.
     *
     * @return void
     */
    public function __construct()
    {
        $this->middleware('guest')->except('logout');
    }
}

```

## 2.3 RegisterController

En el método `create`, se crea el usuario, comprueba si el email es el correcto para el token de registro y lo borra para que no se pueda volver a usar. Luego notifico al bot de telegram que un nuevo usuario ha sido creado y que me notifique en mi canal privado.

```
<?php

namespace App\Http\Controllers\Auth;

use App\Invite;
use App\Notifications\ShowtraktStats;
use App\User;
use App\Http\Controllers\Controller;
use Illuminate\Support\Facades\Hash;
use Illuminate\Support\Facades\Notification;
use Illuminate\Support\Facades\Validator;
use Illuminate\Foundation\Auth\RegistersUsers;

class RegisterController extends Controller
{
    /**
     *
     * -----
     * | Register Controller
     * -----
     *
     * | This controller handles the registration of new users as well as
their
     * | validation and creation. By default this controller uses a trait
to
     * | provide this functionality without requiring any additional
code.
     * |
     */

    use RegistersUsers;

    /**
     * Where to redirect users after registration.
     *
     * @var string
     */
    protected $redirectTo = '/';

    /**
     * Create a new controller instance.
     *
     * @return void
     */
    public function __construct()
    {
        $this->middleware('guest');
    }

    /**
     * Get a validator for an incoming registration request.
     *

```

```

    * @param array $data
    * @return \Illuminate\Contracts\Validation\Validator
    */
protected function validator(array $data)
{
    return Validator::make($data, [
        'name' => ['required', 'string', 'max:255'],
        'email' => ['required', 'string', 'email', 'max:255',
'unique:users'],
        'password' => ['required', 'string', 'min:8',
'confirmed'],
        'custom_title' => ['required', 'string', 'max:255'],

    ]);
}

/**
 * Create a new user instance after a valid registration.
 *
 * @param array $data
 * @return \App\User
 */
protected function create(array $data)
{
    $user= User::create([
        'name' => $data['name'],
        'email' => $data['email'],
        'password' => Hash::make($data['password']),
        'custom_title' => $data['custom_title'],

    ]);

    $invite = Invite::where('email', $data['email'])->first();
    $invite->delete();

    $user->notify(new ShowtraktStats($user));

    return $user;
}
}

```

## 2.4 ResetPasswordController

```

<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Foundation\Auth\ResetsPasswords;

class ResetPasswordController extends Controller
{
    /**
     *
     * -----
     * | Password Reset Controller
     * |-----
     * -----
     * |
     */
}

```



```

    | This controller is responsible for handling password reset
requests
    | and uses a simple trait to include this behavior. You're free to
    | explore this trait and override any methods you wish to tweak.
    |
    */

    use ResetsPasswords;

    /**
     * Where to redirect users after resetting their password.
     *
     * @var string
     */
    protected $redirectTo = '/home';

    /**
     * Create a new controller instance.
     *
     * @return void
     */
    public function __construct()
    {
        $this->middleware('guest');
    }
}

```

## 2.5 VerificationController

```

<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Foundation\Auth\VerifiesEmails;

class VerificationController extends Controller
{
    /**
     |-----
     | Email Verification Controller
     |-----
     |-----
     |
     | This controller is responsible for handling email verification
for any
     | user that recently registered with the application. Emails may
also
     | be re-sent if the user didn't receive the original email
message.
     |
     */

    use VerifiesEmails;

    /**
     * Where to redirect users after verification.

```

```

    *
    * @var string
    */
    protected $redirectTo = '/home';

    /**
     * Create a new controller instance.
     *
     * @return void
     */
    public function __construct()
    {
        $this->middleware('auth');
        $this->middleware('signed')->only('verify');
        $this->middleware('throttle:6,1')->only('verify', 'resend');
    }
}

```

### 3. Admin Controllers

#### 3.1 AdminController

```

<?php

namespace App\Http\Controllers\Admin;

use App\Comment;
use App\Item;
use App\User;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;
use Illuminate\Support\Facades\DB;

class AdminController extends Controller
{
    public function index()
    {
        $totalusers=User::count();
        $totalitems = Item::TotalItems();
        $comments=Comment::all()->sortByDesc('created_at')->take(10);
        $totalcomments=Comment::count();
        $topmovies= DB::select("SELECT tmdb_id, poster FROM items
WHERE media_type='movie' GROUP BY tmdb_id, poster ORDER BY count(*)
DESC LIMIT 9");
        $toptvshows= DB::select("SELECT tmdb_id, poster FROM items
WHERE media_type='tv' GROUP BY tmdb_id, poster ORDER BY count(*) DESC
LIMIT 9");
        $topusers= DB::select("SELECT user_id FROM items GROUP BY
user_id ORDER BY count(*) DESC LIMIT 9");

        return view('admin.dashboard')->with('item', $totalitems)
            ->with('user', $totalusers)
            ->with('comments', $comments)
            ->with('totalcomments', $totalcomments)
            ->with('topmovies', $topmovies)
            ->with('toptvshows', $toptvshows)
            ->with('topusers', $topusers);
    }
}

```

```
}  
}
```

### 3.2 CommentController

```
<?php  
  
namespace App\Http\Controllers\Admin;  
  
use App\Comment;  
use App\Item;  
use Illuminate\Http\Request;  
use App\Http\Controllers\Controller;  
  
class CommentController extends Controller  
{  
    public function index()  
    {  
        $comments = Comment::all();  
  
        return view('admin.comments.index')->withComments($comments);  
    }  
  
    public function show(Comment $comment)  
    {  
        $phrase=Item::PhraseRand();  
  
        return view('admin.comments.show',  
compact('comment','phrase'));  
    }  
  
    public function edit(Comment $comment)  
    {  
  
        return view('admin.comments.edit', compact('comment'));  
    }  
  
    public function update(Request $request, Comment $comment)  
    {  
        $this->validate($request, ['body' => 'required']);  
  
        $comment->body = $request->input('body');  
        $comment->save();  
  
        return redirect('/admin/comment');  
    }  
    public function destroy(Comment $comment)  
    {  
  
        $comment->delete();  
  
        return redirect()->back();  
    }  
}
```

### 3.3 PostController

```
<?php

namespace App\Http\Controllers\Admin;

use App\Http\Requests\PostFormRequest;
use App\Post;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;
use Illuminate\Support\Str;

class PostController extends Controller
{
    public function index()
    {
        $posts = Post::all();

        return view('admin.posts.index')->withPosts($posts);
    }

    public function create(Request $request)
    {
        return view('admin.posts.create');
    }

    public function store(PostFormRequest $request)
    {
        $post = new Post();
        $post->title = $request->get('title');
        $post->body = $request->get('body');
        $post->image_url = $request->get('image_url');

        $post->slug = Str::slug($post->title);

        $duplicate = Post::where('slug', $post->slug)->first();

        if ($duplicate) {
            return redirect()->back()->withErrors('Title already
exists.')->withInput();
        }

        $post->author_id = $request->user()->id;

        $post->save();

        return redirect('/admin/post');
    }

    public function edit(Request $request, $slug)
    {
        $post = Post::where('slug', $slug)->first();

        return view('admin.posts.edit')->with('post', $post);
    }

    public function update(Request $request)
    {
        $post_id = $request->input('post_id');
        $post = Post::find($post_id);
```

```

        $title = $request->input('title');
        $slug = Str::slug($title);

        $post->slug = $slug;
        $post->title = $title;
        $post->body = $request->input('body');

        $post->save();

        return redirect('/admin/post');
    }

    public function destroy(Post $post)
    {
        $post->delete();

        return redirect()->back();
    }
}

```

### 3.3 UsersController

En el método `process_invites` valida que el email es válido, luego busca que no exista en la base de datos, crea un token único de registro y se lo añade a una url autogenerada con caducidad, así solo se podrá utilizar una vez y solo será válido durante 300 minutos. Luego procesa y envía la invitación por email.

```

<?php

namespace App\Http\Controllers\Admin;

use App\Comment;
use App\Invite;
use App\Notifications\InviteNotification;
use App\User;
use App\Item;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Notification;
use Illuminate\Support\Facades\URL;
use Illuminate\Support\Facades\Validator;
use Illuminate\Support\Str;

class UsersController extends Controller
{
    public function index()
    {

```

```

        $users = User::all();

        return view('admin.users.index', compact('users'));
    }

    public function invite()
    {
        return view('admin.users.invite');
    }

    public function process_invites(Request $request)
    {
        $validator = Validator::make($request->all(), [
            'email' => 'required|email|unique:users,email'
        ]);
        /* after first validation, look up for email and add a custom
error*/
        $validator->after(function ($validator) use ($request) {
            if (Invite::where('email', $request->input('email'))->exists()) {
                $validator->errors()->add('email', 'There exists an
invite with this email!');
            }
        });
        /* return errors if validator fails*/
        if ($validator->fails()) {
            return redirect(route('admin.users.invite'))
                ->withErrors($validator)
                ->withInput();
        }
        /*Create a unique token and sign the URL to make it unique,
available only for 300 minutes*/
        do {
            $token = Str::random(20);
        } while (Invite::where('token', $token)->first());
        Invite::create([
            'token' => $token,
            'email' => $request->input('email')
        ]);

        $url = URL::temporarySignedRoute(

            'registration', now()->addMinutes(300), ['token' =>
$token]
        );

        Notification::route('mail', $request->input('email'))->
notify(new InviteNotification($url));

        return redirect('/admin/users')->with('success', 'The Invite
has been sent successfully');
    }

    public function show(User $user)
    {
        $phrase=Item::PhraseRand();

        $userItemsWatched = Item::ItemsPerUser($user->id);
        $comments=Comment::where('user_id', $user->id)->
orderByDesc('created_at')->take(10)->get();
    }

```

```
        $items=DB::table('items')->where('user_id', $user->id)->get();

        return view('admin.users.show', compact('user','phrase',
'items', 'userItemsWatched', 'comments'));
    }

    public function destroy(User $user)
    {

        $user->delete();

        return redirect()->back();
    }
}
```

## 4. MiddleWare

### 4.1 IsAdmin

Comprueba que el usuario autenticado es administrador

```
<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Support\Facades\Auth;

class IsAdmin
{
    /**
     * Handle an incoming request.
     *
     * @param  \Illuminate\Http\Request  $request
     * @param  \Closure  $next
     * @return mixed
     */
    public function handle($request, Closure $next)
    {
        if (Auth::user() && Auth::user()->admin == 1) {
            return $next($request);
        }

        return redirect('/');    }
}
```

## 5. Models

### 5.1 Comment

```
<?php

namespace App;
```

```
use Illuminate\Database\Eloquent\Model;

class Comment extends Model
{
    protected $fillable = ['body', 'item_id', 'user_id', 'item_title',
    'media_type'];

    public function author()
    {
        return $this->belongsTo('App\User');
    }
}
```

## 5.2 Episode

El método ImageExist comprueba si el capítulo tiene una imagen representativa, y si no la tiene le pone una por defecto.

```
<?php

namespace App;

use Illuminate\Database\Eloquent\Model;
use Illuminate\Support\Facades\DB;

class Episode extends Model
{
    public static function EpisodeExist($data1, $data2)
    {
        $match=['user_id' => $data1, 'episode_tmdb_id' => $data2];
        $episode= DB::table('episodes')->select('episode_tmdb_id')->
        >where($match)->first();

        return $episode;
    }

    public function ImageExist($url)
    {
        $array = @get_headers($url);

        $string = $array[0];

        if(strpos($string, "404")) {
            return false;
        }

        return true;
    }

    public function item()
    {
        return $this->belongsTo(Item::class, 'tmdb_id', 'tmdb_id');
    }
}
```



### 5.3 Invite

```
<?php

namespace App;

use Illuminate\Database\Eloquent\Model;

class Invite extends Model
{
    protected $fillable=[
        'email',
        'token'
    ];
}
```

### 5.4 Item

El método ítem construye el objeto a partir de métodos del modelo TMDB y devuelve el objeto. E ItemEpisode igual.

```
<?php

namespace App;
use App\TMDB;
use Carbon\Carbon;
use GuzzleHttp\Client;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Support\Arr;
use Illuminate\Support\Collection;
use Illuminate\Support\Facades\DB;
use PhpParser\Node\Expr\Array_;
use Symfony\Component\Finder\Finder;

class Item extends Model
{
    protected $fillable = ['title', 'tmdb_id', 'user_id', 'poster',
    'media_type'];

    private $tmdb;
    private $client;

    public function __construct(TMDB $tmdb)
    {
        $this->tmdb = $tmdb;
    }

    public function item($tmdbId, $mediaType)
    {
        $found = $this->tmdb->details($tmdbId, $mediaType);

        if( ! (array) $found) {
            return response('Not found', Response::HTTP_NOT_FOUND);
        }
    }
}
```

```

        $item = $this->tmdb->createItem($found, $mediaType);

        return $item;
    }

    public function ItemEpisode($data1, $data2)
    {
        $item= $this->tmdb->tvEpisodes($data1,$data2);
        return $item;
    }

    public static function ItemExist($data1, $data2)
    {
        $match=['user_id' => $data1, 'tmdb_id' => $data2];
        $item= DB::table('items')->where($match)->first();

        return $item;
    }

    public static function ItemWatched($data1, $data2, $data3)
    {
        $match=['user_id' => $data1, 'tmdb_id' => $data2, 'watched' =>
        $data3];
        $item= DB::table('items')->where($match)->first();

        return $item;
    }

    public static function ItemWatchlist($data1, $data2, $data3)
    {
        $match=['user_id' => $data1, 'tmdb_id' => $data2, 'watchlist'
=> $data3];
        $item= DB::table('items')->where($match)->first();

        return $item;
    }

    public function user()
    {
        return $this->belongsTo(User::class);
    }

    public function search($title)
    {
        $item= $this->tmdb->search($title);

        return $item;
    }

    public static function PhraseRand()
    {
        $phrases=[
            'Why so serious?', 'I\'m going to make him an offer he
can\'t refuse', 'May the Force be with you',
            'You talking to me?', 'I love the smell of napalm in the
morning', 'Show me the money!', 'You can\'t handle the truth!',
            'I\'ll be back', 'Carpe diem. Seize the day, boys. Make
your lives extraordinary', 'How you doin\'?', 'It\'s gonna be legen –
wait for it – dary.',

```

```

        'Oh, my God! They killed Kenny!';
    ];
    $phrase=Arr::random($phrases, 1);

    return $phrase;

}

public static function ItemsPerUser($id)
{
    $showswatched= DB::table('items')->where('user_id', $id)-
>where('watched' , 1)->where('media_type', 'tv')->select('id')-
>count('id');
    $showswatchlist= DB::table('items')->where('user_id', $id)-
>where('watchlist' , 1)->where('media_type', 'tv')->select('id')-
>count('id');
    $moviesswatched= DB::table('items')->where('user_id', $id)-
>where('watched' , 1)->where('media_type', 'movie')->select('id')-
>count('id');
    $moviesswatchlist= DB::table('items')->where('user_id', $id)-
>where('watchlist' , 1)->where('media_type', 'movie')->select('id')-
>count('id');

    $itemsPerUser= [

        'showswatched' => $showswatched,
        'showswatchlist' => $showswatchlist,
        'moviesswatched' => $moviesswatched,
        'moviesswatchlist' => $moviesswatchlist

    ];

    return $itemsPerUser;
}

public static function TotalItems()
{
    $showswatched= DB::table('items')->where('watched' , 1)-
>where('media_type', 'tv')->select('id')->count('id');
    $moviesswatched= DB::table('items')->where('watched' , 1)-
>where('media_type', 'movie')->select('id')->count('id');

    $totalitems= [

        'showswatched' => $showswatched,
        'moviesswatched' => $moviesswatched,

    ];

    return $totalitems;
}

public function comments()
{
    return $this->hasMany(Comment::class);
}
}

```

## 5.5 Post

```
<?php

namespace App;

use Illuminate\Database\Eloquent\Model;

class Post extends Model
{
    protected $guarded = [];

    public function author()
    {
        return $this->belongsTo('App\User', 'author_id');
    }
}
```

## 5.6 TMDb

En el construct hacemos un método singleton para hacer llamadas al api de TMDb. El método trending devuelve las películas y series más populares del momento, las cuales se muestran en la página principal de la web.

El método requestTmdb sirve como plantilla para hacer llamadas a la api y trabajar con sus resultados.

El método createItems junto con el método createItem recibe el json de respuesta de la api y lo me lo devuelve limpio y preparado para trabajar con él.

El método hasLimitRemaining es para controlar el ritmo de llamadas a la api y no sobrepasar su limite.

El método search hace llamadas a la api en el buscador para devolver los resultado, junto con los métodos anteriormente descritos.

```
<?php

namespace App;

use Carbon\Carbon;
use GuzzleHttp\Client;
use Illuminate\Support\Collection;
use Illuminate\Support\Facades\Cache;
use GuzzleHttp\Exception\ClientException;
use Symfony\Component\HttpFoundation\Response;

class TMDb
{
    private $client;
    private $apiKey;
    private $translation;

    private $base = 'https://api.themoviedb.org';
```

```
/**
 * Get the API Key for TMDb and create an instance of Guzzle.
 */
@param Client $client
*/
public function __construct(Client $client)
{
    $this->apiKey = env('Tmdb_API');
    $this->translation = config('app.TRANSLATION');
    $this->client = $client;
}

public function trending()
{
    $responseMovies = $this->fetchPopular('movie');
    $responseTv = $this->fetchPopular('tv');

    $tv = collect($this->createItems($responseTv, 'tv'));
    $movies = collect($this->createItems($responseMovies,
'movie'));

    $algo=$tv->merge($movies)->shuffle();

    return $algo;
}

private function fetchPopular($mediaType)
{
    return $this->requestTmdb($this->base . '/3/' . $mediaType .
'/popular');
}

private function requestTmdb($url, $query = [])
{
    $query = array_merge([
        'api_key' => $this->apiKey,
    ], $query);

    try {
        $response = $this->client->get($url, [
            'query' => $query
        ]);

        if($this->hasLimitRemaining($response)) {
            return $response;
        }
    } catch (ClientException $e) {

        $response = $e->getResponse();

        if($this->hasLimitRemaining($response)) {
            return $response;
        }
    }

    sleep(1);
    return $this->requestTmdb($url, $query);
}
```

```

private function createItems($response, $mediaType)
{
    $items = [];
    $response = json_decode($response->getBody());

    foreach($response->results as $result) {
        $items[] = $this->createItem($result, $mediaType);
    }

    return $items;
}

public function createItem($data, $mediaType)
{
    $title = $data->name ?? $data->title;

    return [
        'tmdb_id' => $data->id,
        'title' => $title,
        'slug' => getSlug($title),
        'poster' => $data->poster_path,
        'media_type' => $mediaType,
        'episodes' => [],
        'overview' => $data->overview,
        'backdrop' => $data->backdrop_path,
        'homepage' => $data->homepage ?? null,
        'tmdb_rating' => $data->vote_average,
        'popularity' => $data->popularity ?? 0,
    ];
}

public function hasLimitRemaining($response)
{
    if($response->getStatusCode() == 429) {
        return false;
    }

    $rateLimit = $response->getHeader('X-RateLimit-Remaining');

    return $rateLimit ? (int) $rateLimit[0] > 1 : true;
}

/*Get current count of seasons*/

private function tvSeasonsCount($id, $mediaType)
{
    if($mediaType == 'tv') {
        $response = $this->requestTmdb($this->base . '/3/tv/' .
$id);

        $seasons = collect(json_decode($response->getBody())-
>seasons);

        return $seasons->filter(function ($season) {
            return $season->season_number > 0;
        })->count();
    }

    return null;
}

```

```

    }

    public function details($tmdbId, $mediaType)
    {
        $response = $this->requestTmdb($this->base . '/3/' .
        $mediaType . '/' . $tmdbId, [
            'append_to_response' => 'videos,external_ids',
        ]);

        if($response->getStatusCode() != Response::HTTP_OK) {
            // ignore any error
            return json_decode('{}');
        }

        return json_decode($response->getBody());
    }

    /*Get all episodes of each season*/

    public function tvEpisodes($tmdbId)
    {
        $seasons = $this->tvSeasonsCount($tmdbId, 'tv');
        $data = [];

        for($i = 1; $i <= $seasons; $i++) {
            $response = $this->requestTmdb($this->base . '/3/tv/' .
            $tmdbId . '/season/' . $i);

            $data[$i] = json_decode($response->getBody());
        }

        return $data;
    }

    public function search($title, $mediaType = null)
    {
        if( ! $title) {
            return response([], Response::HTTP_UNPROCESSABLE_ENTITY);
        }

        $tv = collect();
        $movies = collect();

        if( ! $mediaType || $mediaType == 'tv') {
            $response = $this->fetchSearch($title, 'tv');
            $tv = collect($this->createItems($response, 'tv'));
        }

        if( ! $mediaType || $mediaType == 'movies' || $mediaType ==
        'movie') {
            $response = $this->fetchSearch($title, 'movie');
            $movies = collect($this->createItems($response, 'movie'));
        }

        $sortedEntries = $movies
            ->merge($tv)
            ->sortByDesc('popularity');

        $withExactTitles = $sortedEntries->filter(function($entry) use
        ($title) {

```

```

        return strtolower($entry['title']) == strtolower($title);
    });

    $rest = $sortedEntries->reject(function($entry) use ($title) {
        return strtolower($entry['title']) == strtolower($title);
    });

    return $withExactTitles->merge($rest)->values()->all();
}

private function fetchSearch($title, $mediaType) {
    return $this->requestTmdb($this->base . '/3/search/' .
$mediaType, [
        'query' => $title,
    ]);
}
}

```

## 5.7 User

```

<?php

namespace App;

use Illuminate\Notifications\Notifiable;
use Illuminate\Contracts\Auth\MustVerifyEmail;
use Illuminate\Foundation\Auth\User as Authenticatable;
use Illuminate\Support\Arr;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\DB;

class User extends Authenticatable
{
    use Notifiable;

    /**
     * The attributes that are mass assignable.
     *
     * @var array
     */
    protected $fillable = [
        'name', 'email', 'password', 'custom_title'
    ];

    /**
     * The attributes that should be hidden for arrays.
     *
     * @var array
     */
    protected $hidden = [
        'password', 'remember_token',
    ];

    /**
     * The attributes that should be cast to native types.
     *

```



```
* @var array
*/
protected $casts = [
    'email_verified_at' => 'datetime',
];

public function items()
{
    return $this->hasMany(Item::class);
}

public function posts()
{
    return $this->hasMany('App\Posts', 'author_id');
}

public function comments()
{
    return $this->hasMany('App\Comments', 'from_user');
}

public static function isAdmin()
{
    if (Auth::user()->admin == 1)
    {
        return true;
    }
    return false;
}

public static function topUsers()
{
    $users= DB::select("SELECT user_id FROM items GROUP BY user_id
ORDER BY count(*) DESC LIMIT 9");

    foreach ($users as $user => $position)
    {
        if ($position->user_id == Auth::id())
        {
            return $user;
        }
    }
}

public static function topUsersTv()
{
    $users= DB::select("SELECT user_id FROM items WHERE
media_type='tv' GROUP BY user_id ORDER BY count(*) DESC LIMIT 9");

    foreach ($users as $user => $position)
    {
        if ($position->user_id == Auth::id())
        {
            return $user;
        }
    }
}

public static function topUsersMovies()
```

```

    {
        $users= DB::select("SELECT user_id FROM items WHERE
media_type='movie' GROUP BY user_id ORDER BY count(*) DESC LIMIT 9");

        foreach ($users as $user => $position)
        {
            if ($position->user_id == Auth::id())
            {
                return $user;
            }
        }
    }
}

```

## 6. Views

### 6.1 Admin Views

#### 6.1.1 Comments

##### 6.1.1.1 *edit.blade*

```

@extends('admin.layouts.layout')

@push('styles')
<style>
    .scrolling-wrapper-flexbox {
        display: flex;
        flex-wrap: nowrap;
        overflow-x: auto;
        -webkit-overflow-scrolling: touch;

        .card {
            flex: 0 0 auto;
        }
    }
</style>
@endpush

@section('content')

    <div class="row">
        <div class="col-md-8">
            <div class="card">
                <div class="card-header">
                    <h5 class="title text-center">Comment</h5>
                </div>
                <div class="card-body">
                    @include('partials.messages')

                    <div class="row">
                        <div class="col-md-12">

                            <form
action="{{route('admin.comment.update', $comment)}}" method="post">
                                @method('PUT')

```

```

        @csrf
        <input type="hidden" name="comment_id"
value="{{ $comment->id }}"{{ old('comment_id') }}">
        <div class="form-group">
            <textarea name='body' class="form-
control">{{ $comment->body }}</textarea>

            </div>
            <button type="submit" class="btn btn-
info">Update Comment</button>

        </form>
    </div>
</div>
</div>
</div>
</div>
</div>
</div>

@endsection

```

#### 6.1.1.2 index.blade

```

@extends('admin.layouts.layout')

@section('content')

    <div class="row">
        <div class="col-md-12">
            <div class="card">
                <div class="card-header">
                    <h3 class="card-title text-center">All
Comments</h3>

                </div>
                <div class="card-body">
                    <div class="toolbar">
                        <!-- Here you can write extra
buttons/actions for the toolbar -->
                    </div>
                    <table id="datatable" class="table table-striped
table-bordered dataTable dtr-inline" cellspacing="0" width="100%"
role="grid" aria-describedby="datatable_info" style="width: 100%;">
<thead>

                        <div class="row">
                            <div class="col-md-12">
                                <tr>

                                    <div class="col-md-1">
                                        <th>Id</th>
                                    </div>
                                    <div class="col-md-4">
                                        <th>User name</th>
                                    </div>
                                    <div class="col-md-5">
                                        <th>Body</th>
                                    </div>
                                    <div class="col-md-2">
                                        <th>Actions</th>

```

```

        </div>
    </tr>
</div>

</div>

</thead>
<tbody>
    @foreach($comments as $comment)
        <div class="row">
            <div class="col-md-12">
                <tr>
                    <div class="col-md-1">
                        <td>{{ $comment->id
}}</td>

                    </div>
                    <div class="col-md-4">
                        <td>{{
\App\User::find($comment->user_id)->name }}</td>
                    </div>
                    <div class="col-md-5">
                        <td>{{substr($comment-
>body,0,100)}}...</td>

                    </div>
                    <div class="col-md-2">
                        <td>
                            <a href="{{
route('admin.comment.show', $comment) }}" class="btn btn-round btn-
warning btn-sm"><i class="fa fa-eye"></i></a>
                            <a href="{{
route('admin.comment.edit', $comment) }}" class="btn btn-round btn-
info btn-sm"><i class="fa fa-pencil-alt"></i></a>
                            <form action="{{
route('admin.comment.destroy', $comment) }}" method="post" class="d-
inline">
                                @csrf
                                @method('DELETE')
                                <button class="btn
btn-round btn-danger btn-sm" onclick="return confirm('¿Seguro que
quieres eliminar este comentario?')">
                                    <i class="fa
fa-times"></i>
                                </button>
                            </form>
                        </td>
                    </div>
                </tr>
            </div>
        </div>
    @endforeach
</tbody>
</table>
</div>
</div>
</div>

```

```

@endsection

@push('scripts')

    <script>
        $(function () {
            $('#datatable').DataTable({
                "paging": true,
                "lengthChange": false,
                "searching": false,
                "ordering": true,
                "info": true,
                "autoWidth": false,
            });
        });
    </script>
@endpush

```

### 6.1.1.3 show.blade

```

@extends('admin.layouts.layout')

@push('styles')
    <style>
        .scrolling-wrapper-flexbox {
            display: flex;
            flex-wrap: nowrap;
            overflow-x: auto;
            -webkit-overflow-scrolling: touch;

            .card {
                flex: 0 0 auto;
            }
        }
    </style>
@endpush

@section('content')

    <div class="row">
        <div class="col-md-4">
            <div class="card card-user">
                <div class="image">
                    
                </div>
                <div class="card-body">
                    <div class="author">
                        
                        <h5 class="title text-info">{{\App\User::find($comment->user_id)->name}}</h5>
                    </div>
                    <br>
                    <hr>
                    <br>

```

```

        <p class="description text-center">
            {{ $phrase[0] }}
        </p>
        <br>
        <hr>
    </div>
</div>
</div>

<div class="col-md-8">
    <div class="card">
        <div class="card-header">
            <h5 class="title text-center">Comment</h5>
        </div>
        <div class="card-body">
            <div class="row">
                <div class="col-md-12">
                    <p class="text-center font-italic"
style="solid-color: #3f9ae5">{{ $comment->body }}</p>
                </div>
            </div>
        </div>
    </div>
</div>
</div>
</div>

@endsection

```

## 6.1.2 Layouts

### 6.1.2.1 layout.blade

```

<!DOCTYPE html>
<html lang="en">

<head>
    <meta charset="utf-8" />
    <link rel="apple-touch-icon" sizes="76x76"
href="../../../assets/img/apple-icon.png">
    <link rel="icon" type="image/png"
href="../../../assets/img/favicon.png">
    <meta http-equiv="X-UA-Compatible" content="IE=edge,chrome=1" />
    <title>
        Showtrakt Admin Panel
    </title>
    <meta content='width=device-width, initial-scale=1.0, maximum-
scale=1.0, user-scalable=0, shrink-to-fit=no' name='viewport' />
    <!--      Fonts and icons      -->
    <link
href="https://fonts.googleapis.com/css?family=Montserrat:400,700,200"
rel="stylesheet" />
    <link
href="https://use.fontawesome.com/releases/v5.0.6/css/all.css"
rel="stylesheet">
    <!-- CSS Files -->
    <link href="/dashboard-pro/assets/css/bootstrap.min.css"
rel="stylesheet" />
    <link href="/dashboard-pro/assets/css/noui-
dashboard.css?v=1.2.0" rel="stylesheet" />

```

```

@stack('styles')

<style>
  ::-webkit-scrollbar {
    width: 5px;
    height: 5px;
  }
  ::-webkit-scrollbar-button {
    width: 13px;
    height: 13px;
  }
  ::-webkit-scrollbar-thumb {
    background: #0395b2;
    border: 2px none #ffffff;
    border-radius: 93px;
  }
  ::-webkit-scrollbar-thumb:hover {
    background: #1d2ac7;
  }
  ::-webkit-scrollbar-thumb:active {
    background: #3f60df;
  }
  ::-webkit-scrollbar-track {
    background: #666666;
    border: 3px none #ffffff;
    border-radius: 77px;
  }
  ::-webkit-scrollbar-track:hover {
    background: #666666;
  }
  ::-webkit-scrollbar-track:active {
    background: #333333;
  }
  ::-webkit-scrollbar-corner {
    background: transparent;
  }
</style>
</head>

<body class=" sidebar-mini ">
<div class="wrapper ">
@include('admin.partials.sidebar')
  <div class="main-panel">
    <!-- Navbar -->
    @include('admin.partials.navbar')
    <!-- End Navbar -->
    <div class="panel-header panel-header-sm">
      <canvas id="bigDashboardChart"></canvas>
    </div>
    <div class="content">
      @yield('content')
    </div>
    @include('admin.partials.footer')
  </div>
</div>
<!-- Core JS Files -->
<script src="/dashboard-pro/assets/js/core/jquery.min.js"></script>
<script src="/dashboard-pro/assets/js/core/popper.min.js"></script>
<script src="/dashboard-pro/assets/js/core/bootstrap.min.js"></script>
<script src="/dashboard-pro/assets/js/plugins/perfect-scrollbar.jquery.min.js"></script>

```

```

<script src="/dashboard-pro/assets/js/plugins/moment.min.js"></script>
<!-- Plugin for Switches, full documentation here:
http://www.jque.re/plugins/version3/bootstrap.switch/ -->
<script src="/dashboard-pro/assets/js/plugins/bootstrap-switch.js"></script>
<!-- Plugin for Sweet Alert -->
<script src="/dashboard-pro/assets/js/plugins/sweetalert2.min.js"></script>
<!-- Forms Validations Plugin -->
<script src="/dashboard-pro/assets/js/plugins/jquery.validate.min.js"></script>
<!-- Plugin for the Wizard, full documentation here:
https://github.com/VinceG/twitter-bootstrap-wizard -->
<script src="/dashboard-pro/assets/js/plugins/jquery.bootstrap-wizard.js"></script>
<!-- Plugin for Select, full documentation here:
http://silviomoreto.github.io/bootstrap-select -->
<script src="/dashboard-pro/assets/js/plugins/bootstrap-selectpicker.js"></script>
<!-- Plugin for the DateTimePicker, full documentation here:
https://eonasdan.github.io/bootstrap-datetimepicker/ -->
<script src="/dashboard-pro/assets/js/plugins/bootstrap-datetimepicker.js"></script>
<!-- DataTables.net Plugin, full documentation here:
https://datatables.net/ -->
<script src="/dashboard-pro/assets/js/plugins/jquery.dataTables.min.js"></script>
<!-- Plugin for Tags, full documentation here:
https://github.com/bootstrap-tagsinput/bootstrap-tagsinputs -->
<script src="/dashboard-pro/assets/js/plugins/bootstrap-tagsinput.js"></script>
<!-- Plugin for Fileupload, full documentation here:
http://www.jasny.net/bootstrap/javascript/#fileinput -->
<script src="/dashboard-pro/assets/js/plugins/jasny-bootstrap.min.js"></script>
<!-- Full Calendar Plugin, full documentation here:
https://github.com/fullcalendar/fullcalendar -->
<script src="/dashboard-pro/assets/js/plugins/fullcalendar.min.js"></script>
<!-- Vector Map plugin, full documentation here:
http://jvectormap.com/documentation/ -->
<script src="/dashboard-pro/assets/js/plugins/jquery-jvectormap.js"></script>
<!-- Plugin for the Sliders, full documentation here:
http://refreshless.com/nouislider/ -->
<script src="/dashboard-pro/assets/js/plugins/nouislider.min.js"></script>
<!-- Chart JS -->
<script src="/dashboard-pro/assets/js/plugins/chartjs.min.js"></script>
<!-- Notifications Plugin -->
<script src="/dashboard-pro/assets/js/plugins/bootstrap-notify.js"></script>
<!-- Control Center for Now Ui Dashboard: parallax effects, scripts
for the example pages etc -->
<script src="/dashboard-pro/assets/js/now-ui-dashboard.min.js?v=1.2.0"
type="text/javascript"></script>

@stack('scripts')
</body>

```



```
</html>
```

### 6.1.3 Partial

#### 6.1.3.1 footer

```
<footer class="footer">
  <div class="container-fluid">
    <nav>
      <ul>
        <li>
          <a href="https://www.creative-tim.com">
            Showtrakt
          </a>
        </li>
        <li>
          <a href="http://presentation.creative-tim.com">
            About Us
          </a>
        </li>
        <li>
          <a href="http://blog.creative-tim.com">
            Blog
          </a>
        </li>
      </ul>
    </nav>
    <div class="copyright" id="copyright">
      &copy;
      <script>

document.getElementById('copyright').appendChild(document.createTextNode(
  new Date().getFullYear())
)
      </script>

    </div>
  </div>
</footer>
```

#### 6.1.3.2 Navbar.blade

```
<nav class="navbar navbar-expand-lg navbar-transparent bg-primary
navbar-absolute">
  <div class="container-fluid">
    <div class="navbar-wrapper">
      <div class="navbar-toggler">
        <button type="button" class="navbar-toggler">
          <span class="navbar-toggler-bar bar1"></span>
          <span class="navbar-toggler-bar bar2"></span>
          <span class="navbar-toggler-bar bar3"></span>
        </button>
      </div>
      <a class="navbar-brand" href="/admin">Dashboard</a>
    </div>
    <button class="navbar-toggler" type="button" data-
toggle="collapse" data-target="#navigation" aria-controls="navigation-
index" aria-expanded="false" aria-label="Toggle navigation">
      <span class="navbar-toggler-bar navbar-kebab"></span>
      <span class="navbar-toggler-bar navbar-kebab"></span>
```

```

        <span class="navbar-toggler-bar navbar-kebab"></span>
    </button>
    <div class="collapse navbar-collapse justify-content-end"
id="navigation">
        <ul class="navbar-nav">
            <li class="nav-item">
                <a class="nav-link" href="#pablo">
                    <i class="now-ui-icons media-2_sound-
wave"></i>
                        <p>
                            <span class="d-lg-none d-md-
block">Stats</span>
                        </p>
                    </a>
                </li>
            <li class="nav-item dropdown">
                <a class="nav-link dropdown-toggle"
href="http://example.com" id="navbarDropdownMenuLink" data-
toggle="dropdown" aria-haspopup="true" aria-expanded="false">
                    <i class="now-ui-icons location_world"></i>
                    <p>
                        <span class="d-lg-none d-md-block">Some
Actions</span>
                    </p>
                </a>
                <div class="dropdown-menu dropdown-menu-right"
aria-labelledby="navbarDropdownMenuLink">
                    <a class="dropdown-item" href="#">Action</a>
                    <a class="dropdown-item" href="#">Another
action</a>
                    <a class="dropdown-item" href="#">Something
else here</a>
                </div>
            </li>
            <li class="nav-item">
                <a class="nav-link" href="#pablo">
                    <i class="now-ui-icons users_single-02"></i>
                    <p>
                        <span class="d-lg-none d-md-
block">Account</span>
                    </p>
                </a>
            </li>
        </ul>
    </div>
</div>
</nav>

```

### 6.1.3.3 sidebar.blade

```

<div class="sidebar" data-color="blue">
    <!--
        Tip 1: You can change the color of the sidebar using: data-
color="blue | green | orange | red | yellow"
    -->
    <div class="logo">
        <a href="/admin" class="simple-text logo-mini">

```

```

        ST
    </a>
    <a href="/admin" class="simple-text logo-normal">
        ShowTrack
    </a>
    <div class="navbar-minimize">
        <button id="minimizeSidebar" class="btn btn-simple btn-
icon btn-neutral btn-round">
            <i class="now-ui-icons text_align-center visible-on-
sidebar-regular"></i>
            <i class="now-ui-icons design_bullet-list-67 visible-
on-sidebar-mini"></i>
        </button>
    </div>
</div>
<div class="sidebar-wrapper">
    <div class="user">
        <div class="photo">
            
        </div>
        <div class="info">
            <a data-toggle="collapse" href="" class="collapsed">
                <span>
                    {{\Illuminate\Support\Facades\Auth::user()->name}}
                </span>
            </a>
            <div class="clearfix"></div>
        </div>
    </div>
    <ul class="nav">
        <li class="active">
            <a href="/admin">
                <i class="now-ui-icons objects_spaceship"></i>
                <p>Dashboard</p>
            </a>
        </li>
        <li>
            <a href="/admin/users">
                <i class="now-ui-icons users_single-02"></i>
                <p>Users</p>
            </a>
        </li>
        <li>
            <a href="/admin/comment">
                <i class="now-ui-icons text_align-center"></i>
                <p>Comments</p>
            </a>
        </li>
        <li>
            <a href="/admin/post">
                <i class="now-ui-icons education_agenda-
bookmark"></i>
                <p>Posts</p>
            </a>
        </li>
    </ul>
</div>
</div>

```

## 6.1.4 posts

### 6.1.4.1 create.blade

```
@extends('admin.layouts.layout')

@section('content')

    <div class="row justify-content-center">
        <div class="col-md-8">
            <div class="card">
                <div class="card-header text-center">
                    <h6>Create new Post</h6>
                </div>
                <div class="card-body">
                    @include('partials.messages')
                    <form action="{{route('admin.posts.store')}}"
method="post">

                        @csrf

                        <div class="form-group">
                            <label
for="exampleInputEmail1">Title</label>
                            <input type="text" required="required"
value="{{ old('title') }}" class="form-control" id="titlepost"
name="title" aria-describedby="emailHelp" placeholder="Enter title">
                            </div>
                            <div class="form-group">
                                <label for="exampleInputEmail1">Image
Url</label>
                                <input type="text" required="required"
value="{{ old('image_url') }}" class="form-control" id="image_url"
name="image_url" aria-describedby="emailHelp" placeholder="Enter image
Url">
                                </div>
                                <div class="form-group" >
                                    <label
for="exampleInputEmail1">Body</label>
                                    <textarea name='body' class="form-
control">{{ old('body') }}</textarea>
                                </div>
                                <button type="submit" class="btn btn-
info">Create Post</button>

                            </form>
                        </div>
                    </div>
                </div>
            </div>
        </div>
    </div>

@endsection
```

### 6.1.4.2 edit.blade

```
@extends('admin.layouts.layout')
```

```

@section('content')

    <div class="row justify-content-center">
        <div class="col-md-8">
            <div class="card">
                <div class="card-header text-center">
                    <h6>Edit Post</h6>
                </div>
                <div class="card-body">
                    @include('partials.messages')

                    <form action="{{route('admin.posts.update')}}"
method="post">
                        @method('PUT')
                        @csrf
                        <input type="hidden" name="post_id" value="{{
$post->id }}"{{ old('post_id') }}">
                        <div class="form-group">
                            <label
for="exampleInputEmail1">Title</label>
                            <input type="text" required="required"
value="{{ $post->title }}" class="form-control" id="titlepost"
name="title" aria-describedby="emailHelp" placeholder="Enter title">
                        </div>
                        <div class="form-group">
                            <label
for="exampleInputEmail1">Body</label>
                            <textarea name='body' class="form-
control">{{ $post->body }}</textarea>

                        </div>
                        <button type="submit" class="btn btn-
info">Update Post</button>

                    </form>
                </div>
            </div>
        </div>
    </div>
</div>

@endsection

```

#### 6.1.4.3 index.blade

```

@extends('admin.layouts.layout')

@section('content')

    <div class="row">
        <div class="col-md-12">
            <div class="card">
                <div class="card-header">
                    <h3 class="card-title text-center">All Posts</h3>

                </div>
                <div class="card-body">
                    <div class="toolbar">
                        <!-- Here you can write extra
buttons/actions for the toolbar -->

```

```

        <div class=" col-md-2 ml-auto">
            <a href="{{ route('admin.posts.create')
}} " class="btn btn-info btn-xl "> Create New Post</a>
        </div>
    </div>
    <table id="datatable" class="table table-striped
table-bordered dataTable dtr-inline" cellpadding="0" width="100%"
role="grid" aria-describedby="datatable_info" style="width: 100%;">
<thead>
    <div class="row">
        <div class="col-md-12">
            <tr>

                <div class="col-md-1">
                    <th>Id</th>
                </div>
                <div class="col-md-4">
                    <th>Title</th>
                </div>
                <div class="col-md-5">
                    <th>Body</th>
                </div>
                <div class="col-md-2">
                    <th>Actions</th>
                </div>
            </tr>
        </div>

    </thead>
    <tbody>
    @foreach($posts as $post)
        <div class="row">
            <div class="col-md-12">
                <tr>
                    <div class="col-md-1">
                        <td>{{ $post->id }}</td>
                    </div>
                    <div class="col-md-4">
                        <td>{{ $post->title
}}</td>

                    </div>
                    <div class="col-md-5">
                        <td>{{ substr($post-
>body,0,100) }}...</td>

                    </div>
                    <div class="col-md-2">
                        <td>
                            <a href="{{
route('admin.posts.edit', $post->slug) }}" class="btn btn-round btn-
warning btn-sm"><i class="fa fa-eye"></i></a>
                            <a href="{{
route('admin.posts.edit', $post->slug) }}" class="btn btn-round btn-
info btn-sm"><i class="fa fa-pencil-alt"></i></a>
                            <form action="{{
route('admin.posts.destroy', $post) }}" method="post" class="d-
inline">
                                @csrf
                                @method('DELETE')

```

```

        <button class="btn
btn-round btn-danger btn-sm" onclick="return confirm('¿Seguro que
quieres eliminar este post?')">
        <i class="fa
fa-times"></i>
        </button>
    </form>
</td>
</div>
</tr>
</div>
</div>
    @endforeach
</tbody>
</table>
</div>
</div>
</div>
</div>

@endsection

@push('scripts')
    <script>
        $(function () {
            $('#datatable').DataTable({
                "paging": true,
                "lengthChange": false,
                "searching": false,
                "ordering": true,
                "info": true,
                "autoWidth": false,
            });
        });
    </script>
@endpush

```

## 6.1.5 Users

### 6.1.5.1 index.blade

```

@extends('admin.layouts.layout')

@section('content')
    <div class="row">
        <div class="col-md-12">
            <div class="card">
                <div class="card-header">
                    <h3 class="card-title text-center">All Users</h3>
                </div>
                <div class="card-body">

```

```

        <div class="toolbar">
            <!-- Here you can write extra
buttons/actions for the toolbar -->
            <div class=" col-md-2 ml-auto">
                <a href="{{ route('admin.users.invite')
}}" class="btn btn-info btn-xl "> Invite new User</a>
            </div>
        </div>
        <table id="datatable" class="table table-striped
table-bordered dataTable dtr-inline" cellspacing="0" width="100%"
role="grid" aria-describedby="datatable_info" style="width: 100%;">
<thead>
        <div class="row">
            <div class="col-md-12">
                <tr>

                    <div class="col-md-1">
                        <th>Id</th>
                    </div>
                    <div class="col-md-4">
                        <th>Name</th>
                    </div>
                    <div class="col-md-5">
                        <th>Email</th>
                    </div>
                    <div class="col-md-2">
                        <th>Actions</th>
                    </div>

                </tr>
            </div>

        </thead>
        <tbody>
        @foreach($users as $user)
            <div class="row">
                <div class="col-md-12">
                    <tr>
                        <div class="col-md-1">
                            <td>{{ $user->id }}</td>
                        </div>
                        <div class="col-md-4">
                            <td>{{ $user->name }}</td>
                        </div>
                        <div class="col-md-5">
                            <td>{{ $user->email
}}</td>

                        </div>
                        <div class="col-md-2">
                            <td>
                                <a href="{{
route('admin.users.show', $user) }}" class="btn btn-round btn-warning
btn-sm"><i class="fa fa-eye"></i></a>

                                <form action="{{
route('admin.users.destroy', $user) }}" method="post" class="d-
inline">

                                    @csrf
                                    @method('DELETE')

```



```

        <button class="btn
btn-round btn-danger btn-sm" onclick="return confirm('¿Seguro que
quieres eliminar este usuario?')">
        <i class="fa
fa-times"></i>
        </button>
    </form>
</td>
</div>
</tr>
</div>
</div>
    @endforeach
</tbody>
</table>
</div>
</div>
</div>
</div>

```

```
@endsection
```

```
@push('scripts')
```

```

    <script>
        $(function () {
            $('#datatable').DataTable({
                "paging": true,
                "lengthChange": false,
                "searching": false,
                "ordering": true,
                "info": true,
                "autoWidth": false,
            });
        });
    </script>
@endpush

```

#### 6.1.5.2 Invite.blade

```
@extends('admin.layouts.layout')
```

```
@section('content')
```

```

<div class="row justify-content-center">
    <div class="col-md-8">
        <div class="card">
            <div class="card-header text-center">
                <h6>Invite a new User</h6>
            </div>
            <div class="card-body">
                @include('partials.messages')
            </div>
        </div>
    </div>
</div>

```

```

        <form action="{{route('process_invite')}}"
method="post">
            @csrf

            <div class="form-group">
                <label for="exampleInputEmail1">Email
address</label>
                <input type="email" class="form-control"
id="exampleInputEmail1" name="email" aria-describedby="emailHelp"
placeholder="Enter email">
                <small id="emailHelp" class="form-text
text-muted">We'll never share your email with anyone else.</small>
                </div>
                <button type="submit" class="btn btn-
info">Send Invitation</button>

            </form>
        </div>
    </div>
</div>
</div>
@endsection

```

### 6.5.1.3 show.blade

```

@extends('admin.layouts.layout')

@push('styles')
    <style>
        .scrolling-wrapper-flexbox {
            display: flex;
            flex-wrap: nowrap;
            overflow-x: auto;
            -webkit-overflow-scrolling: touch;

            .card {
                flex: 0 0 auto;
            }
        }
    </style>
@endpush

@section('content')

    <div class="row">
        <div class="col-md-4">
            <div class="card card-user">
                <div class="image">
                    
                </div>
                <div class="card-body">
                    <div class="author">
                        
                        <h5 class="title text-info">{{ $user-
>name }}</h5>

```

```

        </div>
        <br>
        <hr>
        <br>
        <br>
        <p class="description text-center">
            {{ $phrase[0] }}
        </p>
        <br>
        <hr>
    </div>
    <div class="card-footer">
        <div class="row">
            <div class="col-md-12">
                <h5 class="category-social text-center ">
                    TV Shows: <strong style="display:
inline;"><i>{{ $userItemsWatched['showswatched'] }}</i></strong>
                </h5>
            </div>
        </div>
        <div class="row">
            <div class="col-md-12">
                <h5 class="category-social text-center">
                    Movies: <strong style="display:
inline;"><i>{{ $userItemsWatched['moviesswatched'] }}</i></strong>
                </h5>
            </div>
        </div>
    </div>

    </div>
</div>
<div class="card">
    <div class="card-header">
        <h5 class="title text-center">Last Comments</h5>
    </div>
    <div class="card-body">
        @forelse($comments as $comment)
            <div class="row">
                <div class="col-md-12">
                    <p class="description text-center">{!!
$comment->body !!}</p>
                    <hr>
                </div>
            </div>
            @empty
                <div class="col-md-12">
                    <p class="description text-center">
                        This user hasn't yet made any
comments</p>
                    <hr>
                </div>
            @endforelse
        </div>
    </div>
</div>

<div class="col-md-8">
    <div class="card">
        <div class="card-header">
            <h5 class="title text-center">Progress</h5>

```

```

</div>
<div class="card-body">
  <div class="row">
    <div class="col-md-12">
      <label>TV Shows watchlist</label>
    </div>
  </div>
  <div class="scrolling-wrapper-flexbox">
    @foreach($items as $item)

        @if($item->media_type == 'tv' &&
$item->watchlist == 1)

            <div class="col-md-2" >
                <div class="card card-product
card-plain">

                    <div class="card-image">
                        <a
href="/item/{{ $item->tmdb_id }}/{{ $item->media_type }}">
                            
                            </a>
                        </div>
                    </div>
                </div>
            @endif
        @endforeach
    </div>
    <br>
    <div class="row">
      <div class="col-md-12">
        <label>TV Shows watched</label>
      </div>
    </div>
    <div class="row">
      <div class="scrolling-wrapper-flexbox">
        @foreach($items as $item)

            @if($item->media_type == 'tv' &&
$item->watched == 1)

                <div class="col-md-2" >
                    <div class="card card-product
card-plain">

                        <div class="card-image">
                            <a
href="/item/{{ $item->tmdb_id }}/{{ $item->media_type }}">
                                
                                </a>
                            </div>
                        </div>
                    </div>
                </div>
            @endif
        @endforeach
      </div>
    <br>
    <div class="row">
      <div class="col-md-12">
        <label>Movies Watchlist</label>

```

```

        </div>
    </div>
    <div class="row">
        <div class="scrolling-wrapper-flexbox">
            @foreach($items as $item)

                @if($item->media_type == 'movie' &&
$item->watchlist == 1)

                    <div class="col-md-2" >
                        <div class="card card-product
card-plain">

                            <div class="card-image">
                                <a
href="/item/{{ $item->tmdb_id }}/{{ $item->media_type }}">
                                    
                                    </a>
                                </div>
                            </div>
                        </div>
                    @endif
                @endforeach
            </div>
        </div>
        <br>
        <div class="row">
            <div class="col-md-12">
                <label>Movies watched</label>
            </div>
        </div>
        <div class="row">
            <div class="scrolling-wrapper-flexbox">
                @foreach($items as $item)

                    @if($item->media_type == 'movie' &&
$item->watched == 1)

                        <div class="col-md-2" >
                            <div class="card card-product
card-plain">

                                <div class="card-image">
                                    <a
href="/item/{{ $item->tmdb_id }}/{{ $item->media_type }}">
                                        
                                        </a>
                                    </div>
                                </div>
                            </div>
                        @endif
                    @endforeach
                </div>
            </div>
        </div>
    </div>
</div>
@endsection

```

## 6.1.6 Dashboard.blade

```

@extends('admin.layouts.layout')

@section('content')

    <div class="row">
        <div class="col-md-12">
            <div class="card card-stats">
                <div class="card-body">
                    <div class="row">
                        <div class="col-md-3">
                            <div class="statistics">
                                <div class="info">
                                    <div class="icon icon-primary">
                                        <i class="now-ui-icons
tech_tv"></i>
                                    </div>
                                    <h3 class="info-
title">{{ $item['showswatched'] }}</h3>
                                    <h6 class="stats-title">Watched TV
Shows</h6>
                                </div>
                            </div>
                        </div>
                        <div class="col-md-3">
                            <div class="statistics">
                                <div class="info">
                                    <div class="icon icon-success">
                                        <i class="now-ui-icons media-
2_sound-wave"></i>
                                    </div>
                                    <h3 class="info-
title">{{ $item['moviesswatched'] }}</h3>
                                    <h6 class="stats-title">Watched
Movies</h6>
                                </div>
                            </div>
                        </div>
                        <div class="col-md-3">
                            <div class="statistics">
                                <div class="info">
                                    <div class="icon icon-info">
                                        <i class="now-ui-icons
users_single-02"></i>
                                    </div>
                                    <h3 class="info-
title">{{ $user }}</h3>
                                    <h6 class="stats-title">Total
Users</h6>
                                </div>
                            </div>
                        </div>
                        <div class="col-md-3">
                            <div class="statistics">
                                <div class="info">
                                    <div class="icon icon-danger">
                                        <i class="now-ui-icons ui-
2_chat-round"></i>
                                    </div>
                                </div>
                            </div>
                        </div>
                    </div>
                </div>
            </div>
        </div>
    </div>

```

54

```

        <div class="card card-product card-
plain">
            <div class="card-image">
                <a target="_blank"
href="/item/{{ $stopmovie->tmdb_id }}/movie">
                    
                </a>
            </div>
        </div>
    </div>
    @empty
    <div class="col-md-4">
        <p>No Movies yet!</p>
    </div>
    @endforelse
</div>
</div>
</div>
<div class="col-lg-6 col-md-6">
    <div class="card">
        <div class="card-header">
            <h4 class="card-title text-center">
                Top TV Shows
            </h4>
            <hr>
        </div>
        <div class="card-body">
            <div class="row">
                @forelse($toptvshows as $toptvshow)
                    <div class="col-md-4">
                        <div class="card card-product card-
plain">
                            <div class="card-image">
                                <a target="_blank"
href="/item/{{ $toptvshow->tmdb_id }}/tv">
                                    
                                </a>
                            </div>
                        </div>
                    </div>
                @empty
                    <div class="col-md-12">
                        <p class="text-center">No TV Shows
yet!</p>
                    </div>
                @endforelse
            </div>
        </div>
    </div>
</div>
<div class="row">
    <div class="col-md-12">
        <div class="card">

```



```

        <div class="card-header">
            <h4 class="card-title text-center"> Latest
Comments</h4>
        </div>
        <div class="card-body">
            <hr>
            @forelse($comments as $comment)
                <p>{{ $comment->body }}</p>
            <hr>
            @empty
                <p>No comments yet!</p>
            @endforelse
        </div>
    </div>
</div>
</div>

```

```
@endsection
```

## 6.2 Auth Views

### 6.2.1 Login.blade

```

<!DOCTYPE html>
<html>
@include('partials.head')

<body class="login-page">
<!-- Google Tag Manager (noscript) -->
<noscript>
    <iframe src="https://www.googletagmanager.com/ns.html?id=GTM-
NKDMSK6" height="0" width="0"
style="display:none;visibility:hidden"></iframe>
</noscript>
<!-- End Google Tag Manager (noscript) -->

@include('partials.nav')

<div class="page-header header-filter" filter-color="black">
    <div class="page-header-image" style="background-
image:url('/assets/img/game.jpg')"></div>
    <div class="content">
        <div class="container">
            <div class="col-md-5 ml-auto mr-auto">
                <div class="card card-login card-plain">
                    <form class="form" method="POST" action="{{
route('login') }}">
                        @csrf
                        <div class="card-header text-center">
                            <div class="logo-container">
                                
                            </div>
                            Showtrakt
                        </div>
                        <div class="card-body">
                            <div class="input-group no-border input-
lg">
                                <div class="input-group-prepend">

```

```

        <span class="input-group-text"><i
class="now-ui-icons ui-1_email-85"></i></span>
        </div>
        <input id="email" type="email"
class="form-control @error('email') is-invalid @enderror" name="email"
value="{{ old('email') }}" autocomplete="email" autofocus>

        @error('email')
        <span class="invalid-feedback"

role="alert">

            <strong>{{ $message

}}</strong>

        </span>
        @enderror
    </div>
    <div class="input-group no-border input-
lg">

        <div class="input-group-prepend">
            <span class="input-group-text"><i
class="now-ui-icons objects_key-25"></i></span>
            </div>
            <input id="password" type="password"
class="form-control @error('password') is-invalid @enderror"
name="password" autocomplete="current-password">

            @error('password')
            <span class="invalid-feedback"

role="alert">

                <strong>{{ $message

}}</strong>

            </span>
            @enderror
        </div>
    </div>
    <div class="card-footer text-center">
        <button type="submit" class="btn btn-
primary btn-round btn-lg btn-block">
            {{ __( 'Login' ) }}
        </button>
    </div>
    <div class="pull-left">
        <h6>

            <a href="#pablo" class="link footer-
link">Create Account</a>

        </h6>
    </div>
</form>
</div>
</div>
</div>
</div>
<div class="footer">
    <div class="container">
        <nav>
            <ul>
                <li>
                    <a href="/">
                        Showtrakt
                    </a>
                </li>

```

```

        <li>
            <a href="/">
                About Us
            </a>
        </li>
        <li>
            <a href="/">
                Blog
            </a>
        </li>
    </ul>
</nav>
<div class="copyright" id="copyright">
    &copy;
</div>
</div>
</div>
</div>
</div>
<!-- Core JS Files -->
<script src="/assets/js/core/jquery.min.js"
type="text/javascript"></script>
<script src="/assets/js/core/popper.min.js"
type="text/javascript"></script>
<script src="/assets/js/core/bootstrap.min.js"
type="text/javascript"></script>
<!-- Plugin for Switches, full documentation here:
http://www.jque.re/plugins/version3/bootstrap.switch/ -->
<script src="/assets/js/plugins/bootstrap-switch.js"></script>
<!-- Plugin for the Sliders, full documentation here:
http://refreshless.com/nouislider/ -->
<script src="/assets/js/plugins/nouislider.min.js"
type="text/javascript"></script>
<!-- Plugin for the DatePicker, full documentation here:
https://github.com/uxsolutions/bootstrap-datepicker -->
<script src="/assets/js/plugins/moment.min.js"></script>
<!-- Plugin for Tags, full documentation here:
https://github.com/bootstrap-tagsinput/bootstrap-tagsinputs -->
<script src="/assets/js/plugins/bootstrap-tagsinput.js"></script>
<!-- Plugin for Select, full documentation here:
http://silviomoreto.github.io/bootstrap-select -->
<script src="/assets/js/plugins/bootstrap-selectpicker.js"
type="text/javascript"></script>
<!-- Plugin for the DateTimePicker, full documentation here:
https://eonasdan.github.io/bootstrap-datetimepicker/ -->
<script src="/assets/js/plugins/bootstrap-datetimepicker.js"
type="text/javascript"></script>
<!-- Google Maps Plugin -->
<script
src="https://maps.googleapis.com/maps/api/js?key=YOUR_KEY_HERE"></scri
pt>
<!-- Control Center for Now Ui Kit: parallax effects, scripts for the
example pages etc -->
<script src="/assets/js/now-ui-kit.js?v=1.2.2"
type="text/javascript"></script>
</body>

```

```
</html>
```

### 6.2.2 Register.blade

```
<!DOCTYPE html>
<html>
@include('partials.head')

<body class="signup-page">
<!-- Google Tag Manager (noscript) -->
<noscript>
    <iframe src="https://www.googletagmanager.com/ns.html?id=GTM-
NKDMSK6" height="0" width="0"
    style="display:none;visibility:hidden"></iframe>
</noscript>
<!-- End Google Tag Manager (noscript) -->
<!-- Navbar -->

@include('partials.nav')

<div class="page-header header-filter" filter-color="black">
    <div class="page-header-image" style="background-
image:url(../assets/img/starwars.jpg)"></div>
    <div class="content">
        <div class="container">
            <div class="row">
                <div class="col-md-4 ml-auto mr-auto">
                    <div class="info info-horizontal">
                        <div class="icon icon-primary">
                            <i class="now-ui-icons business_chart-pie-
36"></i>

                            </div>
                            <div class="description">
                                <h5 class="info-title">Stats</h5>
                                <p class="description">
                                    We collect data to better understand
our users.

                                </p>
                            </div>
                        </div>
                        <div class="info info-horizontal">
                            <div class="icon icon-primary">
                                <i class="now-ui-icons
design_palette"></i>

                                </div>
                                <div class="description">
                                    <h5 class="info-title">Beautifuly
Design</h5>

                                    <p class="description">
                                        Our designer work steadily to improve
the user experience.

                                    </p>
                                </div>
                            </div>
                        <div class="info info-horizontal">
                            <div class="icon icon-info">
                                <i class="now-ui-icons
emoticons_satisfied"></i>

                                </div>
```

```

        <div class="description">
            <h5 class="info-title">User
Experience</h5>
            <p class="description">
                Our top priority is to fully
understand how users consume our app and improve it.
            </p>
        </div>
    </div>
</div>
<div class="col-md-4 mr-auto">
    <div class="card card-signup" >
        <div class="card-body">
            <h4 class="card-title text-
center">Register</h4>
            <form class="form" method="POST"
action="{{route('accept')}}">
                @csrf
                <div class="input-group">
                    <div class="input-group-prepend">
                        <span class="input-group-
text"><i class="now-ui-icons users_circle-08"></i></span>
                    </div>
                    <input id="name" type="text"
class="form-control @error('name') is-invalid @enderror" name="name"
value="{{ old('name') }}" autocomplete="name" placeholder="Name">
                        @error('name')
                        <span class="invalid-feedback"
role="alert">
                            <strong>{{ $message
}}</strong>
                        </span>
                    @enderror
                </div>
                <div class="input-group">
                    <div class="input-group-prepend">
                        <span class="input-group-
text"><i class="now-ui-icons media-2_note-03"></i></span>
                    </div>
                    <input id="custom_title"
type="text" class="form-control @error('custom_title') is-invalid
@enderror" name="custom_title" value="{{ old('custom_title') }}"
autocomplete="custom_title" placeholder="custom_title">
                        @error('custom_title')
                        <span class="invalid-feedback"
role="alert">
                            <strong>{{ $message
}}</strong>
                        </span>
                    @enderror
                </div>
                <div class="input-group
@error('password') is-invalid @enderror ">
                    <div class="input-group-prepend">
                        <span class="input-group-
text"><i class="now-ui-icons objects_key-25"></i></span>
                    </div>
                    <input id="password"
type="password" class="form-control @error('password') is-invalid
@enderror" name="password" autocomplete="new-password">

```

```

                                @error('password')
                                <span class="invalid-feedback"
role="alert">
                                <strong>{{ $message
}}</strong>
                                </span>
                                @enderror
                                </div>
                                <div class="input-group">
                                    <div class="input-group-prepend">
                                        <span class="input-group-
text"><i class="now-ui-icons objects_key-25"></i></span>
                                        </div>
                                        <input id="password-confirm"
type="password" class="form-control" name="password_confirmation"
autocomplete="new-password">
                                </div>
                                <div class="input-group">
                                    <div class="input-group-prepend">
                                        <span class="input-group-
text"><i class="now-ui-icons ui-1_email-85"></i></span>
                                        </div>
                                        <input id="email" readonly
type="email" class="form-control @error('email') is-invalid @enderror"
name="email" value="{{ $invite->email }}" autocomplete="email">
                                </div>
                                @error('email')
                                <span class="invalid-feedback"
role="alert">
                                <strong>{{ $message
}}</strong>
                                </span>
                                @enderror
                                </div>
                                {{--<!-- If you want to add a checkbox
to this form, uncomment this code -->--}}
                                {{--<div class="form-check">--}}
                                    {{--<label class="form-check-
label">--}}
                                        {{--<input class="form-check-
input" type="checkbox">--}}
                                            {{--<span class="form-check-
sign"></span>--}}
                                                {{--I agree to the terms and--
}}
                                            {{--<a
href="#something">conditions</a>.--}}
                                                {{--</label>--}}
                                            {{--</div>--}}
                                <div class="card-footer text-center">
                                    <button type="submit" class="btn
btn-primary btn-round btn-lg">
                                        {{ __('Register') }}
                                    </button>
                                </div>
                                </form>
                                </div>
                                </div>
                                </div>
                                </div>
                                </div>

```

```

        </div>
    </div>
    <footer class="footer">
        <div class="container">
            <nav>
                <ul>
                    <li>
                        <a href="/">
                            Showtrakt
                        </a>
                    </li>
                    <li>
                        <a href="/">
                            About Us
                        </a>
                    </li>
                    <li>
                        <a href="/">
                            Blog
                        </a>
                    </li>
                </ul>
            </nav>
            <div class="copyright" id="copyright">
                &copy;
                <script>

document.getElementById('copyright').appendChild(document.createTextNode(new Date().getFullYear()))
                </script>
            </div>
        </div>
    </footer>
</div>

<!-- Core JS Files -->
<script src="/assets/js/core/jquery.min.js"
type="text/javascript"></script>
<script src="/assets/js/core/popper.min.js"
type="text/javascript"></script>
<script src="/assets/js/core/bootstrap.min.js"
type="text/javascript"></script>
<!-- Plugin for Switches, full documentation here:
http://www.jque.re/plugins/version3/bootstrap.switch/ -->
<script src="/assets/js/plugins/bootstrap-switch.js"></script>
<!-- Plugin for the Sliders, full documentation here:
http://refreshless.com/nouislider/ -->
<script src="/assets/js/plugins/nouislider.min.js"
type="text/javascript"></script>
<!-- Plugin for the DatePicker, full documentation here:
https://github.com/uxsolutions/bootstrap-datepicker -->
<script src="/assets/js/plugins/moment.min.js"></script>
<!-- Plugin for Tags, full documentation here:
https://github.com/bootstrap-tagsinput/bootstrap-tagsinputs -->
<script src="/assets/js/plugins/bootstrap-tagsinput.js"></script>
<!-- Plugin for Select, full documentation here:
http://silviomoreto.github.io/bootstrap-select -->
<script src="/assets/js/plugins/bootstrap-selectpicker.js"
type="text/javascript"></script>
<!-- Plugin for the DateTimePicker, full documentation here:
https://eonasdan.github.io/bootstrap-datetimepicker/ -->

```

```

<script src="/assets/js/plugins/bootstrap-datetimepicker.js"
type="text/javascript"></script>
<!-- Google Maps Plugin -->
<script
src="https://maps.googleapis.com/maps/api/js?key=YOUR_KEY_HERE"></scri
pt>
<!-- Control Center for Now Ui Kit: parallax effects, scripts for the
example pages etc -->
<script src="/assets/js/now-ui-kit.js?v=1.2.2"
type="text/javascript"></script>
</body>

</html>

```

## 6.3 Comments Views

### 6.3.1 index.blade

```

@extends('layouts.layout')

@section('content')
    <br>
    <br>
    <h2 class="text-white text-center font-weight-bold">Your
Comments</h2>
    <div class="container">
        <hr style="background-color: white">

        <div class="row">
            @forelse($comments as $comment)
                <div class="col-md-12" onclick="window.location.href
=' /item/{{ $comment->item_id }}/{{ $comment->media_type }}'">
                    <div class="card card-blog" style="background-color:
#3b5998">
                        <div class="card-body">
                            <h6 class="card-title text-center text-white">
                                {{ $comment->item_title }}
                            <div class="col-md-6 ml-auto mr-auto">
                                <hr style="background-color: white">

                                </div>
                            </h6>
                            <p class="card-description text-white">
                                {!! substr($comment->body,0,100) !!}...
                            </p>
                        </div>
                    </div>
                @empty
                    <div class="col-md-12">
                        <br><br><br>
                        <h6 class="text-white text-center">Sorry but
you don't have any comment yet.</h6>
                        <br><br><br>
                    </div>
                </div>

            @endforelse
        </div>
    </div>

```



```

        <div class="container">
            <div class="row" style="background-color: #3b5998;">
                <div class="col-md-4"></div>
                <div class="col-md-6 ml-auto mr-auto text-white"
style="margin-top: 1.5%" >
                    {{ $comments->links() }}
                </div>
            </div>
        </div>

```

```
</div>
```

```
@endsection
```

## 6.4 Items Views

### 6.4.1 index.blade

```
@extends('layouts.layout')
```

```
@section('content')
```

```

    <div class="container">
        <h4 class="text-center text-white">Popular Movies</h4>
        <div class="row">
            <div class="col-md-12">
                <div class="row">
                    @foreach($movies as $movie)
                        @if($movie['media_type'] == 'movie')
                            <div class="col-lg-3 col-md-6" >
                                <div class="card card-product card-
plain">
                                    <div class="card-image">
                                        <a href="#">
                                            
                                            </a>
                                        </div>
                                    </div>
                                    <!-- end card -->
                                </div>
                            @endif
                        @endforeach
                    </div>
                </div>
            </div>
        </div>

```

```
@endsection
```

### 6.4.2 Search.blade

```

@extends('layouts.layout')

@section('content')

    <div class="row">
        <div class="col-sm-6 col-lg-8 ml-auto mr-auto">
            <form action="{{route('item.search')}}" method="GET"
style="display: inline;">
                @csrf
                <div class="input-group" style="margin-top: -2%">
                    <div class="input-group-prepend">
                        <span class="input-group-text"></span>
                    </div>
                    <input type="text" id="search" name="search"
class="form-control text-center"
                        placeholder="Search..." style="background-
color: white" autocomplete="off">

                </div>

            </form>
        </div>
    </div>
    <br>
    <div class="container">
        @if(isset($items))
            <div class="row">
                <div class="col-md-12">
                    <div id="accordion" role="tablist" aria-
multiselectable="true"
                        class="card-collapse">
                            <div class="card card-plain">
                                <div class="card-header" role="tab"
id="headingmovies">
                                    <a data-toggle="collapse" data-
parent="#accordion"
                                    href="#collapsemovies" aria-
expanded="false"
                                    aria-controls="collapsemovies"
class="collapsed">
                                        <div class="text-white"><h2
class="text_bold text-center">
                                            Movies <i class="now-ui-
icons arrows-1_minimal-down text-white"></i>
                                        </h2></div>
                                    </a>
                                </div>

                                <div id="collapsemovies" class="collapse"
role="tabpanel" aria-
labelledby="headingOne" style="">
                                    <div class="row">
                                        @foreach($items as $item)

                                            @if($item['media_type'] ==
'movie' && !empty($item['poster']))
                                                <div class="col-lg-2 col-
md-6">
                                                    <div class="card card-
product card-plain">

```

```

                                <div class="card-
image">
                                <a
href="/item/{{ $item['tmdb_id'] }}/{{ $item['media_type'] }}">
                                
                                </a>
                                </div>
                                </div>
                                </div>
                                @endif
                                @endforeach
                                </div>
                                </div>
                                </div>
                                </div>
                                <div class="row">
                                <div class="col-md-12">
                                <div id="accordion" role="tablist" aria-
multiselectable="true"
                                class="card-collapse">
                                <div class="card card-plain">
                                <div class="card-header" role="tab"
id="headingshows">
                                <a data-toggle="collapse" data-
parent="#accordion"
                                href="#collapseseshows" aria-
expanded="false"
                                aria-controls="collapseseshows"
                                class="collapsed">
                                <div class="text-white"><h2
                                class="text_bold text-center">
                                TV Shows <i class="now-ui-
icons arrows-1_minimal-down text-white"></i></h2></div>
                                </a>
                                </div>
                                <div id="collapseseshows" class="collapse"
                                role="tabpanel" aria-
labelledby="headingOne" style="">
                                <div class="row">
                                @foreach($items as $item)
                                @if($item['media_type'] ==
'tv' && !empty($item['poster']))
                                <div class="col-lg-2 col-
md-6">
                                <div class="card card-
product card-plain">
                                <div class="card-
image">
                                <a
href="/item/{{ $item['tmdb_id'] }}/{{ $item['media_type'] }}">
                                
  <!-- Google Tag Manager (noscript) -->
  <noscript>
    <iframe src="https://www.googletagmanager.com/ns.html?id=GTM-
NKDMSK6" height="0" width="0"
        style="display:none;visibility:hidden"></iframe>
  </noscript>
  <!-- End Google Tag Manager (noscript) -->
  @include('partials.nav')

  <div class="wrapper" id="up" name="up">

    <div class="page-header page-header-small">
      <div class="page-header-image" data-parallax="true"
        style="background-image:
url('https://image.tmdb.org/t/p/original{{ $item['backdrop'] }}');
transform: translate3d(0px, 0px, 0px);">
      </div>
    </div>
    <div class="section bg-dark">
      <div class="container ">
        @if($item['media_type'] == 'tv')

          <a class='float btn btn-info' href='#up'>
            <h5><i class="my-float now-ui-icons arrows-
1_minimal-up"></i>
            </h5>
          </a>

        @endif
        <div class="row">
          <div class="col-md-5">
            <div class="carousel slide">
              
            </div>
            <div><p></p></div>

            <div class="col-md-5 ml-5">

              <form action="{{ route('items.store',
$item) }}" method="post" style="display: inline;">
                @csrf

                <button class="btn {{isset($watched) ?
'btn-facebook' : 'btn-linkedin'}} btn-round ml-3"
                    type="submit">
                  <i class="now-ui-icons media-
2_sound-wave"> </i> {{isset($watched) ? 'Watched' : 'Watch'}}
                </button>
              </form>

              <button class="btn btn-linkedin btn-round"
type="button" onclick="myFunction2()"

```

```

                style="display: inline;">
                <i class="now-ui-icons
objects_spaceship"

href="https://www.themoviedb.org/{{ $item['media_type'] }}/{{ $item['tmdb
_id'] }}"></i>

                See on Tmdb
                </button>
            </div>

        </div>
        <div class="col-md-7 ml-auto mr-auto">
            <h2 class="title text-white">
{{ $item['title'] }} </h2>
            <hr style="background-color: white">
            <div class="container">
                <p class="text-white ">
{{ $item['overview'] }} </p>
            </div>
            <hr style="background-color: white">
            <div class="ml-auto mr-auto">

                <div class="btn btn-linkedin ml-5">
                    <i class="now-ui-icons media-2_sound-
wave"></i> Tmdb Rating: {{ $item['tmdb_rating'] }}
                </div>

                <button class="btn btn-linkedin ml-5"
onclick="myFunction()">

                    <i class="now-ui-icons users_single-
02"></i> Full Cast

                </button>
                <form action="{{ route('item.watchlist',
$item) }}" method="post" style="display: inline;">
                    @csrf
                    <button class="btn {{ isset($watchlist)
? 'btn-facebook' : 'btn-linkedin' }} ml-5">
                        <i class="now-ui-icons
education_agenda-bookmark"></i> {{ isset($watchlist) ? 'Quit Watch
List' : 'Watch List' }}
                    </button>
                </form>
            </div>
        </div>
    </div>
    @if(isset($episodes))
        @inject('episodeiswatched', 'App\Episode')
        <hr style="background-color: white">
        <div class="container">
            <div class="row">
                <div class="col-md-12">
                    @foreach($episodes as $season)
                        <div id="accordion" role="tablist"
aria-multiselectable="true"

                            class="card-collapse">
                                <div class="card card-plain">
                                    <div class="card-header"
role="tab" id="heading{{ $season->season_number }}">
                                        <a data-
toggle="collapse" data-parent="#accordion"

```

```

href="#collapse{{$season->season_number}}" aria-expanded="false"
                                aria-
controls="collapse{{$season->season_number}}" class="collapsed">
                                <div class="text-
white"><h2 class="text_bold text-center">
                                Season
{{$season->season_number}}</h2></div>
                                </a>
                                </div>

                                <div
id="collapse{{$season->season_number}}" class="collapse"
                                role="tabpanel" aria-
labelledby="headingOne" style="">
                                <br>
                                <div class="row">
                                    @foreach($season-
>episodes as $episode)
                                    <div
class="col-lg-3 col-md-3">

                                    <div
class="card card-blog">
                                    <div
class="card-image">

                                    @if(!empty($episode->still_path))

                                    
                                    </a>

                                    @else

                                    
                                    </a>

                                    @endif

                                    </div>
                                    <div
class="card-body">

                                    <h6 class="category text-primary text-center">

Season {{$episode->season_number}} Episode {{$episode-
>episode_number}}</h6>

                                    <h5 class="card-title p-2">

```

```

    {{ $episode->name }}

</h5>

@if (!empty($episode->overview))
    class="card-description p-2">
        {{ substr($episode->overview, 0, 100) }}...
    </p>
@else

    <p class="card-description p-2">
        Coming Soon...
    </p>

@endif

<div class="card-footer">

    <form action="{{ route('episodes.store', ['tmdb_id'=>$episode->show_id,
    'episode_tmdb_id'=>$episode->id, 'item'=>$item]) }}"
    method="post" style="display: inline;">

    @csrf

    @if ($episodeiswatched-
    >EpisodeExist(\Illuminate\Support\Facades\Auth::id(), $episode->id))

    <button class="btn btn-facebook btn-round ml-5"
    type="submit">
        <i class="now-ui-icons media-2_sound-wave"> </i> Watched
    </button>

    @else

    <button class="btn btn-linkedin btn-round ml-5"
    type="submit">
        <i class="now-ui-icons media-2_sound-wave"> </i> Watch
    </button>

@endif

```



```
</form>
</div>
</div>
</div>
@endforeach
</div>
</div>
</div>
</div>
@endforeach
</div>
</div>
</div>
</div>
</div>
@endif
</div>
@auth
    <br><br><br><br>
    <div class="col-md-12 mr-auto">
        <h2 class="text-white font-weight-bold" data-
toggle="modal" data-target="#helpModal">Comments <small>(Click
me)</small></h2>
    </div>
    @include('partials.messages')
    <form action="{{route('comments.create')}}"
method="post">
        @csrf @method('put')
        <div class="media media-post">
            <a class="pull-left author" href="#pablo">
                <div class="avatar">
                    
                </div>
            </a>
            <div class="media-body">
                <input type="hidden" name="tmdb_id"
id="tmdb_id" value="{{ $item['tmdb_id'] }}" />
                <input type="hidden" name="item_title"
id="item_title" value="{{ $item['title'] }}" />
                <input type="hidden" name="media_type"
id="media_type" value="{{ $item['media_type'] }}" />
                <textarea class="form-control" name="body"
placeholder="What do you think about?" rows="6"></textarea>
                <div class="media-footer">
                    <button class="btn btn-info btn-wd
pull-right">
                        Post Comment
                    </button>
                </div>
            </div>
        </div>
    </div>
```

```

        </div>
    </form>
    @forelse($comments as $comment)
        <div class="row">
            <div class="col-md-12">
                <div class="media">
                    <a class="pull-left" href="#pablo">
                        <div class="avatar">
                            
                        </div>
                    </a>
                    <div class="media-body">
                        <h5 class="media-heading text-
white">{{\App\User::find($comment->user_id)->name}}
                        </h5>
                        <p class="text-white font-weight-
bold">{!! $comment->body !!}</p>
                    </div>
                </div>
                <div class="col-md-8 ml-auto mr-auto">
                    <hr style="background-color:
white">
                </div>
            </div>
        </div>
    @empty
        <div class="row ">
            <div class="col-md-12 mr-auto">
                <h6 class="text-white">No comments yet, be
the first!</h6>
            </div>
        </div>
    @endforelse
@endauth

    </div>
</div>
</div>
</d>

<footer class="footer" data-background-color="black">
    <div class="container">
        <a class="footer-brand" href="/">Showtrakt</a>
        <p class="pull-center small">This product uses the TMDb API
but is not endorsed or certified by TMDb</p>
        <ul class="social-buttons pull-right">
            <li>
                <a href="https://twitter.com/CreativeTim"
target="_blank" class="btn btn-icon btn-link btn-neutral">
                    <i class="fab fa-twitter"></i>
                </a>
            </li>
            <li>
                <a href="https://www.facebook.com/CreativeTim"
target="_blank"
                class="btn btn-icon btn-neutral btn-link">
                    <i class="fab fa-facebook-square"></i>
                </a>
            </li>
        </ul>
    </div>
</div>

```

```

        </li>
        <li>
            <a
href="https://www.instagram.com/CreativeTimOfficial" target="_blank"
class="btn btn-icon btn-neutral btn-link">
                <i class="fab fa-instagram"></i>
            </a>
        </li>
    </ul>
</div>
</footer>

<script>
    function myFunction() {
        location.href =
"https://www.themoviedb.org/{{ $item['media_type'] }}/{{ $item['tmdb_id']
}}/cast";
    }

    function myFunction2() {
        location.href =
"https://www.themoviedb.org/{{ $item['media_type'] }}/{{ $item['tmdb_id']
}}";
    }
</script>

<!-- Core JS Files -->
<script src="/assets/js/core/jquery.min.js"
type="text/javascript"></script>
<script src="/assets/js/core/popper.min.js"
type="text/javascript"></script>
<script src="/assets/js/core/bootstrap.min.js"
type="text/javascript"></script>
<!-- Plugin for Switches, full documentation here:
http://www.jque.re/plugins/version3/bootstrap.switch/ -->
<script src="/assets/js/plugins/bootstrap-switch.js"></script>
<!-- Plugin for the Sliders, full documentation here:
http://refreshless.com/nouislider/ -->
<script src="/assets/js/plugins/nouislider.min.js"
type="text/javascript"></script>
<!-- Plugin for the DatePicker, full documentation here:
https://github.com/uxsolutions/bootstrap-datepicker -->
<script src="/assets/js/plugins/moment.min.js"></script>
<!-- Plugin for Tags, full documentation here:
https://github.com/bootstrap-tagsinput/bootstrap-tagsinputs -->
<script src="/assets/js/plugins/bootstrap-tagsinput.js"></script>
<!-- Plugin for Select, full documentation here:
http://silviomoreto.github.io/bootstrap-select -->
<script src="/assets/js/plugins/bootstrap-selectpicker.js"
type="text/javascript"></script>
<!-- Plugin for the DateTimePicker, full documentation here:
https://eonasdan.github.io/bootstrap-datetimepicker/ -->
<script src="/assets/js/plugins/bootstrap-datetimepicker.js"
type="text/javascript"></script>
<!-- Control Center for Now Ui Kit: parallax effects, scripts for the
example pages etc -->
<script src="/assets/js/now-ui-kit.js?v=1.2.2"
type="text/javascript"></script>
</body>

</html>

```

## 6.5 Layouts Views

### 6.5.1 layout.blade

```
<!DOCTYPE html>
<html>

@include('partials.head')

<body class="landing-page bg-dark">
<!-- Google Tag Manager (noscript) -->
<noscript>
    <iframe src="https://www.googletagmanager.com/ns.html?id=GTM-
NKDMSK6" height="0" width="0"
style="display:none;visibility:hidden"></iframe>
</noscript>
<!-- End Google Tag Manager (noscript) -->
@include('partials.nav')
<div class="wrapper ">
    <div class="page-header @if(url()->current() ==
"http://showtrakt.local") page-header-medium @else page-header-small
@endif">
        <div class="page-header-image" data-parallax="true"
style="background-image: url('/assets/img/mandalorian.jpg');">
        </div>
        <div class="content-center">
            @if(url()->current() == "http://showtrakt.local")
            <div class="container">
                <h1 class="title">Showtrakt</h1>
                <div class="text-center">
                    {{--<a href="#pablo" class="btn btn-primary btn-
icon btn-round">--}}
                    {{--<i class="fab fa-facebook-square"></i>--}}
                    {{--</a>--}}
                    {{--<a href="#pablo" class="btn btn-primary btn-
icon btn-round">--}}
                    {{--<i class="fab fa-twitter"></i>--}}
                    {{--</a>--}}
                    {{--<a href="#pablo" class="btn btn-primary btn-
icon btn-round">--}}
                    {{--<i class="fab fa-google-plus"></i>--}}
                    {{--</a>--}}
                    
                </div>
            </div>
            @endif
        </div>
    </div>
</div>

@yield('content')

<footer class="footer" data-background-color="black">
    <div class="container">
        <a class="footer-brand" href="/">Showtrakt</a>
        <p class="pull-center small">This product uses the TMDb
API but is not endorsed or certified by TMDb</p>
    </div>
</div>
```

```

        <ul class="social-buttons pull-right">
            <li>
                <a href="https://twitter.com/CreativeTim"
target="_blank" class="btn btn-icon btn-link btn-neutral">
                    <i class="fab fa-twitter"></i>
                </a>
            </li>
            <li>
                <a href="https://www.facebook.com/CreativeTim"
target="_blank" class="btn btn-icon btn-neutral btn-link">
                    <i class="fab fa-facebook-square"></i>
                </a>
            </li>
            <li>
                <a
href="https://www.instagram.com/CreativeTimOfficial" target="_blank"
class="btn btn-icon btn-neutral btn-link">
                    <i class="fab fa-instagram"></i>
                </a>
            </li>
        </ul>
    </div>
</footer>

<!-- Core JS Files -->
<script src="/assets/js/core/jquery.min.js"
type="text/javascript"></script>
<script src="/assets/js/core/popper.min.js"
type="text/javascript"></script>
<script src="/assets/js/core/bootstrap.min.js"
type="text/javascript"></script>
<!-- Plugin for Switches, full documentation here:
http://www.jque.re/plugins/version3/bootstrap.switch/ -->
<script src="/assets/js/plugins/bootstrap-switch.js"></script>
<!-- Plugin for the Sliders, full documentation here:
http://refreshless.com/nouislider/ -->
<script src="/assets/js/plugins/nouislider.min.js"
type="text/javascript"></script>
<!-- Plugin for the DatePicker, full documentation here:
https://github.com/uxsolutions/bootstrap-datepicker -->
<script src="/assets/js/plugins/moment.min.js"></script>
<!-- Plugin for Tags, full documentation here:
https://github.com/bootstrap-tagsinput/bootstrap-tagsinputs -->
<script src="/assets/js/plugins/bootstrap-tagsinput.js"></script>
<!-- Plugin for Select, full documentation here:
http://silviomoreto.github.io/bootstrap-select -->
<script src="/assets/js/plugins/bootstrap-selectpicker.js"
type="text/javascript"></script>
<!-- Plugin for the DateTimePicker, full documentation here:
https://eonasdan.github.io/bootstrap-datetimepicker/ -->
<script src="/assets/js/plugins/bootstrap-datetimepicker.js"
type="text/javascript"></script>
<!-- Google Maps Plugin -->
<script
src="https://maps.googleapis.com/maps/api/js?key=YOUR_KEY_HERE"></scri
pt>
<!-- Control Center for Now Ui Kit: parallax effects, scripts for the
example pages etc -->
<script src="/assets/js/now-ui-kit.js?v=1.2.2"
type="text/javascript"></script>
@stack('scripts')

```

```
</body>

</html>
```

## 6.6 Partial Views

### 6.6.1 avatarmodal.blade

```
<div class="modal fade" id="avatarModal" tabindex="-1" role="dialog"
aria-labelledby="avatarModal" style="display: none;" aria-
hidden="true">
  <div class="modal-dialog modal-notice">
    <div class="modal-content">
      <div class="modal-header">
        <button type="button" class="close" data-
dismiss="modal" aria-hidden="true">
          <i class="now-ui-icons ui-1_simple-remove"
style="color: #0062cc"></i>
        </button>
        <h5 class="modal-title" id="myModalLabel">Change your
Avatar</h5>
      </div>
      <div class="modal-body">
        <div class="col-md-8 ml-auto mr-auto">
          
        </div>
      </div>
      <div class="modal-footer justify-content-center ml-auto
mr-auto">
        <form action="/profile" method="post"
enctype="multipart/form-data" style="inline">
          @csrf
          <div class="form-group ml-auto mr-auto">
            <span class="btn btn-raised btn-round btn-
default btn-file">
              <span class="fileinput-new">Upload Photo</span>
              <input type="file" name="avatar" id="avatarFile">
            </span>
          </div>
          <br>
          <div class="form-group ml-1">
            <button type="submit" class="btn btn-info btn-
round">Update Avatar</button>
          </div>
        </form>
      </div>
    </div>
  </div>
</div>
```

### 6.6.2 head.blade

```
<head>
  <meta charset="utf-8" />
```

```

    <link rel="apple-touch-icon" sizes="76x76"
href="/assets/img/apple-icon.png">
    <link rel="icon" type="image/png" href="/assets/img/favicon.png">
    <meta http-equiv="X-UA-Compatible" content="IE=edge,chrome=1" />
    <title>
        Showtrakt
    </title>
    <meta content='width=device-width, initial-scale=1.0, maximum-
scale=1.0, user-scalable=0, shrink-to-fit=no' name='viewport' />
    <!-- Fonts and icons -->
    <link
href="https://fonts.googleapis.com/css?family=Montserrat:400,700,200|O
pen+Sans+Condensed:700" rel="stylesheet">
    <link
href="https://use.fontawesome.com/releases/v5.0.6/css/all.css"
rel="stylesheet">
    <!-- CSS Files -->
    <link href="/assets/css/bootstrap.min.css" rel="stylesheet" />
    <link href="/assets/css/circle.css" rel="stylesheet" />
    <link href="/assets/css/now-ui-kit.css?v=1.2.2" rel="stylesheet"
/>
    @stack('styles')
    <style>
        ::-webkit-scrollbar {
            width: 5px;
            height: 5px;
        }
        ::-webkit-scrollbar-button {
            width: 13px;
            height: 13px;
        }
        ::-webkit-scrollbar-thumb {
            background: #0395b2;
            border: 2px none #ffffff;
            border-radius: 93px;
        }
        ::-webkit-scrollbar-thumb:hover {
            background: #1d2ac7;
        }
        ::-webkit-scrollbar-thumb:active {
            background: #3f60df;
        }
        ::-webkit-scrollbar-track {
            background: #666666;
            border: 3px none #ffffff;
            border-radius: 77px;
        }
        ::-webkit-scrollbar-track:hover {
            background: #666666;
        }
        ::-webkit-scrollbar-track:active {
            background: #333333;
        }
        ::-webkit-scrollbar-corner {
            background: transparent;
        }
        summary::-webkit-details-marker {
            display: none
        }

        details > summary {

```

```

        padding: 6px;
        width: 100%;
        background-color: white;
        border: none;
        box-shadow: 1px 1px 2px #bbbbbb;
        cursor: pointer;
    }

    details > p {
        background-color: black;
        color:white;
        padding: 4px;
        margin: 0;
        box-shadow: 1px 1px 2px #bbbbbb;
    }
    *{padding:0;margin:0;}

    .float{
        position:fixed;
        width:40px;
        height:40px;
        bottom:15px;
        right:15px;
        background-color:#3f9ae5;
        border-radius:20px;
        text-align:center;
    }

    .my-float{
        margin-top: -15px;
        margin-left: -8px;
    }
</style>
</head>

```

### 6.6.3 helpmodal.blade

```

<div class="modal fade" id="helpModal" tabindex="-1" role="dialog"
aria-labelledby="helpModal" style="display: none;" aria-hidden="true">
    <div class="modal-dialog modal-notice">
        <div class="modal-content">
            <div class="modal-header">
                <button type="button" class="close" data-
dismiss="modal" aria-hidden="true">
                    <i class="now-ui-icons ui-1_simple-remove"
style="color: #0062cc"></i>
                </button>
                <h5 class="modal-title text-center"
id="myModalLabel">Spoilers in Comments</h5>
            </div>
            <div class="modal-body">
                <div class="col-md-12 ml-auto mr-auto">
                    <p class="font-weight-bold">If you wish to write
about a Movie/TV Show and keep safe sensible content about the plot,
please use this to hide the content:</p>
                    <p class="font-
italic">&lt;details&gt;&lt;summary&gt;Spoiler&lt;/summary>&lt;p&gt;Thi
s is a Spoiler&lt;/p&gt;&lt;/details&gt;</p>
                    <p class="font-weight-bold">Example:</p>

```



```

        <details><summary>Spoiler</summary><p>This is a
    Spoiler</p></details>
    </div>
</div>
</div>
</div>
</div>

```

#### 6.6.4 loginmodal.blade

```

<div class="modal fade modal-primary" id="loginModal" tabindex="-1"
role="dialog" aria-labelledby="myModalLabel" aria-hidden="true">
    <div class="modal-dialog modal-login">
        <div class="modal-content" >
            <div class="card card-login card-plain">
                <div class="modal-header justify-content-center">
                    <button type="button" class="close" data-
dismiss="modal" aria-hidden="true">
                        <i class="now-ui-icons ui-1_simple-
remove"></i>
                    </button>
                    <div class="header header-primary text-center">
                        <div class="logo-container">
                            <br>
                            <br>
                            <br>

                            
                        </div>
                    </div>
                </div>
                <div class="modal-body">
                    <form class="form" method="POST" action="{{
route('login') }}">
                        @csrf
                        <div class="card-body">
                            <div class="input-group no-border input-
lg">
                                <div class="input-group-prepend">
                                    <span class="input-group-text"><i
class="now-ui-icons users_circle-08"></i></span>
                                </div>
                                <input id="email" type="text"
class="form-control @error('email') is-invalid @enderror" name="email"
value="{{ old('email') }}" autocomplete="email" autofocus>
                            </div>
                            <div class="input-group no-border input-
lg">
                                <div class="input-group-prepend">
                                    <span class="input-group-text"><i
class="now-ui-icons ui-1_lock-circle-open"></i></span>
                                </div>
                                <input id="password" type="password"
class="form-control @error('password') is-invalid @enderror"
name="password" autocomplete="current-password">
                            </div>
                        </div>
                    </form>
                </div>
            </div>
        </div>
    </div>
</div>

```

```

        <button type="submit" class="btn btn-neutral
btn-round btn-lg btn-block">Login</button>
    </form>
</div>

</div>
</div>
</div>
</div>

```

### 6.6.5 messages.blade

```

@if ($errors->any())
    <ul class="list-group">
        @foreach($errors->all() as $error)
            <li class="list-group-item-danger">
                {{ $error }}
            </li>
        @endforeach
    </ul>
@endif

```

### 6.6.6 nav.blade

```

<nav class="navbar navbar-expand-lg navbar-transparent bg-primary
navbar-absolute">
    <div class="container">
        <div class="navbar-translate">
            <button class="navbar-toggler" type="button" data-
toggle="collapse" aria-controls="navbarSupportedContent" aria-
expanded="false" aria-label="Toggle navigation">
                <span class="navbar-toggler-bar bar1"></span>
                <span class="navbar-toggler-bar bar2"></span>
                <span class="navbar-toggler-bar bar3"></span>
            </button>
            <a class="navbar-brand" href="/">Showtrakt</a>
        </div>
        <div class="collapse navbar-collapse">
            <ul class="navbar-nav mx-auto">
                @guest
                    <li class="nav-item">
                        <a class="nav-link" href="" data-
toggle="modal" data-target="#loginModal" >
                            Log In
                        </a>
                    </li>
                @endguest

                @auth
                    <li class="nav-item">
                        <a class="nav-link" href="/profile">
                            Profile
                        </a>
                    </li>
                    @if(\App\User::isAdmin())
                        <li class="nav-item">
                            <a class="nav-link" href="/admin">

```

```

        Admin
      </a>
    </li>
  @endif
  <li class="nav-item">
    <a class="nav-link" href="/blog">
      Blog
    </a>
  </li>
  <li class="nav-item">
    <a class="nav-link" href="/search">
      Search
    </a>
  </li>

  @endauth

</ul>
<ul class="nav navbar-nav">
  @auth
    <li class="nav-item">
      <div class="nav-link">
        <form action="{{route('logout')}}"
method="POST" style="display: inline;">
          @csrf
          <button class="text-white"
style="background: transparent; border: none
!important;">LOGOUT</button>
        </form>
      </div>
    </li>
    @endauth
    <li class="nav-item">
      <a class="nav-link"
href="https://twitter.com/CreativeTim">
        <i class="fab fa-twitter"></i>
      </a>
    </li>
    <li class="nav-item">
      <a class="nav-link"
href="https://www.facebook.com/CreativeTim">
        <i class="fab fa-facebook-square"></i>
      </a>
    </li>
    <li class="nav-item">
      <a class="nav-link"
href="https://www.instagram.com/CreativeTimOfficial">
        <i class="fab fa-instagram"></i>
      </a>
    </li>
  </ul>
</div>
</div>
</nav>

@include('partials.loginmodal')

```

## 6.7 Posts Views

### 6.7.1 Index.blade

```
@extends('layouts.layout')

@section('content')
    <br>
    <br>
    <h2 class="text-white text-center font-weight-bold">Blog</h2>
    <div class="container">
        <hr style="background-color: white">
        <div class="row">

            @forelse($posts->reverse() as $post)

                <div class="col-md-4">
                    <div class="card card-blog">
                        <div class="card-image">
                            <a href="/blog/{{ $post->slug }}">
                                
                                    </a>
                                </div>
                                <div class="card-body">
                                    <h6 class="category text-primary">Movies</h6>
                                    <h5 class="card-title">
                                        {{ $post->title }}
                                    </h5>
                                    <p class="card-description">
                                        {{ substr($post->body,0,100) }}...
                                    </p>
                                </div>
                            </div>
                        </div>
                    </div>

                    @empty
                        <div class="row">
                            <div class="col-md-1"></div>
                            <div class="col-md-5 ml-auto mr-auto">
                                <br><br>
                                <h6 class="text-white">We are sorry, but right
now this blog have no Post</h6>
                            </div>
                        </div>

                        <div class="row">
                            <div class="col-md-4"></div>
                            <div class="col-md-7">
                                
                                <br><br><br>
                            </div>
                        </div>

                    @endforelse
                </div>
            </div>
        </div>
    </div>
</div>
```

```

    </div>

@endsection

```

## 6.7.2 Show.blade

```

<!DOCTYPE html>
<html>

@include('partials.head')

<d class="product-page">
    <!-- Google Tag Manager (noscript) -->
    <noscript>
        <iframe src="https://www.googletagmanager.com/ns.html?id=GTM-
NKDMSK6" height="0" width="0"
            style="display:none;visibility:hidden"></iframe>
    </noscript>
    <!-- End Google Tag Manager (noscript) -->
    @include('partials.nav')

    <div class="wrapper">
        <div class="page-header page-header-small">
            <div class="page-header-image" data-parallax="true"
                style="background-image:
url('/assets/img/mandalorian.jpg'); transform: translate3d(0px, 0px,
0px);">
            </div>
        </div>
        <div class="section bg-dark" >
            <div class="container" style="margin-top: -7%">
                <div class="row">
                    <div class="card bg-info">
                        <div class="col-md-6 mr-auto ml-auto">
                            <div class="card-header ">
                                <br>
                                
                                <br>
                            </div>
                        </div>

                        <div class="card-body">
                            <br>
                            <h2 class="text-white text-
center">{{ $post->title }}</h2>
                            <hr style="background-color: white">
                            <p class="text-white"><strong>{!! $post-
>body !!}</strong></p>
                            <hr style="background-color: white">
                        </div>
                        <div class="card-footer col-md-2 ml-auto">

                            <h6 class="text-white">{{ $post-
>created_at }}</h6>

                            <br>
                        </div>
                    </div>
                </div>
            </div>
        </div>
    </div>

```

```

        </div>
    </div>
</div>
</d>

<footer class="footer" data-background-color="black">
    <div class="container">
        <a class="footer-brand" href="/">Showtrakt</a>
        <p class="pull-center small">This product uses the TMDb API
but is not endorsed or certified by TMDb</p>
        <ul class="social-buttons pull-right">
            <li>
                <a href="https://twitter.com/CreativeTim"
target="_blank" class="btn btn-icon btn-link btn-neutral">
                    <i class="fab fa-twitter"></i>
                </a>
            </li>
            <li>
                <a href="https://www.facebook.com/CreativeTim"
target="_blank"
                    class="btn btn-icon btn-neutral btn-link">
                        <i class="fab fa-facebook-square"></i>
                    </a>
            </li>
            <li>
                <a
href="https://www.instagram.com/CreativeTimOfficial" target="_blank"
                    class="btn btn-icon btn-neutral btn-link">
                        <i class="fab fa-instagram"></i>
                    </a>
            </li>
        </ul>
    </div>
</footer>

<!-- Core JS Files -->
<script src="/assets/js/core/jquery.min.js"
type="text/javascript"></script>
<script src="/assets/js/core/popper.min.js"
type="text/javascript"></script>
<script src="/assets/js/core/bootstrap.min.js"
type="text/javascript"></script>
<!-- Plugin for Switches, full documentation here:
http://www.jque.re/plugins/version3/bootstrap.switch/ -->
<script src="/assets/js/plugins/bootstrap-switch.js"></script>
<!-- Plugin for the Sliders, full documentation here:
http://refreshless.com/nouislider/ -->
<script src="/assets/js/plugins/nouislider.min.js"
type="text/javascript"></script>
<!-- Plugin for the DatePicker, full documentation here:
https://github.com/uxsolutions/bootstrap-datepicker -->
<script src="/assets/js/plugins/moment.min.js"></script>
<!-- Plugin for Tags, full documentation here:
https://github.com/bootstrap-tagsinput/bootstrap-tagsinputs -->
<script src="/assets/js/plugins/bootstrap-tagsinput.js"></script>
<!-- Plugin for Select, full documentation here:
http://silviomoreto.github.io/bootstrap-select -->
<script src="/assets/js/plugins/bootstrap-selectpicker.js"
type="text/javascript"></script>
<!-- Plugin for the DateTimePicker, full documentation here:
https://eonasdan.github.io/bootstrap-datetimepicker/ -->

```

```

<script src="/assets/js/plugins/bootstrap-datetimepicker.js"
type="text/javascript"></script>
<!-- Control Center for Now Ui Kit: parallax effects, scripts for the
example pages etc -->
<script src="/assets/js/now-ui-kit.js?v=1.2.2"
type="text/javascript"></script>
</body>

</html>

```

## 6.8 Profiles

### 6.8.1 Show.blade

```

<!DOCTYPE html>
<html>

@include('partials.head')

<div class="product-page">
    <!-- Google Tag Manager (noscript) -->
    <noscript>
        <iframe src="https://www.googletagmanager.com/ns.html?id=GTM-
NKDMSK6" height="0" width="0"
            style="display:none;visibility:hidden"></iframe>
    </noscript>
    <!-- End Google Tag Manager (noscript) -->
    @include('partials.nav')

    <style>
        .scrolling-wrapper-flexbox {
            display: flex;
            flex-wrap: nowrap;
            overflow-x: auto;
            -webkit-overflow-scrolling: touch;

            .card {
                flex: 0 0 auto;
            }
        }

    </style>

    <div class="wrapper">
        @include('partials.avatarmodal')
        <div class="page-header page-header-small">
            <div class="page-header-image" data-parallax="true"
                style="background-image:
url('/assets/img/mandalorian.jpg'); transform: translate3d(0px, 0px,
0px);">
            </div>
        </div>
        <div class="section bg-dark">
            <div class="container ">
                <div class="row">
                    <div class="col-md-2" >
                        <div class="carousel slide" >
                            <a class="btn btn-link">

```

```

        
    </a>

    </div>
    <div><p></p></div>
</div>
<div class="col-md-10">
    <div class="card" data-background-
color="blue">
        <div class="card-body">
            <h6 class="category-social text-
center">
                <i class="fa fa-fire"></i> Profile
            </h6>
            <hr style="background-color: white">
            <br>
            <div class="row">
                <div class="col-md-4">
                    <h6 class="category-social">
                        <i class="now-ui-icons
users_single-02"></i> Username: <strong
                                style="display:
inline;"><i>{{ $user->name }}</i></strong>
                        </h6>
                    </div>
                    <div class="col-md-4">
                        <h6 class="category-social">
                            <i class="now-ui-icons ui-
1_email-85"></i> Email: <strong
                                style="display:
inline;"><i>{{ $user->email }}</i></strong>
                            </h6>
                        </div>
                        <div class="col-md-4">
                            <h6 class="category-social">
                                <i class="now-ui-icons
users_single-02"></i> Custom Title: <strong
                                    style="display:
inline;"><i>{{isset($user->custom_title) ? $user->custom_title :
'Muggle'}}</i></strong>
                                </h6>
                            </div>
                        </div>
                        <hr style="background-color: white">
                        <br>
                        <p class="card-description text-
center">
                            <strong><i>"{{ $user-
>phrase[0] }}"</i></strong>
                        </p>
                    </div>
                </div>
            </div>
        </div>
    </div>
    <div class="row">
        <div class="col-md-1"></div>
        <div class="col-md-3">

```



```

        <div class="card" data-background-color="blue"
            style="padding-top: -3%; background-
color: royalblue">
            <div class="card-body">
                <h5 class="category-social text-
center">
                    <i class="now-ui-icons
business_chart-bar-32"></i> TV Shows Stats
                </h5>
                <hr style="background-color: white">
                <div class="row text-center">
                    <div class="col-md-12">
                        <h4 class="category-social">
                            <i class="now-ui-icons
media-2_sound-wave"></i> Watched: <strong
                                style="display:
inline;"><i>{{ $user->userItemsWatched['showswatched'] }}</i></strong>
                            </h4>
                        </div>
                    </div>
                    <div class="row text-center">
                        <div class="col-md-12">
                            <h4 class="category-social">
                                <i class="now-ui-icons
education_agenda-bookmark"></i> Watchlist: <strong
                                    style="display:
inline;"><i>{{ $user->userItemsWatched['showswatchlist'] }}</i></strong>
                                </h4>
                            </div>
                        </div>
                    </div>
                </div>
            </div>

        <div class="col-md-3">
            <div class="card" data-background-color="blue"
                style="padding-top: -3%; background-
color: #0062cc">
                <div class="card-body">
                    <h5 class="category-social text-
center">
                        <i class="now-ui-icons
business_chart-bar-32"></i> Movies Stats
                    </h5>
                    <hr style="background-color: white">
                    <div class="row text-center">
                        <div class="col-md-12">
                            <h4 class="category-social">
                                <i class="now-ui-icons
media-2_sound-wave"></i> Watched: <strong
                                    style="display:
inline;"><i>{{ $user->userItemsWatched['moviesswatched'] }}</i></strong>
                                </h4>
                            </div>
                        </div>
                    </div>
                    <div class="row text-center">
                        <div class="col-md-12">
                            <h4 class="category-social">

```

```

<i class="now-ui-icons
education_agenda-bookmark"></i> Watchlist: <strong
style="display:
inline;"><i>{{ $user-
>userItemsWatched['moviesswatchlist'] }}</i></strong>
</h4>
</div>
</div>
</div>
</div>
</div>
<div class="col-md-4">
<div class="card" data-background-color="blue"
style="padding-top: -3%; background-
color: #3b5998">
<div class="card-body">
<h5 class="category-social text-
center">
<i class="now-ui-icons
sport_trophy"></i> Ranking
</h5>
<hr style="background-color: white">
<div class="row text-center">
<div class="col-md-12">
<h4 class="category-social">
<i class="now-ui-icons
media-1_button-play"></i> Movies: <strong
style="display:
inline;"><i>{{isset($user->topusersMovie) ? $user->topusersMovie + 1 :
$user->totalusers}} of {{ $user->totalusers}}</i>
Users</strong>
</h4>
</div>
</div>
</div>
<div class="row text-center">
<div class="col-md-12">
<h4 class="category-social">
<i class="now-ui-icons
tech_tv"></i> TV Shows: <strong
style="display:
inline;"><i>{{isset($user->topusersTv) ? $user->topusersTv + 1 :
$user->totalusers}} of {{ $user->totalusers}}</i>
Users</strong>
</h4>
</div>
</div>
</div>
<div class="row text-center">
<div class="col-md-12">
<h4 class="category-social">
<i class="now-ui-icons
objects_spaceship"></i> General: <strong
style="display:
inline;"><i>{{isset($user->topusers) ? $user->topusers + 1 : $user-
>totalusers}} of {{ $user->totalusers}}</i>
Users</strong>
</h4>
</div>
</div>

```

```

        </div>
    </div>
</div>

</div>
<br>
<br>
<hr style="background-color: white">
<div class="row">
    <div class="col-md-12">
        <h6 class="text-white">TV Shows watchlist</h6>
    </div>
</div>
<div class="row">
    <div class="scrolling-wrapper-flexbox">
        @forelse($items as $item)

                                <div class="col-md-2">
                                <div class="card card-product
card-plain">
                                    <div class="card-image">
                                        <a href="/item/{{ $item->
>tmdb_id }}/{{ $item->media_type }}">
                                            
                                            </a>
                                        </div>
                                    </div>
                                </div>
                                @endif
                                @empty
                                <p class="text-white">
                                    You haven't seen anything yet.
                                </p>
                                Please, start your Journey!</p>
                                @endforelse
                            </div>
    </div>
<br>
<div class="row">
    <div class="col-md-12">
        <h6 class="text-white">TV Shows watched</h6>
    </div>
</div>
<div class="row">
    <div class="scrolling-wrapper-flexbox">
        @forelse($items as $item)

                                <div class="col-md-2">
                                <div class="card card-product
card-plain">
                                    <div class="card-image">

```

```

                                <a href="/item/{{ $item-
>tmdb_id }}/{{ $item->media_type }}">
                                
                                </a>
                                </div>
                                </div>
                                </div>
                                @endif
                                @empty
                                <p class="text-white">
                                    You haven't seen anything yet. Please,
start your Journey!</p>
                                @endforelse
                                </div>
                                </div>
                                <br>
                                <div class="row">
                                    <div class="col-md-12">
                                        <h6 class="text-white">Movies Watchlist</h6>
                                    </div>
                                </div>
                                <div class="row">
                                    <div class="scrolling-wrapper-flexbox">
                                        @forelse($items as $item)

                                @if($item->media_type == 'movie' && $item-
>watchlist == 1)
                                    <div class="col-md-2">
                                        <div class="card card-product
card-plain">
                                            <div class="card-image">
                                                <a href="/item/{{ $item-
>tmdb_id }}/{{ $item->media_type }}">
                                                    
                                                </a>
                                            </div>
                                        </div>
                                        </div>
                                @endif
                                @empty
                                <p class="text-white">
                                    You haven't seen anything yet. Please,
start your Journey!</p>
                                @endforelse
                                </div>
                                </div>
                                <br>
                                <div class="row">
                                    <div class="col-md-12">
                                        <h6 class="text-white">Movies watched</h6>
                                    </div>
                                </div>
                                <div class="row">
                                    <div class="scrolling-wrapper-flexbox">
                                        @forelse($items as $item)

```

```

@if($item->media_type == 'movie' && $item-
>watched == 1)
    <div class="col-md-2">
        <div class="card card-product
card-plain">
            <div class="card-image">
                <a href="/item/{{ $item-
>tmdb_id }}/{{ $item->media_type }}">
                    
                </a>
            </div>
        </div>
    </div>
@endif
@empty
<p class="text-white">
    You haven't seen anything yet. Please,
start your Journey!</p>
@endforelse
</div>
</div>
<br><br><br>
<div class="row">
    <a class="btn btn-link" href="/comments/show">
        <h6 class="text-white">Latest Comments</h6>
    </a>
</div>
<div class="row">
    @forelse($user->comments as $comment)
        <div class="col-md-12">
            <p class="text-white font-
italic">{!!$comment->body!!}</p>
            <hr style="background-color: white">
        </div>
    @empty
        <p class="text-white">
            You haven't made any comments yet</p>
    @endforelse
</div>
</div>
</d>

<footer class="footer" data-background-color="black">
    <div class="container">
        <a class="footer-brand" href="/">Showtrakt</a>
        <p class="pull-center small">This product uses the TMDb API
but is not endorsed or certified by TMDb</p>
        <ul class="social-buttons pull-right">
            <li>
                <a href="https://twitter.com/CreativeTim"
target="_blank" class="btn btn-icon btn-link btn-neutral">
                    <i class="fab fa-twitter"></i>
                </a>
            </li>

```

```

        <li>
            <a href="https://www.facebook.com/CreativeTim"
target="_blank"
            class="btn btn-icon btn-neutral btn-link">
                <i class="fab fa-facebook-square"></i>
            </a>
        </li>
        <li>
            <a
href="https://www.instagram.com/CreativeTimOfficial" target="_blank"
            class="btn btn-icon btn-neutral btn-link">
                <i class="fab fa-instagram"></i>
            </a>
        </li>
    </ul>
</div>
</footer>

<!-- Core JS Files -->
<script src="/assets/js/core/jquery.min.js"
type="text/javascript"></script>
<script src="/assets/js/core/popper.min.js"
type="text/javascript"></script>
<script src="/assets/js/core/bootstrap.min.js"
type="text/javascript"></script>
<!-- Plugin for Switches, full documentation here:
http://www.jque.re/plugins/version3/bootstrap.switch/ -->
<script src="/assets/js/plugins/bootstrap-switch.js"></script>
<!-- Plugin for the Sliders, full documentation here:
http://refreshless.com/nouislider/ -->
<script src="/assets/js/plugins/nouislider.min.js"
type="text/javascript"></script>
<!-- Plugin for the DatePicker, full documentation here:
https://github.com/uxsolutions/bootstrap-datepicker -->
<script src="/assets/js/plugins/moment.min.js"></script>
<!-- Plugin for Tags, full documentation here:
https://github.com/bootstrap-tagsinput/bootstrap-tagsinputs -->
<script src="/assets/js/plugins/bootstrap-tagsinput.js"></script>
<!-- Plugin for Select, full documentation here:
http://silviomoreto.github.io/bootstrap-select -->
<script src="/assets/js/plugins/bootstrap-selectpicker.js"
type="text/javascript"></script>
<!-- Plugin for the DateTimePicker, full documentation here:
https://eonasdan.github.io/bootstrap-datetimepicker/ -->
<script src="/assets/js/plugins/bootstrap-datetimepicker.js"
type="text/javascript"></script>
<!-- Control Center for Now Ui Kit: parallax effects, scripts for the
example pages etc -->
<script src="/assets/js/now-ui-kit.js?v=1.2.2"
type="text/javascript"></script>
</body>

</html>

```

## 6.9 CookieConsent Views

### 6.9.1 dialogContents.blade

```

<div class="js-cookie-consent cookie-consent text-center text-white"
style="background-color: rgb(63, 154, 229, 0.9); position: fixed;
width:100%;
height:auto;
bottom:0px;">

  <div class="row">
    <div class="col-md-1"></div>
    <div class="col-md-7" style="padding-top: 1%">
      <span class="cookie-consent__message">
        <p><strong>
          On our website, we use cookies to collect data about
the user to improve day by day.
          Therefore, for the proper performance of the website,
please allow cookies.
        </strong></p>
      </span>

    </div>
    <div class="col-md-4" style="padding-top: 1%">
      <button class="js-cookie-consent-agree cookie-
consent__agree btn btn-info">
        {{ trans('cookieConsent::texts.agree') }}
      </button>
    </div>
  </div>
</div>

```

### 6.9.2 index.blade

```

@if($cookieConsentConfig['enabled'] && ! $alreadyConsentedWithCookies)

  @include('cookieConsent::dialogContents')

  <script>

    window.laravelCookieConsent = (function () {

      const COOKIE_VALUE = 1;
      const COOKIE_DOMAIN = '{{ config('session.domain') ??
request()->getHost() }}';

      function consentWithCookies() {
        setCookie('{{ $cookieConsentConfig['cookie_name'] }}',
COOKIE_VALUE, {{ $cookieConsentConfig['cookie_lifetime'] }});
        hideCookieDialog();
      }

      function cookieExists(name) {
        return (document.cookie.split('; ').indexOf(name + '='
+ COOKIE_VALUE) !== -1);
      }

      function hideCookieDialog() {
        const dialogs = document.getElementsByClassName('js-
cookie-consent');

```

```

        for (let i = 0; i < dialogs.length; ++i) {
            dialogs[i].style.display = 'none';
        }
    }

    function setCookie(name, value, expirationInDays) {
        const date = new Date();
        date.setTime(date.getTime() + (expirationInDays * 24 *
60 * 60 * 1000));
        document.cookie = name + '=' + value
            + ';expires=' + date.toUTCString()
            + ';domain=' + COOKIE_DOMAIN
            + ';path=/{{ config('session.secure') ? ';secure'
: null }}';
    }

    if (cookieExists('{{ $cookieConsentConfig['cookie_name']
}}')) {
        hideCookieDialog();
    }

    const buttons = document.getElementsByClassName('js-
cookie-consent-agree');

    for (let i = 0; i < buttons.length; ++i) {
        buttons[i].addEventListener('click',
consentWithCookies);
    }

    return {
        consentWithCookies: consentWithCookies,
        hideCookieDialog: hideCookieDialog
    };
    })();
</script>

@endif

```

## 6.10 home.blade

```

@extends('layouts.layout')

@section('content')

    <div class="container">
        <h4 class="text-center text-white">Popular Movies</h4>
        <div class="row">
            <div class="col-md-12">
                <div class="row">
                    @foreach($movies as $movie)
                        @if($movie['media_type'] == 'movie')
                            <div class="col-lg-3 col-md-6" >
                                <div class="card card-product card-
plain">
                                    <div class="card-image">
                                        <a href="#">

```





```
<?php

namespace App\Notifications;

use Illuminate\Bus\Queueable;
use Illuminate\Notifications\Notification;
use Illuminate\Contracts\Queue\ShouldQueue;
use Illuminate\Notifications\Messages\MailMessage;

class InviteNotification extends Notification
{
    use Queueable;
    protected $notification_url;

    /**
     * Create a new notification_url instance.
     *
     * @param $notification_url
     */
    public function __construct($notification_url)
    {
        $this->notification_url = $notification_url;
    }

    /**
     * Get the notification's delivery channels.
     *
     * @param mixed $notifiable
     * @return array
     */
    public function via($notifiable)
    {
        return ['mail'];
    }

    /**
     * Get the mail representation of the notification.
     *
     * @param mixed $notifiable
     * @return \Illuminate\Notifications\Messages\MailMessage
     */
    public function toMail($notifiable)
    {
        return (new MailMessage)
            ->greeting('Hi There!')
            ->line('This is to invite you to join our platform ' .
config('app.name'))
            ->action('Click to start!',$this->notification_url)
            ->line('Thank you for using our application!');
    }

    /**
     * Get the array representation of the notification.
     *
     * @param mixed $notifiable
     * @return array
     */
    public function toArray($notifiable)
    {
        return [

```

```

        //
    ];
}
}

```

## 7.2 ShowtraktStats

Con el paquete que aparece en el *Readme* del proyecto, se nos crea un nuevo canal por el que enviar la notificación hacia telegram. Luego necesitamos crear el método *ToTelegram* y rellenarlo como está mas abajo, indicando el ID del canal al que el bot escribirá. Y el ID del bot de telegram a utilizar, está en el *.env*

Esta notificación se ejecutará cada vez que se registre un usuario, como hemos visto mas arriba en el RegisterController

```

<?php

namespace App\Notifications;

use Illuminate\Bus\Queueable;
use Illuminate\Notifications\Notification;
use Illuminate\Contracts\Queue\ShouldQueue;
use Illuminate\Notifications\Messages\MailMessage;
use NotificationChannels\Telegram\TelegramChannel;
use NotificationChannels\Telegram\TelegramFile;
use NotificationChannels\Telegram\TelegramMessage;

class ShowtraktStats extends Notification implements ShouldQueue
{
    use Queueable;

    /**
     * Create a new notification instance.
     *
     * @return void
     */
    public function __construct()
    {
        //
    }

    /**
     * Get the notification's delivery channels.
     *
     * @param mixed $notifiable
     * @return array
     */
    public function via($notifiable)
    {
        return [TelegramChannel::class];
    }

    /**
     * Get the mail representation of the notification.
     *
     * @param mixed $notifiable
     * @return \Illuminate\Notifications\Messages\MailMessage
     */
}

```

```

    */
    public function toTelegram($notifiable)
    {
        return TelegramMessage::create()
            // Optional recipient user id.
            ->to('-1001157340449')
            // Markdown supported.
            ->content("Welcome to our new User:\n\n*Name:* " .
                $notifiable->name . "\n*Email:* " . $notifiable->email . "\n*Custom
                Title:* " . $notifiable->custom_title);
    }

    /**
     * Get the array representation of the notification.
     *
     * @param mixed $notifiable
     * @return array
     */
    public function toArray($notifiable)
    {
        return [
            //
        ];
    }
}

```

### 7.3 TotalStats

Esta notificación funciona igual que la anterior, indicándole a qué canal lo va a enviar el Bot a través de su ID.

Se ha creado un comando específico *artesan* (como se indica en siguientes apartados), para poder ejecutarlo cuando queramos desde consola y, además, se ha añadido al kernel del programa para que se ejecute dos veces al día.

```

<?php

namespace App\Notifications;

use Illuminate\Bus\Queueable;
use Illuminate\Notifications\Notification;
use Illuminate\Contracts\Queue\ShouldQueue;
use Illuminate\Notifications\Messages\MailMessage;
use NotificationChannels\Telegram\TelegramChannel;
use NotificationChannels\Telegram\TelegramMessage;

class TotalStats extends Notification
{
    use Queueable;

    /**
     * Create a new notification instance.
     *
     * @return void
     */
    public function __construct()
    {
        //
    }
}

```

```

    }

    /**
     * Get the notification's delivery channels.
     *
     * @param mixed $notifiable
     * @return array
     */
    public function via($notifiable)
    {
        return [TelegramChannel::class];
    }

    /**
     * Get the mail representation of the notification.
     *
     * @param mixed $notifiable
     * @return \Illuminate\Notifications\Messages\MailMessage
     */
    public function toTelegram($notifiable)
    {
        //dd($notifiable->stats);
        return TelegramMessage::create()
            // Optional recipient user id.
            ->to('-1001157340449')
            // Markdown supported.
            ->content("*Showtrakt Stats*\n"
                . "-----"
                . "\n*Total of Users:* " . $notifiable->stats['totalusers'] .
                "\n*Total TV Shows:* " . $notifiable->stats['totalitems']['showswatched'] .
                "\n*Total Movies:* " . $notifiable->stats['totalitems']['moviesswatched'] .
                "\n*Total Comments:* " . $notifiable->stats['totalcomments'] .
                "\n*Top Movies:* \n" . "    -" . $notifiable->stats['topmovies'][0]->title .
                "\n" . "    -" . $notifiable->stats['topmovies'][1]->title .
                "\n" . "    -" . $notifiable->stats['topmovies'][2]->title .
                "\n*Top TV Shows:* \n" . "    -" . $notifiable->stats['topshows'][0]->title .
                "\n" . "    -" . $notifiable->stats['topshows'][1]->title .
                "\n" . "    -" . $notifiable->stats['topshows'][2]->title);
    }

    /**
     * Get the array representation of the notification.
     *
     * @param mixed $notifiable
     * @return array
     */
    public function toArray($notifiable)
    {
        return [
            //
        ];
    }

```

```
    }
}
```

## 8. Commands

### 8.1 TotalStats

Se ha creado un comando, que se puede utilizar con *php artisan showtrakt:stats*, el comando saca las estadísticas que queremos que envíe a telegram y se las pasa a la notificación TotalStats (que se ha desarrollado arriba). Para que se ejecute dos veces al día se ha añadido este comando al kernel (siguiente apartado).

```
<?php

namespace App\Console\Commands;

use App\Comment;
use App\Item;
use App\User;
use Illuminate\Console\Command;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Notification;

class TotalStats extends Command
{
    /**
     * The name and signature of the console command.
     *
     * @var string
     */
    protected $signature = 'showtrakt:stats';

    /**
     * The console command description.
     *
     * @var string
     */
    protected $description = 'Send stats of all activity to Telegram
Channel, twice a day';

    /**
     * Create a new command instance.
     *
     * @return void
     */
    public function __construct()
    {
        parent::__construct();
    }

    /**
     * Execute the console command.
     *
     * @return mixed
     */
    public function handle()
```

```

    {
        $user= new User();
        $totalusers=User::count();
        $totalitems = Item::TotalItems();
        $totalcomments=Comment::count();

        $topmovies= DB::select("SELECT title FROM items WHERE
media_type='movie' GROUP BY title ORDER BY count(*) DESC LIMIT 3");
        $toptvshows= DB::select("SELECT title FROM items WHERE
media_type='tv' GROUP BY title ORDER BY count(*) DESC LIMIT 3");

        $stats= [
            'totalusers' => $totalusers,
            'totalitems' => $totalitems,
            'totalcomments' => $totalcomments,
            'topmovies' => $topmovies,
            'topshows' => $toptvshows,
        ];
        $user->stats = $stats;

        $user->notify(new \App\Notifications\TotalStats($stats));

    }
}

```

## 9. Kernel

Como se puede ver, en el método *Schedule* se llama al comando de *artisan* dos veces al día (twiceDaily).

Y para que esto tenga efecto, en el crontab de nuestro servidor, donde está desplegada la web, hay que meter la siguiente línea de código:

```
* * * * * cd /path-to-your-project && php artisan schedule:run >>
/dev/null 2>&1
```

```

<?php

namespace App\Console;

use Illuminate\Console\Scheduling\Schedule;
use Illuminate\Foundation\Console\Kernel as ConsoleKernel;

class Kernel extends ConsoleKernel
{
    /**
     * The Artisan commands provided by your application.
     *
     * @var array
     */
    protected $commands = [
        'App\Console\Commands\TotalStats',
    ];
}

```

```

/**
 * Define the application's command schedule.
 *
 * @param \Illuminate\Console\Scheduling\Schedule $schedule
 * @return void
 */
protected function schedule(Schedule $schedule)
{
    $schedule->command('showtrakt:stats')->twiceDaily(14,22);
}

/**
 * Register the commands for the application.
 *
 * @return void
 */
protected function commands()
{
    $this->load(__DIR__.'/Commands');

    require base_path('routes/console.php');
}
}

```

## 10. Requests

### 10.1 PostFormRequest

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class PostFormRequest extends FormRequest
{
    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {
        return [
            'title' => 'required|unique:posts|max:255',
            'title' => array('Regex:/^[A-Za-z0-9 ]+$/'),
            'body' => 'required',
            'image_url' => 'required'
        ];
    }
}

```



