

---

# Model Evaluation

— Boston University CS 506 - Lance Galletti —

*evaluate how our model is!*

---

# Confusion Matrix

we prefer TP + TN

	Predicted Class		
Actual Class		Class = Yes	Class = No
	Class = Yes	a (TP) <i>prefer</i>	b (FN) <i>not prefer</i>
	Class = No	c (FP) <i>not prefer</i>	d (TN) <i>prefer.</i>

$$\text{Accuracy} = (a + d) / (a + b + c + d)$$

# Accuracy can be misleading

Binary classification problem where:

Number of Class 0 examples: 9990

Number of Class 1 examples: 10

A model that predicts everything to be class 0 will have an accuracy of 99.9%

not always true

# Cost Matrix

	Predicted Class		
		Class = Yes	Class = No
	Class = Yes	$C(\text{Yes} \text{Yes})$	$C(\text{No} \text{Yes})$
	Class = No	$C(\text{Yes} \text{No})$	$C(\text{No} \text{No})$

# Cost of Classification

COST	Predicted Class		
		Yes	No
Actual Class	Yes	-1	100
	No	1	0

$-250 + 45 =$

$+ 5 + 0$

$1250$

$\sim 4255$

by my just multiply corresponding num here

Model 1	Predicted Class		
Actual Class		Yes	No
	Yes	150	40
	No	60	250

Accuracy = 80%  
Cost = 3910

Model 2	Predicted Class		
Actual Class		Yes	No
	Yes	250	45
	No	5	200

Accuracy = 90%  
Cost = 4255

# FORM

# Other metrics

COST	Predicted Class		
		Yes	No
Actual Class	Yes	a	b
	No	c	d

- Precision =  $a / (a + c)$
- Recall =  $a / (a + b)$
- F-measure =  $2RP / (R + P)$


# Methods of Estimation

**Goal:** get a reliable estimate of the performance of the model on unseen data



# Methods of Estimation

- Holdout:
  - Ex: reserve  $\frac{1}{4}$  of the dataset for testing and use  $\frac{3}{4}$  for training




# Methods of Estimation

- Holdout:
  - Ex: reserve  $\frac{1}{4}$  of the dataset for testing and use  $\frac{3}{4}$  for training
- Cross Validation:
  - Partition into K disjoint subsets
  - K-fold: train on K-1 partitions, test on the remaining on
  - K = n : leave-one-out



# Validation Set

For tuning parameters



---

together they're better than  
individually

# Ensemble Methods

— Boston University CS 506 - Lance Galletti —

---

# The idea

Suppose you have trained 17 different classifiers on a dataset.

# The idea

Suppose you have trained 17 different classifiers on a dataset.

- Every classifier has error rate  $\epsilon = .20$
- Assume all classifiers are independent

# The idea

Suppose you have trained 17 different classifiers on a dataset.

- Every classifier has error rate  $\epsilon = .20$
- Assume all classifiers are independent

In order to classify a new record we poll all 17 classifiers and take the class that the majority agrees on.

What is the probability that this ensemble classifier makes a wrong prediction?

# The idea

The majority needs to make a mistake (i.e. at least 9 out of 17 make mistakes)

$$P(X \geq 9) = \sum_{k=9}^{17} \binom{17}{k} (.2)^k (1 - .2)^{17-k} = 0.002581463$$

\* from error rate of  
20 to like 0.25814  
percent!



# How to generate independent classifiers?

By generating samples of the data to train on

- Bagging → *replacement*
- Boosting → *.*

# Bagging

Original data	1	2	3	4	5	6	7	8	9	10
Bootstrap sample 1	7	8	10	10	3	6	1	1	4	5
Bootstrap sample 2	6	2	7	9	3	5	7	7	1	8
Bootstrap sample 3	2	5	6	1	4	1	8	9	4	3

Build a classifier on each bootstrapped sample

# Boosting

at each step adjust sample + weight  
so they explored more next time

An adaptive sampling process to change the sampling distribution based on difficult-to-classify examples.

Start with all samples having equal probability of being selected. Next boosting round, increase the weights of those samples that were misclassified, decrease the weights of those samples that were correctly classified.

depend on how  
well it does, modify the weight.

# Boosting

Original data	1	2	3	4	5	6	7	8	9	10
Bootstrap sample 1	7	8	10	10	3	6	1	1	4	5
Bootstrap sample 2	6	4	7	9	3	5	7	4	1	8
Bootstrap sample 3	2	5	4	1	4	1	4	4	2	3

Here, sample 4 is hard to classify.

# Boosting

*have weight-*

Original data	1	2	3	4	5	6	7	8	9	10
Bootstrap sample 1	7	8	10	10	3	6	1	1	4	5
Bootstrap sample 2	6	4	7	9	3	5	7	4	1	8
Bootstrap sample 3	2	5	4	1	4	1	4	4	2	3

Classifiers trained on each sample and are given a weight that is a function of their error rate.

# Boosting

bagging

Example: 5 classifiers

, independent?

$C_1$  predicts 1

$C_2$  predicts 0

$C_3$  predicts 0

$C_4$  predicts 1

$C_5$  predicts 0

# Boosting

Example: 5 classifiers

subsets w/ weight.

$C_1$  predicts 1 has a weight of .25

$C_2$  predicts 0 has a weight of .1

$C_3$  predicts 0 has a weight of .5

$C_4$  predicts 1 has a weight of .05

$C_5$  predicts 0 has a weight of .1