



PCB MOUNTING LAYOUT

# SPECIFICATION

- (1) ITEM NO. :
- (2) HOUSING MATERIAL: NYLON66+30%GF UL94V0 BLACK COLOR
- (3) CONTACT MATERIAL: PHOSPHOR BRONZE 0.25MM THICK NICKEL PLATED
- (4) CURRENT RATING : 0.5A DC
- (5) VOLTAGE RATING : 12V DC
- (6) CONTACT RESISTANCE:30m Ω MAX
- (7) INSULATION RESISTANCE: 100M Ω MIN
- (8) OPERATING TEMPERATURE RANGE: -25° TO +85°
- (9) HUMIDITY: 40℃ AND 90~95% RH FOR 96 HOURS
- (10) RoHS COMPLIANT

3						
2						
1						
NO.	MODIFICATION	DATE	NAME	COIN CELL HOLDER		
			SCALE	2:1	APPD	
General Tolerances			UNIT	MM	CHKD	
0 ~ >3	± 0.10	30 ~ >120	± 0.30	MAT'L	SEE NOTES	DWN
3 ~ >6	± 0.10	120 ~ >400	± 0.50	DATE	AUG. 12. 2017	DR NO
6 ~ >30	± 0.20	Angle: ± 3°	CH74-0817			

