

Design Principles for Modular Programs

Lect. PhD. Arthur Molnar

Babes-Bolyai University

arthur@cs.ubbcluj.ro

Overview

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

1 Design principles for modular programs

- Design principles
- Layered Architecture
- A first example

Organizing source code

Lecture 06

Lect. PhD.
Arthur Molnar

Design principles for modular programs

Design principles
Layered
Architecture
A first example

What does it mean to organize source code?

- Determine what code goes where ... d'uh!
- We split code into functions, classes and modules
- The purpose of this section is to discuss a few principles that help us do it correctly

Modules

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

Discussion

What do we mean by **organizing the code correctly**?

Organizing source code

Lecture 06

Lect. PhD.
Arthur Molnar

Design principles for modular programs

Design principles
Layered
Architecture
A first example

We use a few key design principles that help determine how to organize source code

- Single responsibility principle
- Separation of concerns
- Dependency
- Coupling and cohesion

Single responsibility principle

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

- Each function should be responsible for one thing
- Each class should represent one entity
- Each module should address one aspect of the application

Single responsibility principle - functions

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

Let's take the function below as example

```
#Function with multiple responsibilities
#implement user interaction (read/print)
#implement a computation (filter)
def filterScore():
    st = input("Start score:")
    end = input("End score:")
    for c in l:
        if c[1]>st and c[1]<end:
            print c
```

Single responsibility principle - functions

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

Why could the **filterScore()** function change?

- The program's input format or channel changes
 - e.g. command/menu based UI as in Lab2-4
 - How about GUI/web/mobile/voice-based UI?
- The filter has to be updated

NB!

The **filterScore()** function has 2 responsibilities

Single responsibility principle - modules

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

How did we characterize a module?

[modules] ... each of which accomplishes one aspect within the program and contains everything necessary to accomplish this.

Single responsibility principle - modules

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

Discussion

Is there any similarity between how we design a function and a module?

Single responsibility principle

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

Multiple responsibilities are...

- Harder to understand and use
- Difficult/impossible to test
- Difficult/impossible to reuse
- Difficult to maintain and evolve

Separation of concerns

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

- Separate the program into distinct sections
- Each section addresses a particular concern
- **Concern** - information that affects the code of a computer program (e.g. computer hardware that runs the program, requirements, function and module names)
- Correctly implemented, leads to a program that is easy to test and from which parts can be reused

Separation of concerns - example

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

Let's take the function below as example (**again!**)

```
#Function with multiple responsibilities
#implement user interaction (read/print)
#implement a computation (filter)
def filterScore():
    st = input("Start score:")
    end = input("End score:")
    for c in l:
        if c[1]>st and c[1]<end:
            print c
```

Separation of concerns - the UI

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

The refactored function below only addresses the UI, functionalities are delegated to the **filterScore()** function

```
def filterScoreUI () :  
    st = input("Start sc:")  
    end = input("End sc:")  
    rez = filtrareScore(1, st, end)  
    for e in rez:  
        print e
```

Separation of concerns - the test

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

The **filterScore()** function can be tested using a testing function such as the one below

```
def testScore() :  
    l = [[ "Ana", 100]]  
    assert filterScore(l,10,30)==[]  
    assert filterScore(l,1,30)==l  
    l = [[ "Ana", 100], [ "Ion", 40], [ "P", 60]]  
    assert filterScore(l,3,50)==[[ "Ion", 40]]
```

Separation of concerns - the operation

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

The **filterScore()** function only has one responsibility!

```
def filterScore(l,st, end):  
    """  
    filter participants  
    l - list of participants  
    st, end - integers -scores  
    return list of participants  
        filtered by st end score  
    """  
    rez = []  
    for p in l:  
        if p[1]>st and p[1]<end:  
            rez.append(p)  
    return rez
```


Separation of concerns

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

NB!

These design principles are in many cases interwoven!

Dependency

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

What is a **dependency**?

- Function level - a function invokes another function
- Class level - a class method invokes a method of another class
- Module level - any function from one module invokes a function from another module

Example

Say we have functions **a**, **b**, **c** and **d**. **a** calls **b**, **b** calls **c** and **c** calls **d**.

What might happen if we change function **d** ?

Coupling

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

- **Coupling** - a measure of how strongly one element is connected to, has knowledge of, or relies on other elements
- More connections between one module and others, the harder to understand that module, the harder to re-use it in another situation, the harder to test it and isolate failures
- **Low coupling** - facilitates the development of programs that can handle change because they minimize the interdependency between functions/modules

Cohesion

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

- **Cohesion** - a measure of how strongly related and focused the responsibilities of an element are.
- A module may have:
 - **High Cohesion**: it is designed around a set of related functions
 - **Low Cohesion**: it is designed around a set of unrelated functions
- A cohesive module performs a single task within a software, requiring little interaction with code from other parts of a program.

Cohesion

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

- Modules with less tightly bound internal elements are more difficult to understand
- Higher cohesion is better

NB!

Cohesion is a more general concept than the single responsibility principle, but modules that follow the SRP tend to have high cohesion.

Cohesion

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles

Layered
Architecture

A first example

NB!

Simply put, a cohesive module should do just one thing - **now where have I heard that before... ?**

How to apply these design principles

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

- **Separate concerns** - divide the program into distinct sections, so that each addresses a separate concern
- Make sure the modules are **cohesive** and **loosely coupled**
- Make sure that each module, class have **one responsibility**, or that there is only one reason for change

Layered Architecture

We employ the layered architecture pattern keeping in mind the detailed design principles

Layered Architecture

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

Structure the application to:

- **Minimize module coupling** - modules don't know much about one another, makes future change easier
- **Maximize module cohesion** - each module consists of strongly inter-related code

Layered Architecture

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
**Layered
Architecture**
A first example

Layered Architecture - an architectural pattern that allows you to design flexible systems using components

- Each layer communicates only with the one immediately below
- Each layer has a well-defined interface used by the layer immediately above (hide implementation details)

Layered Architecture

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
**Layered
Architecture**
A first example

Common layers in an information system architecture

- **User interface, Presentation** - user interface related functions, classes, modules
- **Domain, Application Logic** - provide application functions determined by the use-cases
- **Infrastructure** - general, utility functions or modules
- **Application coordinator** - start and stop application, instantiate components

A first example - Lab2-4

Lecture 06

Lect. PhD.
Arthur Molnar

Design
principles for
modular
programs

Design principles
Layered
Architecture
A first example

Layered architecture in Lab2-4

- **User interface** - Functions related to the user interaction. Contains input and data validation, print operations. This is the only module where input/print operations are present.
- **Functions** - Contains the functions required to implement program features
- **Application coordinator** - Initialize the UI and start the application.