Checklists

Aircraft:

Aircraft specific identification

Aircraft make/model:

Aircraft Make and Model

Manufacturer:

Manufacturer Identification

Copyright:

Copyright Information

Generated by https://github.com/rdamazio/efis-editor/

Preflight

Flight Planning		
Pilot Currency	. . . . .	Checked
Aircraft Inspection & Performance	. . . . .	Checked
Flight Plan	. . . . .	Established
NWKRAFT	. . . . .	Checked
Airport Chart Supplement	. . . . .	Checked
Instrument Plates	. . . . .	Reviewed
Weight & Balance	. . . . .	Performed
IFR Flight Plan	. . . . .	Filed
Contingency Plan Email	. . . . .	If Required
Checklist SD Cards	. . . . .	If Required
Database SD Cards	. . . . .	If Required
Batteries	. . . . .	Charged

Aircraft Fluids		
Cover & Tail Diaper	. . . . .	Removed
Fuel Tank Sumps	. . . . .	Sampled
Fuel Tank Level	. . . . .	Checked
Fuel Vent Caps	. . . . .	Secured
Pilot Seat Drain	. . . . .	If Water Present
Engine Fuel Drain	. . . . .	Pulled
Oil Level	. . . . .	7 Nominal/8 for 3+ hours
Tire Pressures	. . . . .	31 Nose, 68 Main
Windshield	. . . . .	Cleaned

Cabin Check		
S.P.A.R.R.O.W	. . . . .	Supp, Placs,Airworthy, Reg, Radio, POH, WB
Sentry, Backup Radio, InReach	. . . . .	In Plane
Life Jackets	. . . . .	Ready
Landing Gear Lever	. . . . .	Down
Control Wheel Lock	. . . . .	Removed
Ignition Switch	. . . . .	Off
Avionics Backup	. . . . .	On
Avionics Power	. . . . .	If on Ground Power
Master Switch	. . . . .	On
Gear Light	. . . . .	Illuminated
Gear Horn	. . . . .	Test
Flaps Down	. . . . .	Fully Extended
Pitot Cover	. . . . .	Removed
Lights & Pitot Heat Switches	. . . . .	Turned On
G3X & G5	. . . . .	On
Fuel Quantity Indicators	. . . . .	Verified
Light Operation	. . . . .	Checked

Stall Horn	. . . . .	Tested
Pitot Heat	. . . . .	Tested
Light Switches	. . . . .	Reset
Master Switch	. . . . .	Off

Exterior Inspection

Empennage		
Tail Body	. . . . .	Inspected
Stabilator	. . . . .	Checked
Rudder	. . . . .	Checked
Right Wing		
Right Aileron & Flaps	. . . . .	Checked
Right Fuel Bay Vent Opening	. . . . .	Checked
Leading Edge & Tip	. . . . .	Checked
Right Main Tire	. . . . .	Checked
Right Static Port	. . . . .	Inspected
Nose		
Cowl Plugs	. . . . .	Removed
Alternator Belt	. . . . .	Checked
Propeller & Spinner	. . . . .	Checked
Pitch Control	. . . . .	Checked

Landing Lights	. . . . .	Checked
Air Filter	. . . . .	Checked
Exhaust Pipe	. . . . .	Secured
Nose Wheel Strut	. . . . .	Checked
Nose Wheel Tire	. . . . .	Checked
Nose Wheel Doors	. . . . .	Checked
Left Static Port	. . . . .	Checked
Left Wing		
Leading Edge & Tip	. . . . .	Checked
Pitot Tube & Cover	. . . . .	Checked
Stall Warning	. . . . .	Checked
Left Fuel Bay Vent Opening	. . . . .	Checked
Left Aileron & Flaps	. . . . .	Checked
Left Main Tire	. . . . .	Checked

Before Starting Engine		
Tug Bolts	. . . . .	Detatched
Walk Around	. . . . .	Completed
Fuel Sump	. . . . .	If Fueled
Chocks, Baggage Door, Tie Downs	. . . . .	Ready
Seat Belts, Air Flow, Fire, Egress/Emergency		
Traffic, Questions?		
Passenger Brief	. . . . .	Completed
Seat Rails, Doors, & Seat Belts	. . . . .	Checked
Fuel Selector Valve	. . . . .	Both
Avionics Master	. . . . .	Off
Circuit Breakers	. . . . .	Checked
Brakes	. . . . .	Test and Set
Cowl Flaps	. . . . .	Open
Landing Gear Lever	. . . . .	Down
Headset & Battery	. . . . .	On & Checked

Engine Start		
Mixture	. . . . .	Idle Cutoff
Propeller	. . . . .	High RPM
Avionics Backup	. . . . .	On
Master Switch	. . . . .	On
Voltage	. . . . .	12V
G3X Fuel Level	. . . . .	Expected
Prime (If Required)	. . . . .	Complete
Throttle	. . . . .	Open 1/4 Inch
Clear Prop & Start	. . . . .	Done
Throttle Setpoint	. . . . .	1000 RPM
Oil Pressure	. . . . .	Check
Mixture	. . . . .	Lean
Voltage	. . . . .	14V
Manifold Pressure	. . . . .	~12"

Post Engine Start

Clean Up & Avionics		
Flaps	. . . . .	Up
Avionics Master	. . . . .	On
GTN Database	. . . . .	Verified
GTN CDI Test	. . . . .	Complete
GTN & G3X Fuel Calc	. . . . .	Correct
Autopilot PFT	. . . . .	No Error
G3X FPL Source	. . . . .	External GPS
Starlink Power	. . . . .	On
FlightStream Devices	. . . . .	Connected
Clearance		
ATIS/AWOS	. . . . .	Received
G5 Baro Pressure	. . . . .	Set
G3X Baro Pressure	. . . . .	Verify
IFR Clearance	. . . . .	Recorded
GPS Flight Plan	. . . . .	Loaded
COM Radios	. . . . .	Set
NAV Radios	. . . . .	Set
Transponder	. . . . .	Checked

Taxi		
Day: Beacon		
Low Viz: Beacon, Nav, Land, Taxi		
Night: Beacon, Nav, Taxi		
Lights	. . . . .	Configured
Taxi Wind Correction	. . . . .	Applied
Taxi Clearance	. . . . .	Obtained
Brakes	. . . . .	Test
Instrument Checks		
HSI Heading	. . . . .	Aligned
Altimeter	. . . . .	Within 75ft
Attitude Indicator	. . . . .	Bank in Turns
Airspeed	. . . . .	0kts
Inclinometer	. . . . .	Trend in Turns
Slip/Skid	. . . . .	Slide Out in Turns
Vertical Speed	. . . . .	0fpm
Compass Card	. . . . .	Correct

Engine Runup		
Parking Brake	. . . . .	Set
Flight Controls	. . . . .	Free & Correct
Stabilizer and Rudder Trim	. . . . .	Takeoff Setting
Oil Temp	. . . . .	100F
Engine Check		
Mixture	. . . . .	Mostly Rich
Throttle	. . . . .	1800 RPM Or Full Power
Mixture	. . . . .	1350 EGT or Peak RPM
Magnetos	. . . . .	150 Drop, 50 Diff
Cylinder EGT	. . . . .	Consistent Rise & Drop
Drop-off may signal a fouled spark plug		
Propeller	. . . . .	High to Low
Engine Instruments	. . . . .	Checked
Idle Power	. . . . .	Checked

Power & Mixture	. . . . .	Restore Idle

Departure Preparation

Autopilot		
Autopilot Engage Test	. . . . .	Begin
Heading Bug	. . . . .	Set
Altitude Bug	. . . . .	Set
AP Mode Configuration	. . . . .	Set
Departure Configuration		
G3X Instruments	. . . . .	Checked
G5 Instruments	. . . . .	Checked
Alternate Static Source	. . . . .	Test
Density Altitude Lean	. . . . .	As Required
Flap Configuration	. . . . .	Set & Confirm 10deg
Loved Ones	. . . . .	Message
Pitot Heat	. . . . .	As Required
Brief: Runway, Departure, Failures, Abort	. . . . .	Complete

Return Instrument Approach	. . . . .	Brief
GoPro	. . . . .	As Required
Normal: Rotate 55, 75, Gear, Flaps, 82		
Perf: Rotate 50, 62, Clear, Gear, 70, Flaps		
Brief Wind & Special Takeoff	. . . . .	Complete
Ready for Takeoff		
Autopilot	. . . . .	Disconnected
Day: Beacon, Strobe		
Low Viz: Beacon Strobe, Land, Taxi		
Night: Beacon, Nav, Strobe, Land, Taxi		
Lights	. . . . .	Configured
Windows	. . . . .	Closed
Flap Position	. . . . .	Confirm
Clear Pattern	. . . . .	Completed
Mixture	. . . . .	Rich

Cruise

Enroute Climb		
Cowl Flaps	. . . . .	Open
Gas Tank Selector	. . . . .	Both
Flaps & Gear	. . . . .	Retracted
Mixture	. . . . .	Sea Lvl EGT (1250-1300F)
Power	. . . . .	Full Open & Tightened
Propeller	. . . . .	2500RPM above 5000ft
Delay power reduction until MP boost needed		
Autopilot	. . . . .	Above 800AGL
Cylinder Head Temps	. . . . .	~380F, <400F
Airspeed	. . . . .	90-100kts

Cruise		
Cowl Flaps	. . . . .	Closed
Gas Tank Fuel Selector	. . . . .	As Required
Mixture	. . . . .	Lean For EGT
Throttle 24/25 (fuel) - RPM 23/24 efficiency		
Power	. . . . .	As Desired
Pitot Heat	. . . . .	As Required
Day: Beacon, Strobe		
Low Viz: Beacon, Nav, Strobe		
Night: Beacon, Nav, Strobe		
Lights	. . . . .	Configured

VFR Approach		
Fuel Selector	. . . . .	Both
Mixture	. . . . .	Enrichen if MP drops, Keep CHT > 300
Approach Lighting	. . . . .	Set
Radio Frequencies	. . . . .	Set
Weather & NOTAMS	. . . . .	Received
Baro Setpoint	. . . . .	Adjusted
Airspaces & Clearance	. . . . .	Received
Top of Descent	. . . . .	Considered
Runway & Pattern Entry	. . . . .	Decided

IFR Approach		
Fuel Selector	. . . . .	Both
Mixture	. . . . .	Enrichen if MP drops, Keep CHT > 300
Approach Lighting	. . . . .	Set
Approach Plate Brief	. . . . .	Completed
Visual Descent Point	. . . . .	Known
Weather & NOTAMs	. . . . .	Complete
Baro & Minimums	. . . . .	Set
COM Frequencies	. . . . .	Configured
NAV Frequencies	. . . . .	Configured
Approach Loaded & Sequenced	. . . . .	Completed
Vertical Track Minimum Altitude	. . . . .	Set
Nav Station Morse	. . . . .	Identified
Autopilot Approach Mode	. . . . .	Annunciated
GPS Approach Mode	. . . . .	Annunciated

Landing

Clear Runway		
Cowl Flaps	. . . . .	Open
Mixture	. . . . .	Lean
Wing Flaps	. . . . .	Up
Transponder	. . . . .	Ground/Alt
Pitot Heat	. . . . .	Off
Day: Beacon		
Low Viz: Beacon, Nav, Land, Taxi		
Night: Beacon, Nav, Taxi		
Lights	. . . . .	Configured
Flight Plan	. . . . .	Closed

Shutdown		
Tach/Hobbs	. . . . .	Record
Cockpit GoPro	. . . . .	Stop
Avionics	. . . . .	Off
Mixture	. . . . .	Idle Cutoff
Ignition Switch	. . . . .	Off
Master Switch	. . . . .	Off
Avionics Backup	. . . . .	Off
Starlink Power	. . . . .	Off
Light Switches	. . . . .	Beacon Only

Post Flight Checks		
Chocks	. . . . .	Present
Parking Brake	. . . . .	Off
Tow Bar	. . . . .	Away
Tie Downs	. . . . .	Attached
Cabin Air	. . . . .	Closed
Avionics Switch	. . . . .	Off
Avionics Backup	. . . . .	Off
Master Switch	. . . . .	Off
Aux Pump	. . . . .	Off
Mags	. . . . .	Off
Control Lock	. . . . .	Installed
Lights	. . . . .	Beacon Only
Mixture	. . . . .	Cutoff
Cowl Flaps	. . . . .	Closed
Fuel Selector	. . . . .	As Desired
Cabin Heat	. . . . .	Off
Circuit Breakers	. . . . .	Not Popped
Flaps	. . . . .	Up
Windows	. . . . .	Closed

Batteries, Sentry, Radio, InReach	. . . . .	Removed
SD Cards	. . . . .	Removed
Tach & Hobbs	. . . . .	Recorded
Side Pockets & Glove Box	. . . . .	Emptied
Pitot Cover	. . . . .	Installed
Cowl Plugs	. . . . .	Installed
Tail Diaper	. . . . .	On
Airframe Cover	. . . . .	On
Doors	. . . . .	Locked
Walk Around	. . . . .	Completed

Abnormal

IFR Required Reporting	
Missed Approach	
True Airspeed 10kts, 5%	
Reaching Holding Fix	
VFR on Top - Altitude Change	
(Non-Radar) ETA changed 2min	
Leaving a holding fix	
(Non-Radar) Outer Marker	
(FAR) Unforcasted Weather	
(FAR) Safety of Flight	
Vacating an Altitude	
(Non-Radar) Final Approach Fix	
(FAR) Radio/Nav/Approach Equipment Failure	
(FAR/Non-Radar) Comp Reporting Point	
500fpm Climb Descent	
Aircraft ID	. . . . .
Position	. . . . .
Time	. . . . .
Altitude	. . . . .
Type of Flight Plan	. . . . .

ETA and Name Next Report Fix	. . . . .
Name of Next Point on Route	. . . . .
Remarks	. . . . .

Light Gun Ground		
Steady Green	. . . . .	Cleared for Takeoff
Flashing Green	. . . . .	Cleared for Taxi
Steady Red	. . . . .	STOP!
Flashing Red	. . . . .	Taxi Clear of Runway
Flashing White	. . . . .	Return to Start
Alternating Red/Green	. . . . .	Extreme Caution

Light Gun Air		
Steady Green	. . . . .	Cleared to Land
Flashing Green	. . . . .	Return for Landing
Steady Red	. . . . .	Give Way to Other Aircraft - Circle
Flashing Red	. . . . .	Airport Unsafe - Do Not Land
Alternating Red/Green	. . . . .	Exercise Extreme Caution

Loss of GPS		
G3X Reversionary	. . . . .	Test
Sentry	. . . . .	Test
Vectors or direct VOR	. . . . .	Ask
KTIW ILS 17 - OLM/SEA	. . . . .	
KHIO ILS 13R - BTG	. . . . .	

Emergency

Engine Out		
Best Glide	. . . . .	75 kts
Landing Site	. . . . .	Select
Radio Emergency	. . . . .	Complete
Transponder Emergency	. . . . .	Complete
InReach Emergency	. . . . .	Complete
If Time Permits Troubleshooting		
Fuel Quantity	. . . . .	Check
Fuel Shutoff	. . . . .	Check
Mixture	. . . . .	Check
Aux Fuel Pump	. . . . .	On
Fuel Flow Indication	. . . . .	Check
Ignition Switch	. . . . .	Check
Prepare For Landing		
Seats & Seat Belts	. . . . .	Adjust
Aux Fuel Pump	. . . . .	Off
Mixture	. . . . .	Cutoff
Fuel Shutoff Valve	. . . . .	Off
Approach	. . . . .	75kts

Flaps	. . . . .	Within Glide Distance
Gear	. . . . .	Hard Field - Glide Distance
Master Switch	. . . . .	Off
Cabin Doors	. . . . .	Unlatched

Ditching

Heavy Objects	. . . . .	Secure & Jettison
Life Jackets	. . . . .	Ready
Transmit Mayday	. . . . .	Radio & Transponder
High Winds/Heavy Seas	. . . . .	Into Wind
Heavy Swells/Light Winds	. . . . .	Parallel Swells
Gear	. . . . .	Up
Flaps	. . . . .	30
Power	. . . . .	300fpm 60kts
Doors	. . . . .	Unlatched

Face	. . . . .	Cushion Impact
Vent Windows	. . . . .	If Required

Lost Comms

Frequencies	. . . . .	Correct
Stuck Mic	. . . . .	Check
Cords	. . . . .	Check
Alternate Radio	. . . . .	Test
Backup Radio	. . . . .	Test
Squawk	. . . . .	7600
Route	. . . . .	Clearace, Vector, Expected, Filed
Altitude	. . . . .	Assigned, MEA, Expected
Clearance Limit	. . . . .	Fly

Manual Gear Extension

Landing Gear Handle	. . . . .	Down
Breaker	. . . . .	Out
Hand Pump Cover	. . . . .	Lift
Hand Pump	. . . . .	Extend
Hand Pump	. . . . .	Until Heavy
Gear Light	. . . . .	Green
Pressure	. . . . .	Relieve & Stow
Breaker	. . . . .	In

Icing

Pitot Heat	. . . . .	On
Altitude	. . . . .	Change
Cabin Air	. . . . .	On
Heater	. . . . .	On
Defroster	. . . . .	On
RPM	. . . . .	Increase
Plan Landing	. . . . .	Nearest

If <1 Inch

Flaps (No heavy accumulation)	. . . . .	10
Forward Slip	. . . . .	Visibility
Approach	. . . . .	75-85
Landing Attitude	. . . . .	Level

Engine Fire Flight

Mixture	. . . . .	Cutoff
Fuel Shutoff	. . . . .	Off
Master Switch	. . . . .	Off
Glide Speed	. . . . .	>87
Cabin Heat & Air	. . . . .	Closed
Overhead Air	. . . . .	Open
Landing Site	. . . . .	Select
Fire Extinguisher	. . . . .	As Needed
If Fire	. . . . .	Speed Incombustable Mixture
Forced Landing	. . . . .	Done
Do Not Attempt Restart		

Electrical Fire Flight		
Master Switch	. . . . .	Off
Vent Air	. . . . .	Close
Switches Except Ignition	. . . . .	Off
Breakers	. . . . .	Check
Fire Extinguisher	. . . . .	As Needed
Master	. . . . .	On
Select Switches	. . . . .	Short Delays
If Extinguised	. . . . .	Open Vents

Engine Failure After Takeoff

Airspeed	70
Mixture	Cutoff
Fuel Selector Valve	Off
Ignition Switch	Off
Wing Flaps	As Required
Master Switch	Off

Precautionary Landing

Airspeed	65
Wing Flaps	20
Selected Field	Overfly
Radio and Electrical Switches	Off
Landing Gear (Not Rough/Soft)	Down
Wing Flaps	30 Final
Airspeed	65
Master Switch	Off
Doors	Unlatch
Touchdown	Tail Low

Ignition Switch	. . . . .	Off
Brakes	. . . . .	Heavy

Engine Start Fire

Fuel Pump	. . . . .	Off
Mixture	. . . . .	Cut Off
Ignition Switch	. . . . .	Off
Parking Brake	. . . . .	Release
Fire Extinguisher	. . . . .	Obtain
Airplane	. . . . .	Evacuate
Fire	. . . . .	Extinguish
Push airplane from fire		
Fire Damage	. . . . .	Inspect

Cabin Fire		
Master Switch	. . . . .	Off
Vents/Cabin Air/Heat	. . . . .	Closed
Fire Extinguisher	. . . . .	Use
Vent Cabin	. . . . .	Done
Airplane	. . . . .	Land

Wing FIre		
Nav Light	. . . . .	Off
Pitot Heat	. . . . .	Off
Side Slip	. . . . .	Flames Away From Tank
Land	. . . . .	ASAP

Failed Gear Retract

Master Switch	. . . . .	On
Gear Lever	. . . . .	Up
Breakers	. . . . .	In
Gear Light	. . . . .	Check
Gear Lever	. . . . .	Cycle
Gear Motor	. . . . .	Ammeter

Gear Up Landing

Gear Lever	. . . . .	Up
Breaker	. . . . .	In
Radio and Electrical Switches	. . . . .	Off
Wing Flaps	. . . . .	30 Final
Airspeed	. . . . .	65
Master Switch	. . . . .	Off
Doors	. . . . .	Unlatch
Touchdown	. . . . .	Tail Low
Ignition Switch	. . . . .	Off
Airplane	. . . . .	Evacuate

No Gear Indication

Before Landing Check	Complete
Approach	Normal
Gear Pressure	Mantain
Landing	Tail Low
Taxi	Slow

Failed Nose Gear

Moveable Load	Move Back
Passenger	Move Back
Before Landing Checklist	Complete
Runway	Hard
Emergency Hand Pump	Mantain Pressure
Wing Flaps	30
Master Switch	Off
Land	Tail Low
Mixture	Cutoff
Ignition Switch	Off
Fuel Selector Valve	Off

Attitude	. . . . .	Hold Nose Up
Airplane	. . . . .	Evacuate

Overvoltage Light

Master Switch	. . . . .	Off
Master Switch	. . . . .	On
Over-Voltage Light	. . . . .	Check
If Light		
Flight	. . . . .	Terminate
Electrical Load	. . . . .	Reduce

Discharge

Alternator	. . . . .	Off
Nonessential Equipment	. . . . .	Off
Flight	. . . . .	End