



# CERTIFICATE



Certificate No. PCS 00002.01

## SUCOFINDO INTERNATIONAL CERTIFICATION SERVICES

Graha Sucofindo B1 Floor - Jl. Raya Pasar Minggu Kav. 34 Jakarta 12780

Phone : +62-21-7983666 ext. 1040; Fax : +62-21-7987015 / 7987029; Email : cs.sics@sucofindo.co.id

Menganugerahkan kepada  
Hereby grants to

**PT. EWINDO**  
Jl. Cimuncang No. 68, Bandung 40125

Sertifikat Produk Penggunaan Tanda **SNI** dan   
Product Certificate for the Use of Marking on:

**PRODUK** : TUSUK KONTAK DAN KOTAK KONTAK  
(Product) (Non Rewirable plug)

**TIPE / MODEL** : Lihat Lampiran  
(Type / Model) (See Attachment)

**SPESIFIKASI** : Lihat Lampiran  
(Specification) (See Attachment)

**MEREK** : EWINDO  
(Brand)

**PABRIK** : PT. EWINDO  
(Factory/ Production Site)

**PENANGGUNG JAWAB** : KEIJI MATSUMURA  
(Person in Charge)

Telah memenuhi standar : **SNI IEC 60884-1:2014**  
(Comply with standard)

Tusuk-kontak dan Kontak-kontak untuk Keperluan Rumah Tangga dan Sejenisnya –  
Bagian 1: Persyaratan Umum

Sertifikat ini berdasarkan skema yang terdiri dari: Audit Pabrik, Pengujian  
Dan Pengawasan Berkala (Tipe 5)

This certificate is based on the scheme consists of: Factory Audit, Testing and Surveillance (Type 5)

PCA: 5453/SERCO-IX/PCS/2022



**Budi Utomo**

Vice President

This certificate is valid from August 03<sup>rd</sup>, 2022 until August 02<sup>nd</sup> 2025

05-Rev.00

Sertifikat ini diberikan tunduk pada syarat-syarat pada "Product Certification Agreement"

This certificate is granted Subject to the provisions on "Product Certification Agreement"

Issued date: September 16<sup>th</sup>, 2022





# Lampiran 1- Sertifikat No. PCS 00002.01

(Attachment 1- to Certificate No. PCS 00002.01)

No. Reg.: 00002.SUC.TK.0819

Tgl. Reg.: 10/01/2020

No.	Model	Spesifikasi (Specification)
1	P-129	<p><b>2.5A/250V~, 2 Kutub tanpa kontak pembumian dengan pin padat berselubung insulasi, diameter 4.0mm dan dilengkapi kabel fleksibel</b> (2 poles without earthing contacts with insulating sheathed solid pin, 4.0mm diameter and connected with flexible cables):</p> <ul style="list-style-type: none"> <li>- 60227 IEC 52 Cu/PVC/PVC-f / H03VVH2-F 2x0.5-0.75 mm<sup>2</sup> 300/300V</li> <li>- 60227 IEC 52 Cu/PVC/PVC-f / H03VV-F 2x0.5-0.75 mm<sup>2</sup> 300/300V</li> <li>- 60227 IEC 53 Cu/PVC/PVC-f / H05VVH2-F 2x0.75 mm<sup>2</sup> 300/500V</li> <li>- 60227 IEC 56 Cu/PVC/PVC-f / H03V2V2H2-F 2x0.5-0.75 mm<sup>2</sup></li> </ul>
2	P-28	<p><b>2.5A/250V~, 2 Kutub tanpa kontak pembumian dengan pin padat berselubung insulasi, diameter 4.0mm dan dilengkapi kabel fleksibel</b> (2 poles without earthing contacts with insulating sheathed solid pin, 4.0mm diameter and connected with flexible cables):</p> <ul style="list-style-type: none"> <li>- 60227 IEC 52 Cu/PVC/PVC-f H03VVH2-F 2x0.5-0.75 mm<sup>2</sup> 300/300V</li> <li>- 60227 IEC 53 Cu/PVC/PVC-f H05VVH2-F 2x0.75 mm<sup>2</sup> 300/500V</li> <li>- 60227 IEC 56 Cu/PVC/PVC-f H03V2V2H2-F 2x0.5-0.75 mm<sup>2</sup> 300/300V</li> </ul>
3	P-128	<p><b>16A/250V~, 2 Kutub tanpa kontak pembumian dengan pin padat diameter 4.8mm dan dilengkapi kabel fleksibel</b> (2 poles without earthing contacts with solid pin, 4.8mm diameter and connected with flexible cables):</p> <ul style="list-style-type: none"> <li>- 60227 IEC 52 Cu/PVC/PVC-f H03VVH2-F 2x0.5-0.75 mm<sup>2</sup> 300/300V</li> <li>- 60227 IEC 52 Cu/PVC/PVC-f H03VV-F 2x0.5 - 0.75 mm<sup>2</sup> 300/300V</li> <li>- 60227 IEC 53 Cu/PVC/PVC-f H05VVH2-F 2x0.75-1.0 mm<sup>2</sup> 300/500V</li> <li>- 60227 IEC 53 Cu/PVC/PVC-f H05VV-F 2x0.75-1.5 mm<sup>2</sup> 300/500V</li> <li>- 60227 IEC 56 Cu/PVC/PVC-f H03V2V2H2-F 2x0.5-0.75 mm<sup>2</sup> 300/300V</li> <li>- 60227 IEC 89 / H03RT-H 2x0.75 mm<sup>2</sup> 300/300V</li> </ul>
4	P-94P	<p><b>16A/250V~, 2 Kutub tanpa kontak pembumian dengan pin padat diameter 4.8mm dan dilengkapi kabel fleksibel</b> (2 poles without earthing contacts with solid pin, 4.8mm diameter and connected with flexible cables):</p> <ul style="list-style-type: none"> <li>- 60227 IEC 52 Cu/PVC/PVC-f H03VVH2-F 2x0.5-0.75 mm<sup>2</sup> 300/300V</li> <li>- 60227 IEC 52 Cu/PVC/PVC-f H03VV-F 2x0.5-0.75 mm<sup>2</sup> 300/300V</li> <li>- 60227 IEC 53 Cu/PVC/PVC-f H05VVH2-F 2x0.75-1.0 mm<sup>2</sup> 300/500V</li> <li>- 60227 IEC 53 Cu/PVC/PVC-f H05VV-F 2x0.75-1.5 mm<sup>2</sup> 300/500V</li> <li>- 60227 IEC 89 / H03RT-H 2x0.75 mm<sup>2</sup> 300/300V</li> </ul>





**Lampiran 2- Sertifikat No. PCS 00002.01**

(Attachment 2- to Certificate No. PCS 00002.01)

No. Reg.: 00002.SUC.TK.0819

Tgl. Reg.: 10/01/2020

No.	Model	Spesifikasi (Specification)
5	P-94	<b>16A/250V~, 3 Kutub dengan kontak pembumian samping, dengan pin padat diameter 4.8mm dan dilengkapi kabel fleksibel (3 poles with side earthing contacts and solid pin, 4.8mm diameter and connected with flexible cables):</b> <ul style="list-style-type: none"><li>- 60227 IEC 52 Cu/PVC/PVC-f H03VV-F 3x0.5-0.75 mm<sup>2</sup> 300/300V</li><li>- 60227 IEC 53 Cu/PVC/PVC-f H05VV-F 3x0.75-1.5 mm<sup>2</sup> 300/500V</li><li>- 60245 IEC 57 / H05RN-F 3x0.75-1.5 mm<sup>2</sup> 300/500V</li><li>- 60245 IEC 89 / H03RT-H 3x0.75-1.0 mm<sup>2</sup> 300/300V</li></ul>

