

2025-04-15 16:45

tags :

- [Machine Learning](#)
- [Hands on ML - book](#)

Chapter 4 - Hands on

- This chapter dives into how machine learning models work under the hood. It covers:
 - **Linear Regression** using closed-form solutions and **Gradient Descent** (plus its variants).
 - **Polynomial Regression**, overfitting, and how to prevent it with **learning curves** and **regularization**.
 - **Logistic** and **Softmax Regression** for classification tasks.

Linear Regression

- What is Linear Regression?
 - It's a model that predicts an output by computing a **weighted sum of input features**, plus a **bias** (intercept).
 - The general form is:
$$\hat{y} = \theta_0 + \theta_1 x_1 + \theta_2 x_2 + \dots + \theta_n x_n$$
 - In vector form:
$$\hat{y} = \theta^T \cdot x$$
 - (where θ is the vector of parameters, and x is the vector of input features including a 1 for the bias term)
- How Do We Train It?
 - We adjust θ (the model's parameters) to best fit the training data.
 - To measure how well it fits, we use **Mean Squared Error (MSE)** as the cost/loss function:
 - This helps us find the values of θ that minimize prediction errors.
- Training loss (like MSE) is optimized during training.
- Evaluation metrics (like precision/recall) may differ from training loss, especially for classifiers.
- Good loss functions are **easy to optimize** and **correlate with real-world goals**.

The Normal Equation




- What is the **Normal Equation**?
 - It's a **direct formula** to compute the best parameters θ that minimize the MSE (no iteration needed):
- How It Works:
 1. Generate training data with some noise:
 2. Add a column of 1s to X (to handle the bias term).
 3. Use NumPy to compute θ directly using matrix operations.
 4. Predictions are made by multiplying new input data by the computed θ .
- Example Results:
 - The true parameters were 4 and 3.
 - The model estimated them as **4.215** and **2.770** — close, but slightly off due to noise.
- Using Scikit-Learn:
 - You can use `LinearRegression()` from scikit-learn to do the same thing with `.fit()` and `.predict()`.
 - It separates the **intercept_** (bias) and **coef_** (feature weights).
- **Pseudoinverse Alternative**:
 - Instead of using the Normal Equation, you can use the **pseudoinverse**:
 - is the of X . Computed using `np.linalg.pinv(X)`
 - More stable and handles edge cases where $X^T X$ is not invertible (e.g., redundant features or too few data points).
- **Normal Equation** is a fast, direct way to compute parameters for linear regression.
- **Pseudoinverse** is more robust and always works, even when the Normal Equation fails.
- Libraries like **scikit-learn** and **NumPy** make it easy to use both.

Computational Complexity

- Normal Equation & SVD Complexity:
 - **Normal Equation** has a complexity of about $O() \text{ to } O()$ → gets **slow with many features**.
 - **SVD** (used by Scikit-Learn) is about $O(n^2)$ → still slow when **n (features)** is very large.
 - **Both handle large datasets (many rows, m) well**, since they are **linear in m: $O(m)$** .
- Prediction Time:
 - Once the model is trained, making predictions is **very fast**.
 - Time grows **linearly** with the number of instances and features.

Gradient Descent

- What is Gradient Descent?

- An **optimization algorithm** that finds the best model parameters (like θ) by minimizing a **cost function** (e.g., MSE).
- It does this by **iteratively moving in the direction of the steepest slope** (i.e., negative gradient).
- How It Works:
 1. **Start** with random parameter values (random initialization).
 2. Repeatedly **adjust parameters** to reduce the cost.
 3. **Stop when** the gradient becomes zero \rightarrow minimum reached.
- Learning Rate (Step Size):
 - **Too small** \rightarrow slow convergence (takes many steps).
 - **Too large** \rightarrow may overshoot or diverge (never settles).
 - Must choose a **balanced learning rate**!
- challenges:
 - Some cost functions can have **plateaus, local minima, or complex shapes**.
 - BUT for **linear regression**, the MSE cost function is:
 -  **Convex** (no local minima)
 -  **Smooth** (no sharp changes)
 -  So, gradient descent is **guaranteed** to find the global minimum eventually.
- Feature Scaling:
 - If features have **different scales**, gradient descent:
 - Takes weird zigzag paths,
 - Converges **very slowly**.
 - Use tools like `StandardScaler` to **normalize** feature scales.

Batch Gradient Descent

- **What is Batch Gradient Descent?**
 - Batch Gradient Descent is an optimization algorithm used to **minimize the cost function** (like MSE in linear regression) by adjusting model parameters .
- **Key Concepts**
 1. **Cost Function (MSE)**
Measures how bad the model's predictions are:
 2. **Gradient (Slope Vector)**
Tells you how to tweak to reduce the error. It's the vector of **partial derivatives** of the cost function with respect to each parameter .
 - manual for each paramete :
 - vectorized for all parameters :

3. Gradient Descent Update Rule

Use the gradient to update θ by taking a step **opposite the slope**:

- = learning rate (step size)

4. Code :-

```
eta = 0.1          # learning rate
n_epochs = 1000    # number of passes over the dataset
m = len(X_b)       # number of samples

theta = np.random.randn(2, 1) # random initialization

for epoch in range(n_epochs):
    gradients = 2 / m * X_b.T @ (X_b @ theta - y)
    theta = theta - eta * gradients
```

5. Learning Rate Matters

- **Too small** → very slow convergence
- **Just right** → fast and stable
- **Too large** → divergence (jumps around, doesn't settle)

6. When to Stop?

- Set a max number of epochs, **or**
- Stop early when the gradient becomes very small (i.e., close to minimum)

7. Convergence

- Gradient descent will converge for convex functions like MSE
- The convergence speed depends on the **learning rate** and **tolerance**

Stochastic Gradient Descent

- **What is SGD?**
 - Unlike **Batch Gradient Descent** (which uses the whole dataset per step), **SGD** uses **only one random data point per update**.
 - This makes each step much **faster** and allows training on very **large datasets**.
- **Pros and Cons**
 - pros
 - Faster updates
 - Can escape local minima
 - Scalable to huge datasets
 - Cons
 - More noisy (bouncy) path to minimum
 - Doesn't settle exactly at the minimum
 - May require careful tuning of learning rate

- **Epochs and Iterations**

- One **epoch** = one full pass through the dataset.
- Each **epoch** consists of m **updates** (one per training example).
- If random sampling is used, some examples might be picked multiple times or not at all in one epoch.

- **Learning Rate Schedule**

- To reduce noise and allow convergence, **learning rate should shrink over time**.
- This is done using a **learning schedule**, e.g.:

```
def learning_schedule(t):  
    return t0 / (t + t1)
```

- Starts with larger steps (fast progress), then gets smaller (finer tuning).

- **Important Considerations**

- Data must be **IID (independent and identically distributed)** — shuffle it!
- If data is ordered (e.g., by label), SGD can behave badly.

- **SGD in Code**

- ```
for epoch in range(n_epochs):
 for iteration in range(m): # m training instances
 random_index = np.random.randint(m)
 xi = X_b[random_index : random_index + 1]
 yi = y[random_index : random_index + 1]
 gradients = 2 * xi.T @ (xi @ theta - yi)
 eta = learning_schedule(epoch * m + iteration) # t which is the
i/p of learning_schedule
 theta = theta - eta * gradients
```

- **Scikit-Learn's SGDRegressor**

- ```
from sklearn.linear_model import SGDRegressor  
sgd_reg = SGDRegressor(  
    max_iter=1000, tol=1e-5, eta0=0.01, penalty=None,  
    n_iter_no_change=100, random_state=42  
)  
sgd_reg.fit(X, y.ravel())
```

Mini-Batch Gradient Descent


- Mini-batch Gradient Descent (MBGD) is a hybrid between:
 - **Batch GD**: Uses the whole dataset per step (slow but stable).
 - **Stochastic GD (SGD)**: Uses 1 sample per step (fast but noisy).
- **MBGD** uses **small random batches** of data (e.g. 32 or 64 samples).

- **Advantages**

- Faster than Batch GD.
- Less noisy than SGD.
- Can benefit from hardware acceleration (like GPUs).
- Works well with **large datasets**.

- **Disadvantages**

- Still bounces around the minimum (but less than SGD).
- Might get stuck in local minima (especially for non-convex problems).
- Needs a learning schedule (like SGD).



- **Batch GD** : smooth, direct to the minimum, stops there.
- **Stochastic GD** : very noisy path, keeps bouncing.
- **Mini-batch GD** : less noisy than SGD, ends near the minimum.

Algorithm	Large m	Out-of-core support	Large n	Hyperparams	Scaling required	Scikit-Learn
Normal Equation	Fast	No	Slow	0	No	n/a
SVD	Fast	No	Slow	0	No	LinearRegression
Batch GD	Slow	No	Fast	2	Yes	SGDRegressor
Stochastic GD	Fast	Yes	Fast	≥ 2	Yes	SGDRegressor
Mini-batch GD	Fast	Yes	Fast	≥ 2	Yes	SGDRegressor

Polynomial Regression

- **Polynomial Regression Overview**

- **Goal:** Fit **nonlinear data** using a **linear model**.
- **How:** Add **powers of features** (e.g. etc.) as **new features**, then apply **linear regression**.

- **Example Process:**

1. **Generate nonlinear data:**

2. **Use** `PolynomialFeatures` from `sklearn`:

- ```
from sklearn.preprocessing import PolynomialFeatures
poly_features = PolynomialFeatures(degree=2, include_bias=False)
X_poly = poly_features.fit_transform(X)
```
- Turns into

3. **Train Linear Regression** on transformed data:

- ```
from sklearn.linear_model import LinearRegression
lin_reg = LinearRegression()
lin_reg.fit(X_poly, y)
```

- **Model Output Example:**

- The model learns:
- Close to the original:


- **Key Points:**

- **Polynomial regression \neq nonlinear model** — it's still **linear in parameters**.
- When multiple features are present, **interactions** (e.g.,) are added automatically.


- **Warning:** With high degree d and many features n , the number of features grows **combinatorially**:
- Increasing polynomial degree can **cause overfitting**.

Learning Curves

- What Are They?
 - **Plots of:** Training error and Validation error **vs.** Training set size.
 - Help diagnose:
 - **Underfitting** (high bias)
 - **Overfitting** (high variance)
- Key Observations
 - **Underfitting Example (Linear Model):**



- **Training error:** Starts low (small data) then rises and plateaus
- **Validation error:** Starts high, decreases, then plateaus near training error
- → **Both errors high & close** = Model too simple (high bias)
- **Overfitting Example (10th-degree Polynomial):**



- **Training error:** Very low
- **Validation error:** Higher and doesn't match training error
- → **Big gap between curves** = Model too complex (high variance)
- ☒ Can often fix with **more training data**
- **Tips:**
 - **Underfitting?** → Try a more complex model or better features
 - **Overfitting?** → Try regularization or add more data
 - **Irreducible error?** → Clean up your dataset

Regularized Linear Models

- **Regularization** helps reduce **overfitting** by limiting model complexity.
- For **polynomial models**, reduce the **degree**.
- For **linear models**, **constrain the weights** using:
 1. **Ridge Regression (L2)** – Shrinks all weights.
 2. **Lasso Regression (L1)** – Shrinks some weights to **zero** (feature selection).
 3. **Elastic Net** – Mix of L1 and L2 regularization.

Ridge Regression

- What Is Ridge Regression?
 - **Ridge Regression** (aka **Tikhonov regularization**) is **Linear Regression + L2 regularization**.

- The goal: Fit the data **while keeping model weights small**, reducing overfitting.
- **Cost Function**
 - Adds a **penalty** for large weights.
 - Bias term is **not** regularized.
 - controls regularization strength:
 - $\alpha = 0 \rightarrow$ plain Linear Regression.
 - Large $\alpha \rightarrow$ very flat model.
- **Important: Always Scale Your Features**
 - Use `StandardScaler` before applying Ridge. Regularization is sensitive to feature scales.
- **Intuition**
 - **High** $\alpha \rightarrow$ simple, flat predictions \rightarrow **low variance, high bias**.
 - **Low** $\alpha \rightarrow$ **more flexible model** \rightarrow **low bias, high variance**.
 - This helps manage the **bias-variance trade-off**.

- **How To Use Ridge in Scikit-Learn**

1. Closed-form (exact solution):

```
from sklearn.linear_model import Ridge
ridge_reg = Ridge(alpha=0.1, solver="cholesky")
ridge_reg.fit(X, y)
ridge_reg.predict([[1.5]])
```

2. Using Stochastic Gradient Descent (SGD):

```
from sklearn.linear_model import SGDRegressor
sgd_reg = SGDRegressor(penalty="l2", alpha=0.1/m, tol=None,
                        max_iter=1000, eta0=0.01, random_state=42)
sgd_reg.fit(X, y.ravel()) # y must be 1D
sgd_reg.predict([[1.5]])
```

- **Extra Tip: Automatic Tuning**

- Use `RidgeCV` for **automatic α tuning** with cross-validation:

```
from sklearn.linear_model import RidgeCV
ridge_cv = RidgeCV(alphas=[0.01, 0.1, 1.0, 10.0])
ridge_cv.fit(X, y)
```

Lasso Regression

- **What is Lasso Regression?**
 - **Lasso** stands for **Least Absolute Shrinkage and Selection Operator**.

- It's a regularized version of **linear regression** that adds an ℓ_1 (**absolute value**) **penalty** to the cost function.
- Cost Function:
 - ℓ_1 norm = sum of absolute values of the weights (no squares like Ridge).
 - This encourages some weights to become exactly **zero** → **feature selection**!
- **Effect of Lasso:**
 - Can **zero out** unimportant features, making the model **sparse** and easier to interpret.
 - Increasing α increases regularization (more weights shrink to zero).
 - Decreasing α moves the solution toward plain linear regression (no regularization).
- **Gradient and Subgradient:**
 - Lasso's cost function is **not differentiable at $\theta = 0$** .
 - Gradient descent uses a **subgradient** instead:
 - `sign(θ_i)` is used: returns -1, 0, or 1 based on the sign of each θ .
- You can also use `SGDRegressor(penalty="l1")` to perform lasso-style training with SGD.
- Scikit-Learn Example:

```
from sklearn.linear_model import Lasso

lasso_reg = Lasso(alpha=0.1)
lasso_reg.fit(X, y)
lasso_reg.predict([[1.5]])
# Output: array([1.53788174])
```

Elastic Net Regression

- **What is Elastic Net?**
 - **Elastic Net** combines both **Ridge (ℓ_2)** and **Lasso (ℓ_1)** penalties.
 - It's a **weighted average** of Ridge and Lasso regularization.
- **Cost Function:**
 - `r = 0` : behaves like **Ridge**
 - `r = 1` : behaves like **Lasso**
- **When to Use Elastic Net?**
 - Use **regularization** in general (avoid plain linear regression).
 - **Ridge** is a good default.
 - Use **Lasso/Elastic Net** if you believe:
 - Only a few features are important
 - You want **automatic feature selection**
 - Prefer **Elastic Net** over Lasso when:

- You have **more features than samples**
- Some features are **highly correlated**
- Scikit-Learn Example:

```
from sklearn.linear_model import ElasticNet

elastic_net = ElasticNet(alpha=0.1, l1_ratio=0.5) # l1_ratio = r
elastic_net.fit(X, y)
elastic_net.predict([[1.5]])
# Output: array([1.54333232])
```

Early Stopping

- **What is Early Stopping?**
 - A **regularization technique** for iterative learning (like gradient descent).
 - You **stop training** when the **validation error stops improving**.
 - Helps **prevent overfitting** by not overtraining the model.
 - Called a “**beautiful free lunch**” by Geoffrey Hinton because it's simple yet powerful.
- **How It Works (Conceptually)**
 - During training:
 - Training error keeps going **down**.
 - Validation error goes **down**, then **up** (indicating overfitting).
 - **Early stopping** halts training **at the lowest validation error**, before overfitting begins.
- **Code**

1. Data Prep

```
X_train, y_train, X_valid, y_valid = [...] # split dataset

preprocessing = make_pipeline(
    PolynomialFeatures(degree=90, include_bias=False),
    StandardScaler())
X_train_prep = preprocessing.fit_transform(X_train)
X_valid_prep = preprocessing.transform(X_valid)
```

2. Model Setup

```
sgd_reg = SGDRegressor(penalty=None, eta0=0.002, random_state=42)
```

- Uses **Stochastic Gradient Descent** (SGD).
- **No regularization** (penalty=None).
- Small learning rate eta0=0.002 .

3. Training with Early Stopping

```

from copy import deepcopy
n_epochs = 500
best_valid_rmse = float('inf') # start with the worst possible error

for epoch in range(n_epochs):
    sgd_reg.partial_fit(X_train_prep, y_train) # train one step
    y_valid_predict = sgd_reg.predict(X_valid_prep)
    val_error = mean_squared_error(y_valid, y_valid_predict,
    squared=False) # RMSE

    if val_error < best_valid_rmse: # if new best
        best_valid_rmse = val_error
        best_model = deepcopy(sgd_reg) # save current model

```

Logistic Regression

- A classification algorithm (despite its name).
- Predicts the **probability** an instance belongs to class **1** (positive class).
- If probability > 50%, it predicts **1**, else **0** (negative class).
- Used for **binary classification** problems (e.g., spam detection).

Estimating Probabilities

- Logistic regression computes:
- Output is a **probability** between 0 and 1.
- Prediction rule:
 - If ≥ 0.5 , predict class **1**.
 - If < 0.5 , predict class **0**.

Training and Cost Function

- Train the model so that:
 - High probabilities for **positive class (y = 1)**
 - Low probabilities for **negative class (y = 0)**
- Single Instance Cost
 -
- Total Cost (Log Loss)
 -
 - Called **log loss**, and it's **convex**, so Gradient Descent can find the **global minimum**.

- Gradient
 - Same idea as linear regression: error \times feature \rightarrow average over all samples.
 - Used in **batch**, **stochastic**, or **mini-batch Gradient Descent** to update weights.

Decision Boundaries

- Dataset Used: Iris Dataset
 - 150 iris flowers, 3 species: **Setosa**, **Versicolor**, **Virginica**
 - Features: sepal/petal **length** and **width**
- **Goal:**
 - Classify **whether a flower is Iris Virginica** based on petal width.
- **Steps:**
 1. **Load data** using `load_iris()`
 2. **Use only petal width** as input feature
 3. Create binary labels:


```
y = True if Virginica, False otherwise
```
 4. **Split data** \rightarrow Train/Test
 5. **Train** logistic regression model with `fit()`
 6. **Predict probabilities** with `predict_proba()`
- **Decision Boundary:**
 - Model predicts **Virginica** if **probability ≥ 0.5**
 - This creates a **threshold (decision boundary)** at **~ 1.65 cm**
 - If **petal width > 1.65 cm** \rightarrow **Virginica**, else not

Softmax Regression

- Softmax Regression is a generalization of logistic regression that works for **multiple classes** directly — no need to train separate binary classifiers.
- **How It Works (Prediction)**
 1. For an input x , the model calculates a **score** for each class:


```
score = w · x + b
```

 ,Each class has its own weight vector
 2. It then applies the **softmax function** to convert these scores into **probabilities**:
 - K is the number of classes.
 - The output is a probability distribution over the classes.
 3. It **predicts** the class with the **highest probability**:
- Training the Model
 - The model is trained to **maximize the probability** of the correct class.
 - It uses the **cross-entropy loss function**:

- =1 if example belongs to class k, else 0.
- This function penalizes the model when it assigns **low probability** to the correct class.
- When K=2, this reduces to the familiar **log loss** used in binary logistic regression.
- Key Tip
 - Softmax is good for **mutually exclusive classes** (e.g., flower types), but **not** for multi-label problems (like detecting multiple objects in one image).
- Cross Entropy in Machine Learning
 - Used as the **loss function** for classification tasks.
 - Penalizes wrong class probability predictions.
 - Especially common in **softmax regression** and **neural networks**.
- Gradient of Cross Entropy
 - Helps in **training the model** using gradient descent:
 - Compute gradient per class → update weights → repeat.
- **Softmax Regression with Scikit-Learn**
 - Automatically used when there are **more than 2 classes**.
 - Uses **LogisticRegression** with `solver="lbfgs"` (default).
 - Regularized using L2 by default (controlled by `C`).
 - **Example: Classify Iris Flowers**

```
X = iris.data[["petal length (cm)", "petal width (cm)"]].values
y = iris["target"]
X_train, X_test, y_train, y_test = train_test_split(X, y,
                                                    random_state=42)
softmax_reg = LogisticRegression(C=30, random_state=42)
softmax_reg.fit(X_train, y_train)
```

- Prediction Example:

```
softmax_reg.predict([[5, 2]]) # → array([2])
softmax_reg.predict_proba([[5, 2]]) # → [[0. , 0.04, 0.96]]
```

- **Visualization**




Figure 4-25. Softmax regression decision boundaries

-
- Softmax regression creates **linear decision boundaries** between classes.
- Curved lines represent **equal probability contours**.
- At the center where all three classes meet → model gives ~33% to each class.

Resources :

-

Related notes :

-

References :

- **Internal :**
 -
 -
 -
- **External :**
 - [notebook of the chapter](#)
 - [hegab videos](#)

- [the book](#)