Checklist — talk day

The night before

- ☐ Install the published release on the talk laptop, the one the audience will install: protoCore 2.14.6 and protoST 0.6.5 (0.6.2, which made the adaptive heap controller the default memory policy, plus 0.6.3's correct release of transient pins in the dispatch loop and clear error when the kernel is missing, the demos inside the package, in `/usr/share/protoST/talks/`, and, in 0.6.5, protoCore 2.14.6, whose integer arithmetic creates no temporaries). On Windows, inside WSL2 with Ubuntu 24.04: `wget https://github.com/numaes/protoCore/releases/download/v2.14.6/protoCore-2.14.6-Linux.deb` `wget https://github.com/gamarino/protoST/releases/download/v0.6.5/protost-0.6.5-Linux.deb` `sudo apt install ./protoCore-2.14.6-Linux.deb ./protost-0.6.5-Linux.deb` (`apt install ./...` also installs any missing dependency and upgrades an earlier protoCore, such as 0.5.0's 2.6.2, or an earlier protoST). There are two floors: the protoST 0.6.5 `.deb` requires protoCore 2.14.6 or later (the package declares it); built from source, protoST 0.6.5 needs protoCore 2.11.0 or later.
- ☐ `protost --version` → `protoST 0.6.5`; `ldd $(command -v protost) | grep protoCore` → `libprotoCore.so.3 => /usr/bin/../lib/x86_64-linux-gnu/libprotoCore.so.3 (0x...)`: a path that ends in `lib/x86_64-linux-gnu/lib` not `/usr/local` or a build directory.
- ☐ `python3 --version` answers (demo 4 uses it).
- ☐ The demos come with the package: `cd /usr/share/protoST/talks/2026-10-15-fas/demos && RUNS=20 ./check_all.sh` → all four demos 20/20 (the same from the repository, in `docs/talks/2026-10-15-fas/demos`). `run_demo.sh` runs the `protost` on the `PATH`; to try another binary, `PROTOST=/path/to/protost`.
- ☐ Test the recordings (they are in the repository, not in the package): `scriptreplay --timing=../recordings/01-familiar- ../recordings/01-familiar-code.typescript` (and 02, 03, 04).
- ☐ Keep an offline copy of the deck PDF (`slides/protoST-FAST-2026-en.pdf`, regenerated on 12/10 with the protoCore 2.14.6 figures; also in `/usr/share/protoST/talks/2026-10-15-fas/slides/`), of the speaker notes (`en/speaker-notes.md`) and of the repository.

One hour before

- ☐ Close everything that uses CPU (browser with heavy tabs, builds, indexers). Demo 2 shows times measured on the spot: on an idle machine it prints about 2.4× (2.1–2.6×, 12/10 on DEV12); under load the result is unpredictable (1.6–3.2× on 12/10 with an editor's indexer using the CPU).
- ☐ Machine on AC power and in the performance power mode (Settings → Power; with TLP, `sudo tlp ac` and check with `tlp-stat -s`).
- ☐ Terminal: large font (≥ 20 pt), light or dark background depending on the projector, full-screen window.
- ☐ `cd` to the demos folder; have `less 01-familiar-code.st` ready to show the code before running it.
- ☐ Turn off notifications.

During

- ☐ If a demo fails or is slow: do not debug live. Say so and switch to the recording (`scriptreplay`).
- ☐ Quote the figures that appear on screen or those in the report, never from memory.