
Introduction to High-Performance Computing

Exercise1

Giorgio Amati
Alessandro Ceci

Corso di dottorato in Ingegneria Aeronautica e Spaziale 2025

g.amati@cineca.it / g.amaticode@gmail.com

alessandro.ceci@uniroma1.it

Agenda

- ✓ Simple “warm-up” exercise: Matrix-Matrix Multiplication
- ✓ Complete the code
 - Fortran/C
- ✓ Check the results
- ✓ Extract some Performance figure (in MFLOPs)

You can use:

- ✓ Any available HW
 - ✓ Any available compiler
 - ✓ Any compiler option
-

Example: matrix-matrix multiplication

Simple problem: for 2 n^2 matrices we have to:

- ✓ compute n^3 products and n^3 sums
- ✓ load $2 \cdot n^2$ data and to store n^2 data
 - Ratio computation vs. load/store is $O(n)$!

$$c_{ij} = a_{i1}b_{1j} + a_{i2}b_{2j} + \cdots + a_{in}b_{nj} = \sum_{k=1}^n a_{ik}b_{kj}$$

Fortran:	$c(i,j) = c(i,j) + a(i,k)*b(k,j)$
C:	$c[i][j] = c[i][j] + a[i][k]*b[k][j];$

- ✓ **MM multiplication is used for supercomputing rankings (top500)**
-

How to do

✓ Clone the repository

- `git clone https://github.com/gamati01/HPCLessons.git`

```
.
├── LESSON1
│   ├── clean.sh
│   ├── compile.c.sh
│   ├── compile.fortran.sh
│   ├── EXERCISE1.pdf
│   ├── HPC-1.pdf
│   ├── inc_precision.h
│   ├── mm.c
│   ├── mm.F90
│   ├── mod_tools.F90
│   └── README
├── HPC-0.pdf
└── README.rst
```

✓ Complete the code

```
70 ! main loop
71     call system("date          > time.log")
72     call timing(time1)
73 !
74 ! write bottom here 3 nested loops....
75 !
76         c(i,j) = c(i,j) + a(i,k)*b(k,j)
77
78     call timing(time2)
79     call system("date          >> time.log")
```

✓ Complete the code

```
45  time1 = clock();
46  /*                                     */
47  /* write here 3 nested loop          */
48  /*                                     */
49          c[i][j] = c[i][j] + a[i][k]*b[k][j];
50
51
52  time2 = clock();
```

compile.fortran.sh

- ✓ simple script to compile the code
- ✓ choose the available compiler & compiler options

```
rm -rf *.o mm.x *.mod
#
...
#
# gfortran (GNU)
COMP=gfortran
OPT=
#
echo "compiling with " $COMP $OPT
#
$COMP $OPT mod_tools.F90 -c
$COMP $OPT mm.F90 -c
$COMP $OPT mod_tools.o mm.o -o mm.x
#
echo "That's all folks!!!"
```

compile.c.sh

- ✓ simple script to compile the code
- ✓ choose the available compiler & compiler options

```
rm -rf *.o mm.x *.mod
#
...
#
# gcc (GNU)
COMP=gcc
OPT=
#
echo "compiling with " $COMP $OPT
#
$COMP $OPT mm.c -c
$COMP $OPT mm.o -o mm.x
#
echo "That's all folks!!!"
```


./mm.x (Fortran)

- ✓ Fortran: If coded correctly, it should give an output like that

```
-----  
Matrix-Matrix Multiplication  
precision used          15  
rel. 0, naive multiplication  
Which matrix size?  
1024  
Matrix size      =      1024  
Memory size (MB) =      24  
-----  
initialization    1.1718750000000000E-002  
0.4293334354359644      0.9410485065499756      0.0000000000000000  
-----  
CPU:time for multiplication 3.1406250000000000  
CPU:MFLOPS      683.7758861940298  
CPU:check      257.1789318419338
```

- ✓ size (e.g. 1024) given by standard input
- ✓ check \sim size/4

- ✓ C: If coded correctly, it should give an output like that

```
=====
Enter the size
1024
  single precision
size 1024
=====
Initialization
Elapsed time for initialization
Total time -----> 0.043431
=====
Time -----> 7.044017
Mflops -----> 304.866335
Check -----> 252.884160
```

- ✓ size (e.g. 1024) given by standard input
- ✓ check \sim size/4
-

Homework: Fill the table

Size	Fortran	C
256*256		
512*512		
1024*1024		
2048*2048		

- ✓ Compiler used:
 - ✓ Compiler option used:
 - ✓ HW used:
-