



Shubham Pack®  
PACK WITH CONFIDENCE!

REF: SPM/EXP/P/SK0218/2024-25 REV02

DATE: 18-05-2024

## Techno-Commercial

### Proposal for

### **COLLAR TYPE MACHINE MODEL SPM 500P-4A-VCF-Twin Head For 1000g Pack with 200g & 500g ChangoverParts**

Global Standards Unmatched Performance

Specially prepared for

=====

**Mr Ashit Desai**

**Team Lead**

**BIDCO AFRICA LIMITED**

**KENYA**

=====

**Prepared by:**

Shiv Om Kaushik

Marketing

Email: [shivom@shubhampack.com](mailto:shivom@shubhampack.com)

Cell: +91-8130192043

**SHUBHAM FLEXIBLE PACKAGING MACHINES PVT. LTD.**

B-8A, Sector 59 Part II, Ballabgarh, Faridabad - 121004, Haryana, India

EPABX.: 0091 129 4272350/4272352 Fax: 0091 129 4272351, E-mail: [sales@shubhampack.com](mailto:sales@shubhampack.com)



**Shubham Pack®**  
PACK WITH CONFIDENCE!

## Index

Annexure- I

Project Data

Annexure-II

Technical Specifications

Annexure- III

Exclusions

Annexure- IV

Price Schedule & Optional Items

Annexure- V

Commercial terms and conditions

Annexure- VI

Attachments E-Brochure

**SHUBHAM FLEXIBLE PACKAGING MACHINES PVT. LTD.**

B-8A, Sector 59 Part II, Ballabgarh, Faridabad - 121004, Haryana, India

**EPABX.:** 0091 129 4272350/4272352 **Fax:** 0091 129 4272351, **E-mail:** [sales@shubhampack.com](mailto:sales@shubhampack.com)



## **Annexure-I**

### **Project Data**

|    |                                   |                        |                                                                       |
|----|-----------------------------------|------------------------|-----------------------------------------------------------------------|
| 1  | <b>Product to be Packed</b>       |                        | Powder                                                                |
| 2  | <b>Product name</b>               |                        | Detergent Powder                                                      |
| 3  | <b>Characteristics of product</b> | Density                | B/D - 370±20<br>MOISTURE MAX - 3%                                     |
| 4  | <b>Pouch Size &amp; Type</b>      | W X L                  | 200g - 345mm X 190mm<br>500g - 445mm X 240mm<br>1000g - 505mm X 300mm |
| 5  | <b>Quantity to be packed</b>      | Gm                     | 200g, 500g, 1000g                                                     |
| 6  | <b>Horizontal Sealing Width</b>   | mm                     | 15mm                                                                  |
| 7  | <b>Vertical Sealing Width</b>     | mm                     | 20mm                                                                  |
| 8  | <b>Core Dia.</b>                  | 76/152                 | 76mm                                                                  |
| 9  | <b>Perforation Pitch</b>          | mm                     | 3mm                                                                   |
| 10 | <b>Type of Perforation</b>        | V/Y                    | V type                                                                |
| 11 | <b>Single Pouch</b>               | Cutting/String         | Cutting                                                               |
| 12 | <b>Type of Sealing</b>            | V-Lining/Butt/Knurling | V – Lining                                                            |
| 13 | <b>PLC Make</b>                   | Omron/AB               | OMRON/Mitsubishi                                                      |
| 14 | <b>Power Supply</b>               | VAC/Ph/Hz              | 415 VAC, 3 Ph, 50 Hz                                                  |



**Annexure-II**  
**Technical specification**

| Sr. No. | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 01      | <p>Vertical Collar type m/c to pack Detergent Powder <b>SPM 500P-4A-VCF-TWIN HEAD</b></p> <p>Change parts required depending upon the pouch size</p> <p><b><u>Features</u></b></p> <ul style="list-style-type: none"><li>➤ Mild steel machine Structure to absorb vibration at higher speed.</li><li>➤ Former &amp; former pipe to form the pouch.</li><li>➤ All contact Parts SS 304</li><li>➤ SS 304 Cladding where as required.</li><li>➤ Laminate pulling through <b>servo motor</b>.</li><li>➤ HMI to interface the problem and to adjust the temperature, speed and pouch length etc.</li><li>➤ Horizontal sealing unit <b>servo operated</b> Batch cutter cum perforation knife.</li><li>➤ Electrical Equipment for standard machine with Air-cooled panel.</li><li>➤ Standard front Acrylic Guarding with limit switches.</li><li>➤ Automatic web tension control by Dancing Roller and Pneumatic operated brake.</li><li>➤ Filling through Volumetric Slide Cup Filler System</li></ul> |
| 02      | <p><b>For accuracy in fill weights, following is necessary:</b></p> <ul style="list-style-type: none"><li>• Consistent Bulk Density of product.</li><li>• Maintaining RH of the packing room, if product is hygroscopic in nature.</li><li>• Maintaining product level in product Hopper.</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| 03      | <p><b>AXIS OF MACHINE: 4 SERVO</b></p> <p>2 Nos. – Laminate Pulling</p> <p>2 Nos. – Horizontal Sealing System</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |



|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                             |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Machine Model</b>                 | SPM – 500P Twin Head                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Product to be packed</b>          | Detergent Powder                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Filling capacity</b>              | 200g, 500g, 1000g                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Sealing Style</b>                 | Center Sealing                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Speed</b>                         | <b>Speed for 200g Pack - **40–45 Strokes/min X 2 Tracks</b><br><b>**80 – 90 Pouches / min</b><br><br><b>Speed for 500g Pack - **35–40 Strokes/min X 2 Tracks</b><br><b>**70 – 80 Pouches / min</b><br><br><b>Speed for 1000g Pack - **30–35 Strokes/min X 2 Tracks</b><br><b>**60 – 70 Pouches / min</b><br><br>**(Output depends upon Characteristics of product, Fill volume, Pouch Length & Characteristics of Laminate) |
| <b>Roll Width</b>                    | Max. - 450 mm                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Laminate Specification</b>        | Max. Reel Dia – 450 mm<br>Reel Core Dia – 76 mm                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Packaging material</b>            | Heat Sealable Laminate                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Control</b>                       | PLC based with touch screen HMI                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Filling Mechanism</b>             | Volumetric Cup Filler System                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Horizontal Sealer</b>             | Servo Motor Driven                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Batch Cutter with Perforation</b> | Pneumatic operated                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Film Pulling</b>                  | <b>Through Servo Motor Driven</b>                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Product contact parts</b>         | SS-304                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Electrical Specification</b>      | Power Supply : 415 VAC, 3 Ph, 50 Hz<br>Power Consumption: 6-8 KW Appx.                                                                                                                                                                                                                                                                                                                                                      |
| <b>Air Consumption</b>               | 5-6 CFM @ 6 bar                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Machine Color</b>                 | Mulshell Grey – Powder coated.                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Layout Dimensions (Approx.)</b>   | Length → 2000 mm<br>Width → 2000 mm<br>Height → 3000 mm                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Weight</b>                        | Net : 2500 Kg. (Approx.)<br>Gross : 3500 Kg. (Approx.)                                                                                                                                                                                                                                                                                                                                                                      |



**Annexure-III**  
**Exclusion**  
**(To be provided by customer)**

- 1.0 Foundation and any civil building work
- 2.0 Dismantling of existing equipment, if any.
- 3.0 Compressed air piping including compressor
- 4.0 Incomer cable and power supply up to Shubham Pack control panel.
- 5.0 Voltage stabilizer of suitable capacity in case voltage and frequency variation is more than 10% & 3% respectively at site.
- 6.0 Bulk material/Laminate during Factory acceptance test (FAT)
- 7.0 Special tools and tackles like cranes, lifts etc., at the time of installation.
- 8.0 Skilled and unskilled man power at site along with qualified supervisor to assist installation.



**Annexure-IV**  
**Price Schedule**

| S No. | Tech. Specs & Scope of supply                       | Qty. | Total Price<br>(In USD) |
|-------|-----------------------------------------------------|------|-------------------------|
| 1.0   | Machine Model SPM 500P-4A-VCF-Twin Head Collar Type | 01   | 60,000.00               |
| 2.0   | Conveyor (Optional) - 2000 X 2 = 4000 USD           | 02   | 4,000.00                |
| 3.0   | Dust Collector (2HP) (Optional)                     | 01   | 3,000.00                |
| 4.0   | TTO Printer – 5000 x 2 = 10000 USD                  | 02   | 10,000.00               |
| 5.0   | Changeover Parts for 200g & 500g ( 4 X 2500 USD)    | 01   | 10,000.00               |
| 6.0   | Servo Stabilizer                                    | 01   | 1,500.00                |
| 7.0   | 1 Year Consumable Spares                            | 01   | 3,500.00                |

| S No. | Item description                                                                                          | Total Price<br>(In USD)         |
|-------|-----------------------------------------------------------------------------------------------------------|---------------------------------|
|       | <b><u>Model-SPM 500P-4A-VCF-TWIN HEAD</u></b>                                                             |                                 |
| A     | Lump sum price of design, manufacturing, supply of machine as per technical specifications at Annexure-II | 92,000.00                       |
|       | Special Discount Given                                                                                    | -9,200.00                       |
|       | Cost After Special Discount                                                                               | 82,800.00                       |
| B     | Packing and forwarding (4.5%)                                                                             | 2,000.00                        |
| C     | Installation and training at site<br>(for details refer terms & conditions attached)                      | Separate<br>quote will<br>share |
|       | <b>*Ex-Works Cost of Machine</b><br>In words: US DOLLARS, Eighty four thousand, eight hundred only.       | 84,800.00                       |



**Shubham Pack®**  
PACK WITH CONFIDENCE!

## **Annexure-V** **Commercial terms and conditions**

### **PRICE BASIS**

All prices are on **Ex-works Ballabgarh Basis** unless otherwise specified.

### **TERMS OF PAYMENT**

- a) **50% Advance along with purchase order.**
- b) **40% After the FAT of machine before dispatch.**
- c) **10% After the Installation & Commissioning of machine**

Supplier's Bankers, as per the below details:

**Axis Bank Ltd.**  
**SCO-40, Sec-7 Market**  
**Ballabgarh, Faridabad 121004**  
**Haryana, India**  
**A/c holder name- Shubham Flexible Packaging Machines Pvt. Ltd.**  
**A/c no.- 039010200025364**  
**Swift code- AXISINBB039**

The Letter of Credit must permit **partial shipment** and transshipment and should be valid for negotiation for a period of 21 days beyond the last permissible date of shipment.

The Letter of Credit must accept **Combined Transport Bill of Lading** issued by the Shipping Company in New Delhi as a negotiable document.

### **PACKING & FORWARDING (P&F):**

In strong seaworthy wooden boxes

### **INSURANCE: -**

**Buyer's responsibility** to take suitable insurance for goods from seller's warehouse in Ballabgarh to the port of discharge covering all risks including erection, installation and commissioning for 110% of CIF value. Documentary evidence of this insurance to be given to us at least 30 days before shipment

### **FREIGHT**

Extra at Actuals, or Shipping line to be arranged by Buyer.

### **DELIVERY:-**

**Within 3months** from the date of receipt of advance or within 3months from the date of receipt of LC, whichever is later.

### **INSTALLATION / START- UP AND TRAINING**

To be done by factory trained engineers of Shubham pack or its authorized sub suppliers. The installation cost is indicated separately in the price schedule at Annexure-IV.

**Buyer has to provide Hotel, Food, local conveyance and medical expenses for all service engineers at customer site.**



In case our engineer has to stay back after **3 days** or has to revisit for the reason not attributed to Shubham, then the Buyer has to bear expenses for extra to and fro air fares, if any, stay in hotel, food, local transport and medical expenses for deputing engineers and also reimburse out of pocket expenses @ **USD 450** per day per including the travel time and intervening holidays.

Local Labour, Power and other connected items including lifting, tackle, foundation and masonry work during installation shall have to be provided by the Buyer.

Buyer is advised to unload the machine from the truck/container and place it at designated place. It is also advisable that inlet of bulk feed, air connection, power supply etc. should be made ready before arrival of Installation engineer. However, all such connections as well as electrical power ON should be done in presence of installation engineer only.

#### **FREE SPARES & START UP PARTS:**

We shall be supplying one lot of requisite start up parts and standard recommended spares along with the equipment.

#### **GURANTEE**

We guarantee for a period of 12 months from the date of erection of products at Buyer's site, all products and parts thereof, when properly installed, adjusted, operated and maintained as per our proposal and / or the applicable technical manuals. This will however not include components made of rubber, plastic and electrical equipment and other parts / components subject to normal wear and tear.

Guarantee does not cover Electrical Switchgears, hoses, belts, burnt out Blowers / Motors, Drives and all external wiring. These parts are considered as consumables and are required to be paid for upon replacement.

Guarantee does not cover damage of part due to poor preventive maintenance OR parts that are subject to damage due to voltage fluctuation or improper voltage at buyer site.

Guarantee does not apply to any equipment which has been improperly installed, adjusted, operated, maintained, repaired or altered by unauthorized persons. We reserve the right to inspect any claimed defect prior to replacement.

We will replace/repair, any defective material or workmanship, provided that we are given written notice of the claimed defects above. Unless caused by us, equipment damaged by overloading, exposure to corrosive or abrasive substance of abnormal dampness or other misuse, neglect or accident, shall not be subject to the warranty set forth above.

The Guarantee as referred to above clause will cease to operate if:

a. The buyer, within the guarantee period, sells or otherwise parts with possession of the products.

AND / OR

b. Any local mechanic or electrician tampers with the Products without Shubham's written permission.

AND / OR

c. The buyer shifts the Products from original place of installation.

AND/OR

d. The buyer changes the original place of installation.



### **LIABILITY**

Liability of Shubham Flexible Packaging Machines Pvt. Ltd is limited to guarantee performance of equipment and does not cover any aspect related to conversion of material. Shubham Flexible Packaging Machines Pvt. Ltd undertakes no responsibility on performance of laminate/film converted on the equipment. Customer must conduct trials at his own risk and cost, to evaluate and achieve satisfactory results before commencing large-scale production. Machine speed and performance are indicative and may vary with different substrates and raw material and may not be accurate. Liability of Shubham Flexible Packaging Machines Pvt. Ltd is only limited to replacement of defective parts and does not cover any incidental or consequential loss to customer.

### **CANCELLATION**

In the event of a request to stop work or to cancel any part of the order:

- a. Any cancellation after half the stipulated time of delivery must be paid in full.
- b. Cancellation of any order other than outlined in "a" above shall be subject to indemnity satisfaction of Shubham Flexible Packaging Machines Pvt. Ltd.
- c. Special machines: If a special machine is ordered by the customer and has entered into production stage, it shall not be cancelled and must be paid in full.

### **FORCE MAJEURE:**

We will not be responsible for any delay in delivery or for non-delivery of our products by reasons of Force Majeure, such as acts of God, war, riots, civil disturbances, acts of authorities, strikes, lockouts or other labour difficulties or any other circumstances beyond our control which might affect us or our suppliers and hinder, impede or prevent deliveries. The notice of force majeure will be sent by us to customer in writing.

### **APPROVAL**

Shubham Flexible Packaging Machines Pvt. Ltd will fully assemble the equipment prior to shipping and a representative of the customer must approve the Equipment in writing prior to shipment. Any modification or change suggested at this point will invalidate the delivery date clause and reasonable time will be allowed to incorporate the modification.

### **ARBITRATION**

Any dispute or differences whatsoever arising between the parties out of or relating to the construction, meaning and operation or effect of this contract or the breach thereof shall be settled by arbitration in accordance with the Rules of Arbitration of the Indian Council of Arbitration and the Award made in pursuance thereof shall be binding on the parties.

### **VALIDITY:**

This Contract and prices are valid for 30 days and supersedes all previous contracts. The terms and conditions mentioned above shall supersede any terms and conditions agreed to earlier proforma invoice if any.

### **GENERAL**

Continuous improvement is standard policy at Shubham. Accordingly, all specification and features are subject to change without any prior notice.

=====X=====