

HINDUSTAN PETROLEUM CORPORATION LIMITED

(A Government of India Enterprise)

QUALITY CONTROL LABORATORY

MAZGAON TERMINAL

LUBE PLANT, HAY BUNDER ROAD, MAZGAON

MUMBAI,400033

LABORATORY TEST REPORT**HP MILCY NO. 1 PLUS (210 L)(2108241)**

Laboratory Serial No.	FB 1640	Sample Drawn By	QC OFFICER
JDE Serial No	1214061	Date Sample Drawn	14/01/23
Batch No / Lot No	M1-23-A-404	Date Received In Lab	14/01/23
Work Order No	1013256	Date Tested	14/01/23
Tank /Kettle/Location	WHS	Particular of Sample	DRUM
Plant Code/ Name		Sampling Plan	IS 1447

Test Line Number	Test Description/ Characteristics	Units	Test Method	Specifications		Result Value
				Min	Max	
1	APPEARANCE	.	VISUAL	B&C	B&C	B&C
2	CCS @ -20°C	Centi Poise	IS1448(P108),ASTMD5293	-	7000	6548
3	DENSITY@29.5°C	gm/cc	P16 D4052 D1298 D7042	-	-	.8627
4	FLASHPOINT,COC	°C	IS1448(P69), ASTMD92	214	-	236
5	SULFATED ASH	%Wt	IS1448(P4), ASTMD874	.992	1.650	1.300
6	TBN	mg KOH/g	IS1448(P86),ASTMD2896	9.90	-	10.19
7	ZINC	%Wt	ASTMD6443, EDTA	.089	.126	.113
8	KV @ 100°C	cSt	IS1448(P25),ASTMD445,D7042	14.00	15.00	14.58
9	POUR POINT	°C	IS1448 (P10), ASTM D97	-	-24	-33
10	VISCOSITY INDEX (VI)	.	IS1448(P56), ASTM D2270	120	-	137

Remarks : FOAMING(I)-0/0,II-30/0,0/0 Sample meets the specification in above tests.

Note:

- 1) The report refers only to the sample tested.
- 2) The test report shall not be reproduced except in full without prior written approval of the Lab Incharge.
- 3) This test report shall not be used in any advertising media or as evidence in the Court of Law without prior written consent of Laboratory.
- 4) Test results reported are valid at the time of testing
- 5) This is a system generated test report and hence does not require signature.

Reviewed and Authorized by:
PARVEEN RUBANA(31989940)