



**HINDUSTAN PETROLEUM CORPORATION LIMITED**  
**(A Government of India Enterprise)**  
**QUALITY CONTROL LABORATORY**  
MAZGAON LUBE PLANT  
HAY BUNDER ROAD, MAZGAON  
MUMBAI - 400033, MAHARASHTRA  
**LABORATORY TEST REPORT**



|                              |                                              |                             |                          |
|------------------------------|----------------------------------------------|-----------------------------|--------------------------|
| Product                      | 0254241 ( HP ENKLO 68 - DRUM 210L (0.9 MM) ) | Test Report Number          | 4546232401511            |
| Loc/ Customer/ Supplier      | 4546 ( MAZGAON TML LUBES )                   | Sample Number               | 40000002918              |
| Process/Purchase/Sales Order | 10005202 4902288107 0001                     | Lab Sr. No                  | FB 595                   |
| Source of the Sample         | DRUM                                         | ULR Number                  | TC-5177230000001511F     |
| Tank No.                     | WHS1 (Lube Warehouse 1)                      | Date of Sampling            | 06.09.2023 12:02:04      |
| Type of the Sample           | COMPOSITE                                    | Date of Receipt of Sample   | 04.09.2023               |
| Number/Quantity of Sample    | 1*1 L                                        | Date(s) of Sample Testing   | 04.09.2023 To 04.09.2023 |
| Batch No.                    | M1-23H0552                                   | Date of Issue of the Report | 06.09.2023 12:28:19      |
| Stock Represented            | 645.000 EA                                   | Sample Drawn By             | QC OFFICER               |
| Test Required                | FB                                           |                             |                          |
| Sampling Plan/Method         | IS 1447                                      | Seal No.                    | Wooden Box Seal          |
| Reason for Testing           | PRODUCTION - DRUM                            |                             | Aluminium Box Seal       |

| S.No | Characteristics                         | UOM               | Test Method | Specifications              | Result           |
|------|-----------------------------------------|-------------------|-------------|-----------------------------|------------------|
| 1    | ACIDITY, TOTAL                          | mgKOH/g           | ASTM D974   | MAX 1.50                    | 0.61             |
| 2    | APPEARANCE                              | -                 | VISUAL      | BRIGHT AND CLEAR            | BRIGHT AND CLEAR |
| 3    | DENSITY AT 29.5°C                       | g/cm <sup>3</sup> | ASTM D7042  | 0.8000 - 0.9500             | 0.8772           |
| 4    | FLASH POINT, COC                        | °C                | ASTM D92    | MIN 210                     | 238              |
| 5    | EMULSION CHARACTERISTICS AT 54°C/20 MIN | -                 | ASTM D1401  | NOT WORSE THAN 40-37-3 (20) | 40-37-3 (20)     |
| 6    | FOAM STABILITY SEQUENCE I               | mL                | ASTM D892   | 0 - 0                       | 0                |
| 7    | FOAM STABILITY SEQUENCE II              | mL                | ASTM D892   | 0 - 0                       | 0                |
| 8    | FOAM STABILITY SEQUENCE III             | mL                | ASTM D892   | 0 - 0                       | 0                |
| 9    | KINEMATIC VISCOSITY AT 100°C            | cSt               | ASTM D7042  | TO REPORT                   | 8.234            |
| 10   | KINEMATIC VISCOSITY AT 40°C             | cSt               | ASTM D7042  | 62.00 - 74.00               | 62.80            |
| 11   | POUR POINT                              | °C                | ASTM D97    | MAX 0                       | -9               |
| 12   | VISCOSITY INDEX                         | -                 | ASTM D2270  | MIN 90                      | 99               |
| 13   | ZINC CONTENT                            | %Wt               | ASTM D6443  | 0.026 - 0.070               | 0.034            |
| 14   | RUST TEST AT 60°C, 4 HOURS, SSW         | -                 | ASTM D665   | PASS                        | PASS             |

Remarks : The Sample meets the Specification in the above tested parameters only.

**Tested By:**  
PAKALE SANTOSH BHIKAJI (38031160)

**Reviewed and Authorised By:**  
PAKALE SANTOSH BHIKAJI (38031160)

Note:  
1) The sample is drawn by client and results apply to the sample as received.  
2) The test report shall not be reproduced except in full without prior written approval of the Lab In-charge.  
3) This test report shall not be used in any advertising media or as evidence in the Court of Law without prior written consent of Laboratory.  
4) Test results reported are valid for the sample tested, which was provided at the time of testing.  
5) The details of sample submitted is provided by sender / customer. The authenticity / correctness of the submitted data is the responsibility of the sender/customer.  
6) This is a system generated test report. Hence, it does not require signature.

