

HINDUSTAN PETROLEUM CORPORATION LIMITED

(A Government of India Enterprise)

QUALITY CONTROL LABORATORY

MAZGAON TERMINAL

LUBE PLANT, HAY BUNDER ROAD, MAZGAON

MUMBAI,400033

LABORATORY TEST REPORT**HYLUBE MILCY 40 DRUM 210 LIT(0605241)**

Laboratory Serial No.	FB 1509	Sample Drawn By	OPNS OFFICER
JDE Serial No	1206780	Date Sample Drawn	22/12/22
Batch No / Lot No	M2-22-M-959	Date Received In Lab	22/12/22
Work Order No	1006502	Date Tested	22/12/22
Tank /Kettle/Location	WHS2	Particular of Sample	DRUM
Plant Code/ Name	14546	Mazgaon TML Lubes-(STP 0101)	Sampling Plan IS 1447

Test Line Number	Test Description/ Characteristics	Units	Test Method	Specifications		Result Value
				Min	Max	
1	APPEARANCE	.	VISUAL	B&C	B&C	B&C
2	HYLUBE MILCY 40 CALCIUM	%Wt	P 77 D 4628 EDTA	.310	.400	.356
3	DENSITY @ 29.5°C	gm/cc	P16 ,ASTM D1298, D4052, D7042	.8000	.9500	.8934
4	FLASH POINT,COC	°C	IS1448(P69), ASTM D92	215	-	248
9	SULFATED ASH	%Wt	IS1448(P4), ASTM D874	1.29	1.58	1.48
10	TBN	mg KOH/g	IS1448(P86), ASTM D2896	9.70	15.00	10.35
11	ZINC	%Wt	ASTM D6443, EDTA	.0960	.1177	.1051
5	KV @ 100°C	cSt	IS 1448(P25),ASTM D445, D7042	14.00	15.20	14.13
6	KV @ 40°C	cSt	IS 1448(P25),ASTM D445, D7042	-	-	140.6
7	POUR POINT	°C	IS1448 (P10), ASTM D97	-	-6	-15
8	VISCOSITY INDEX (VI)	.	IS1448(P56), ASTM D2270	95	-	141

Remarks : SAMPLE MEETS THE SPECIFICATION IN ABOVE TESTS

Note:

- 1) The report refers only to the sample tested.
- 2) The test report shall not be reproduced except in full without prior written approval of the Lab Incharge.
- 3) This test report shall not be used in any advertising media or as evidence in the Court of Law without prior written consent of Laboratory.
- 4) Test results reported are valid at the time of testing
- 5) This is a system generated test report and hence does not require signature.

Reviewed and Authorized by:

AGARWALLA PRIYANKA(31960370)