Repository Verification (Amna's doc — Item 3)

Date of verification: 2026-08-17 **Verified by:** Ghulam (developer)

1. Repository details

Field	Value
Client-owned repository URL	https://github.com/physioguidance1-arch/physioguidance
Redirect from developer account	https://github.com/GHULAM-1/physioguidance → auto-redirects to the client repo above (GitHub transfer redirect)
Default production branch	`main`
Staging/development branch structure	Single-branch trunk model. Feature work happens on short-lived feature branches (e.g. `feat/*`, `fix/*`, `refactor/*`) then squash-merged into `main`. Every push to `main` auto-deploys to production via GitHub Actions (WIF, no local secrets).
Currently open long-lived branches	`refactor/api-worker-split` (mostly merged, retained for reference) — see `git branch -a` for full list; nothing else long-lived.
Latest production commit (SHA)	`33410aed9860385de3e89d151d9dd1d87ef66687`
Latest production commit (message)	`fix(pdpl): sensitive-data toggle now reflects state + optimistic UI`
Latest deploy timestamp	2026-08-16 18:00 UTC (all 3 services green — see GitHub Actions run history)
Tags	None currently in use (trunk-based deploy model — see "Rollback" section for how prior revisions are pinned via Cloud Run's built-in revision history)

2. Confirmations

✅ Currently deployed production version corresponds to code in the repository

The `main` branch HEAD (`33410aed`) is the source that built the currently-serving Cloud Run image tags:

- Backend: `me-central2-docker.pkg.dev/nelc-elearning-platform-479319/physioguidance-repo/physioguidance-api:33410aed...`
- Frontend: `...:33410aed...`
- Strapi: `...` (built from same commit on Strapi CI run)

To re-verify at any time from a clean machine:

```
git clone https://github.com/physioguidance1-arch/physioguidance.git
cd physioguidance
git log -1 --format="%H %s"   # should match the currently deployed SHA
```

✅ No uncommitted production changes on any developer machine

Confirmed via `git status` on the primary developer machine as of 2026-08-17:

- 0 uncommitted source files (backends/, frontend/, strapi/, infra/)
- 0 unpushed local commits
- Only untracked items are the handover deliverables folder (`~/Desktop/PhysioGuidance-Handover/`), a scratch `amna-doc.docx` , and 3 PDF files marked for deletion — none are production artifacts.

✅ All infrastructure/deployment scripts used for production are committed

Every script that runs against production lives in the repo:

Path	Purpose
`infra/backend/deploy.sh`	Cloud Run deploy for `physioguidance-api`
`infra/worker/deploy.sh`	Cloud Run deploy for `physioguidance-api-worker`
`infra/frontend/deploy.sh`	Cloud Run deploy for `physioguidance-web`
`infra/strapi/deploy.sh`	Cloud Run deploy for `physioguidance-cms`
`infra/malware-scanner/deploy.sh`	Cloud Run deploy for `physioguidance-malware-scanner` + Eventarc triggers
`infra/scripts/migrate-production.sh`	Cloud SQL migration runner via cloud-sql-proxy
`infra/scripts/setup-*.sh`	One-shot job creation scripts (captions, transcode, wcag)
`.github/workflows/deploy-backend.yml`	CI trigger for backend + worker
`.github/workflows/deploy-worker.yml`	CI trigger for worker (chains after backend)
`.github/workflows/deploy-strapi.yml`	CI trigger for Strapi
`.github/workflows/deploy-frontend.yml`	CI trigger for frontend

✅ No production dependency on developer's personal machine

- All deploys run in GitHub Actions runners (`ubuntu-latest`) using Workload Identity Federation. **No JSON key files anywhere.**
- No production secrets on developer laptops — they live only in GCP Secret Manager, read at runtime by the per-service runtime service accounts.

- No cron / scheduled task runs on any developer machine — all scheduling is Cloud Scheduler + Cloud Run Jobs.

3. How a newly authorized developer can verify + deploy from a clean machine

```
# 1. Clone
git clone https://github.com/physioguidance1-arch/physioguidance.git
cd physioguidance

# 2. Install gcloud SDK (any OS) and auth
gcloud auth login
gcloud config set project nelc-elearning-platform-479319

# 3. (Trigger a deploy) Push a commit to main OR re-run the last CI workflow
git commit --allow-empty -m "chore: verify CI ownership from new machine"
git push origin main

# 4. Watch it deploy
gh run watch --exit-status

# 5. Verify
curl https://api.physioguidance.org/api/health/ready
# Expected: {"status":"ok",...}
```

The developer needs (a) commit access on the GitHub repo and (b) `gcloud auth login` with an account that has, at minimum, `roles/run.admin` — everything else flows from Workload Identity Federation.

4. Rollback

Cloud Run keeps a **revision history** of every deployed image. To roll back a service:

```
# List revisions
gcloud run revisions list --service=physioguidance-api --region=me-central2

# Roll back to a specific revision (100% traffic)
gcloud run services update-traffic physioguidance-api \
  --region=me-central2 \
  --to-revisions=<REVISION_NAME>=100
```

Same for `physioguidance-web`, `physioguidance-cms`, `physioguidance-api-worker`, `physioguidance-malware-scanner`. Rollback is atomic (traffic switch is instant), safe (no image rebuild), and reversible (roll forward the same way).

For Cloud Run Jobs, revisions are also retained — re-execute a prior revision via the console or `gcloud run jobs execute --revision=<NAME>`.

5. Ownership status

- ✅ **GitHub repo:** owned by `physioguidance1-arch` (client-owned org). Developer's original repo now returns a redirect.
- ✅ **GCP project (`nelc-elearning-platform-479319`):** Amna is Owner.
- ✅ **Cloud Run runtime service accounts:** created + granted by Amna via her setup script.
- ⏳ **Third-party service ownership:** see `third-party-services-ownership.md` (this handover folder) for the full per-service table.