

UNIT-III: Grammar Formalism

Objective:

To understand regular grammars and context free grammars.

Syllabus:

Grammars, Chomsky hierarchy of languages, regular grammars - right linear and left linear grammars, equivalence between regular linear grammar and FA, Contextfree grammars, derivation trees, sentential forms, rightmost and leftmost derivation of strings, ambiguity in context free grammars, Minimization of context free grammars.

Learning Outcomes:

Students will be able to:

- understand Chomsky hierarchy of languages.
- understand and construct the regular grammar for the given regular language or regular expression.
- convert Regular Grammar into equivalent DFA and viceversa.
- construct Context free grammar for the given language.
- construct right most, left most derivation and derivation trees for the given string and grammar.
- Ambiguity and Minimization of Context free grammar

Learning Material

3.1 Chomsky hierarchy of languages:

The four classes of languages are often called the Chomsky hierarchy, after Noam Chomsky, who defined these classes as potential models of natural languages.




Fig:4.1 **Chomsky hierarchy**

Chomsky classifies the grammar into four types:

Table:4.1Types of Grammar

Grammar	Languages	Automaton	Production rules
Type 0	Recursively enumerable/ Phrase Structured	Turing machines	$\alpha \rightarrow \beta$
Type 1	Context-sensitive	Linear-bound automata	$\alpha \rightarrow \beta$ $ \alpha \leq \beta $
Type 2	Context-free	Push-down automata	$A \rightarrow \alpha$
Type 3	Regular	Finite-state automata	$A \rightarrow w$ $A \rightarrow wB$ $A \rightarrow Bw$

3.1.1Regular Grammar:

A right- or left-linear grammar is called a regular grammar.

Right-Linear Grammar:

If all productions of a grammar are of the form $A \rightarrow wB$ or $A \rightarrow w$, where A and B are variables and w is a (possibly empty) string of terminals, then we say the grammar is right-linear.

Example:

Represent the language $0(10)^*$ by the right-linear grammar.

The language generated by the given Regular Expression is

$$L = \{0, 010, 01010, 0101010, \dots\}$$

Right-Linear Grammar:

$$S \rightarrow 0A$$

$$A \rightarrow 10A \mid \epsilon$$

Left-Linear Grammar:

If all productions are of the form $A \rightarrow Bw$ or $A \rightarrow w$, we call it left-linear.

Example:

Represent the language $0(10)^*$ by the left-linear grammar.

The language generated by the given Regular Expression is

$$L = \{0, 010, 01010, 0101010, \dots\}$$

Left-Linear Grammar:

$S \rightarrow S10 \mid 0$

Equivalence of regular grammars and finite automata:

A language is regular if and only if it has a left-linear grammar and if and only if it has a right-linear grammar.

Construction of a Regular Grammar for a given DFA:

Let $M = (\{q_0, q_1 \dots q_n\}, \Sigma, \delta, q_0, F)$. We construct G as $G = (\{A_0, A_1, \dots, A_n\}, \Sigma, P, A_0)$

where P is defined by the following rules:


- (i) $A_i \rightarrow aA_j$ is included in P if $\delta(q_i, a) = q_j \notin F$.
- (ii) $A_i \rightarrow aA_j$ and $A_i \rightarrow a$ are included in P if $\delta(q_i, a) = q_j \in F$.

Note: We can construct only right linear grammar for the given DFA.

If we want to construct **left linear grammar** for the given DFA, reverse the edges of the given DFA and interchange initial and final states.

Example:

1. **Construct regular grammar (right linear grammar) for the given DFA.**



Given $M = (\{q_0, q_1\}, \{a, b\}, \delta, q_0, \{q_1\})$

Construct $G = (\{A_0, A_1\}, \{a, b\}, P, A_0)$ where P is given by

- (i) $A_i \rightarrow aA_j$ is included in P if $\delta(q_i, a) = q_j \notin F$.
 $\delta(q_0, a) = q_0 \notin F \Rightarrow A_0 \rightarrow aA_0$
- (ii) $A_i \rightarrow aA_j$ and $A_i \rightarrow a$ are included in P if $\delta(q_i, a) = q_j \in F$.
 $\delta(q_0, b) = q_1 \in F \Rightarrow A_0 \rightarrow bA_1$ and $A_0 \rightarrow b$
 $\delta(q_1, a) = q_1 \in F \Rightarrow A_1 \rightarrow aA_1$ and $A_1 \rightarrow a$
 $\delta(q_1, b) = q_1 \in F \Rightarrow A_1 \rightarrow bA_1$ and $A_1 \rightarrow b$

$\therefore P$ is given by

$A_0 \rightarrow aA_0, \quad A_0 \rightarrow bA_1, \quad A_0 \rightarrow b$
 $A_1 \rightarrow aA_1, \quad A_1 \rightarrow a, \quad A_1 \rightarrow bA_1, \quad A_1 \rightarrow b$


Steps to convert Finite Automata to Left Linear Grammar:

Step 1: Reverse all the edges of the given automata and interchange initial state and final states.


Step 2: Represent the productions using Left Linear Grammar.

Example:

2. **Construct left linear grammar for the given DFA.**



Step 1: Reverse all the edges of the given automata and interchange initial state and final states.



Step 2: Represent the productions using Left Linear Grammar.

$B \rightarrow Ba$	$B \rightarrow Aa$
$B \rightarrow Bb$	$B \rightarrow a$

3.1.2 Construction of a DFA for a given Regular Grammar:

Let $G = (\{A_0, A_1, \dots, A_n\}, \Sigma, P, A_0)$. We construct a DFA M whose

- (i) states correspond to variables.
- (ii) initial state corresponds to A_0 .
- (iii) transitions in M correspond to productions in P . As the last production applied in any derivation is of the form $A_i \rightarrow a$, the corresponding transition terminates at a new state, and this is the unique final state.

We define M as $(\{q_0, q_1, \dots, q_n, q_f\}, \Sigma, \delta, q_0, \{q_f\})$ where δ is defined as follows:

- (i) Each production $A_i \rightarrow aA_j$ induces a transition from q_i to q_j with label a ,
- (ii) Each production $A_k \rightarrow a$ induces a transition from q_k to q_f with label a .

Example:

1. $G = (\{A_0, A_1\}, \{a, b\}, P, A_0)$ where P consists of $A_0 \rightarrow aA_1$, $A_1 \rightarrow bA_1$, $A_1 \rightarrow a$, $A_1 \rightarrow bA_0$. Construct a DFA M accepting $L(G)$.


$A_0 \rightarrow aA_1$ induces a transition from q_0 to q_1 with label a .

$A_1 \rightarrow bA_1$ induces a transition from q_1 to q_1 with label b .

$A_1 \rightarrow bA_0$ induces a transition from q_1 to q_0 with label b .

$A_1 \rightarrow a$ induces a transition from q_1 to q_f with label a .

$M = (\{q_0, q_1, q_f\}, \Sigma, \delta, q_0, \{q_f\})$, where q_0 and q_f correspond to A_0 and A_1 respectively and q_f is the new final state introduced.




2. Construct Finite Automata for the grammar which consists of the productions

$A \rightarrow aB \mid bA \mid b$

$B \rightarrow aC \mid bB$

$C \rightarrow aA \mid bC \mid a$



3.2 Context-Free Grammar:

A context-free grammar (CFG or just grammar) is denoted $G = (V, T, P, S)$, where

- V and T are finite sets of variables and terminals, respectively.
- P is a finite set of productions; each production is of the form $A \rightarrow \alpha$, where A is a variable and α is a string of symbols from $(V \cup T)^*$.
- S is a special variable called the start symbol.

The language generated by G [denoted $L(G)$] is $\{w \mid w \text{ is in } T^* \text{ and } S \xRightarrow{*} w\}$. That is, a string is in $L(G)$ if:

- 1) The string consists solely of terminals.
- 2) The string can be derived from S .

We call L a context-free language (CFL) if it is $L(G)$ for some CFG G .

Note: C language is an example for Context Free Language.

Examples:

1. Write CFG for the language $L = \{a^n b^n \mid n \geq 1\}$.

$L = \{ab, aabb, aaabbb, aaaabbbb, aaaaabbbbb, \dots\}$

$G = (\{S\}, \{a, b\}, P, S)$

P: $S \rightarrow aSb \mid ab$

(Or)

$S \rightarrow aSB$

$S \rightarrow aB$

$B \rightarrow b$

2. Write CFG for the language $L = \{a^n b^m \mid n, m \geq 1\}$.

$L = \{a, b, ab, aab, abb, aabb, aaabbb, aaaabbbb, \dots\}$

$G = (\{S, A, B\}, \{a, b\}, P, S)$

P: $S \rightarrow AB$

$A \rightarrow aA \mid a$
 $B \rightarrow bB \mid b$

3. Write CFG for the language $L=\{aa,ab,ba,bb\}$

$G = (\{S, A\}, \{a, b\}, P, S)$
 $P: \quad S \rightarrow AA$
 $\quad A \rightarrow a \mid b$

4. Write CFG for the language $L = \{a^n \mid n \geq 0\}$.

$L = \{\epsilon, a, aa, aaa, aaaa, aaaaa, aaaaaa, \dots\}$
 $G = (\{A\}, \{a\}, P, A)$
 $P: \quad A \rightarrow aA \mid \epsilon$

5. Write CFG for the regular expression $(a+b)^*$.

$L = \{\epsilon, a, b, aa, ab, ba, bb, aaa, abb, aba, \dots\}$
 $G = (\{S\}, \{a, b\}, P, S)$
 $P: \quad S \rightarrow aS \mid bS \mid \epsilon$

6. Write CFG to generate all strings of $\{a, b\}$ whose length is atleast 2.

$L = \{aa, ab, ba, bb, aaa, abb, aba, \dots\}$
 $G = (\{S, A, B\}, \{a, b\}, P, S)$
 $P: \quad S \rightarrow AAB$
 $\quad A \rightarrow a \mid b$
 $\quad B \rightarrow aB \mid bB \mid \epsilon$

7. Write CFG to generate all strings of $\{a, b\}$ whose length is atmost 2.

$L = \{\epsilon, a, b, aa, ab, ba, bb\}$
 $G = (\{S, A\}, \{a, b\}, P, S)$
 $P: \quad S \rightarrow AA$
 $\quad A \rightarrow a \mid b \mid \epsilon$

8. Write CFG to generate palindromes over $\{a, b\}$.

$L = \{\epsilon, a, b, aa, bb, aba, bab, aaaa, abba, \dots\}$
 $G = (\{S\}, \{a, b\}, P, S)$
 $P: \quad S \rightarrow aSa \mid bSb$
 $\quad S \rightarrow a \mid b \mid \epsilon$

9. Write CFG to generate equal number of a's and b's.

$L = \{ab, ba, aabb, abab, bbaa, baba, \dots\}$
 $G = (V, T, P, S)$, where $V = \{S, A, B\}$, $T = \{a, b\}$, S and P .
 $P: \quad S \rightarrow aB \quad A \rightarrow bAA$
 $\quad S \rightarrow bA \quad B \rightarrow b$
 $\quad A \rightarrow a \quad B \rightarrow bS$

$A \rightarrow aS$ $B \rightarrow aBB$

Sentential Form:

A string of terminals and variables α is called a sentential form if $S \xRightarrow{*} \alpha$.

Derivation:

Derivation is the process of applying productions repeatedly to expand non-terminals in terms of terminals or non-terminals, until there are no more non-terminals.

A derivation can be either Leftmost derivation or Right most derivation.

Leftmost derivation:

If at each step in a derivation a production is applied to the leftmost variable, then the derivation is said to be leftmost.

Example:

Consider the grammar $G = (\{S, A\}, \{a, b\}, P, S)$, where P consists of

$S \rightarrow aAS \mid a$

$A \rightarrow SbA \mid SS \mid ba$

The corresponding leftmost derivation is

$S \Rightarrow aAS \Rightarrow aSbAS \Rightarrow aabAS \Rightarrow aabbAS \Rightarrow aabbbaa$.

Rightmost derivation:

A derivation in which the rightmost variable is replaced at each step is said to be rightmost.

Example:

Consider the grammar $G = (\{S, A\}, \{a, b\}, P, S)$, where P consists of

$S \rightarrow aAS \mid a$

$A \rightarrow SbA \mid SS \mid ba$

The corresponding rightmost derivation is

$S \Rightarrow aAS \Rightarrow aAa \Rightarrow aSbAa \Rightarrow aSbbAa \Rightarrow aabbbaa$.

Note: "If w is in $L(G)$ for CFG G , then w has at least one parse tree, and corresponding to a particular parse tree, w has a unique leftmost and a unique rightmost derivation."

3.3 Derivation Trees (or) Parse tree:

The derivations in a CFG can be represented using trees. Such trees representing derivations are called derivation trees.

Let $G = (V, T, P, S)$ be a CFG. A tree is a derivation (or parse) tree for G if:

- 1) Every vertex has a label, which is a symbol of $V \cup T \cup \{\epsilon\}$.
- 2) The label of the root is S .
- 3) If a vertex is interior and has label A , then A must be in V .

- 4) If n has label A and vertices $n_1, n_2, n_3, \dots, n_k$ are the sons of vertex n , in order from the left, with labels X_1, X_2, \dots, X_k , respectively, then $A \rightarrow X_1 X_2 \dots X_k$ must be a production in P .
- 5) If vertex n has label ϵ , then n is a leaf and is the only son of its father.

Example:


Consider the grammar $G = (\{S, A\}, \{a, b\}, P, S)$, where P consists of

$S \rightarrow aAS \mid a$

$A \rightarrow SbA \mid SS \mid ba$

Construct a derivation tree for the string “aabbbaa”

A derivation tree is a natural description of the derivation of a particular sentential form of the grammar G . If we read the labels of the leaves from left to right, we have a sentential form. We call this string the yield of the derivation tree.



$S \Rightarrow aAS \Rightarrow aSbAS \Rightarrow aabAS \Rightarrow aabbbaS \Rightarrow aabbbaa$.

Note: Some leaves could be labelled by ϵ .

3.4 Ambiguity in context free grammars:

A context-free grammar G is said to be ambiguous if it has two parse trees for some word.

(or)


A word which has more than one leftmost derivation or more than one rightmost derivation is said to be ambiguous.

Note: A CFL for which every CFG is ambiguous is said to be an inherently ambiguous CFL.

Example:

$G = (\{S\}, \{a, b, +, *\}, P, S)$, where P consists of $S \rightarrow S+S \mid S*S \mid a \mid b$

We have two derivation trees for $a + a * b$



Two derivation trees for $a + a * b$

3.5 Minimization of Context Free Grammars:

- 1) Elimination of useless symbols.
- 2) Elimination of ϵ -Productions.
- 3) Elimination of Unit Productions.

Elimination of Useless Symbols:

Let $G=(V, T, P, S)$ be a grammar. A symbol X is useless if it is not involved in derivation.

(or)

A symbol X is useless if there is no way of getting a terminal string from it.

Example:

Consider the grammar

$$\begin{aligned} S &\rightarrow AB \mid a \\ A &\rightarrow a \end{aligned}$$

We find that no terminal string is derivable from B . We therefore eliminate B and the production $S \rightarrow AB$.

Then the grammar is

$$\begin{aligned} S &\rightarrow a \\ A &\rightarrow a \end{aligned}$$

We find that only S and a appear in sentential forms. Thus $(\{S\}, \{a\}, \{S \rightarrow a\}, S)$ is an equivalent grammar with no useless symbols.

Elimination of ϵ -Productions:

A production of the form $A \rightarrow \epsilon$, where A is a variable, is called a *null production*.

If $L = L(G)$ for some CFG $G = (V, T, P, S)$, then $L - \{\epsilon\}$ is $L(G')$ for a CFG G' with no useless symbols or ϵ -productions.

Example:

Consider the grammar

$$A \rightarrow 0B1 \mid 1B1$$
$$B \rightarrow 0B \mid 1B \mid \varepsilon$$

Remove ε -productions from the grammar.

$B \rightarrow \varepsilon$ is the null production.

The new productions after elimination of ε are

$$A \rightarrow 0B1 \mid 1B1 \mid 01 \mid 11$$
$$B \rightarrow 0B \mid 1B \mid 0 \mid 1$$

Elimination of Unit Productions:

A production of the form $A \rightarrow B$ whose right-hand side consists of a single variable is called a unit production.

All other productions, including those of the form $A \rightarrow a$ and ε -productions, are nonunit productions.

Example:

Consider the grammar

$$S \rightarrow 0A \mid 1B \mid C$$
$$A \rightarrow 0S \mid 00$$
$$B \rightarrow 1 \mid A$$
$$C \rightarrow 01$$

Remove unit production from the grammar.

$S \rightarrow C$ and $B \rightarrow A$ are the unit productions

The new productions after elimination of unit productions are

$$S \rightarrow 0A \mid 1B \mid 01$$
$$A \rightarrow 0S \mid 00$$
$$B \rightarrow 1 \mid 0S \mid 00$$
$$C \rightarrow 01$$

C is a useless symbol. So eliminate C production.

The final set of productions are

$$S \rightarrow 0A \mid 1B \mid 01$$
$$A \rightarrow 0S \mid 00$$
$$B \rightarrow 1 \mid 0S \mid 00$$