

# DOORS

Data Orchestration and On-demand Reporting System

## API User and SDK Manual

Secure DOORS integration and automation

| Document ID               | Version | Audience                  | Classification |
|---------------------------|---------|---------------------------|----------------|
| DOORS-API-USER-SDK-MANUAL | 1.0     | API User and Data Manager | NIC INTERNAL   |

# Document control

| Field                | Value                                                       |
|----------------------|-------------------------------------------------------------|
| Title                | API User and SDK Manual                                     |
| Owner                | DOORS Product Governance                                    |
| Version / status     | 1.0 / Approved for initial publication                      |
| Effective date       | 30 August 2026                                              |
| Review cycle         | At every material release or annually                       |
| Audience             | API User and Data Manager                                   |
| Authoritative source | Current DOORS release, configuration and governance records |

## Publication rule

**Use the authenticated DOORS Documentation Hub as the source of truth. Downloaded copies may become obsolete after a release, security change or policy revision.**

## Learning objectives

After completing this manual, the reader should understand the authorized workflow, required evidence, security boundaries and escalation points for the role.

- Complete tasks without bypassing approval controls.
- Recognize information that must not be disclosed.
- Capture identifiers needed for audit and support.

## Credential model

An API key identifies a governed ClientName. Authorization then follows service/query, agent and instance mappings.

- Keep API keys in environment variables or protected secret files.
- Never embed production API keys or private keys in source or release packages.
- Restrict filesystem permissions and rotate exposed credentials.

## TLS setup

Import only a fingerprint-verified DOORS server or issuing-CA certificate into the SDK truststore.

- Do not use trust-all code.
- Verify hostname/SAN compatibility.
- Treat PKIX failures as trust configuration problems, not reasons to disable validation.

## AES response setup

Register client\_public.pem against the same API client used by the SDK. The matching private key remains with the recipient.

- Compare registered and local SHA-256 fingerprints.
- RSA/ECB/PKCS1Padding unwraps the AES-256 key.
- AES/CBC/PKCS5Padding decrypts the response.

- A `BadPaddingException` normally indicates a public/private key mismatch.

## Document downloads

The SDK requests a governed manifest, streams each file to a temporary part, calculates SHA-256 and renames only after verification.

- Preserve correlation IDs.
- Send the destination checksum receipt.
- Apply bounded retries only to safe transient failures.
- Never invent filenames, bid IDs or downstream parameters.

## Operational checklist

- Set connect/read timeouts.
- Enforce size limits.
- Sanitize logged errors.
- Do not log API keys or decrypted data.
- Monitor HTTP status, correlation ID, checksum and per-file outcome.

## Verification and support

Before closing a task, confirm the expected status, audit entry and resulting access. For failures, preserve the timestamp and correlation ID, redact sensitive content, and escalate through the approved support channel.

- Do not share passwords, API keys, private keys or complete sensitive payloads.
- Use the FAQ and Troubleshooting Runbooks for symptom-led diagnosis.