

Openshift

Introduction to the Side Car

Laurent Valeyre

Orange

August 2018




Table of contents

- 1 The base
 - Containers
 - Understanding Pods
 - Main Ways
 - Patterns
- 2 Use case
 - Apache Status
 - Dockerfile
 - Secret Access
 - The application
 - Deployment and Service
- 3 The Monitoring
 - Prometheus
 - Grafana
- 4 Pipeline and CI
- 5 Links




Containers

Figure: Why Containers



Applications on host
heavyweight, non-portable
Relies on OS package manager



Deploy containers
Small and fast, portable
Uses OS-Level virtualization



Understanding Pods

- A *Pod* is the smallest and simplest unit in the Kubernetes object model that we create or deploy.



Understanding Pods

- A *Pod* is the smallest and simplest unit in the Kubernetes object model that we create or deploy.
- A Pod represents a running process on our cluster.



Understanding Pods

- A *Pod* is the smallest and simplest unit in the Kubernetes object model that we create or deploy.
- A Pod represents a running process on our cluster.
 - A *Pod* encapsulates an application container (or, in some cases, multiple containers)



Understanding Pods

- A *Pod* is the smallest and simplest unit in the Kubernetes object model that we create or deploy.
- A Pod represents a running process on our cluster.
 - A *Pod* encapsulates an application container (or, in some cases, multiple containers)
 - A *Pod* storages resources



Understanding Pods

- A *Pod* is the smallest and simplest unit in the Kubernetes object model that we create or deploy.
- A Pod represents a running process on our cluster.
 - A *Pod* encapsulates an application container (or, in some cases, multiple containers)
 - A *Pod* stores resources
 - A *Pod* has a unique network IP



Understanding Pods

- A *Pod* is the smallest and simplest unit in the Kubernetes object model that we create or deploy.
- A Pod represents a running process on our cluster.
 - A *Pod* encapsulates an application container (or, in some cases, multiple containers)
 - A *Pod* stores resources
 - A *Pod* has a unique network IP
- A *Pod* represents a unit of deployment:



Main ways

Pods in a Kubernetes cluster can be used in two main ways:



Main ways

Pods in a Kubernetes cluster can be used in two main ways:

- Pods that run a single container (most common Kubernetes use case)



Main ways


Pods in a Kubernetes cluster can be used in two main ways:

- Pods that run a single container (most common Kubernetes use case)
- Pods that run multiple containers that need to work together (encapsulate an application composed of multiple co-located containers that tightly coupled)



Patterns for Composite Containers: Sidecar

Figure: schema of our Sidecar



Apache status

Module to enable the output statistic of *Apache*.

```
<Location /server-status>
  SetHandler server-status
  Order deny,allow
  Allow from all
</Location> ExtendedStatus On
```

Figure: status.conf

This module has to be copied in the `/etc/apache2/mods-enabled/` directory.



Dockerfile

The *Dockerfile* includes the copy of the *Apache* module
Important to add the switching between *root* and *1001* user

```
FROM ubuntu:latest
USER root
...
RUN a2enmod status
COPY status.conf /etc/apache2/mods-enabled/
EXPOSE 8080
USER 1001
CMD ["/usr/sbin/apache2ctl", "-DFOREGROUND"]
```

Figure: Dockerfile



Secret Access

And because the credential of *GITLAB*, we'll use the login/password based on the token initialized in our profile

```
apiVersion: v1
kind: Secret
metadata:
  name: gitlab-secret
  namespace: cdnapi
type: kubernetes.io/basic-auth
data:
  username: c3Bpa2U=
  password: dmFsZW50aW5l
```

Figure: gitlab-secret.yaml



New Project

It's time to create our new project *cdnapi*, similar to a namespace

```
$ oc new-project cdnapi \  
--display-name='CDN API Project' \  
--description='CDN API Project'
```



Secret Access

The *username* and *password* are encoded to Base64 format. Finally we load the new *secret*

```
$ echo -n 'spike' | base64
c3Bpa2U=
$ echo -n 'valentine' | base64
dmFsZW50aW5l
$ oc create -f gitlab-secret.yaml
```



New Application

It's time to create our application

```
$ oc new-app https://gitlab.forge.orange-labs.fr/\
laov6410/cdnselect.git --name
$ oc set build-secret --source bc/cdnapi gitlab-secret
$ oc expose service cdnapi
$ oc get all name --selector app=cdnapi
```



Item To Modify

2 parts will be modified to adapted to our application

- DeploymentConfig
- Service



DeploymentConfig

We edit *DeploymentConfig*

```
$ oc edit dc/cdnapi
```

and we add

```
spec:
  containers:
  - name: apache-exporter
    image: previousnext/apache-exporter
    command: [ "apache_exporter", "-scrape_uri", \
      "http://127.0.0.1:8080/server-status/?auto" ]
    ports:
    - containerPort: 9117
```

We edit *service*

```
$ oc edit svc/cdnapi
```

```
spec:
  ...
  - name: 9117-tcp
    port: 9117
    protocol: TCP
    targetPort: 9117
```

9117 is The port related to *exporter apache*



Finally

Finally we create our new application from this *yaml* file

```
$ oc get svc --selector "app=cdnapi"
NAME          TYPE          CLUSTER-IP      PORT(S)
selector      ClusterIP      172.30.127.98    8080/TCP,9117/TCP
$ oc describe dc/cdnapi
```

Et voila...



Pull Image

We pull the image for *Prometheus* from the public Docker Hub registry.

```
$ oc new-app prom/prometheus
$ oc new-app grafana/grafana
$ oc expose service prometheus
$ oc expose service grafana
```



Image and configuration decoupled

```
global:
  scrape_interval:      5s
  evaluation_interval: 5s

scrape_configs:
- job_name: 'apache-exporter'
  scheme: http
  static_configs:
- targets: ['faye:9117']
  labels: {'host': 'cdnapi'}
```



Prometheus Configmap

We create the *configmap* including the prometheus configuration and finally edit the *deploymentconfig* prometheus

```
$ oc create configmap prom-config \
--from-file=prometheus.yml
$ oc edit dc/prometheus
```



DeploymentConfig and ConfigMap

Add these 2 blocks of code

```
- name: prom-config-volume
  configMap:
    name: prom-config
    defaultMode: 420
```

```
- name: prom-config-volume
  mountPath: /etc/prometheus/
```



Grafana Configmap

We create the *configmap* including the grafana configuration

```
$ oc create configmap grafana-config \
--from-file=grafana.ini
$ oc edit dc/grafana
```




DeploymentConfig and ConfigMap

Modification in *spec-containers*

```
- image:
  ...
  volumeMounts:
    - name: grafana-config
      mountPath: /etc/grafana/
    ...
  volumes:
    - name: grafana-config
      configMap:
        name: grafana-config
        defaultMode: 420
```

Figure: diagram of different projects



- Project CICD Containing our Jenkins instance
- Development For building and developing our application images
- Testing For testing our application
- Production Hosting our production application



Create Projects

```
$ oc login -u developer -p developer
$ oc new-project cicd --display-name='CICD Jenkins' \
--description='CICD Jenkins'
$ oc new-project development \
--display-name='Development' --description='Development'
$ oc new-project testing --display-name='Testing' \
--description='Testing'
$ oc new-project production --display-name='Production' \
--description='Production'
```




```
$ oc policy add-role-to-user edit \
system:serviceaccount:cicd:jenkins -n development
$ oc policy add-role-to-user edit \
system:serviceaccount:cicd:jenkins -n testing
$ oc policy add-role-to-user edit \
system:serviceaccount:cicd:jenkins -n production
```



```
$ oc policy add-role-to-group system:image-puller \  
system:serviceaccounts:testing -n development  
$ oc policy add-role-to-group system:image-puller \  
system:serviceaccounts:production -n development
```



Deploy a Jenkins ephemeral instance in *cicd* project

```
$ oc project cicd  
$ oc new-app --template=openshift/jenkins-persistent  
$ oc status
```

Let's create the pipeline itself.

```
$ oc create -n cicd -f \  
https://raw.githubusercontent.com/devops-with-openshift/  
/pipeline-configs/master/empty-pipeline.yaml
```



Deployment of the application

```
$ oc project development
$ oc new-app \
https://github.com/gandalf-the-white/faye.git \
--name=cdnapi
$ oc expose svc/cdnapi
```



Deployment based on the *Development image*

```
$ oc get is -n development
$ oc project testing
$ oc create dc cdnapi \
--image=172.30.1.1:5000/development/cdnapi:promoteQA
$ oc rollout cancel dc/cdnapi
```



Patch

Always trigger a deployment when we tag a new image

```
$ oc patch dc/cdnapi -p \
'{"spec":{"template":\
  {"spec":{"containers":\
    [{"name":"default-\
      container","imagePullPolicy":"Always"}\
    ]}}}}}'
$ oc rollout cancel dc/cdnapi
```



Expose

```
$ oc expose dc cdnapi --port=8080  
$ oc expose svc/cdnapi
```



```
$ oc project production  
$ oc create dc cdnapi \  
--image=172.30.1.1:5000/development/cdnapi:promotePRD  
$ oc rollout cancel dc/cdnapi
```



Patch

Always trigger a deployment when we tag a new image

```
$ oc patch dc/cdnapi -p \
'{"spec":{"template":\
  {"spec":{"containers":\
    [{"name":"default-\
      container","imagePullPolicy":"Always"}\
    ]}}}}}'
$ oc rollout cancel dc/cdnapi
```



Expose and create the service

Expose the application and create a route

```
$ oc expose dc cdnapi --port=8080  
$ oc expose svc/cdnapi
```



Run Our Pipeline Deployment

```
$ oc start-build pipeline -n cicd
```



[https://kubernetes.io/blog/2015/06/
the-distributed-system-toolkit-patterns/](https://kubernetes.io/blog/2015/06/the-distributed-system-toolkit-patterns/)
<https://www.robustperception.io/openshift-and-prometheus>
[http://widerin.net/blog/
official-grafana-docker-image-on-openshift/](http://widerin.net/blog/official-grafana-docker-image-on-openshift/)

