

# Openshift

## Introduction to the Side Car


Laurent Valeyre

Orange

August 2018



Figure: schema of a Side Car



# Apache status

Module to enable the output statistic of *Apache*.

```
<Location /server-status>
  SetHandler server-status
  Order deny,allow
  Allow from all
</Location> ExtendedStatus On
```

Figure: status.conf

This module has to be copied in the `/etc/apache2/mods-enabled/` directory.



# Dockerfile

The *Dockerfile* includes the copy of the *Apache* module  
Important to add the switching between *root* and *1001* user

```
FROM ubuntu:latest
USER root
...
RUN a2enmod status
COPY status.conf /etc/apache2/mods-enabled/
EXPOSE 8080
USER 1001
CMD ["/usr/sbin/apache2ctl", "-DFOREGROUND"]
```

Figure: Dockerfile



# Secret Access

And because the credential of *GITLAB*, we'll use the login/password based on the token initialized in our profile

```
apiVersion: v1
kind: Secret
metadata:
  name: gitlab-secret
  namespace: sidecar
type: kubernetes.io/basic-auth
data:
  username: c3Bpa2U=
  password: dmFsZW50aW5l
```

Figure: gitlab-secret.yaml



# Secret Access

The *username* and *password* are encoded to Base64 format. Finally we load the new *secret*

```
$ echo -n 'spike' | base64
c3Bpa2U=
$ echo -n 'valentine' | base64
dmFsZW50aW5l
$ oc create -f gitlab-secret.yaml
```



# New Project

It's time to create our new project *sidecar*, similar to a namespace

```
$ oc new-project sidecar \  
--display-name='Side Car Project' \  
--description='Side Car Project'
```



# New Application

It's time to create our application

```
$ oc new-app https://gitlab.forge.orange-labs.fr/\
laov6410/cdnselect.git --name sidecar
$ oc set build-secret --source bc/sidecar gitlab-secret
$ oc expose service sidecar
$ oc get all name --selector app=sidecar
```





# Item To Modify

2 parts will be modified to adapted to our application

- DeploymentConfig
- Service



# DeploymentConfig

We edit *DeploymentConfig*

```
$ oc edit dc/sidecar
```

and we add

```
spec:
  containers:
  - name: apache-exporter
    image: previousnext/apache-exporter
    command: [ "apache_exporter", "-scrape_uri", \
      "http://127.0.0.1:8080/server-status/?auto" ]
    ports:
    - containerPort: 9117
```



We edit *service*

```
$ oc edit svc/sidecar
```

```
spec:
  ...
  - name: 9117-tcp
    port: 9117
    protocol: TCP
    targetPort: 9117
```

9117 is The port related to *exporter apache*



# Finally

Finally we create our new application from this *yaml* file

```
$ oc get svc --selector "app=selector"
NAME          TYPE          CLUSTER-IP      PORT(S)
selector      ClusterIP     172.30.127.98    8080/TCP,9117/TCP
$ oc describe dc/sidecar
```

Et voila...

