

Task Execution

Task Execution Environment

- ✓ The MapReduce framework executes mapper and reducer tasks in a **Separate JVM Process**.
- ✓ This process inherits the environment of the parent TaskTracker process.
- ✓ The user can specify additional options to the child JVM via the **Mapreduce.Map.Java.Opts**, **Mapreduce.Reduce.Java.Opts** configuration parameters.




The two essential components of the MapReduce framework are

1. **JobTracker**

2. **TaskTracker**

- **Job Tracker** is responsible for **Scheduling And Monitoring** MapReduce jobs.
- **Task Tracker** is responsible for executing **Individual Mapper And Reducer Tasks**.

MapReduce Architecture



Task Environment Properties

Property name	Type	Description	Example
<code>mapreduce.job.id</code>	String	The job ID (see “Job, Task, and Task Attempt IDs” on page 164 for a description of the format)	<code>job_200811201130_0004</code>
<code>mapreduce.task.id</code>	String	The task ID	<code>task_200811201130_0004_m_000003</code>
<code>mapreduce.task.attempt.id</code>	String	The task attempt ID	<code>attempt_200811201130_0004_m_000003_0</code>
<code>mapreduce.task.partition</code>	Int	The index of the task within the job	3
<code>mapreduce.task.ismap</code>	boolean	Whether this task is a map task	true

Speculative Execution – Killing The Slowest Copies

- ✓ Speculative execution is a technique used to improve the performance of MapReduce jobs by **Running Multiple Copies Of The Same Task And Killing The Slowest Copies**.
- ✓ The MapReduce framework determines which tasks to speculate on based on their progress and the overall state of the job.
- ✓ Speculative execution can be **Enabled Or Disabled** by setting the **mapreduce.map.speculative**, **mapreduce.reduce.speculative** configuration parameters.

Speculative Execution Properties

Property name	Type	Default value	Description
<code>mapreduce.map.speculative</code>	boolean	true	Whether extra instances of map tasks may be launched if a task is making slow progress
<code>mapreduce.reduce.speculative</code>	boolean	true	Whether extra instances of reduce tasks may be launched if a task is making slow progress
<code>yarn.app.mapreduce.job.speculator.class</code>	Class	<code>org.apache.hadoop.mapreduce.v2.app.speculate.DefaultSpeculator</code>	The Speculator class implementing the speculative execution policy (MapReduce 2 only)
<code>yarn.app.mapreduce.job.task.estimator.class</code>	Class	<code>org.apache.hadoop.mapreduce.v2.app.speculate.LegacyTaskRuntimeEstimator</code>	An implementation of TaskRuntimeEstimator used by Speculator instances that provides estimates for task runtimes (MapReduce 2 only)


Output Committers – Output is Durable& Consistent

- The output committer is responsible for writing the **output** of a MapReduce job to the Hadoop Distributed File System (**HDFS**).
- The MapReduce framework provides a number of built-in output committers, but the user can also implement their own custom output committer.
- The output committer is responsible for ensuring that the output of the job is durable and consistent (output files are **Not Corrupted And That They Are Properly Synchronized** with the HDFS metadata)

Task Execution Flow

The following is a simplified overview of the task execution flow in MapReduce:

- ✓ The **JobTracker** assigns a mapper or reducer task to a **TaskTracker**.
- ✓ The **TaskTracker** starts a new JVM process to execute the task.
- ✓ The **Task Execution Environment** is initialized with
 - The Input And Output Splits
 - The Mapper Or Reducer Class
 - The Configuration Parameters
 - The Reporter Object

- 
- ✓ The task is executed.
 - ✓ The **Output Committer** is used to write the output of the task to HDFS.
 - ✓ The task execution environment is cleaned up.

If **Speculative Execution** is enabled, the JobTracker may start multiple copies of the same task and kill the slowest copies.