



WaterMind

Intelligence for Commercial and Industrial Meters

WaterMind helps utilities to protect their revenue, improve their operational efficiency and enhance customer satisfaction.

FEATURES AND BENEFITS

- » IP68, compatible with pit conditions
- » Meter index collection for billing
- » Flow and consumption monitoring
- » High capability on pressure monitoring enabling pressure transient detection
- » Real time alarms
- » On-site and remote configuration
- » Easy installation

Robust & reliable hardware

WaterMind housing is rugged for an easy and safe manipulation and is suitable for installation in flooded pits.

Accurate measurement

WaterMind accurately captures pulse input from the meter in both directions, enabling reliable meter index monitoring and flow-rate based analysis. WaterMind samples pressure every second through built-in transducers, enabling high accuracy pressure monitoring and transients detection.

Real time alarms

In the event of a cable cut, important backflow detection or excessive or inadequate flow or pressure, WaterMind immediately sends a SMS to the operations team and data to the server for analysis. Additionally, the system can be configured to send alarms by email.

Software as a Service (SaaS)

WaterMind data management software is provided as a service.

A pay-per point fee minimizes total cost of ownership considering the limited number of large meters to be connected.

Data analysis is available via a web browser from any PC workstation.


Additionally, integration with utility software is easy and flexible.

Approval & Standards

- » IP68 certification
- » RED, Directive 2014/53/EU,
- » ROHS 2 2011/65/UE

CONTRIBUTES TO ALL WATER DISTRIBUTION PROCESSES

WaterMind contributes in generating outcomes for billing of end users as well as for network monitoring.







WATERMIND NETWORK OPERATIONAL EFFICIENCY

WaterMind provides a web portal with advanced outcomes to help utilities to improve network operation and leak detection.

Hydraulic Network Modelling

WaterMind helps to fine-tune the hydraulic model of the distribution network, through permanent monitoring of flow and pressure.

Network Stability Analysis

Instability, pressure surges and transients can be identified using WaterMind to help further understand network stress.

Leakage Assessment

The system reports night flow analysis that is an indicator of potential new leakage inside a DMA.

Water Balance

WaterMind generates a water balance assessment by accurately monitoring water input in both directions.







REVENUE PROTECTION AND C&I END-USER SATISFACTION

Revenue protection outcomes are enabled for utilities due to the advanced features of the WaterMind software including meter right-sizing assessment and meter index monitoring. A web portal option is available to the end-users that allows to increase the level of services provided to key Commercial and Industrial accounts.

Meter Right-Sizing Assessment

Under-sized meters will age quickly while over-sized meters will not capture accurately the whole range of flow consumption.

WaterMind detects wrongly sized end points, and provides analysis to determine the most appropriate meter size to ensure optimized revenue.

C&I and High-End Tariff Scheme

WaterMind allows the utility to determine the service level requirements for water delivery to large industrial accounts or critical applications customers, who have contractual minimum pressure and capacity flow range of supply.

Back Flow Assessment

Water potability can be potentially impacted upstream of the endpoint due to blackflow. WaterMind provides backflow detection to assess this issue.

Abnormal Consumption Pattern Assessment

The system addresses different categories of abnormal consumption patterns, indicating a deviation from normal usage.

Billing

The system offers a daily and reliable index to the utility for billing purposes. WaterMind allows easy and flexible exports to the billing system.

SOFTWARE AS A SERVICE FEATURES




Bi-directional Flow Monitoring

Forward and backward flow-rates are aggregated with different granularity from 1min interval logging data.



Pressure Monitoring

Average, maximum, minimum and standard deviation pressure values are captured for every logging interval, based on 1 second sampling frequency, allowing night analysis and transient detection.



Flow-rate Alerts Monitoring

Thresholds for acceptable high and low flow-rates are configurable to provide visual follow-up of events on the network.



Backflow Monitoring

Backflow information and statistics, aggregated with different granularity, include the volume and the number of occurrences logged during a period.




Index Monitoring

The daily index is captured for accurate and reliable billing.



Real-Time Alert Messages

- » Blocked meter
- » Tamper / cable cut
- » Flow-rate above or below limits
- » Pressure below or above limits
- Backflow detection
- » Low battery
- » Leakage
- » Over/under-sized meter



Meter Right-Sizing Monitoring

Over and under-sized meters are identified together with potential volume loss based on flow-rate segmentation analysis.



Consumption Monitoring

Consumption is aggregated with a granularity of 1min logging intervals.

End-user consumption can be displayed and benchmarked against previous activity periods.

Technical Specifications

| | reclinical opecinications | | | |
|------------------------------|---|---|--|--|
| Inputs | Meter input | 1 bi-directional meter input Compatible with mechanical meter pulse input (2/5 wires) and with bidirectional electromagnetic/static meter pulse input - Max Pulse Frequency: 100Hz - Min Pulse Width: 5ms | | |
| | Pressure input | Up to 2 pressure sensors as option | | |
| Audit | Pressure audit | Continuous high precision pressure monitoring - Better than +/- 0.1% FS (Full Scale) precision - Better than +/- 0.2% FS drift, no need for recalibration in lifetime | | |
| | Internal back-up memory | From 32 days of storage, up to 4 years depending on model (inputs) and logging frequency configuration | | |
| Output | GSM / GPRS / UMTS 2G /3G | Daily data transmission via GPRS / UMTS network Real-Time Alarms via short messages (SMS) and GPRS / UMTS | | |
| Installation and Maintenance | Protection class | IP68 enclosure compatible with pit conditions | | |
| | Operating temperatures | -10°C to + 50°C | | |
| | SIM card | Internal slot mounting. Easy installation and exchange by utility operators. Roaming SIM supported | | |
| | Local configuration and access to data | Configuration and access to data via Standard USB on any laptop with provided software application | | |
| | Antenna | Internal antenna as standard External antenna port is available as option for hard-to- reach signal locations | | |
| | Firmware upgrade | Over the air through GPRS / UMTS connection | | |
| | Power supply | Autonomous lithium battery type. 5 years lifetime with daily data transmission / Easily exchangeable. External battery pack or connection to external power sources 6V - 30V are available as options | | |
| Variants | Configurations: with/without Pressure sensor | Provided in the below configurations including flow and pressure cables - 3G/2G Pulse - 3G/2G Pulse & Pressure - 3G/2G Pulse & 2xPressure | | |



WaterMind Advanced Logger 3G/2G Pulse & 2xPressure


Ideal combination with any C&I Itron meter



SharpFlow



Woltex





Dimensions

| A(Diameter) | mm | 115 |
|------------------------|----|------|
| B(Height) | mm | 140 |
| C(Total Height) | mm | 155 |
| D(Fast Couples Height) | mm | 15 |
| Weight | kg | 0.68 |



Join us in creating a more **resourceful world**.

To learn more visit **itron.com**

ITRON NOIDA -HEAD OFFICE

C - 7, Sector 3, Noida - 201 301 Uttar Pradesh

Phone: +91 120 465 6666 **Fax:** +91 120 465 6677

ITRON DEHRADUN - WORKS

Khasra No. 3903/3904, Majri Grant, Lal Tappad Industrial Area, Rishikesh, District Dehradun -248140 Uttarakhand

Phone: + 91 0135-2499083

ITRON BANGALORE - SALES & GLOBAL R&D UNIT

Unit No. 501, 502, 5th Floor & Unit 602 at 6th Floor Tower 6B, RMZ Eco-world Sarjapur Marathalli, Outer Ring Road, Devarabeesanahalli Bangalore – 560 103 (Karnataka)

Phone: +91 8061459100 **Mobile:** 9845218310

GANZ METER COMPANY LTD

Tancsics Mihály út 11.P.O.B. 396, H-2101 Gödöllő Hungary

Phone: +36 28 520 600 **Fax:** + 36 28 520 605

ITRON MUMBAI

Western Edge 2, B/05, Off Western Express Highway, Borivali East, Mumbai – 400066

Phone: +91 22 2870 66 33 / 44

While Itron strives to make the content of its marketing materials as timely and accurate as possible, Itron makes no claims, promises, or guarantees about the accuracy, completeness, or adequacy of, and expressly disclaims liability for errors and omissions in, such materials. No warranty of any kind, implied, expressed, or statutory, including but not limited to the warranties of non-infringement of third party rights, title, merchantability, and fitness for a particular purpose, is given with respect to the content of these marketing materials. © Copyright 2018, Itron. All rights reserved. SYS-0066.0-EN-08.18